# X.International.

#### Safety Data Sheet

HAO527 INTERTHERM 875 RED

Version No. 1 Revision Date 11/09/13

## 1. Product and company identification

1.1. Product identifier	INTERTHERM 875 RED
Product Code	HAO527
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Intended use	Refer Technical Data Sheet.
	For professional use only.
Application Method	Refer Technical Data Sheet.
1.3. Details of the supplier of the sa	afety data sheet
Manufacturer	International Paint Sdn Bhd
	Lot 1 & 2, Jalan Gangsa
	Pasir Gudang
	81700
	Malaysia
Telenhone Ne	(07) 054 4400
Telephone No.	(07) 254 1128
Fax No.	(07) 251 4775
1.4. Emergency telephone number	(07) 254 1126
For Poisons Advice telephone	For Advice to Doctors & Hospitals only

## 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

[Prevention]:
[Response]:
[Storage]:
[Disposal]:
2.3. Other hazards

## 3. Composition/information on ingredients

This product contains the following hazardous substances.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Xylene CAS Number: 0001330-20-7		Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]

C.I. pigment red 104 CAS Number: 0012656-85-8	10-25	Carc. 1B;H350 Repr. 1A;H360Df STOT RE 2;H373 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Ethyl Benzene CAS Number: 0000100-41-4	2.5-10	Flam. Liq. 2;H225 Acute Tox. 4;H332	[1][2]
n-Butanol CAS Number: 0000071-36-3	1-2.5	Flam. Liq. 3;H226 Acute Tox. 4;H302 STOT SE 3;H335 Skin Irrit. 2;H315 Eye Dam. 1;H318 STOT SE 3;H336	[1][2]
Barium chromate CAS Number: 0010294-40-3	1-2.5	Acute Tox. 4;H302 Acute Tox. 4;H332	[1]
Methanol CAS Number: 0000067-56-1	<1	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the Hazard (H) phrases are shown in Section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

#### 4. First aid measures

#### 4.1. Description of first aid measures

General

Inhalation

Skin Contact

Eye Contact

Ingestion

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

#### 5. Fire-fighting measures

#### 5.1. Extinguishing media

#### 5.2. Special hazards arising from the substance or mixture

#### 5.3. Advice for fire-fighters

#### 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

## 7. Handling and storage

## 7.1. Precautions for safe handling Handling

#### In Storage

#### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.3. Specific end use(s)

## 8. Exposure controls and personal protection

#### 8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygenists).

Material	Short ter	m (15 min. ave)	Long teri average)	n (8hr time weighted	Comments
	ppm	mg/m³	ppm	mg/M3	
Ethyl Benzene	125	543	100	434	
Methanol	250	328	200	262	
n-Butanol	50	152	-	-	
Xylene	150	651	100	434	

Key to notification

(P) Peak exposure limit

(R) Suppliers Recommended Limit

(Sk) There is a risk of absorption through unbroken skin

(Sen) Sensitiser

(Cat1) Category 1 - established human carcinogen

(Cat2) Category 2 - probable human carcinogen

(Cat3) Category 3 - substances suspected of having carcinogenic potential

#### **DNEL/PNEC** values

#### 8.2. Exposure controls

Eye Protection

Skin Protection

Other

**Respiratory Protection** 

Thermal hazards

#### 9. Physical and chemical properties

Colour Odour Odour threshold pН Melting point / freezing point (°C) Initial boiling point and boiling range (°C) Flash Point (C) Evaporation rate (Ether = 1) Flammability (solid, gas) Upper/lower flammability or explosive limits Lower Explosive Limit: 1.1 (Xylene) Upper Explosive Limit: 6.6 (Xylene) Vapour pressure (Pa) Vapour Density **Specific Gravity** 0.00 Solubility in Water Partition coefficient n-octanol/water (Log Kow) Autoignition temperature () **Decomposition temperature** Viscosity (cSt)

#### 9.2. Other information

No further information

#### 10. Stability and reactivity

- 10.1. Reactivity
- 10.2. Chemical stability
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
- 10.5. Incompatible materials
- 10.6. Hazardous decomposition products

#### **11. Toxicological information**

#### Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Barium chromate - (10294-40-3)	Not Available	Not Available	Not Available	Not Available
C.I. pigment red 104 - (12656-85-8)	5,000.00, Rat	Not Available	Not Available	Not Available
Ethyl Benzene - (100-41-4)	3,500.00, Rat	15,433.00, Rabbit	17.20, Rat	Not Available
Methanol - (67-56-1)	5,628.00, Rat	15,800.00, Rabbit	85.00, Rat	Not Available
n-Butanol - (71-36-3)	2,292.00, Rat	3,430.00, Rabbit	Not Available	Not Available
Xylene - (1330-20-7)	4,299.00, Rat	1,548.00, Rabbit	Not Available	20.00, Rat

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable

Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

## 12.1. Toxicity

## **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
C.I. pigment red 104 - (12656-85-8)	2,500.00, Leuciscus idus	Not Available	Not Available
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss		3.60 (96 hr), Pseudokirchneriella subcapitata
n-Butanol - (71-36-3)	1,376.00, Pimephales promelas	1,328.00, Daphnia magna	500.00 (96 hr), Scenedesmus subspicatus
Barium chromate - (10294-40-3)	Not Available	Not Available	Not Available
Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa

#### 12.2. Persistence and degradability

- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

## 13. Disposal considerations

#### 13.1. Waste treatment methods

## 14. Transport information

#### 14.1. UN number

- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)

#### **Road and Rail Transport**

IMDG reference :	Class/Div	Sub Class		
	Ems			
ICAO/IATA	Class	Sub Class		
14.4. Packing	group			
14.5. Environn	nental hazards			
Road and Rail Transport	Environmentally Hazardou	IS:		
IMDG reference :	Marine Pollutant:			
14.6. Special precautions for user				
	No further information			
14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code				
	Not Applicable			
15. Regulator	ry information			

The product and all its components complies with these local regulations: NICNAS - Australia EPA - New Zealand

#### **16. Other information**

The information on this SDS is based upon the present state of our knowledge and on current law. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H350 May cause cancer.

H360Df May damage the unborn child. Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

#### This SDS is valid for 5 years from the revised date on page 1. The revision date is in American format (e.g. MM/DD/YY).

End of document



All information concerning this product and/or suggesti ons for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information. *Semua maklumat berkenaan produk ini dan/atau cadangan untuk pengendalian dan penggunaan yang terkandung di sini adalah benar dan boleh dipercayai. Walau bagaimanapun, Akzo Nobel tidak memberi jaminan akan maklumat yang tepat dan/atau mencukupi.* 

AkzoNobel