

NVA980_A0

Safety Data Sheet ENVIROLINE 2900LV PART B



Bulk Sales Reference No.:
SDS Revision Date:
SDS Revision Number:

Sales
Order: {SalesOrd}
NVA980
08/26/2016
A0-

1. Identification of the preparation and company

1.1. Product identifier

Product Identity ENVIROLINE 2900LV PART B
Bulk Sales Reference No. NVA980

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
Skin Corr. 1B;H314 Causes severe skin burns and eye damage.
Eye Dam. 1;H318 Causes serious eye damage.
Skin Sens. 1;H317 May cause an allergic skin reaction.
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
 P235 Keep cool.
 P240 Ground / bond container and receiving equipment.
 P241 Use explosion-proof electrical / ventilating / light / equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe mist / vapors / spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P302+352 IF ON SKIN: Wash with soap and water.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
 P310 Immediately call a POISON CENTER or doctor / physician.
 P331 Do NOT induce vomiting.
 P333+313 If skin irritation or a rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P370 In case of fire: Use water spray, fog, or regular foam..
 P403+233 Store in a well ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: Unknown Flammability: Unknown Reactivity: Unknown

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|---|----------|--|--------|
| Nepheline syenite CAS Number: 0037244-96-5 | 50 - 75 | ---- | [1] |
| Diethylene triamine CAS Number: 0000111-40-0 | 1.0 - 10 | Acute Tox. 4;H312 Acute Tox. 4;H302 Skin Corr. 1B;H314 Skin Sens. 1;H317 | [1][2] |
| Benzyl alcohol CAS Number: 0000100-51-6 | 1.0 - 10 | Acute Tox. 4;H332 Acute Tox. 4;H302 | [1] |
| Titanium dioxide CAS Number: 0013463-67-7 | 1.0 - 10 | ---- | [1][2] |
| Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7 | 1.0 - 10 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304 | [1][2] |
| Aluminum oxide CAS Number: 0001344-28-1 | 1.0 - 10 | ---- | [1] |
| Propylene glycol monomethyl ether CAS Number: 0000107-98-2 | 1.0 - 10 | Flam. Liq. 3;H226 STOT SE 3;H336 | [1][2] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

| |
|-----------------------|
| 4. First aid measures |
|-----------------------|

4.1. Description of first aid measures

| | |
|------------|---|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. |

| |
|---------------------------|
| 5. Fire-fighting measures |
|---------------------------|

5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO₂, water spray or foam. LARGE FIRES: Use dry chemical, CO₂, water spray, or alcohol-resistant foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

COMBUSTIBLE MATERIAL: May burn but does not ignite readily. When heated, vapors may form explosive mixtures with air. Indoors, outdoors, and low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Contact with metals may evolve flammable hydrogen gas. Containers may explode when heated.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 153

| |
|--------------------------------|
| 6. Accidental release measures |
|--------------------------------|

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control. DO NOT GET WATER INSIDE CONTAINERS.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

NVA980_A0

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|-----------------------------------|--------------|--|
| 0000100-51-6 | Benzyl alcohol | OSHA | |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | |
| | | Mexico | |
| | | Brazil | |
| 0000107-98-2 | Propylene glycol monomethyl ether | OSHA | 150 ppm STEL; 540 mg/m3 STEL |
| | | ACGIH | 50 ppm TWA100 ppm STEL |
| | | NIOSH | 100 ppm TWA; 360 mg/m3 TWA150 ppm STEL; 540 mg/m3 STEL |
| | | Supplier | |
| | | OHSA, CAN | 100 ppm TWA150 ppm STEL |
| | | Mexico | |
| | | Brazil | |
| 0000111-40-0 | Diethylene triamine | OSHA | |
| | | ACGIH | 1 ppm TWA |
| | | NIOSH | 1 ppm TWA; 4 mg/m3 TWA |
| | | Supplier | |
| | | OHSA, CAN | 1 ppm TWA |
| | | Mexico | 1 ppm TWA LMPE-PPT; 4.2 mg/m3 TWA LMPE-PPT |
| | | Brazil | |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | OSHA | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA150 ppm STEL |
| | | NIOSH | |
| | | Supplier | |
| | | | 100 ppm TWA150 ppm STEL |

NVA980_A0

| | | | |
|--------------|-------------------|--------------|--|
| | | OHSA, CAN | |
| | | Mexico | 100 ppm TWA LMPE-PPT; 435 mg/m3 TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 655 mg/m3 STEL [LMPE-CT] |
| | | Brazil | 78 ppm TWA LT; 340 mg/m3 TWA LT |
| 0001344-28-1 | Aluminum oxide | OSHA | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | |
| | | Mexico | 10 mg/m3 TWA LMPE-PPT |
| | | Brazil | |
| 0013463-67-7 | Titanium dioxide | OSHA | 15 mg/m3 TWA (total dust) |
| | | ACGIH | 10 mg/m3 TWA |
| | | NIOSH | 5000 mg/m3 IDLH |
| | | Supplier | |
| | | OHSA, CAN | 10 mg/m3 TWA |
| | | Mexico | 10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti) |
| | | Brazil | |
| 0037244-96-5 | Nepheline syenite | OSHA | |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | 10 mg/m3 TWA (total dust) |
| | | Mexico | |
| | | Brazil | |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|-----------------------------------|--------|---|
| 0000100-51-6 | Benzyl alcohol | NIOSH | |
| 0000107-98-2 | Propylene glycol monomethyl ether | NIOSH | Eye nose |
| 0000111-40-0 | Diethylene triamine | NIOSH | Skin and respiratory irritation and sensitization |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | NIOSH | Central nervous system depressant; respiratory and eye irritation |
| 0001344-28-1 | Aluminum oxide | NIOSH | |
| 0013463-67-7 | Titanium dioxide | NIOSH | Lung tumors in animals |
| 0037244-96-5 | Nepheline syenite | NIOSH | |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|-----------------------------------|--------|--|
| 0000100-51-6 | Benzyl alcohol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000107-98-2 | Propylene glycol monomethyl ether | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000111-40-0 | Diethylene triamine | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

NVA980_A0

| | | | |
|--------------|-----------------------------|------|---|
| 0001330-20-7 | Xylenes (o-, m-, p-isomers) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0001344-28-1 | Aluminum oxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0037244-96-5 | Nepheline syenite | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

| | |
|----------------------|---|
| Respiratory | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

9. Physical and chemical properties

| | |
|--|---|
| Appearance | Coloured Liquid |
| Odour threshold | Not Measured |
| pH | No Established Limit |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 117 (°C) 243 (°F) |
| Flash Point | 35 (°C) 95 (°F) |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit |
| vapor pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 1.62 |

NVA980_A0

| | |
|---|--|
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | No Established Limit Not Measured |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |
| VOHAP content (gm/litre of paint) | 70.50 (as supplied) |
| VOHAP content (gm/litre of Solid Coating) | 56.88 (as supplied) |

| |
|-------------------------------------|
| 10. Stability and reactivity |
|-------------------------------------|

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

COMBUSTIBLE MATERIAL: May burn but does not ignite readily. When heated, vapors may form explosive mixtures with air. Indoors, outdoors, and low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Contact with metals may evolve flammable hydrogen gas. Containers may explode when heated.

| |
|--------------------------------------|
| 11. Toxicological information |
|--------------------------------------|

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|--|-------------------------------|----------------------------------|---------------------------------|-------------------------------------|
| Nepheline syenite - (37244-96-5) | No data available | No data available | No data available | No data available |
| Diethylene triamine - (111-40-0) | 1,080.00, Rat - Category: 4 | 1,090.00, Rabbit - Category: 4 | No data available | No data available |
| Benzyl alcohol - (100-51-6) | 1,230.00, Rat - Category: 4 | 2,000.00, Rabbit - Category: 4 | No data available | 4.178, Rat - Category: 4 |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA |
| Xylenes (o-, m-, p- isomers) - (1330-20-7) | 4,299.00, Rat - Category: 5 | 1,548.00, Rabbit - Category: 4 | 20.00, Rat - Category: 4 | No data available |
| Aluminum oxide - (1344-28-1) | 5,000.00, Rat - Category: 5 | No data available | No data available | No data available |
| Propylene glycol monomethyl ether - (107-98-2) | 5,000.00, Rat - Category: 5 | 13,000.00, Rabbit - Category: NA | No data available | No data available |

NVA980_A0

| Item | Category | Hazard |
|---|----------------|--|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 1B | Causes severe skin burns and eye damage. |
| Eye damage/irritation | 1 | Causes serious eye damage. |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure) | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|--|---------------------------------|----------------------------|---|
| Nepheline syenite - (37244-96-5) | Not Available | Not Available | Not Available |
| Diethylene triamine - (111-40-0) | 1,014.00, Poecilia reticulata | 53.50, Daphnia magna | 345.60 (96 hr), Pseudokirchneriella subcapitata |
| Benzyl alcohol - (100-51-6) | 10.00, Lepomis macrochirus | 55.00, Daphnia magna | 700.00 (72 hr), Algae |
| Titanium dioxide - (13463-67-7) | 1,000.00, Fundulus heteroclitus | 5.50, Daphnia magna | 5.83 (72 hr), Pseudokirchneriella subcapitata |
| Xylenes (o-, m-, p-isomers) - (1330-20-7) | 3.30, Oncorhynchus mykiss | 8.50, Palaemonetes pugio | 100.00 (72 hr), Chlorococcales |
| Aluminum oxide - (1344-28-1) | Not Available | Not Available | Not Available |
| Propylene glycol monomethyl ether - (107-98-2) | 1,000.00, Oncorhynchus mykiss | 500.00, Daphnia magna | 1,000.00 (96 hr), Selenastrum capricornutum |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

NVA980_A0

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

- 14.1. UN number UN 3066
 14.2. UN proper shipping name PAINT
 14.3. Transport hazard class(es)

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|---|-----------------------------------|---|
| DOT Proper Shipping Name | PAINT | IMDG Proper Shipping Name | PAINT |
| DOT Hazard Class | Class 8, No division Corrosive materials | IMDG Hazard Class Sub Class | Class 8, No division Corrosive materials Not applicable |
| UN / NA Number | UN 3066 | IMDG Packing Group | III |
| CERCLA/DOT RQ | 264 gal. / 3549 lbs. | System Reference Code | 95 |

- 14.4. Packing group III
 14.5. Environmental hazards
 IMDG Marine Pollutant: No
 14.6. Special precautions for user
 Not Applicable
 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
 Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B E

- DOT Marine Pollutants (10%):**
 (No Product Ingredients Listed)
- DOT Severe Marine Pollutants (1%):**
 (No Product Ingredients Listed)
- EPCRA 311/312 Chemicals and RQs (>.1%) :**
 Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)
 Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)
- EPCRA 302 Extremely Hazardous (>.1%) :**
 (No Product Ingredients Listed)
- EPCRA 313 Toxic Chemicals (>.1%) :**
 Aluminum oxide
 Benzene, ethyl-
 Xylenes (o-, m-, p- isomers)
- Mass RTK Substances (>1%) :**
 Aluminum oxide
 Benzyl alcohol
 Diethylene triamine
 Propylene glycol monomethyl ether
 Titanium dioxide
 Xylenes (o-, m-, p- isomers)

Penn RTK Substances (>1%) :

Aluminum oxide
Benzyl alcohol
Diethylene triamine
Propylene glycol monomethyl ether
Titanium dioxide
Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Aluminum oxide
Diethylene triamine
Propylene glycol monomethyl ether
Titanium dioxide
Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

Diethylene triamine
Benzene, ethyl-
Propylene glycol monomethyl ether
Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

Aluminum oxide
Benzene, ethyl-
Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Benzene, ethyl-
Quartz
Titanium dioxide

Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

| |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.

NVA980_A0

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document