

# T011HA\_A1

## Material Safety Data Sheet INTERTHERM 875 LIGHT BASE INTERMEDIATE



Bulk Sales Reference No.:  
MSDS Revision Date:  
MSDS Revision Number:

Sales  
Order: {SalesOrd}  
T011HA  
12/14/2011  
A1-3

### 1. Identification of the preparation and company

Product Identity	INTERTHERM 875 LIGHT BASE INTERMEDIATE
Bulk Sales Reference No.	T011HA
Company Name	International Paint LLC 6001 Antoine Drive Houston Texas 77091
Emergency	
CHEMTREC (USA)	(800) 424-9300
International Paint	(713) 682-1711
Poison Control Center	(800) 854-6813
Customer Service	
International Paint	(800) 589-1267
Fax No.	(800) 631-7481

### 2. Hazard identification of the product



Danger

#### GHS Classification:

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	5	May be harmful if swallowed
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	2	Causes skin irritation
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system, kidneys, liver, respiratory system
	2	central nerve system
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	central nerve system, kidneys, liver, lung, respiratory system
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects

## T011HA\_A1

Carcinogenicity	1A	May cause cancer
Reproductive Toxicity	2	Suspected of damaging fertility or the unborn child.
Organic Peroxide	Not classified	Not applicable

**Safety Phrases:**

- S1: Keep locked up.
- S23: Do not breathe vapor/spray.
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S27: Take off immediately all contaminated clothing.
- S28: After contact with skin, wash immediately with plenty of soap and water.
- S36/37: Wear suitable protective clothing and gloves.
- S39: Wear eye/face protection.
- S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S51: Use only in well-ventilated areas.
- S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.
- S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Birth defect hazard. Contains an ingredient which can cause birth defects (See Section 2 and Section 15 for each ingredient). Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.
HMIS Rating	Health: Unknown Flammability: Unknown Reactivity: Unknown PPE: X

3. Composition/information on ingredients
---

Ingredient	CAS No.	Percent
1,2,4-Trimethyl benzene	0000095-63-6	1.0 – 10
Benzene, ethyl-	0000100-41-4	1.0 – 10
1,3,5-Trimethylbenzene	0000108-67-8	1.0 – 10
Benzene, methyl-	0000108-88-3	1.0 – 10
Xylenes (o-, m-, p- isomers)	0001330-20-7	10 – 25
Silica, amorphous	0007631-86-9	1.0 – 10
Titanium dioxide	0013463-67-7	10 – 25
Aluminum hydroxide	0021645-51-2	1.0 – 10
Petroleum naphtha, light aromatic	0064742-95-6	1.0 – 10
Talc (*non-asbestiform)	14807-96-6*	1.0 – 10

4. First aid measures
-----------------------

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	

# T011HA\_A1

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.

Ingestion      If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures
---------------------------

Flash Point      F: 75  
C: 24

Lower Explosive Limit (LEL)      .9 (%vol in air) at Normal Atmospheric Temp and Pressure  
ERG Guide No.      128

6. Accidental release measures
--------------------------------

Spill Response Procedures      ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

Public Safety      CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No.      128

7. Handling and storage
-------------------------

Storage Temperature      Store between 40-100F (4-38C).

Handling and Storage Precautions      Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection
--

Exposure			
CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000100-41-4	Benzene, ethyl-	OSHA	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		ACGIH	100 ppm TWA125 ppm STEL
		NIOSH	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA125 ppm STEL

T011HA\_A1

		Mexico	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
0000108-67-8	1,3,5-Trimethylbenzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
		0000108-88-3	Benzene, methyl-
ACGIH	20 ppm TWA		
NIOSH	100 ppm TWA; 375 mg/m3 TWA150 ppm STEL; 560 mg/m3 STEL500 ppm IDLH		
Supplier	No Established Limit		
OHSA, CAN	20 ppm TWA		
Mexico	50 ppm TWA; 188 mg/m3 TWA		
Brazil	78 ppm TWA; 290 mg/m3 TWA		
0001330-20-7	Xylenes (o-, m-, p- isomers)		
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
		0007631-86-9	Silica, amorphous
ACGIH	No Established Limit		
NIOSH	6 mg/m3 TWA3000 mg/m3 IDLH		
Supplier	No Established Limit		
OHSA, CAN	No Established Limit		
Mexico	No Established Limit		
Brazil	No Established Limit		
0013463-67-7	Titanium dioxide		
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
		0021645-51-2	Aluminum hydroxide
ACGIH	No Established Limit		
NIOSH	No Established Limit		
Supplier	No Established Limit		
OHSA, CAN	No Established Limit		
Mexico	No Established Limit		
Brazil	No Established Limit		
0064742-95-6	Petroleum naphtha, light aromatic		
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

T011HA\_A1

		OSHA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
14807-96-6*	Talc (*non-asbestiform)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OSHA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	NIOSH	No Established Limit
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin
0000108-67-8	1,3,5-Trimethylbenzene	NIOSH	No Established Limit
0000108-88-3	Benzene, methyl-	NIOSH	Central nervous system depressant
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit
0064742-95-6	Petroleum naphtha, light aromatic	NIOSH	No Established Limit
14807-96-6*	Talc (*non-asbestiform)	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-41-4	Benzene, ethyl-	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000108-67-8	1,3,5-Trimethylbenzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-88-3	Benzene, methyl-	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0021645-51-2	Aluminum hydroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

T011HA\_A1

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha, light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
14807-96-6*	Talc (*non-asbestiform)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

**Respiratory** Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

**Eyes** Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

**Skin** Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

**Engineering Controls** Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

**Other Work Practices** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State            Liquid Coloured  
 pH                            No Established Limit  
 Specific Gravity            1.20  
 Boiling Point F            231  
 Vapor Density              Heavier than air  
 VOC %                      Refer to the Technical Data Sheet or label where information is available.  
 Evaporation Rate          Slower than ether

10. Stability and reactivity

**General** This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

**Incompatible Materials** Strong oxidizing agents.

**Hazardous Decomposition** May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr

T011HA\_A1

1,2,4-Trimethyl benzene – (0000095-63-6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit – Category: 5	-----
Benzene, ethyl– (0000100-41-4)	3,500.00, Rat – Category: 5	15,354.00, Rabbit – Category: NA	17.20, Rat – Category: 4
1,3,5-Trimethylbenzene – (0000108-67-8)	5,000.00, Rat – Category: 5	-----	-----
Benzene, methyl– (0000108-88-3)	636.00, Rat – Category: 4	8,390.00, Rabbit – Category: NA	12.50, Rat – Category: 4
Xylenes (o-, m-, p- isomers) – (0001330-20-7)	4,300.00, Rat – Category: 5	1,700.00, Rabbit – Category: 4	29.08, rat – Category: NA
Silica, amorphous – (0007631-86-9)	5,000.00, Rat – Category: 5	2,000.00, Rabbit – Category: 4	-----
Titanium dioxide – (0013463-67-7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA
Aluminum hydroxide – (0021645-51-2)	5,000.00, Rat – Category: 5	-----	-----
Petroleum naphtha, light aromatic – (0064742-95-6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit – Category: 4	5.20, Rat – Category: 3
Talc (*non-asbestiform) – (14807-96-6*)	-----	-----	-----

General NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined  
No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class	3 – Flammable and Combustible liquid
UN / NA Number	UN 1263	UN / NA Number	UN 1263
DOT Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	61 gal. / 616 lbs.	System Reference Code	1

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification No Established Limit

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :  
Cumene (5000 lb final RQ; 2270 kg final RQ)

## T011HA\_A1

Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)  
Methyl methacrylate (1000 lb final RQ; 454 kg final RQ)  
BUTYL ACETATE (5000 lb final RQ; 2270 kg final RQ)  
Benzene, 1,2-dimethyl- (1000 lb final RQ; 454 kg final RQ)  
Benzene, methyl- (1000 lb final RQ; 454 kg final RQ)  
Benzene, 1,3-dimethyl- (1000 lb final RQ; 454 kg final RQ)  
Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

1,2,4-Trimethyl benzene  
Cumene  
Benzene, ethyl-  
Methyl methacrylate  
Benzene, 1,2-dimethyl-  
Benzene, methyl-  
Benzene, 1,3-dimethyl-  
Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Benzene, ethyl-  
Silica, amorphous  
Titanium dioxide  
Benzene, methyl-  
1,3,5-Trimethylbenzene  
Xylenes (o-, m-, p- isomers)

Mass Extraordinarily Haz Sub (>.01%) :  
(No Product Ingredients Listed)

Penn RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Benzene, ethyl-  
Silica, amorphous  
Titanium dioxide  
Benzene, methyl-  
Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%) :

Cumene  
Benzene, ethyl-  
Methyl methacrylate  
BUTYL ACETATE  
Stoddard solvent  
Titanium dioxide  
Benzene, methyl-  
Xylenes (o-, m-, p- isomers)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-Trimethyl benzene  
Benzene, ethyl-  
Titanium dioxide  
Benzene, methyl-  
Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

Cumene  
Benzene, ethyl-



Methyl methacrylate  
BUTYL ACETATE  
Benzene, 1,2-dimethyl-  
BUTYL ALCOHOL  
Benzene, methyl-  
Benzene, 1,3-dimethyl-  
Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-Trimethyl benzene  
Cumene  
Benzene, ethyl-  
Methyl methacrylate  
Benzene, 1,2-dimethyl-  
Benzene, methyl-  
Benzene, 1,3-dimethyl-  
Xylenes (o-, m-, p- isomers)

Proposition 65 – Carcinogens (>0%):

Cumene  
Benzene, ethyl-  
Naphthalene

Proposition 65 – Female Repro Toxins (>0%):

Benzene, methyl-

Proposition 65 – Male Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

Benzene, methyl-

Risk Phrases:

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R45: May cause cancer.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information
-----------------------

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.