### Material Safety Data Sheet INTERCURE 4500 KPI BEIGE PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number:

Sales Order: {SalesOrd} AGN99E 07/03/2014 A0-

# XInternational.

1. Identification of the preparation and company		
1.1. Product identifier		
Product Identity	INTERCURE 4500 KPI BEIGE PART A	
Bulk Sales Reference No.	AGN99E	
1.2. Relevant identified uses of the s	ubstance or mixture and uses advised against	
Intended Use	See Technical Data Sheet.	
Application Method	See Technical Data Sheet.	
1.3. Details of the supplier of the safe	ety data sheet	
Company Name	International Paint LLC	
	6001 Antoine Drive	
	Houston Texas 77091	
Emergency		
CHEMTREC (USA)	(800) 424-9300	
International Paint	(713) 682-1711	
Poison Control Center	(800) 854-6813	
Customer Service		
International Paint	(800) 589-1267	
Fax No.	(800) 631-7481	

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Skin Irrit. 3;H316	Causes mild skin irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapor.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking. P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P333 If skin irritation or a rash occurs:.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P391 Collect spillage.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating	Health: 2	Flammability: 3	Reactivity: 0
-------------	-----------	-----------------	---------------

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	<b>GHS Classification</b>	Notes
Wollastonite (Ca(SiO3)) CAS Number: 0013983-17-0	25 - 50		[1]
SECONDARY DIAMINES CAS Number: TS-KH8070	10 - 25		[1]
Petroleum naphtha CAS Number: 0064742-95-6	10 - 25	Asp. Tox. 1;H304 Aquatic Chronic 2;H411 (Self Classification)	[1]
1,2,4-Trimethyl benzene CAS Number: 0000095-63-6	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	[1]
ZEOLITE CAS Number: 0001318-02-1	1.0 - 10		[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10		[1][2]
1,3,5-Trimethylbenzene CAS Number: 0000108-67-8	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H335 Aquatic Chronic 2;H411	[1]
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate CAS Number: 0041556-26-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410 Aquatic Acute 1;H400	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

# AGN99E A0

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important sy	mptoms and effects, both acute and delayed
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes lung irritation. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.
Skin	Causes skin irritation. May cause delayed skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO2, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses. 128

ERG Guide No.

#### 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

## 7. Handling and storage

7.1. Precautions for safe handling Handling

Vapors may cause flash fire or ignite explosively.

In Storage Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities Store between 40-100F (4-38C). Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

#### 8. Exposure controls and personal protection

### 8.1. Control parameters

Exposure				
CAS No.	Ingredient	Source	Value	
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	25 ppm TWA; 125 mg/m3 TWA	
		Supplier	No Established Limit	
		OHSA, CAN	No Established Limit	
		Mexico	No Established Limit	
		Brazil	No Established Limit	
0000108-67-8	1,3,5-Trimethylbenzene	OSHA	No Established Limit	
		ACGIH	No Established Limit	
		NIOSH	25 ppm TWA; 125 mg/m3 TWA	
		Supplier	No Established Limit	
	OHSA, CAN	No Established Limit		
		Mexico	No Established Limit	
		Brazil	No Established Limit	
0001318-02-1	ZEOLITE	OSHA	No Established Limit	
		ACGIH	No Established Limit	
	NIOSH	No Established Limit		
		Supplier	No Established Limit	
		OHSA, CAN	No Established Limit	
		Mexico	No Established Limit	
		Brazil	No Established Limit	
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)	
		ACGIH	10 mg/m3 TWA	
		NIOSH	5000 mg/m3 IDLH	
		Supplier	No Established Limit	
		OHSA, CAN	10 mg/m3 TWA	

Ì	1	Marilan	
		Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)
		Brazil	No Established Limit
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0041556-26-7	Bis	OSHA	No Established Limit
	(1,2,2,6,6-pentamethyl-4-piperidinyl)	ACGIH	No Established Limit
	sebacate	NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-95-6	Petroleum naphtha	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
TS-KH8070	SECONDARY DIAMINES	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data			
CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	NIOSH	No Established Limit
0000108-67-8	1,3,5-Trimethylbenzene	NIOSH	No Established Limit
0001318-02-1	ZEOLITE	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit
	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	NIOSH	No Established Limit
0064742-95-6	Petroleum naphtha	NIOSH	No Established Limit
TS-KH8070	SECONDARY DIAMINES	NIOSH	No Established Limit

Carcinogen Data			
CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-67-8	1,3,5-Trimethylbenzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

0001318-02-1	ZEOLITE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0041556-26-7 Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Bis	OSHA	Select Carcinogen: No
	NTP	Known: No; Suspected: No	
	sebacate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
TS-KH8070	SECONDARY DIAMINES	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

	9. Physical and chemical properties
Appearance	Coloured Liquid
Odour threshold	Not Measured
рН	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	35 (C) 95 (F)
Flash Point	50 (C) 122 (F)

Evaporation rate (Ether = 1) Flammability (solid, gas)	Not Measured Not Applicable		
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1		
	Upper Explosive Limit: No Established Limit		
vapor pressure (Pa)	Not Measured		
Vapor Density	Heavier than air		
Specific Gravity	1.48		
Partition coefficient n-octanol/water (Log Kow)	Not Measured		
Auto-ignition temperature	Not Measured		
Decomposition temperature	Not Measured		
Viscosity (cSt)	No Established Limit Not Measured		
VOC %	Refer to the Technical Data Sheet or label where information is available.		
9.2. Other information			

No further information

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Wollastonite (Ca(SiO3)) - (13983-17-0)	No data available	No data available	No data available	No data available
SECONDARY DIAMINES - (TS-KH8070)	No data available	No data available	No data available	No data available
Petroleum naphtha - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
1,2,4-Trimethyl benzene - (95-63-6)	3,400.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	18.00, Rat - Category: 4	No data available
ZEOLITE - (1318-02-1)				

	5,110.00, Rat - Category: NA	2,000.00, Rabbit - Category: 4	No data available	5.00, Rat - Category: 4
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
1,3,5-Trimethylbenzene - (108-67-8)	No data available	No data available	24.00, Rat - Category: NA	No data available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	2,615.00, Rat - Category: 5	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Wollastonite (Ca(SiO3)) - (13983-17-0)	Not Available	Not Available	Not Available
SECONDARY DIAMINES - (TS-KH8070)	Not Available	Not Available	Not Available
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
1,2,4-Trimethyl benzene - (95-63-6)	7.72, Pimephales promelas	3.60, Daphnia magna	Not Available
ZEOLITE - (1318-02-1)	1,800.00, Danio rerio	1,000.00, Daphnia magna	560.00 (96 hr), Chlorella vulgaris
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
1,3,5-Trimethylbenzene - (108-67-8)	12.52, Carassius auratus	6.00, Daphnia magna	25.00 (48 hr), Scenedesmus subspicatus
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	1.00, Lepomis macrochirus	20.00, Daphnia magna	Not Available

12.2. Persistence and degradability No data available

12.3. Bioaccumulative potential Not Measured 12.4. Mobility in soil No data available 12.5. Results of PBT and vPvB assessment This product contains no PBT/vPvB chemicals. 12.6. Other adverse effects No data available

#### 13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

	1	4. Transport info	ormation		
14.1. UN number		UN 1263			
14.2. UN proper shippin	g name	PAINT			
14.3. Transport hazard of	class(es)				
DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)					
DOT Proper Shipping PAINT Name			IMDG Proper Shipping Name	PAINT	
DOT Hazard Clas	ss 3		IMDG Hazard Class Sub Class	3 3	
UN / NA Number	UN 1263				
DOT Packing Gro			IMDG Packing Group	III	
CERCLA/DOT R	Q 1259 gal. / 1	5504 lbs.	System Reference Code	2	
14.4. Packing group III   14.5. Environmental hazards IMDG   IMDG Marine Pollutant: Yes (Petroleum naphtha )   14.6. Special precautions for user Not Applicable   14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code   Not Applicable					
	1	5. Regulatory int	formation		
Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.   WHMIS Classification B3 D2B					
DOT Marine Pollutants (10%): (No Product Ingredients Listed) DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) EPCRA 311/312 Chemicals and RQs (>.1%) : Cumene (5000 lb final RQ; 2270 kg final RQ) Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ) EPCRA 302 Extremely Hazardous (>.1%) :					

(No Product Ingredients Listed) EPCRA 313 Toxic Chemicals (>.1%) : 1,2,4-Trimethyl benzene Cumene Xylenes (o-, m-, p- isomers) Mass RTK Substances (>1%) : 1,2,4-Trimethyl benzene Titanium dioxide 1,3,5-Trimethylbenzene Penn RTK Substances (>1%) : 1,2,4-Trimethyl benzene Titanium dioxide Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : 1,2,4-Trimethyl benzene Titanium dioxide N.J. Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Carbon black Cumene Quartz Silica, cristobalite Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%) : 1,2,4-Trimethyl benzene Cumene Xylenes (o-, m-, p- isomers) Proposition 65 - Carcinogens (>0%): Carbon black Cumene Nickel Quartz Titanium dioxide Proposition 65 - Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 - Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 - Developmental Toxins (>0%): (No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.H335 May cause respiratory irritation.H400 Very toxic to aquatic life.H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document