

**Safety Data Sheet**
**ECB000C INTERGARD 740 WHITE**
**Version No 1 Revision Date 08/19/13**
**1. Product and company identification**
**1.1. Product identifier** INTERGARD 740 WHITE

Product Code ECB000C

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use Refer Technical Data Sheet.

Application Method Refer Technical Data Sheet.

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer** International Paint (Korea) Limited  
 (8-6B/L Chilseo Industrial Complex),  
 626-6 Gyenae-Ri,  
 Chilseo-Myeon, Haman-Gun,  
 Gyeongsangnam-Do  
 Korea

**Telephone No.** 055-632-6286(R&D), 055 586 2310(Fact

**Fax No.** 055 632-6287(R&D), 055 587 6276(Fact

**1.4. Emergency telephone number** 055-586-2310(Factory)

**For Poisons Advice telephone** 055-586-2310(Factory) For Advice to Doctors & Hospitals only

**2. Hazard identification of the product**
**2.1. Classification of the substance or mixture**
**2.2. Label elements**

Using the Toxicity Data listed in section 11 &amp; 12 the product is labelled as follows.

**[Prevention]:**
**[Response]:**
**[Storage]:**
**[Disposal]:**
**2.3. Other hazards**
**3. Composition/information on ingredients**

This product contains the following hazardous substances.

| Ingredient/Chemical Designations   | Weight % | GHS Classification  | Notes  |
|------------------------------------|----------|---|--------|
| Xylene<br>CAS Number: 0001330-20-7 | 20-30    | Flam. Liq. 3;H226<br>Acute Tox. 4;H312<br>Acute Tox. 4;H332<br>Skin Irrit. 2;H315<br>Eye Dam. 2A;H319 | [1][2] |

|  |       |  |        |
|--|-------|--|--------|
|  |       | STOT SE 3;H336<br>STOT RE 1;H372   |        |
| Titanium dioxide<br>CAS Number: 0013463-67-7     | 20-30 |  | [1][2] |
| Talc<br>CAS Number: 0014807-96-6                 | 10-20 |  | [1][2] |
| Epoxy Resin liquid<br>CAS Number: 0025036-25-3   | 10-20 | Eye Irrit. 2;H319<br>Skin Irrit. 2;H315,<br>Skin Sens. 1;H317  | [1]    |
| Ethyl Benzene<br>CAS Number: 0000100-41-4        | 2.5-5 | Flam. Liq. 2;H225<br>Acute Tox. 4;H332   | [1][2] |
| 1-METHOXYPROPAN-2-OL<br>CAS Number: 0000107-98-2 | 2.5-5 | Flam. Liq. 3;H226<br>STOT SE 3;H336  | [1][2] |
| Epoxy Resin<br>CAS Number: 0025068-38-6          | 2.5-5 | Eye Irrit. 2;H319<br>Skin Irrit. 2;H315<br>Skin Sens. 1;H317<br>Aquatic Chronic 2;H411                   | [1]    |
| Barium Sulphate<br>CAS Number: 0007727-43-7      | 1-2.5 |  | [1][2] |
| Silica (quartz)<br>CAS Number: 0014808-60-7      | 1-2.5 | Acute Tox. 4;H332<br>STOT RE 2;H373  | [1][2] |
| Nonylphenol<br>CAS Number: 0025154-52-3          | <1    | Acute Tox. 4;H302<br>Skin Corr. 1;H314<br>Repr. 2;H361<br>Aquatic Acute 1;H400<br>Aquatic Chronic 1;H410 | [1]    |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the Hazard (H) phrases are shown in Section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

#### Inhalation

#### Skin Contact

#### Eye Contact

#### Ingestion

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## 5. Fire-fighting measures

### 5.1. Extinguishing media

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for fire-fighters

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Handling

#### In Storage

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.3. Specific end use(s)

## 8. Exposure controls and personal protection

### 8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygienists).

| Material             | Short term (15 min. ave) |                   | Long term (8hr time weighted average) |       | Comments |
|----------------------|--------------------------|-------------------|---------------------------------------|-------|----------|
|                      | ppm                      | mg/m <sup>3</sup> | ppm                                   | mg/M3 |          |
| 1-METHOXYPROPAN-2-OL | 150                      | 540               | 100                                   | 360   |          |
| Barium Sulphate      |                          |                   | 2                                     | 10    |          |
| Ethyl Benzene        | 125                      | 545               | 100                                   | 435   |          |
| Silica (quartz)      |                          |                   |                                       | 0.1   |          |
| Talc                 |                          |                   |                                       | 2     |          |
| Titanium dioxide     |                          |                   |                                       | 10    |          |
| Xylene               | 150                      | 655               | 100                                   | 434   |          |

Key to notification

(P) Peak exposure limit

(R) Suppliers Recommended Limit

(Sk) There is a risk of absorption through unbroken skin

(Sen) Sensitiser

(Cat1) Category 1 - established human carcinogen

(Cat2) Category 2 - probable human carcinogen

(Cat3) Category 3 - substances suspected of having carcinogenic potential

### DNEL/PNEC values

### 8.2. Exposure controls

#### Eye Protection

#### Skin Protection

#### Other

#### Respiratory Protection

## Thermal hazards

### 9. Physical and chemical properties

Colour

Odour

Odour threshold

pH

Melting point / freezing point (°C)

Initial boiling point and boiling range (°C)

Flash Point (C)

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Lower Explosive Limit: 1.1 ( Xylene )

Upper Explosive Limit: 6.6 ( Xylene )

Vapour pressure (Pa)

Vapour Density

Specific Gravity

0.00

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Autoignition temperature ( )

Decomposition temperature

Viscosity (cSt)

#### 9.2. Other information

No further information

### 10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

### 11. Toxicological information

#### Acute toxicity

| Ingredient                        | Oral LD50, mg/kg | Skin LD50, mg/kg  | Inhalation Vapour LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|-----------------------------------|------------------|-------------------|----------------------------------|-------------------------------------|
| 1-METHOXYPROPAN-2-OL - (107-98-2) | 5,000.00, Rat    | 13,000.00, Rabbit | Not Available                    | Not Available                       |
| Barium Sulphate - (7727-43-7)     | 3,000.00, Mouse  | Not Available     | Not Available                    | Not Available                       |
| Epoxy Resin - (25068-38-6)        | 2,000.00, Rat    | 2,000.00, Rabbit  | Not Available                    | Not Available                       |
| Epoxy Resin liquid - (25036-25-3) | Not Available    | Not Available     | Not Available                    | Not Available                       |
| Ethyl Benzene - (100-41-4)        | 3,500.00, Rat    | 15,433.00, Rabbit | 17.20, Rat                       | Not Available                       |

|                                 |                |                   |               |               |
|---------------------------------|----------------|-------------------|---------------|---------------|
| Nonylphenol - (25154-52-3)      | 580.00, Rat    | 2,000.00, Rabbit  | Not Available | Not Available |
| Silica (quartz) - (14808-60-7)  | Not Available  | Not Available     | Not Available | Not Available |
| Talc - (14807-96-6)             | Not Available  | Not Available     | Not Available | Not Available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat | 10,000.00, Rabbit | Not Available | 6.82, Rat     |
| Xylene - (1330-20-7)            | 4,299.00, Rat  | 1,548.00, Rabbit  | Not Available | 20.00, Rat    |

| Item  | Category       | Hazard         |
|---|----------------|----------------|
| Acute Toxicity (mouth)                                      | Not Classified | Not Applicable |
| Acute Toxicity (skin)                                       | Not Classified | Not Applicable |
| Acute Toxicity (inhalation)                                 | Not Classified | Not Applicable |
| Skin corrosion/irritation                                   | Not Classified | Not Applicable |
| Eye damage/irritation                                       | Not Classified | Not Applicable |
| Sensitization (respiratory)                                 | Not Classified | Not Applicable |
| Sensitization (skin)  | Not Classified | Not Applicable |
| Germ toxicity   | Not Classified | Not Applicable |
| Carcinogenicity   | Not Classified | Not Applicable |
| Reproductive Toxicity                                       | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure)   | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard   | Not Classified | Not Applicable |

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

| Ingredient                        | 96 hr LC50 fish, mg/l           | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l                             |
|-----------------------------------|---------------------------------|----------------------------|---|
| Xylene - (1330-20-7)              | 3.30, Oncorhynchus mykiss       | 8.50, Palaemonetes pugio   | 100.00 (72 hr), Chlorococcales                |
| Titanium dioxide - (13463-67-7)   | 1,000.00, Fundulus heteroclitus | 5.50, Daphnia magna        | 5.83 (72 hr), Pseudokirchneriella subcapitata |
| Talc - (14807-96-6)               | Not Available                   | Not Available              | Not Available                                 |
| Epoxy Resin liquid - (25036-25-3) | Not Available                   | Not Available              | Not Available                                 |
| Ethyl Benzene - (100-41-4)        | 4.20, Oncorhynchus mykiss       | 2.93, Daphnia magna        | 3.60 (96 hr), Pseudokirchneriella subcapitata |
| 1-METHOXYPROPAN-2-OL - (107-98-2) | 1,000.00, Oncorhynchus mykiss   | 500.00, Daphnia magna      | 1,000.00 (96 hr), Selenastrum capricornutum   |
| Epoxy Resin - (25068-38-6)        | 3.10, Pimephales promelas       | 1.40, Daphnia magna        | Not Available                                 |
| Barium Sulphate - (7727-43-7)     | 59,000.00, Poecilia sphenops    | 32.00, Daphnia magna       | Not Available                                 |
| Silica (quartz) - (14808-60-7)    | Not Available                   | Not Available              | Not Available                                 |
| Nonylphenol - (25154-52-3)        | 0.135, Pimephales promelas      | 0.104, Daphnia magna       | 1.30 (72 hr), Scenedesmus subspicatus         |

- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

### 13. Disposal considerations

- 13.1. Waste treatment methods

### 14. Transport information

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)

#### Road and Rail Transport

IMDG                      Class/Div                      Sub Class  
reference :

Ems

ICAO/IATA              Class                                      Sub Class

- 14.4. Packing group

- 14.5. Environmental hazards

Road and Rail Environmentally Hazardous:  
Transport

IMDG                      Marine Pollutant:  
reference :

- 14.6. Special precautions for user

No further information

- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15. Regulatory information

The product and all its components complies with these local regulations:

NICNAS - Australia  
EPA - New Zealand

|                             |   |
|-----------------------------|---|
| <b>Korean OHS Act</b>       | See Section 2   |
| <b>Toxic Substances Act</b> | Not Toxic   |
| <b>Dangerous Goods Act</b>  | Class 4 Flammable Liquid, 1st Petroleum Division, Hazard Class II |
| <b>Waste Control Act</b>    | Hazardous Waste   |

## 16. Other information

The information on this SDS is based upon the present state of our knowledge and on current law. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

**This SDS is valid for 5 years from the revised date on page 1.  
The revision date is in American format (e.g. MM/DD/YY).**

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.