

NCA613_A1

Safety Data Sheet CEILCOTE 610 CEILPATCH HARDENER PT B



Bulk Sales Reference No.:
SDS Revision Date:
SDS Revision Number:

Sales
Order: {SalesOrd}
NCA613
02/13/2015
A1-2

1. Identification of the preparation and company

1.1. Product identifier

Product Identity CEILCOTE 610 CEILPATCH HARDENER PT B
Bulk Sales Reference No. NCA613

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Acute Tox. 5;H303 May be harmful if swallowed.
Skin Corr. 1;H314 Causes severe skin burns and eye damage.
Eye Dam. 1;H318 Causes serious eye damage.
Skin Sens. 1;H317 May cause an allergic skin reaction.
Repr. 2;H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H303 May be harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

NCA613_A1

H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe mist / vapors / spray.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+352 IF ON SKIN: Wash with soap and water.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
 P308+313 IF exposed or concerned: Get medical advice/attention.
 P310 Immediately call a POISON CENTER or doctor / physician.
 P312 Call a POISON CENTER or doctor / physician if you feel unwell.
 P314 Get Medical advice / attention if you feel unwell.
 P333 If skin irritation or a rash occurs:.
 P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P363 Wash contaminated clothing before reuse.
 P391 Collect spillage.
 P405 Store locked up.
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3 Flammability: 1 Reactivity: 1

| |
|---|
| 3. Composition/information on ingredients |
|---|

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|--|----------|---|--------|
| Quartz CAS Number: 0014808-60-7 | 25 - 50 | Acute Tox. 4;H332 STOT RE 2;H373 | [1][2] |
| FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENAT CAS Number: 0135108-88-2 | 10 - 25 | Acute Tox. 4;H302 Skin Corr. 1;H314 | [1] |
| Hexylene glycol CAS Number: 0000107-41-5 | 1.0 - 10 | Eye Irrit. 2;H319 Skin Irrit. 2;H315 | [1][2] |
| Tetraethylenepentamine CAS Number: 0000112-57-2 | 1.0 - 10 | Acute Tox. 4;H312 Acute Tox. 4;H302 Skin Corr. 1B;H314 Skin Sens. 1;H317 Aquatic Chronic 2;H411 | [1] |
| Nonylphenol CAS Number: 0025154-52-3 | 1.0 - 10 | Repr. 2;H361fd Acute Tox. 4;H302 Skin Corr. 1B;H314 Aquatic Acute 1;H400 Aquatic Chronic 1;H410 | [1] |
| 2,4,6-Tri(dimethylaminomethyl)phenol CAS Number: 0000090-72-2 | 1.0 - 10 | Acute Tox. 4;H302 Eye Irrit. 2;H319 Skin Irrit. 2;H315 | [1] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

| | |
|------------|---|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. May cause lung injury. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. |

5. Fire-fighting measures

5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO₂, water spray or foam. LARGE FIRES: Use dry chemical, CO₂, water spray, or alcohol-resistant foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

COMBUSTIBLE MATERIAL: May burn but does not ignite readily. When heated, vapors may form explosive mixtures with air. Indoors, outdoors, and low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Contact with metals may evolve flammable hydrogen gas. Containers may explode when heated.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 153

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control. DO NOT GET WATER INSIDE CONTAINERS.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

NCA613_A1

| |
|-------------------------|
| 7. Handling and storage |
|-------------------------|

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

| |
|--|
| 8. Exposure controls and personal protection |
|--|

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|--------------------------------------|-----------|--|
| 0000090-72-2 | 2,4,6-Tri(dimethylaminomethyl)phenol | OSHA | |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | |
| | | Mexico | |
| | | Brazil | |
| 0000107-41-5 | Hexylene glycol | OSHA | 25 ppm Ceiling; 125 mg/m3 Ceiling |
| | | ACGIH | 25 ppm Ceiling |
| | | NIOSH | 25 ppm Ceiling; 125 mg/m3 Ceiling |
| | | Supplier | |
| | | OHSA, CAN | 25 ppm Ceiling |
| | | Mexico | |
| | | Brazil | |
| 0000112-57-2 | Tetraethylenepentamine | OSHA | |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | |
| | | Mexico | |
| | | Brazil | |
| 0014808-60-7 | Quartz | OSHA | |
| | | ACGIH | 0.025 mg/m3 TWA (respirable fraction) |
| | | NIOSH | 0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust) |
| | | Supplier | |
| | | OHSA, CAN | 0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, |

NCA613_A1

| | | | |
|--------------|--|-----------|--|
| | | | crystalline)0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline) |
| | | Mexico | 0.1 mg/m3 TWA LMPE-PPT (respirable fraction) |
| | | Brazil | |
| 0025154-52-3 | Nonylphenol | OSHA | |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | |
| | | Mexico | |
| | | Brazil | |
| 0135108-88-2 | FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENAT | OSHA | |
| | | ACGIH | |
| | | NIOSH | |
| | | Supplier | |
| | | OHSA, CAN | |
| | | Mexico | |
| | | Brazil | |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|----------------------------------|
| 0000090-72-2 | 2,4,6-Tri(dimethylaminomethyl)phenol | NIOSH | |
| 0000107-41-5 | Hexylene glycol | NIOSH | CNS depression; eye skin |
| 0000112-57-2 | Tetraethylenepentamine | NIOSH | |
| 0014808-60-7 | Quartz | NIOSH | Chronic lung disease (silicosis) |
| 0025154-52-3 | Nonylphenol | NIOSH | |
| 0135108-88-2 | FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENAT | NIOSH | |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000090-72-2 | 2,4,6-Tri(dimethylaminomethyl)phenol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000107-41-5 | Hexylene glycol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000112-57-2 | Tetraethylenepentamine | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0014808-60-7 | Quartz | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: Yes; Suspected: No |
| | | IARC | Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0025154-52-3 | Nonylphenol | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0135108-88-2 | FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENAT | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

NCA613_A1

8.2. Exposure controls

| | |
|----------------------|---|
| Respiratory | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

| |
|-------------------------------------|
| 9. Physical and chemical properties |
|-------------------------------------|

| | |
|---|--|
| Appearance | Coloured Liquid |
| Odour threshold | Not Measured |
| pH | 10 |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 143 (°C) 290 (°F) |
| Flash Point | 93 (°C) 200 (°F) |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 1.2 Upper Explosive Limit: No Established Limit |
| vapor pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 1.13 |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | No Established Limit Not Measured |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |

| |
|------------------------------|
| 10. Stability and reactivity |
|------------------------------|

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

NCA613_A1

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

COMBUSTIBLE MATERIAL: May burn but does not ignite readily. When heated, vapors may form explosive mixtures with air. Indoors, outdoors, and low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Contact with metals may evolve flammable hydrogen gas. Containers may explode when heated.

| |
|-------------------------------|
| 11. Toxicological information |
|-------------------------------|

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|--|-----------------------------|---------------------------------|---------------------------------------|---|
| Quartz - (14808-60-7) | No data available | No data available | No data available | No data available |
| FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENAT - (135108-88-2) | 367.00, Rat - Category: 4 | 1,000.00, Rabbit - Category: 3 | No data available | No data available |
| Hexylene glycol - (107-41-5) | 3,700.00, Rat - Category: 5 | 7,892.00, Rabbit - Category: NA | No data available | No data available |
| Tetraethylenepentamine - (112-57-2) | 2,140.00, Rat - Category: 5 | No data available | No data available | No data available |
| Nonylphenol - (25154-52-3) | 580.00, Rat - Category: 4 | 2,000.00, Rabbit - Category: 4 | No data available | No data available |
| 2,4,6-Tri(dimethylaminomethyl)phenol - (90-72-2) | 1,200.00, Rat - Category: 4 | 1,280.00, Rat - Category: 4 | No data available | No data available |

| Item | Category | Hazard |
|---|----------------|--|
| Acute Toxicity (mouth) | 5 | May be harmful if swallowed. |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 1 | Causes severe skin burns and eye damage. |
| Eye damage/irritation | 1 | Causes serious eye damage. |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | 2 | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| Specific target organ systemic toxicity (single exposure) | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | 2 | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | Not Classified | Not Applicable |

| |
|----------------------------|
| 12. Ecological information |
|----------------------------|

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

NCA613_A1

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|--|--------------------------------|----------------------------------|---|
| Quartz - (14808-60-7) | Not Available | Not Available | Not Available |
| FORMALDEHYDE, POLYMER WITH BENZENAMINE, HYDROGENAT - (135108-88-2) | Not Available | Not Available | Not Available |
| Hexylene glycol - (107-41-5) | 10,000.00, Lepomis macrochirus | 2,800.00, Cerodaphnia reticulata | Not Available |
| Tetraethylenepentamine - (112-57-2) | 420.00, Poecilia reticulata | 24.00, Daphnia magna | 2.00 (72 hr), Pseudokirchneriella subcapitata |
| Nonylphenol - (25154-52-3) | 0.135, Pimephales promelas | 0.104, Daphnia magna | 1.30 (72 hr), Scenedesmus subspicatus |
| 2,4,6-Tri(dimethylaminomethyl)phenol - (90-72-2) | Not Available | Not Available | Not Available |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

| |
|-----------------------------|
| 13. Disposal considerations |
|-----------------------------|

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

| |
|---------------------------|
| 14. Transport information |
|---------------------------|

14.1. UN number

UN 2735

14.2. UN proper shipping name

AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS: TETRAETHYLENEPENTAMINE, TRIS-2,4,6-(DIMETHYLAMINOMETHYL) PHENOL)

14.3. Transport hazard class(es)

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|---|-----------------------------------|---|
| DOT Proper Shipping Name | AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS: TETRAETHYLENEPENTAMINE, TRIS-2,4,6-(DIMETHYLAMINOMETHYL) PHENOL) | IMDG Proper Shipping Name | AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS: TETRAETHYLENEPENTAMINE, TRIS-2,4,6-(DIMETHYLAMINOMETHYL) PHENOL) |
| DOT Hazard Class | Class 8, No division Corrosive materials | IMDG Hazard Class | Class 8, No division Corrosive materials Not applicable |
| UN / NA Number | UN 2735 | Sub Class | |

NCA613_A1

DOT Packing III
Group

IMDG III
Packing
Group

CERCLA/DOT Not Applicable gal. / Not Applicable lbs.
RQ

System 219
Reference
Code

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: Yes (Nonylphenol)

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification D2A E

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%):
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

Aluminum oxide

Mass RTK Substances (>1%):

Hexylene glycol

Nonylphenol

Quartz

Tetraethylenepentamine

Penn RTK Substances (>1%):

Hexylene glycol

Nonylphenol

Quartz

Tetraethylenepentamine

Penn Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Hexylene glycol

Quartz

Tetraethylenepentamine

N.J. Special Hazardous Substances (>.01%):

Carbon black

Quartz

Tetraethylenepentamine

N.J. Env. Hazardous Substances (>.1%):

Aluminum oxide

Proposition 65 - Carcinogens (>0%):

Carbon black

Quartz

Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

| |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document