SAFETY DATA SHEET

INTERCURE 4500 RAL 7004 GREY PART A

Section 1. Identification

Г

INTERCURE 4500 RAL 7004 GREY PART A AGQ20W

: GHS product identifier

: Product code

	Identified uses	
Professional application of co-	atings and inks	
Uses a	dvised against	Reason
All Other Uses		
International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden		: Supplier's details
Tel: +46 (0) 31 928500 Fax:	+46 (0) 31 928530	
+46 8 33 12 31		: Emergency telephone number (with hours of operation)
+966 55 388 0087		: <u>National advisory body/</u> <u>Poison Centre (For use only</u> <u>by licensed medical</u> <u>professionals.)</u>
sdsfellinguk@akzonobel.com		: e-mail address of person responsible for this SDS
Section 2. Hazards	s identification	
FLAMMABLE LIQUIDS - Categ SKIN SENSITIZATION - Categ ACUTE AQUATIC HAZARD - (LONG-TERM AQUATIC HAZA	ory 1 Category 3	: Classification of the substance or mixture
GHS label elements		
		: Hazard pictograms
Warning	•	: Signal word
Flammable liquid and vapour. May cause an allergic skin read Harmful to aquatic life with long		: Hazard statements
Precautionary statements		
surfaces, sparks, open flames explosion-proof electrical, venti Use only non-sparking tools. T Keep container tightly closed.	eye or face protection. Keep away fro and other ignition sources. No smokin lating, lighting and all material-handlin ake precautionary measures against s Avoid release to the environment. Avo othing should not be allowed out of the	g. Use g equipment. static discharge. bid breathing
Date of issue/Date of revision	: 07/05/2017	AkzoNobel
Version : 3	1/11	ARZUNUDEI



Section 2. Hazards identification

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention.	: Response
Store in a well-ventilated place. Keep cool.	: Storage
Dispose of contents and container in accordance with all local, regional, national and international regulations.	: Disposal
Wear appropriate respirator when ventilation is inadequate.	: Supplemental label elements
None known.	: Other hazards which do not

None known.

Section 3. Composition/information on ingredients

Mixture

: Substance/mixture

result in classification

Classification	CAS number	% by weight	Ingredient name
Skin Sens. 1, H317	136210-30-5	≥10 - ≤25	tetraethylN,N'-(methylenedicyclohexane-4, 1-diyl)bis-dl-aspartate
Aquatic Chronic 3, H412			
Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	64742-95-6	≥10 - ≤19	Solvent naphtha (petroleum), light arom.
Acute Tox. 4, H302	623-91-6	≤3	diethyl fumarate
Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	41556-26-7	≤0.37	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate
Skin Sens. 1, H317	82919-37-7	≤0.16	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Aquatic Acute 1, H400 Aquatic Chronic 1, H410			

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

: 07/05/2017

- : Eye contact
- : Inhalation



Section 4. First aid measures Wash with plenty of soap and water. Remove contaminated clothing and shoes. : Skin contact Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air : Ingestion and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Most important symptoms/effects, acute and delayed Potential acute health effects No known significant effects or critical hazards. : Eye contact Exposure to decomposition products may cause a health hazard. Serious effects : Inhalation may be delayed following exposure. May cause an allergic skin reaction. : Skin contact No known significant effects or critical hazards. : Ingestion **Over-exposure signs/symptoms** No specific data. : Eye contact Adverse symptoms may include the following: : Inhalation headache drowsiness/fatigue dizziness/vertiao muscle weakness unconsciousness : Skin contact Adverse symptoms may include the following: irritation redness : Ingestion

No specific data.

gloves.

Indication of immediate medical attention and special treatment needed, if necessary

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.	:	Notes to physician
No specific treatment.	:	Specific treatments
No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear	:	Protection of first-aiders

3/11

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Use dry chemical, CO2, water spray (fog) or foam.

Do not use water jet.

- : Suitable extinguishing media
- : Unsuitable extinguishing media



Section 5. Firefighting measures	
Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	: Specific hazards arising from the chemical
Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides	: Hazardous thermal decomposition products
Promptly isolate the scene by removing all persons from the vicinity of the incident i there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.	f : Special protective actions for fire-fighters
Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	: Special protective equipment for fire-fighters
Section 6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	
No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	: For non-emergency personnel
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	: For emergency responders
Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmenta pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.	
Methods and material for containment and cleaning up	
Stop leak if without risk. Move containers from spill area. Use spark-proof tools an explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	d : Small spill
Stop leak if without risk. Move containers from spill area. Use spark-proof tools an explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with nor combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.)-



Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Use only with adequate ventilation. Use process enclosures, local exhaust : Appropriate engineering ventilation or other engineering controls to keep worker exposure to airborne controls contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some controls cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures Wash hands, forearms and face thoroughly after handling chemical products, before : Hygiene measures eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk : Eye/face protection assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Skin protection

5/11

: Protective measures

- : Advice on general occupational hygiene
- : Conditions for safe storage, including any incompatibilities

- : Environmental exposure



Section 8. Exposure controls/personal protection

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.	:	Hand protection
Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.	:	Body protection
Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	:	Other skin protection
Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and	:	Respiratory protection

Section 9. Physical and chemical properties

the safe working limits of the selected respirator.

Appearance	
Liquid.	: Physical state
Grey.	: Colour
Solvent.	: Odour
Not available.	: Odour threshold
Not applicable.	: рН
Not available.	: Melting point
Lowest known value: 140 to 200°C (284 to 392°F)(Solvent naphtha (petroleum), light arom.).	: Boiling point
Closed cup: 50°C (122°F)	: Flash point
Not available.	: Evaporation rate
Not available.	: Flammability (solid, gas)
Greatest known range: Lower: 1.4% Upper: 7.6% (Solvent naphtha (petroleum), light arom.)	: Lower and upper explosive (flammable) limits
Not available.	: Vapour pressure
Not available.	: Vapour density
1.53	: Relative density
Insoluble in the following materials: cold water.	: Solubility
Not available.	: Partition coefficient: n- octanol/water
Not available.	: Auto-ignition temperature
Not available.	: Decomposition temperature
Kinematic (room temperature): 245 mm ² /s (245 cSt)	: Viscosity

X.International.

Section 10. Stability and reactivity

Section 11. Toxicological information	
Under normal conditions of storage and use, hazardous decomposition products should not be produced.	: Hazardous decomposition products
Reactive or incompatible with the following materials: oxidizing materials	: Incompatible materials
Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	: Conditions to avoid
Under normal conditions of storage and use, hazardous reactions will not occur.	: Possibility of hazardous reactions
The product is stable.	: Chemical stability
No specific test data related to reactivity available for this product or its ingredients.	: Reactivity

Information on toxicological effects

Acute toxicity

Exposure	Dose	Species	Result	Product/ingredient name
-	8400 mg/kg	Rat		Solvent naphtha (petroleum), light arom.
-	1780 mg/kg	Rat	LD50 Oral	diethyl fumarate

Irritation/Corrosion

Observation	Exposure	Score	Species	Result	Product/ingredient name
	24 hours 100 microliters	-	Rabbit	Eyes - Mild irritant	Solvent naphtha (petroleum), light arom.

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Target organs	Route of exposure	Category	Name
Respiratory tract irritation and Narcotic effects	Not applicable.	Category 3	Solvent naphtha (petroleum), light arom.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard





Section 11. Toxicological information

U			
Result	Name		
ASPIRATION HAZARD - Category 1	Solvent naphtha (petroleum), light aro	m.	
Not available.		:	Information on likely routes of exposure
Potential acute health effects			
No known significant effects or critical hazards	S.	:	Eye contact
Exposure to decomposition products may cau may be delayed following exposure.	se a health hazard. Serious effects	:	Inhalation
May cause an allergic skin reaction.		:	Skin contact
No known significant effects or critical hazards	5.	:	Ingestion
Symptoms related to the physical, chemica	al and toxicological characteristics		
No specific data.		:	Eye contact
Adverse symptoms may include the following: headache drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness		:	Inhalation
Adverse symptoms may include the following: irritation redness		:	Skin contact
No specific data.		:	Ingestion
Delayed and immediate effects as well as o	chronic effects from short and long-	tern	n exposure
Short term exposure			
Not available.		:	Potential immediate effects
Not available.		:	Potential delayed effects
Long term exposure			
Not available.		:	Potential immediate effects
Not available.		:	Potential delayed effects
Potential chronic health effects			
Not available.			
Once sensitized, a severe allergic reaction ma to very low levels.	ay occur when subsequently exposed	:	General
No known significant effects or critical hazards	5.	:	Carcinogenicity
No known significant effects or critical hazards	S.	:	Mutagenicity
No known significant effects or critical hazards	S.	:	Teratogenicity
No known significant effects or critical hazards	S.	:	Developmental effects
No known significant effects or critical hazards	5.	:	Fertility effects

Numerical measures of toxicity

Acute toxicity estimates

ATE value	Route
155074 mg/kg	Oral

Section 11. Toxicological information

Section 12. Ecological information

<u>Toxicity</u>

Exposure	Species	Result	Product/ingredient name
48 hours	Daphnia	•	Solvent naphtha (petroleum), light arom.
96 hours	Fish - Mykiss	Acute LC50 9.22 mg/m ³	
96 hours	Fish - Pimephales promelas	Acute LC50 4500 µg/l Fresh water	diethyl fumarate

Persistence and degradability

Not available.

Bioaccumulative potential

Potential	BCF	LogPow	Product/ingredient name
low	0.25		tetraethylN,N'- (methylenedicyclohexane-4, 1-diyl)bis-dl-aspartate

Mobility in soil

Not available.

: Soil/water partition coefficient (Koc)

: Other adverse effects

: Disposal methods

No known significant effects or critical hazards.

Section 13. Disposal considerations

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

ΙΑΤΑ	IMDG	UN	
UN1263	UN1263	UN1263	UN number
PAINT	PAINT	PAINT	UN proper shipping name
3	3	3	Transport hazard class(es)

Date of issue/Date of revision Version : 3 : 07/05/2017

K.International.

Section 14. Transport information

	Ш	Ш	Packing group
No.	No.	No.	Environmental hazards
-	-	-	Additional information

Not applicable.

: IMDG Code Segregation group

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Special precautions for user

Not available.

: Transport in bulk according to Annex II of Marpol and the IBC Code

regulations specific for

Safety, health and

environmental

the product

:

Section 15. Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

Justification

Justification	Classification
On basis of test data Calculation method Calculation method Calculation method	Flam. Liq. 3, H226 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
listory	
)7/05/2017	: Date of printing
07/05/2017	Date of issue/Date of revision
02/06/2016	: Date of previous issue
3	: Version
ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a ATA = International Air Transport Association BC = International Air Transport Association MDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff MARPOL = International Convention for the Preventior 1973 as modified by the Protocol of 1978. ("Marpol" = 1 JN = United Nations	icient n of Pollution From Ships,
Not available.	: References
ndicates information that has changed from previo	ously issued version.
Notice to reader	



Section 16. Other information

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel

