In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

SAFETY DATA SHEET

Intercrete 4842 Grey

Section 1. Chemical product and company identification

: Intercrete 4842 Grey A. Product name

Product code : NXA420

B. Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

C. Manufacturer	: International Farg AB Holmedalen 3 Aspereds Industriomrade SE-424 22 Angered Sweden
	Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530
Emergency telephone number (with hours of operation)	: +46 8 33 12 31
e-mail address of person responsible for this SDS	: sdsfellinguk@akzonobel.com

Section 2. Hazards identification

A. Hazard classification	: SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

B. GHS label elements, including precautionary statements :

Symbol

:



Signal word : Danger Hazard statements : Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation.

Precautionary statements



Section 2. Hazards identification

	Prevention	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.	
Response		:	IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.	
	Storage	:	Store locked up.	
	Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.	
	upplemental label ements	:	Wear appropriate respirator when ventilation is inadequate.	
C.	Other hazards which do not result in	:	May form explosible dust-air mixture if dispersed. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes,	

Section 3. Composition/information on ingredients

skin, nose and throat.

Substance/mixture

classification

: Mixture

Ingredient name	Common name	CAS number	%	Classification
crystalline silica, respirable powder	silica, crystalline - quartz	14808-60-7	≥40 - <50	Carc. 1A, H350
Cement, portland, chemicals	Portland cement mixture	65997-15-1	≥20 - <30	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335
glass, oxide, chemicals	glass, oxide, chemicals	65997-17-3	<10	Carc. 1B, H350
calcium dihydroxide	calcium hydroxide	1305-62-0	<10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412
Calcium aluminate sulphate	Aluminum calcium oxide sulfate	12005-25-3	≥1 - <5	Skin Sens. 1, H317
sodium nitrite	sodium nitrite	7632-00-0	<1	Ox. Sol. 2, H272 Acute Tox. 3, H301 Aquatic Acute 1, H400
crystalline silica, respirable powder	Respirable content of crystalline silica in whole product	14808-60-7	<10	Carc. 1A, H350
				STOT RE 1, H372

:

AkzoNobel

X.International.

Section 3. Composition/information on ingredients

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Α.	Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
В.	Skin contact	:	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
C.	Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
D.	Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
E.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

			-
Α.	Extinguishing media		
	Suitable extinguishing media	:	Use dry chemical powder.
	Unsuitable extinguishing media	:	Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture.
В.	Specific hazards arising from the chemical	:	May form explosible dust-air mixture if dispersed.
	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides
C.	Special protective equipment for fire- fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Special precautions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Section 6. Accidental release measures

Α.	Personal precautions, protective equipment and emergency procedures	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
В.	Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
С.	Methods and material for o	co	ntainment and cleaning up
	Small spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
	Large spill	:	Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Avoid creating dusty conditions and prevent wind dispersal. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.



Section 7. Handling and storage

Α.	Precautions for safe handling				
	Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe dust. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.			
	Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.			
В.	Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.			

Section 8. Exposure controls/personal protection

A. <u>Control parameters</u>

Occupational exposure limits

Ingredient name	Exposure limits
crystalline silica, respirable powder	Ministry of Labor (Republic of Korea, 8/2013).
	TWA: 0.05 mg/m ³ 8 hours. Form:
	Respirable fraction
Cement, portland, chemicals	Ministry of Labor (Republic of Korea,
	8/2013).
	TWA: 10 mg/m ³ 8 hours. Form: total dust
	with less than 1% of free SiO2
glass, oxide, chemicals	Ministry of Labor (Republic of Korea,
	8/2013).
	TWA: 10 mg/m ³ 8 hours. Form: fibers
calcium dihydroxide	Ministry of Labor (Republic of Korea,
	8/2013).
	TWA: 5 mg/m ³ 8 hours.
crystalline silica, respirable powder	Ministry of Labor (Republic of Korea,
	8/2013).
	TWA: 0.05 mg/m ³ 8 hours. Form:
	Respirable fraction



X.International.

S	Section 8. Exposure controls/personal protection				
B. Appropriate engineering controls		:	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.		
	Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
C.	Personal protective equip	ome	ent		
	Respiratory protection	:	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.		
	Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.		
	Hand protection	:	Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.		
	Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
	Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		

Section 9. Physical and chemical properties

Α.	Appearance		
	Physical state	:	Solid. [Powder.]
	Colour	:	Grey.
В.	Odour	:	Mild.
C.	Odour threshold	:	Not available.
D.	рН	:	Not applicable.
Ε.	Melting/freezing point	:	Not available.





%International.

Section 9. Physical and chemical properties

F.	Boiling point/boiling range	:	Not available.
G.	Flash point	:	Closed cup: Not applicable. [Product does not sustain combustion.]
	Fire point	:	Not available.
Н.	Evaporation rate	:	Not available.
I.	Flammability (solid, gas)	:	Not available.
J.	Lower and upper explosive (flammable) limits	:	Not applicable.
Κ.	Vapour pressure	:	Not available.
L.	Solubility	:	Insoluble in the following materials: cold water.
Μ.	Vapour density	:	Not available.
Ν.	Relative density	:	1.99
0.	Partition coefficient: n- octanol/water	:	Not available.
Ρ.	Auto-ignition temperature	:	Not available.
Q.	Decomposition temperature	:	Not available.
R.	Viscosity	:	Kinematic (room temperature): Not applicable.
S.	Molecular weight	:	Not applicable.

Section 10. Stability and reactivity

Α.	Chemical stability	:	The product is stable.
	Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
В.	Conditions to avoid	:	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Prevent dust accumulation.
C.	Incompatible materials	:	Reactive or incompatible with the following materials: oxidizing materials
D.	Hazardous	:	Under normal conditions of storage and use, hazardous decomposition products

decomposition products should not be produced.

Section 11. Toxicological information

Α.	Information on likely routes of exposure	:	Not available.
	Potential acute health eff	ect	<u>s</u>
	Inhalation	:	May cause respiratory irritation.
	Ingestion	:	Irritating to mouth, throat and stomach.
	Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.
	Eye contact	:	Causes serious eye damage.
	Over-exposure signs/sym	npt	<u>oms</u>





Section 11. Toxicological information

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Ingestion	: Adverse symptoms may include the following: stomach pains
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	: Adverse symptoms may include the following: pain watering redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
calcium dihydroxide	LD50 Oral	Rat	7340 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
calcium dihydroxide sodium nitrite	Eyes - Severe irritant Eyes - Mild irritant	Rabbit Rabbit	-	10 milligrams 24 hours 500 milligrams	-

Sensitisation

Not available.

CMR - ISHA Article 42 Public Notice No 2013-38 Occupational Exposure Limits

Product/ingredient name	CAS number	Classification
Silica (Crystalline quartz)	14808-60-7	Carc. 1A
Mineral wool fiber	65997-17-3	Carc. 2
Silica (Crystalline quartz)	14808-60-7	Carc. 1A

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

:

Version 3 :

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Cement, portland, chemicals	Category 3		Respiratory tract irritation
calcium dihydroxide	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

K.International.

Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
crystalline silica, respirable powder	Category 1	Not determined	Not determined

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not available.	
General	 Repeated or prolonged inhalation of dust may lead to chronic respiratory irritation. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

ATE value

Route	Result	
Oral	20000 mg/kg	

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
calcium dihydroxide	Acute LC50 33884.4 µg/l Fresh water	Fish - Clarias gariepinus - Fingerling	96 hours
sodium nitrite	Acute EC50 159000 µg/l Marine water	Algae - Tetraselmis chuii	72 hours
	Acute EC50 1600000 µg/l Marine water	Algae - Tetraselmis chuii	96 hours
	Acute LC50 1100 µg/l Fresh water	Crustaceans - Cherax quadricarinatus	48 hours
	Acute LC50 48 µg/l Fresh water	Fish - Ictalurus punctatus - Fingerling	96 hours
	Chronic NOEC 0.912 mg/l Marine water	Fish - Hippocampus abdominalis - Juvenile (Fledgling, Hatchling, Weanling)	35 days

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential	
sodium nitrite	-3.7	-	low	

D. Mobility in soil

:

Soil/water partition : Not available. coefficient (Koc)

Date of issue/Date of revision: 25/04/2017Version3:

Section 12. Ecological information

Section 13. Disposal considerations

A. Disposal methods	 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
B. Disposal precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of

spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
A. UN number	Not regulated.	Not regulated.	Not regulated.
B. UN proper shipping name	-	-	-
C. Transport hazard class(es)	-	-	-
D. Packing group	-	-	-
E. Environmental hazards	No.	No.	No.
F. Additional information	-	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.

IMDG Code Segregation : Not applicable. group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do it is the person of the person of

upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

A. <u>Regulation according to ISHA</u>

1

ISHA article 37 : None of the components are listed. (Harmful substances prohibited from manufacture)





Section 15. Regulatory information

	ootion iei itogaa			
. <u> </u>	ISHA article 38 (Harmful substances	:	None of the components are listed.	
	requiring permission)			
	Article 2 of Youth Protection Act on Substances Hazardous to Youth	:	Not applicable.	
	Exposure Limits of Chemical Substances and Physical Factors			
	The following components have an OEL: crystalline silica, respirable powder Cement, portland, chemicals glass, oxide, chemicals calcium dihydroxide crystalline silica, respirable powder			
	ISHA Enforcement Regs Annex 11-3 (Exposure standards established for harmful factors)	:	None of the components are listed.	
	ISHA Enforcement Regs Annex 11-4 (Harmful factors subject to Work Environment Measurement)	:	The following components are listed: Aluminum compounds; Portland cement; Quartz	
	•	:	The following components are listed: Aluminum and compounds	
	Standard of Industrial Safety and Health Annex 12 (Hazardous substances subject to control)	:	The following components are listed: Aluminum and its compounds	
В.	Regulation according to	<u>Ch</u>	emicals Control Act	
	K-Reach Article 20 (Toxic chemicals)	:	Not applicable	
	K-Reach Article 27 (Prohibited)		None of the components are listed.	
	K-Reach Article 27 (Restricted)		None of the components are listed.	
	CSCA Article 11 (TRI)		The following components are listed: Aluminium and its compounds	
	Korea inventory	:	Not determined.	
	CSCA Article 39 (Accident Precaution Chemicals)	:	None of the components are listed.	
C.	Dangerous Materials Safety Management Act	:	Not available.	
	Wastes regulation		Dispose of contents and container in accordance with all local, regional, national and international regulations.	
Ε.	Regulation according to	<u>oth</u>	ner foreign laws	
	Europe inventory	:	Not determined.	
	United States inventory (TSCA 8b)	:	Not determined.	

:

AkzoNobel

X.International.

Section 15. Regulatory information

Japan inventory

: Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.

Section 16. Other information

Α.	References	:	Not available.			
В.	Date of issue/Date of revision	:	25/04/2017			
C.	Version	:	3			
	Date of printing	:	25/04/2017			
D.	Other					
	Indicates information that has changed from previously issued version.					
	Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations			

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel

AkzoNobel