In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

SAFETY DATA SHEET

Interline 925 White Part B

S	ection 1. Chemic	al	product and com	pany identification
Α.	Product name	:	Interline 925 White Part B	
	Product code	:	THA127	
	Identified uses	:	Professional application of coal Industrial application of coatin	
В.	Relevant identified uses	of t	he substance or mixture and	<u>uses advised against</u>
	Not applicable.			
C.	Manufacturer	:	International Paint Ltd. Stoneygate Lane Felling Gateshead Tyne and Wear NE10 0JY UK Tel: +44 (0)191 469 6111	Fax: +44 (0)191 438 3711
	Emergency telephone number (with hours of operation)	:	+44 (0)191 469 6111 (24H)	
	-mail address of person esponsible for this SDS	:	sdsfellinguk@akzonobel.com	

Section 2. Hazards identification

A. Hazard classification	: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	AQUATIC TOXICITY (CHRONIC) - Category 3

B. <u>GHS label elements, including precautionary statements</u> Symbol :



Signal word	:	Danger
Hazard statements		Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
Precautionary statements	5	
Prevention	:	Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour or spray. Avoid breathing vapour. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.



Section 2. Hazards identification

Response	: Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

C. Other hazards which do : None known. not result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	Common name	CAS number	%	Classification
Quartz (SiO2)	silica, crystalline - quartz	14808-60-7	>=30 - <40	Not classified.
3-aminomethyl-3,5,	3-aminomethyl-3,5,	2855-13-2	>=20 - <30	Acute Tox. 4, H302
5-trimethylcyclohexylamine	5-trimethylcyclohexylamine			Acute Tox. 4, H312
				Skin Corr. 1, H314
				Skin Sens. 1, H317
				Aquatic Chronic 3,
				H412
Quartz (SiO2)	Respirable content of crystalline silica in whole product	14808-60-7	>=10 - <20	STOT RE 2, H373
2,2'-dimethyl-4,4'-methylenebis	2,2'-dimethyl-4,	6864-37-5	<10	Acute Tox. 4, H302
(cyclohexylamine)	4'methylenebis			Acute Tox. 3, H311
	(cyclohexylamine)			Acute Tox. 2, H330
				Skin Corr. 1, H314
				Aquatic Chronic 2,
				H411

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

A. Eye contact

٠

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.



Section 4. First-aid measures

В.	Skin contact	:	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
C.	Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
D.	Ingestion	:	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
E.	Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Α.	Extinguishing media		
	Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
	Unsuitable extinguishing media	:	None known.
В.	Specific hazards arising from the chemical	:	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.



Section 5. Fire-fighting measures

	Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
C.	Special protective	:	Fire-fighters should wear appropriate protective equipment and self-contained

equipment for fire-
fightersbreathing apparatus (SCBA) with a full face-piece operated in positive pressure
mode.Special precautions for
fire-fightersPromptly isolate the scene by removing all persons from the vicinity of the incident if
there is a fire. No action shall be taken involving any personal risk or without
suitable training.

Section 6. Accidental release measures

Α.	Personal precautions, protective equipment and emergency procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
В.	Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
C.	Methods and materials for	containment and cleaning up
	Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
	Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Α.	Precautions for safe hand	ling
	Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
	Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.



Section 7. Handling and storage

- B. Conditions for safe storage, including any incompatibilities
- : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

A. <u>Control parameters</u>

Occupational exposure limits

Ingredient name	Exposure limits
	Ministry of Labor (Republic of Korea, 3/2012). TWA: 0.05 mg/m ³ 8 hours. Form: Respirable fraction

В.	Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
	Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

C. Personal protective equipment

Respiratory protection	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Hand protection	:	Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

٠



X.International.

Section 8. Exposure controls/personal protection

```
Hygiene measures
```

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9. Physical and chemical properties

Α.	<u>Appearance</u>		
	Physical state	:	Liquid.
	Colour	:	White.
В.	Odour	:	Amine-like.
C.	Odour threshold	:	Not available.
D.	рН	:	Not applicable.
Ε.	Melting/freezing point	:	Not available.
F.	Boiling point/boiling range	:	Lowest known value: 247°C (476.6°F) (3-aminomethyl-3,5, 5-trimethylcyclohexylamine).
G.	Flash point	:	Closed cup: 101°C (213.8°F)
Н.	Evaporation rate	:	Not available.
I.	Flammability (solid, gas)	:	Not available.
J.	Lower and upper explosive (flammable) limits	:	Not available.
Κ.	Vapour pressure	:	Not available.
L.	Solubility	:	Insoluble in the following materials: cold water.
Μ.	Vapour density	:	Not available.
Ν.	Relative density	:	1.63
0.	Partition coefficient: n- octanol/water	:	Not available.
Ρ.	Auto-ignition temperature	:	Not available.
Q.	Decomposition temperature	:	Not available.
R.	Viscosity	:	Kinematic (room temperature): 337 mm ² /s (337 cSt)
S.	Molecular weight	:	Not applicable.

Section 10. Stability and reactivity

Α.	Chemical stability Possibility of hazardous reactions		The product is stable. Under normal conditions of storage and use, hazardous reactions will not occur.
в.	Conditions to avoid	:	No specific data.
C.	Incompatible materials	:	No specific data.
D.	Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

٠

Α.

Section 11. Toxicological information

Information on the likely routes of exposure	:	Not available.
Potential acute health effe	ect	<u>s</u>
Inhalation	:	Harmful if inhaled. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	:	Harmful if swallowed. May cause burns to mouth, throat and stomach.
Skin contact	:	Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	:	Causes serious eye damage.
Over-exposure signs/sym	pt	oms
Inhalation	:	No specific data.
Ingestion	:	Adverse symptoms may include the following: stomach pains
Skin contact	:	Adverse symptoms may include the following: pain or irritation redness blistering may occur
Eye contact	:	Adverse symptoms may include the following: pain watering redness

B. Health hazards

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	LC50 Inhalation Dusts and mists	Rat	420 mg/m ³	4 hours
(0)0.0.19.2.1.1.0)	LD50 Dermal	Rabbit	200 mg/kg	-
	LD50 Oral	Rat	320 mg/kg	-
	LOAEL Oral	Rat	12 mg/kg	-
	NOAEL Oral	Rat	2.5 mg/kg	-

Irritation/Corrosion

Not available.

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision : 04/08/2014.

:

AkzoNobel



Section 11. Toxicological information

Name	·····	Route of exposure	Target organs
Quartz (SiO2)	Category 2	Not determined	Not determined

Aspiration hazard

Not available.

Potential chronic health effects

Chronic toxicity

Not	avai	lable.
-----	------	--------

General	:	May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

ATE value

Route	Result
Oral	1287.1 mg/kg
Dermal	1938.7 mg/kg
Inhalation (dusts and mists)	4.939 mg/l

Section 12. Ecological information

A. Ecotoxicity

Product/ingredient name	Result	Species	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Acute EC50 17.4 to 21.5 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

B. Persistence and degradability

Not available.

C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	0.99	-	low
2,2'-dimethyl-4,4'- methylenebis (cyclohexylamine)	2.5	<60	low

D. Mobility in soil

:

Soil/water partition	: Not available.
coefficient (Koc)	

E. Other adverse effects : No known significant effects or critical hazards.



Section 13. Disposal considerations

A. Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

B. Disposal precautions
This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	ΙΑΤΑ		
A. UN number	UN3066	UN3066	UN3066		
B. UN proper shipping name	PAINT	PAINT	PAINT 8		
C. Transport hazard class(es)	8	8			
D. Packing group	I	Ш	11		
E. Environmental hazards	No.	No.	No.		
F. Additional information	-	-	-		

IMDG Code Segregation : Not applicable. group

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

A. <u>Regulation according to ISHA</u> **ISHA Article 37** : None of the components are listed. **ISHA Article 38** : None of the components are listed. Article 2 of Youth : Not applicable. **Protection Act on Substances Hazardous** to Youth **Exposure Limits of Chemical Substances and Physical Factors** The following components have an OEL: Quartz (SiO2) **Exposure Standards** : None of the components are listed. established for Harmful Factors

•



Section 15. Regulatory information

	foction i of i togate		
	Harmful Factors Subject to Work Environment Measurement	:	The following components are listed: Quartz; Quartz
	Harmful Factors Subject to Special Health Check- up	:	None of the components are listed.
	Hazardous Substances Subject to Control	:	None of the components are listed.
В.	Regulation according to 1	ГС	<u>CA</u>
	TCCA Toxic chemicals	:	Not applicable
	TCCA Observational chemicals	:	None of the components are listed.
	TCCA Article 32 (Banned)	:	None of the components are listed.
	TCCA Article 32 (Restricted)	:	None of the components are listed.
	TCCA Article 17 (TRI)	:	The following components are listed: Barium and its compounds
	Korea inventory	:	Not determined.
	Accident Precaution chemicals	:	None of the components are listed.
C.	Dangerous Materials Safety Management Act	:	Not available.
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ε.	Regulation according to other foreign laws		
	Europe inventory	:	Not determined.
	United States inventory (TSCA 8b)	:	Not determined.
	Japan inventory	:	Not determined.
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).

Section 16. Other information

Α.	References	:	Not available.			
В.	Date of issue/Date of revision	:	04/08/2014.			
C.	Version	:	1			
	Date of printing	:	04/08/2014.			
D.	Other					
	Indicates information that has changed from previously issued version.					
	Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations			



Section 16. Other information

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

AkzoNobel