

# SAFETY DATA SHEET

## CEILCOTE CEILLINE BC HORIZONTAL PART A

### Section 1. Identification

**CEILCOTE CEILLINE BC HORIZONTAL PART A**  
**NCA045**

: GHS product identifier  
 : Product code

| Identified uses                               |        |
|---|--------|
| Professional application of coatings and inks |        |
| Uses advised against                          | Reason |
| All Other Uses                                |        |

International Farg AB  
 Holmedalen 3  
 Aspereds Industriområde  
 SE-424 22 Angered  
 Sweden

: **Supplier's details**

Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

+46 8 33 12 31

: **Emergency telephone number (with hours of operation)**

+966 55 388 0087

: **National advisory body/ Poison Centre (For use only by licensed medical professionals.)**

sdsfellinguk@akzonobel.com

: **e-mail address of person responsible for this SDS**

### Section 2. Hazards identification

FLAMMABLE LIQUIDS - Category 3  
 SKIN CORROSION/IRRITATION - Category 2  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
 SKIN SENSITIZATION - Category 1  
 TOXIC TO REPRODUCTION (Fertility) - Category 2  
 TOXIC TO REPRODUCTION (Unborn child) - Category 2  
 ACUTE AQUATIC HAZARD - Category 2  
 LONG-TERM AQUATIC HAZARD - Category 2

: **Classification of the substance or mixture**

#### GHS label elements



: **Hazard pictograms**

Warning

: **Signal word**

Flammable liquid and vapour.

: **Hazard statements**

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Toxic to aquatic life with long lasting effects.

## Section 2. Hazards identification

### Precautionary statements

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid release to the environment. Avoid breathing vapour. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. : **Prevention**

Collect spillage. IF exposed or concerned: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. : **Response**

Store locked up. Store in a well-ventilated place. Keep cool. : **Storage**

Dispose of contents and container in accordance with all local, regional, national and international regulations. : **Disposal**

:

**Supplemental label elements**

None known.

: **Other hazards which do not result in classification**

## Section 3. Composition/information on ingredients

Mixture : **Substance/mixture**

| Classification  | CAS number | % by weight | Ingredient name  |
|---|------------|-------------|--|
| Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411   | 25068-38-6 | ≥10 - ≤25   | reaction product: bisphenol-A-(epichlorhydrin); epoxy resin                            |
| Flam. Liq. 3, H226<br>Acute Tox. 5, H303<br>Acute Tox. 4, H332<br>Eye Irrit. 2B, H320   | 110-12-3   | ≤10         | 5-methylhexan-2-one  |
| Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Skin Sens. 1, H317  | 25068-38-6 | ≤3          | Reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin, 700 <mol weight < 1000 |
| Acute Tox. 4, H302<br>Skin Corr. 1B, H314<br>Repr. 2, H361fd (Fertility and Unborn child)<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 | 84852-15-3 | <2.5        | 4-nonylphenol, branched  |

**There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

|   |                       |
|---|-----------------------|
| Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.   | : <b>Eye contact</b>  |
| Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.  | : <b>Inhalation</b>   |
| Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.   | : <b>Skin contact</b> |
| Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. | : <b>Ingestion</b>    |

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

|  |                       |
|--|-----------------------|
| Causes serious eye irritation.                               | : <b>Eye contact</b>  |
| No known significant effects or critical hazards.            | : <b>Inhalation</b>   |
| Causes skin irritation. May cause an allergic skin reaction. | : <b>Skin contact</b> |
| Irritating to mouth, throat and stomach.                     | : <b>Ingestion</b>    |

#### Over-exposure signs/symptoms

|  |                       |
|--|-----------------------|
| Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness   | : <b>Eye contact</b>  |
| Adverse symptoms may include the following:<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations                          | : <b>Inhalation</b>   |
| Adverse symptoms may include the following:<br>irritation<br>redness<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations | : <b>Skin contact</b> |
| Adverse symptoms may include the following:<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations                          | : <b>Ingestion</b>    |

### Indication of immediate medical attention and special treatment needed, if necessary

## Section 4. First aid measures

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

: Notes to physician

No specific treatment.

: Specific treatments

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

: Protection of first-aiders

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

: Suitable extinguishing media

Do not use water jet.

: Unsuitable extinguishing media

Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

: Specific hazards arising from the chemical

Decomposition products may include the following materials:

carbon dioxide  
carbon monoxide  
metal oxide/oxides

: Hazardous thermal decomposition products

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

: Special protective actions for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

: Special protective equipment for fire-fighters

## Section 6. Accidental release measures

### **Personal precautions, protective equipment and emergency procedures**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

: For non-emergency personnel

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

: For emergency responders

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

: Environmental precautions

### Methods and material for containment and cleaning up

## Section 6. Accidental release measures

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. : **Small spill**

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. : **Large spill**

## Section 7. Handling and storage

### Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. : **Protective measures**

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. : **Advice on general occupational hygiene**

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. : **Conditions for safe storage, including any incompatibilities**

## Section 8. Exposure controls/personal protection

### Control parameters

### Occupational exposure limits

## Section 8. Exposure controls/personal protection

| Exposure limits  | Ingredient name     |
|--|---------------------|
| <b>ACGIH TLV (United States, 3/2015).</b><br>TWA: 93 mg/m <sup>3</sup> 8 hours.<br>TWA: 20 ppm 8 hours.<br>STEL: 50 ppm 15 minutes.<br>STEL: 234 mg/m <sup>3</sup> 15 minutes. | 5-methylhexan-2-one |

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

: **Appropriate engineering controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

: **Environmental exposure controls**

### **Individual protection measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

: **Hygiene measures**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

: **Eye/face protection**

### **Skin protection**

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

: **Hand protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

: **Body protection**

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

: **Other skin protection**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

: **Respiratory protection**

## Section 9. Physical and chemical properties

### Appearance

|   |  |
|---|--|
| Liquid.   | : Physical state                               |
| Grey.   | : Colour                                       |
| Solvent.  | : Odour  |
| Not available.  | : Odour threshold                              |
| Not applicable.   | : pH   |
| Not available.  | : Melting point                                |
| Not available.  | : Boiling point                                |
| Closed cup: 36°C (96.8°F)   | : Flash point                                  |
| Not available.  | : Evaporation rate                             |
| Not available.  | : Flammability (solid, gas)                    |
| Greatest known range: Lower: 1.8% Upper: 9% (5-methylhexan-2-one) | : Lower and upper explosive (flammable) limits |
| Not available.  | : Vapour pressure                              |
| Not available.  | : Vapour density                               |
| 1.07  | : Relative density                             |
| Insoluble in the following materials: cold water.                 | : Solubility                                   |
| Not available.  | : Partition coefficient: n-octanol/water       |
| Not available.  | : Auto-ignition temperature                    |
| Not available.  | : Decomposition temperature                    |
| Kinematic (room temperature): 9784 mm <sup>2</sup> /s (9784 cSt)  | : Viscosity                                    |

## Section 10. Stability and reactivity

|   |                                      |
|---|--------------------------------------|
| No specific test data related to reactivity available for this product or its ingredients.  | : Reactivity                         |
| The product is stable.  | : Chemical stability                 |
| Under normal conditions of storage and use, hazardous reactions will not occur.   | : Possibility of hazardous reactions |
| Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. | : Conditions to avoid                |
| Reactive or incompatible with the following materials:<br>oxidizing materials   | : Incompatible materials             |
| Under normal conditions of storage and use, hazardous decomposition products should not be produced.  | : Hazardous decomposition products   |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Exposure | Dose       | Species | Result    | Product/ingredient name |
|----------|------------|---------|-----------|-------------------------|
| -        | 3200 mg/kg | Rat     | LD50 Oral | 5-methylhexan-2-one     |
| -        | 1300 mg/kg | Rat     | LD50 Oral | 4-nonylphenol, branched |

#### Irritation/Corrosion

## Section 11. Toxicological information

| Observation | Exposure                 | Score | Species | Result                   | Product/ingredient name                                     |
|-------------|--------------------------|-------|---------|--------------------------|---|
| -           | 100 milligrams           | -     | Rabbit  | Eyes - Mild irritant     | reaction product: bisphenol-A-(epichlorhydrin); epoxy resin |
| -           | 24 hours 20 milligrams   | -     | Rabbit  | Eyes - Moderate irritant |   |
| -           | 24 hours 5 milligrams    | -     | Rabbit  | Eyes - Severe irritant   |   |
| -           | 24 hours 500 microliters | -     | Rabbit  | Skin - Moderate irritant |   |
| -           | 24 hours 2 milligrams    | -     | Rabbit  | Skin - Severe irritant   |   |
| -           | 24 hours 100 microliters | -     | Rabbit  | Eyes - Mild irritant     | 5-methylhexan-2-one   |
| -           | 100 milligrams           | -     | Rabbit  | Eyes - Severe irritant   | 4-nonylphenol, branched                                     |
| -           | 24 hours 500 milligrams  | -     | Rabbit  | Skin - Severe irritant   |   |

### **Sensitisation**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

### **Specific target organ toxicity (single exposure)**

Not available.

### **Specific target organ toxicity (repeated exposure)**

Not available.

### **Aspiration hazard**

Not available.

Not available.

: Information on likely routes of exposure

### **Potential acute health effects**

Causes serious eye irritation.

: Eye contact

No known significant effects or critical hazards.

: Inhalation

Causes skin irritation. May cause an allergic skin reaction.

: Skin contact

Irritating to mouth, throat and stomach.

: Ingestion

### **Symptoms related to the physical, chemical and toxicological characteristics**

Adverse symptoms may include the following:

: Eye contact

pain or irritation

watering

redness



## Section 11. Toxicological information

Adverse symptoms may include the following: : Inhalation  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations

Adverse symptoms may include the following: : Skin contact  
 irritation  
 redness  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations

Adverse symptoms may include the following: : Ingestion  
 reduced foetal weight  
 increase in foetal deaths  
 skeletal malformations

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Short term exposure**

Not available. : Potential immediate effects  
 Not available. : Potential delayed effects

**Long term exposure**

Not available. : Potential immediate effects  
 Not available. : Potential delayed effects

**Potential chronic health effects**

Not available.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. : General

No known significant effects or critical hazards. : Carcinogenicity  
 No known significant effects or critical hazards. : Mutagenicity  
 Suspected of damaging the unborn child. : Teratogenicity  
 No known significant effects or critical hazards. : Developmental effects  
 Suspected of damaging fertility. : Fertility effects

**Numerical measures of toxicity**

**Acute toxicity estimates**

| ATE value     | Route                |
|---------------|----------------------|
| 26434.3 mg/kg | Oral                 |
| 132.9 mg/l    | Inhalation (vapours) |

## Section 12. Ecological information

**Toxicity**

## Section 12. Ecological information

| Exposure | Species  | Result                               | Product/ingredient name                        |
|----------|--|--------------------------------------|--|
| 96 hours | Fish - Pimephales promelas   | Acute LC50 159000 µg/l Fresh water   | 5-methylhexan-2-one<br>4-nonylphenol, branched |
| 72 hours | Algae - Skeletonema costatum   | Acute EC50 0.03 mg/l Marine water    |  |
| 96 hours | Algae - Skeletonema costatum   | Acute EC50 0.027 mg/l Marine water   |  |
| 48 hours | Crustaceans - Americamysis bahia - Juvenile (Fledgling, Hatchling, Weanling) | Acute LC50 0.047 mg/l Marine water   |  |
| 96 hours | Fish - Pleuronectes americanus - Larvae                                      | Acute LC50 17 µg/l Marine water      |  |
| 96 hours | Algae - Skeletonema costatum   | Chronic EC10 0.012 mg/l Marine water |  |
| 33 days  | Fish - Pimephales promelas - Embryo  | Chronic NOEC 7.4 µg/l Fresh water    |  |

### Persistence and degradability

| Biodegradability | Photolysis | Aquatic half-life | Product/ingredient name                                     |
|------------------|------------|-------------------|---|
| Not readily      | -          | -                 | reaction product: bisphenol-A-(epichlorhydrin); epoxy resin |

### Bioaccumulative potential

| Potential | BCF          | LogP <sub>ow</sub> | Product/ingredient name                                     |
|-----------|--------------|--------------------|---|
| low       | -            | 2.64 to 3.78       | reaction product: bisphenol-A-(epichlorhydrin); epoxy resin |
| low       | -            | 1.88               | 5-methylhexan-2-one   |
| low       | 251.18864315 | 5.4                | 4-nonylphenol, branched                                     |

### Mobility in soil

Not available.

: Soil/water partition coefficient (K<sub>oc</sub>)

No known significant effects or critical hazards.

: Other adverse effects

## Section 13. Disposal considerations





The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

: Disposal methods

## Section 14. Transport information

| IATA   | IMDG   | UN   |                            |
|--|--|--|----------------------------|
| UN1263   | UN1263   | UN1263   | UN number                  |
| PAINT  | PAINT. Marine pollutant (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin, 4-nonylphenol, branched)   | PAINT  | UN proper shipping name    |
| 3<br>                   | 3<br>  | 3<br> | Transport hazard class(es) |
| III  | III  | III  | Packing group              |
| No.  | Yes.   | No.  | Environmental hazards      |
| The environmentally hazardous substance mark may appear if required by other transportation regulations. | The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.  | -  | Additional information     |

Not applicable.

: IMDG Code Segregation group

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

: Special precautions for user

Not available.

: Transport in bulk according to Annex II of Marpol and the IBC Code

## Section 15. Regulatory information

No known specific national and/or regional regulations applicable to this product (including its ingredients).

: Safety, health and environmental regulations specific for the product

## Section 16. Other information

### Justification

| Justification         | Classification               |
|-----------------------|------------------------------|
| On basis of test data | Flam. Liq. 3, H226           |
| Calculation method    | Skin Irrit. 2, H315          |
| Calculation method    | Eye Irrit. 2A, H319          |
| Calculation method    | Skin Sens. 1, H317           |
| Calculation method    | Repr. 2, H361 (Fertility)    |
| Calculation method    | Repr. 2, H361 (Unborn child) |
| Calculation method    | Aquatic Acute 2, H401        |
| Calculation method    | Aquatic Chronic 2, H411      |

### History

31/05/2017

: Date of printing

31/05/2017

:

## Section 16. Other information

10/06/2016

3

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Not available.

Date of issue/Date of revision

: Date of previous issue

: Version

: Key to abbreviations

: References

Indicates information that has changed from previously issued version. 

### Notice to reader

**IMPORTANT NOTE:** the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel