Material Safety Data Sheet BAR-RUST 231 FLINT GREY KIT

Sales

 $Order: \{SalesOrd\}$

Bulk Sales Reference No.: DC231K2505
MSDS Revision Date: 08/22/2012
MSDS Revision Number: 0-2



1. Identification of the preparation and company

Product Identity BAR-RUST 231 FLINT GREY KIT

Bulk Sales Reference No. DC231K2505

Company Name International Paint LLC

6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product







Danger

GHS Classification;

| Item | Category | Hazard |
|---|----------------|---|
| Flammability | 3 | Flammable liquid and vapor |
| Acute Toxicity (mouth) | Not classified | Not applicable |
| Acute Toxicity (skin) | Not classified | Not applicable |
| Acute Toxicity (inhalation) | Not classified | Not applicable |
| Acute Toxicity (ingestion) | Not classified | Not applicable |
| Skin corrosion/irritation | Not classified | Not applicable |
| Eye damage/irritation | 1 | Causes serious eye damage |
| Sensitization (respiratory) | Not classified | Not applicable |
| Sensitization (skin) | 1 | May cause allergic reaction. |
| Germ toxicity | Not classified | Not applicable |
| Specific target organ systemic toxicity (single exposure) | 1 | respiratory system |
| | 2 | Not applicable |
| | 3 | narcotic effects, respiratory tract irritation |
| Specific target organ systemic Toxicity (repeated exposure) | 1 | auditory apparatus, central nerve system, lung, systemic toxicity |
| | 2 | kidneys, liver, respiratory system |
| Aspiration hazard | Not classified | Not applicable |
| Harmfulness to aquatic Environment (acute) | 3 | Harmful to aquatic life. |
| Harmfulness to aquatic Environment (long term effect) | 4 | May cause harm to aquatic life with long lasting effects |

| Carcinogenicity | Not classified | Not applicable |
|-----------------------|----------------|----------------|
| Reproductive Toxicity | Not classified | Not applicable |
| Organic Peroxide | Not classified | Not applicable |

Safety Phrases:

S24: Avoid contact with skin.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes May cause severe eye damage. Avoid contact with eyes.

Skin Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed

through the skin.

Ingestion May be fatal or cause blindness if swallowed. Cannot be made non–poisonous.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 3 Flammability: 2 Reactivity: 0 PPE: X

3. Composition/information on ingredients

| Ingredient | CAS No. | Percent |
|--|--------------|------------|
| Butanol | 0000071-36-3 | 1.0 – 10 |
| Bisphenol A | 0000080-05-7 | 1.0 – 10 |
| 1,2,4–Trimethyl benzene | 0000095-63-6 | 1.0 – 10 |
| Benzene, ethyl- | 0000100-41-4 | 0.10 - 1.0 |
| Methylisobutyl ketone | 0000108-10-1 | 1.0 – 10 |
| 1,3,5-Trimethylbenzene | 0000108-67-8 | 1.0 – 10 |
| Methyl n-amyl ketone | 0000110-43-0 | 1.0 – 10 |
| Triethylene tetramine | 0000112-24-3 | 1.0 – 10 |
| Magnesium carbonate | 0000546-93-0 | 1.0 – 10 |
| Silica, amorphous | 0007631-86-9 | 1.0 – 10 |
| Titanium dioxide | 0013463-67-7 | 1.0 – 10 |
| Wollastonite (Ca(SiO3)) | 0013983-17-0 | 1.0 – 10 |
| Talc | 0014807-96-6 | 10 – 25 |
| Quartz | 0014808-60-7 | 0.10 - 1.0 |
| Polymer of epoxy resin and bisphenol A | 0025036-25-3 | 1.0 – 10 |
| Reaction of epichlorohydrin and bisphenol A | 0025085-99-8 | 10 – 25 |
| Petroleum naphtha | 0064742-95-6 | 1.0 – 10 |
| FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT | 0068410-23-1 | 1.0 – 10 |

This product contains 0.11 percent Quartz.

4. First aid measures

General

Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious

person.

5. Fire-fighting measures

Flash Point F: 100

C: 38

Lower Explosive Limit (LEL)

1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 12

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non–sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non–combustible material and transfer to containers. Use non–sparking tools to collect absorbed material.

Public Safety

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. 127

7. Handling and storage

Storage Temperature

Store between 40–100F (4–38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build—up of vapors by opening all windows and doors to achieve cross—ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|------------|--------------|--|
| 0000071-36-3 | Butanol | OSHA | 100 ppm TWA; 300 mg/m3 TWA50 ppm Ceiling; 150 mg/m3 Ceiling |
| | | ACGIH | 20 ppm TWA |
| | | NIOSH | 50 ppm Ceiling; 150 mg/m3 Ceiling1400 ppm IDLH (10% LEL) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 20 ppm TWA |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |

| | <u>.</u> | I | T |
|--------------|-------------------------|--------------|---|
| 0000080-05-7 | Bisphenol A | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000095-63-6 | 1,2,4–Trimethyl benzene | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | 25 ppm TWA; 125 mg/m3 TWA |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000100-41-4 | Benzene, ethyl- | OSHA | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA125 ppm STEL |
| | | NIOSH | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 100 ppm TWA125 ppm STEL |
| | | Mexico | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | Brazil | 78 ppm TWA; 340 mg/m3 TWA |
| 0000108–10–1 | Methylisobutyl ketone | OSHA | 100 ppm TWA; 410 mg/m3 TWA75 ppm STEL; 300 mg/m3 STEL |
| | | ACGIH | 20 ppm TWA75 ppm STEL |
| | | NIOSH | 50 ppm TWA; 205 mg/m3 TWA75 ppm STEL; 300 mg/m3 STEL500 ppm IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 50 ppm TWA75 ppm STEL |
| | | Mexico | 50 ppm TWA; 205 mg/m3 TWA75 ppm STEL; 307 mg/m3 STEL |
| | | Brazil | No Established Limit |
| 0000108-67-8 | 1,3,5–Trimethylbenzene | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | 25 ppm TWA; 125 mg/m3 TWA |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000110-43-0 | Methyl n-amyl ketone | OSHA | 100 ppm TWA; 465 mg/m3 TWA |
| | | ACGIH | 50 ppm TWA |
| | | NIOSH | 100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 25 ppm TWA; 115 mg/m3 TWA |
| | | Mexico | 50 ppm TWA; 235 mg/m3 TWA100 ppm STEL; 465 mg/m3 STEL |
| | | Brazil | No Established Limit |
| 0000112-24-3 | Triethylene tetramine | OSHA | No Established Limit |
| • | , | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | Sapplion | |

| | | OHSA, CAN | 0.5 ppm TWA; 3 mg/m3 TWA |
|--------------|----------------------------|--------------------------|---|
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0000546–93–0 | Magnesium carbonate | OSHA | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| | | ACGIH | No Established Limit |
| | | NIOSH | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 10 mg/m3 TWA (containing no Asbestos and |
| | | Mexico | 10 mg/m3 TWA20 mg/m3 STEL |
| | | Brazil | No Established Limit |
| 0007631–86–9 | Silica, amorphous | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | 6 mg/m3 TWA3000 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0013463–67–7 | Titanium dioxide | OSHA | 15 mg/m3 TWA (total dust) |
| | | ACGIH | 10 mg/m3 TWA |
| | | NIOSH | 5000 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 10 mg/m3 TWA (total dust) |
| | | Mexico | 10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti) |
| | | Brazil | No Established Limit |
| 0013983–17–0 | Wollastonite (Ca(SiO3)) | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0014807–96–6 | Talc | OSHA | No Established Limit |
| | | ACGIH | 2 mg/m3 TWA (particulate matter containing no asbestos and |
| | | NIOSH | 2 mg/m3 TWA (containing no Asbestos and |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 2 mg/m3 TWA (containing no Asbestos and |
| | | Mexico | 2 mg/m3 TWA (respirable fraction) |
| | | Brazil | No Established Limit |
| 0014808–60–7 | Quartz | OSHA | No Established Limit |
| | | ACGIH | 0.025 mg/m3 TWA (respirable fraction) |
| | | NIOSH | 0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH |
| | | 0 " | (respirable dust) |
| | | Supplier | No Established Limit |
| | | Supplier OHSA, CAN | No Established Limit 0.10 mg/m3 TWA (designated substance regulation, respirable)0.10 mg/m3 TWA (respirable |
| | | OHSA, CAN | No Established Limit 0.10 mg/m3 TWA (designated substance regulation, respirable)0.10 mg/m3 TWA (respirable fraction) |
| | | OHSA, CAN Mexico | No Established Limit 0.10 mg/m3 TWA (designated substance regulation, respirable)0.10 mg/m3 TWA (respirable fraction) 0.1 mg/m3 TWA (respirable fraction) |
| 0025036-25-3 | Polymer of epoxy resin and | OHSA, CAN | No Established Limit 0.10 mg/m3 TWA (designated substance regulation, respirable)0.10 mg/m3 TWA (respirable fraction) |

| | | NIOSH | No Established Limit |
|--------------|-----------------------------|----------------------|----------------------|
| | | | No Established Limit |
| | | | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0025085-99-8 | Reaction of epichlorohydrin | OSHA | No Established Limit |
| | and bisphenol A | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0064742-95-6 | Petroleum naphtha | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0068410-23-1 | FATTY ACIDS, | OSHA | No Established Limit |
| | C18-UNSATD., DIMERS, | ACGIH | No Established Limit |
| | REACTION PRODUCT | NIOSH | No Established Limit |
| | Supplier | No Established Limit | |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000071–36–3 | Butanol | NIOSH | Eye and mucous membrane irritation CNS depression |
| 0000080-05-7 | Bisphenol A | NIOSH | No Established Limit |
| 0000095-63-6 | 1,2,4–Trimethyl benzene | NIOSH | No Established Limit |
| 0000100-41-4 | Benzene, ethyl- | NIOSH | Eye skin |
| 0000108-10-1 | Methylisobutyl ketone | NIOSH | Irritation liver |
| 0000108-67-8 | 1,3,5-Trimethylbenzene | NIOSH | No Established Limit |
| 0000110-43-0 | Methyl n-amyl ketone | NIOSH | Irritation; liver kidney |
| 0000112-24-3 | Triethylene tetramine | NIOSH | No Established Limit |
| 0000546-93-0 | Magnesium carbonate | NIOSH | Skin mucous membrane |
| 0007631-86-9 | Silica, amorphous | NIOSH | No Established Limit |
| 0013463-67-7 | Titanium dioxide | NIOSH | Lung tumors in animals |
| 0013983-17-0 | Wollastonite (Ca(SiO3)) | NIOSH | No Established Limit |
| 0014807–96–6 | Talc | NIOSH | (containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects |
| 0014808-60-7 | Quartz | NIOSH | Chronic lung disease (silicosis) |
| 0025036-25-3 | Polymer of epoxy resin and bisphenol A | NIOSH | No Established Limit |
| 0025085–99–8 | Reaction of epichlorohydrin and bisphenol A | NIOSH | No Established Limit |
| 0064742-95-6 | Petroleum naphtha | NIOSH | No Established Limit |
| 0068410-23-1 | FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT | NIOSH | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|----------------------|-------------------------|--------|--|
| 0000071-36-3 Butanol | | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000080-05-7 | Bisphenol A | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000095-63-6 | 1,2,4-Trimethyl benzene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000100-41-4 | Benzene, ethyl- | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0000108-10-1 | Methylisobutyl ketone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000108-67-8 | 1,3,5-Trimethylbenzene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000110-43-0 | Methyl n-amyl ketone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000112–24–3 | Triethylene tetramine | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000546-93-0 | Magnesium carbonate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007631–86–9 | Silica, amorphous | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0013463–67–7 | Titanium dioxide | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0013983–17–0 | Wollastonite (Ca(SiO3)) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0014807–96–6 | Talc | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0014808–60–7 | Quartz | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: Yes; Suspected: No |
| | | IARC | Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0025036–25–3 | Polymer of epoxy resin | OSHA | Select Carcinogen: No |
| | and bisphenol A | NTP | Known: No; Suspected: No |

| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | | |
|--------------------------------|----------------------|------|---|--|--|
| 0025085-99-8 | Reaction of | OSHA | Select Carcinogen: No | | |
| | | NTP | Known: No; Suspected: No | | |
| bisphenol A | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: N Group 4: No; | | |
| 0064742-95-6 Petroleum naphtha | Petroleum naphtha | OSHA | Select Carcinogen: No | | |
| | | NTP | Known: No; Suspected: No | | |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | | |
| | | | Select Carcinogen: No | | |
| | C18-UNSATD., DIMERS, | NTP | Known: No; Suspected: No | | |
| REACTION PRODUCT | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; | | |

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls

Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured pH No Established Limit

Specific Gravity 1.41 Boiling Point F 210

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr |
|--|----------------------------------|-------------------------------------|---------------------------------------|
| Butanol - (0000071-36-3) | 790.00, Rat – Category: 4 | 3,400.00, Rabbit - Category: 5 | 17.70, Rat – Category: 4 |
| Bisphenol A – (0000080–05–7) | 3,200.00, Rat – Category: 5 | 3,000.00, Rabbit - Category: 5 | |
| 1,2,4-Trimethyl benzene – (0000095–63–6) | 3,400.00, Rat – Category: 5 | 3,160.00, Rabbit – Category: 5 | |
| Benzene, ethyl (0000100-41-4) | 3,500.00, Rat – Category: 5 | 15,354.00, Rabbit - Category: NA | 17.20, Rat – Category: 4 |
| Methylisobutyl ketone – (0000108–10–1) | 2,080.00, Rat – Category: 5 | 16,000.00, Rabbit - Category: NA | 8.20, Rat – Category: 3 |
| 1,3,5–Trimethylbenzene – (0000108–67–8) | 5,000.00, Rat – Category: 5 | | |
| Methyl n-amyl ketone - (0000110-43-0) | 1,670.00, Rat – Category: 4 | | |
| Triethylene tetramine – (0000112–24–3) | 2,500.00, Rat – Category: 5 | 550.00, Rabbit – Category: 3 | |
| Magnesium carbonate – (0000546–93–0) | | | |
| Silica, amorphous – (0007631–86–9) | 5,000.00, Rat – Category: 5 | 2,000.00, Rabbit - Category: 4 | |
| Titanium dioxide – (0013463–67–7) | 10,000.00, Rat – Category: NA | 10,000.00, Rabbit - Category: NA | 6,082.00, Rat – Category: NA |
| Wollastonite (Ca(SiO3)) - (0013983-17-0) | | | |
| Talc - (0014807-96-6) | | | |
| Quartz – (0014808–60–7) | 500.00, Rat – Category: 4 | | |
| Polymer of epoxy resin and bisphenol A – (0025036–25–3) | | | |
| Reaction of epichlorohydrin and bisphenol A – (0025085–99–8) | | | |
| Petroleum naphtha – (0064742–95–6) | 8,400.00, Rat – Category: NA | 2,000.00, Rabbit - Category: 4 | 5.20, Rat – Category: 3 |
| FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT - (0068410-23-1) | | | |

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation)

DOT Proper Shipping PAINT RELATED

Name MATERIAL

DOT Hazard Class 3

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping PAINT RELATED

Name MATERIAL

IMDG Hazard Class 3.3 – High flashpoint flammable liquids

UN / NA Number UN 1263 UN / NA Number UN 1263

DOT Packing Group III IMDG Packing Group III

CERCLA/DOT RQ 853 gal. / 10008 lbs. System Reference 30

Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification B2:D2B

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Cumene (5000 lb final RQ; 2270 kg final RQ)

Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)

Methylisobutyl ketone (5000 lb final RQ; 2270 kg final RQ)

Butanol (5000 lb final RQ; 2270 kg final RQ)

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

1,2,4-Trimethyl benzene

Bisphenol A

Cumene

Benzene, ethyl-

Methylisobutyl ketone

Butanol

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%):

1,2,4-Trimethyl benzene

Bisphenol A

Magnesium carbonate

Methyl n-amyl ketone

Methylisobutyl ketone

Butanol

Silica, amorphous

Talc

Titanium dioxide

Triethylene tetramine

1,3,5-Trimethylbenzene

Mass Extraordinarily Haz Sub (>.01%):

Quartz

Penn RTK Substances (>1%):

1,2,4-Trimethyl benzene

Bisphenol A

Methyl n-amyl ketone

Methylisobutyl ketone

Butanol

Silica, amorphous

Talc

Titanium dioxide

Triethylene tetramine

Penn Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%): 2-Butoxyethanol Cumene Benzene, ethyl-Magnesium carbonate Methyl n-amyl ketone Methylisobutyl ketone Butanol Quartz Talc Titanium dioxide Xylenes (o-, m-, p- isomers) **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%): 1,2,4-Trimethyl benzene Bisphenol A Magnesium carbonate Methyl n-amyl ketone Methylisobutyl ketone Butanol Talc Titanium dioxide Triethylene tetramine N.J. Special Hazardous Substances (>.01%): 2-Butoxyethanol Carbon black Cumene Benzene, ethyl-Isobutyl alcohol Methylisobutyl ketone Butanol Quartz Triethylene tetramine Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%): 1,2,4-Trimethyl benzene Bisphenol A Cumene Benzene, ethyl-Methylisobutyl ketone Butanol Xylenes (o-, m-, p- isomers) Proposition 65 – Carcinogens (>0%): Carbon black Cumene Benzene, ethyl-Quartz Proposition 65 - Female Repro Toxins (>0%): Benzene, methyl-Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): Benzene, methyl-Risk Phrases:

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.