

**Safety Data Sheet****NVA155 Enviroline 125LV Part B Low Temperature****Version No. 1 Date Last Revised 26/08/11**

Conforms to the requirements of Regulation (EC) No.1907/2006 (REACH), Annex II and Regulation (EC) No.1272/2008

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier** Enviroline 125LV Part B Low Temperature

Product Code NVA155

Registration Number

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

**1.3. Details of the supplier of the safety data sheet****Manufacturer** International Paint Ltd.  
Stoneygate Lane  
Felling Gateshead  
Tyne and Wear  
NE10 0JY UK**Telephone No.** +44 (0)191 469 6111**Fax No.** +44 (0)191 438 3711**1.4. Emergency telephone number****Manufacturer** +44 (0)191 469 6111 24hr**Official Advisory Body Telephone No.:**  
**Advice for Doctors and Hospitals**

+44 (0)844 892 0111

**Email** sdsfellinguk@akzonobel.com**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Mixture NOT yet classified according to Regulation (EC) No. 1272/2008****Classification according to 67/548/EEC or 1999/45/EC.**

C Corrosive.

R20/22 Harmful by inhalation and if swallowed.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R68 Possible risk of irreversible effects.

## 2.2. Label elements

According to 1999/45/EC



Corrosive

**Contains:** Phenol, M-xylylenediamine, 4,4'-diaminodicyclohexylmethane,

R20/22 Harmful by inhalation and if swallowed.

R34 Causes burns.

R43 May cause sensitisation by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R68 Possible risk of irreversible effects.

S23 Do not breathe vapour/spray.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51 Use only in well-ventilated areas.

### P. Phrases;

## 2.3. Other hazards

This product contains no PBT/vPvB chemicals.

## SECTION 3: Composition/information on ingredients

If the product contains substances that present a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC, or have occupational exposure limits detailed in EH40, these substances are listed below.

Ingredient/Chemical Designations	Weight %	67/548/EEC Classification	EC No. 1272/2008 Classification	Notes
Benzyl alcohol CAS Number: 0000100-51-6 EC No. 202-859-9 Index No.: 603-057-00-5 REACH Reg. No.: 01-2119492630-38-xxxx	10 - < 25	Xn;R20/22	Acute Tox. 4;H332 Acute Tox. 4;H302	[1]
M-xylylenediamine CAS Number: 0001477-55-0 EC No. 216-032-5 Index No.: REACH Reg. No.:	2.5 - < 10	Xn;R20/22 C;R35 Xi;R43 N;R52/53	Acute Tox. 4;H302 Acute Tox. 3;H331 Skin Corr. 1;H314 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1][2]
Phenol CAS Number: 0000108-95-2 EC No. 203-632-7 Index No.: 604-001-00-2 REACH Reg. No.:	2.5 - < 10	Muta. Cat. 3;R68 T;R23/24/25 C;R34 Xn;R48/20/21/22	Muta. 2;H341 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT RE 2;H373 Skin Corr. 1B;H314	[1][2]
4,4'-diaminodicyclohexylmethane CAS Number: 0001761-71-3 EC No. 217-168-8 Index No.: REACH Reg. No.:	1 - < 2.5	Xn;R22 C;R34 Xi;R43 N;R51/53	Acute Tox. 4;H302 Skin Corr. 1;H314 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]

Amorphous silica, hydrophobic CAS Number: 0067762-90-7 EC No. Index No.: REACH Reg. No.:	1 - < 2.5			[1]
Xylene CAS Number: 0001330-20-7 EC No. 215-535-7 Index No.: 601-022-00-9 REACH Reg. No.:	1 - < 2.5	R10 Xn;R20/21 Xi;R38	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	C [1][2]
2,4,6-Tris(dimethylaminomethyl) phenol CAS Number: 0000090-72-2 EC No. 202-013-9 Index No.: 603-069-00-0 REACH Reg. No.:	1 - < 2.5	Xn;R22 Xi;R36/38	Acute Tox. 4;H302 Eye Irrit. 2;H319 Skin Irrit. 2;H315	[1]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6 EC No. 265-199-0 Index No.: 649-356-00-4 REACH Reg. No.:	0 - < 1	Xn;R65	Asp. Tox. 1;H304	H; P [1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

#### Eye

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

#### Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sup>2</sup>. powder, water spray.

Do not use; water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

### 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Handling

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

#### In Storage

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.

### 7.3. Specific end use(s)

There are no exposure scenarios, see details in section 1.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

The following workplace exposure limits have been established by the Health and Safety Executive as published in EH40.

Material	Short term (15 min. ave)		Long term (8hr TWA)		Comments
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
Amorphous silica, hydrophobic	-	-	-	4	
Phenol	-	-	2	-	
Xylene	100	441	50	220	

For Key to entries in 'Comments' column see Section 16

### DNEL/PNEC values

No Data Available

### 8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

#### Eye/face protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should meet the requirements of standard EN 166.

#### Skin protection

For prolonged or repeated handling, use the following type of gloves:

Recommended: foil.

Not recommended: butyl rubber, PVC.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: [www.esig.org](http://www.esig.org)

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

## Other

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

## Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators. For maximum protection when spraying this product it is recommended that a multi layer combination type filter, such as ABEK1, is used. In confined spaces use compressed air or fresh air respiratory equipment.

## Thermal hazards

No Data Available

## SECTION 9: Physical and chemical properties

Appearance	Light Coloured Liquid
Odour	Smell of Amine
Odour threshold	Not Measured
pH	Not Measured
Melting point / freezing point (°C)	Not Measured
Initial boiling point and boiling range (°C)	110
Flash point (°C)	66
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .8 Not Measured Upper Explosive Limit: 13 Not Measured
Vapour pressure (Pa)	Not Measured
Vapour density	Heavier than air.
Relative density	1.37
Solubility(ies)	Immiscible
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature (°C)	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured

### 9.2. Other information

No further information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions (See section 7).

### 10.3. Possibility of hazardous reactions

May react exothermically with: oxidising agents, strong alkalis, strong acids.

### 10.4. Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

## 10.6. Hazardous decomposition products

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

## SECTION 11: Toxicological information

### Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Amine based materials may cause skin irritation and sensitisation.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
2,4,6-Tris(dimethylaminomethyl)phenol - (90-72-2)	1,200.00, Rat	1,280.00, Rat	Not Available	Not Available
4,4'-diaminodicyclohexylmethane - (1761-71-3)	1,000.00, Rat	Not Available	Not Available	0.40, Mouse
Amorphous silica, hydrophobic - (67762-90-7)	1,000.00, Rat	2,000.00, Rat	Not Available	Not Available
Benzyl alcohol - (100-51-6)	1,230.00, Rat	2,000.00, Rabbit	4.178, Rat	Not Available
M-xylenylenediamine - (1477-55-0)	930.00, Rat	2,000.00, Rabbit	Not Available	Not Available
Phenol - (108-95-2)	317.00, Rat	630.00, Rabbit	Not Available	Not Available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat	3,400.00, Rabbit	Not Available	Not Available
Xylene - (1330-20-7)	4,299.00, Rat	1,700.00, Rabbit	21.00, Rat	Not Available

## SECTION 12: Ecological information

### 12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

There are no data available on the product itself.

The product should not be allowed to enter drains or water courses.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
------------	-----------------------	----------------------------	-------------------

Benzyl alcohol - (100-51-6)	10.00, Lepomis macrochirus	55.00, Daphnia magna	700.00 (72 hr), Algae
M-xylolenediamine - (1477-55-0)	100.00, Oncorhynchus mykiss	16.00, Daphnia magna	Not Available
Phenol - (108-95-2)	3.73, Oncorhynchus gorbuscha	3.29, Ceriodaphnia dubia	46.42 (96 hr), Pseudokirchneriella subcapitata
4,4'-diaminodicyclohexylmethane - (1761-71-3)	46.00, Leuciscus idus	6.84, Daphnia magna	140.00 (72 hr), Algae
Amorphous silica, hydrophobic - (67762-90-7)	Not Available	Not Available	Not Available
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
2,4,6-Tris(dimethylaminomethyl) phenol - (90-72-2)	Not Available	Not Available	Not Available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum

## 12.2. Persistence and degradability

There is no data available on the preparation itself.

## 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

## 12.6. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

European Waste Catalogue Classification: 08 01 12 Waste paint other than those mentioned in 08 01 11

## SECTION 14: Transport information

**14.1. UN number** 3066  
**14.2. UN proper shipping name** PAINT  
**14.3. Transport hazard class(es)**

**ADR/RID/ADN** UN3066 Paint, 8, III

**IMDG class/div 8** **Sub Class -**  
**Segregation Group** No segregation group appropriate

**EmS** F-A,S-B

**ICAO/IATA Air class 8** **Sub Class -**



#### 14.4. Packing group

III

#### 14.5. Environmental hazards

**ADR/RID/ADN** Environmentally Hazardous: No

**IMDG** Marine Pollutant: No

#### 14.6. Special precautions for user

No further information

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### SECTION 15: Regulatory information

#### EU Legislation

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

#### National Legislation

UKSI 2009 No. 716 CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) REGULATIONS 2009.

### SECTION 16: Other information

**IMPORTANT NOTE:** the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

**MANUFACTURER'S DISCLAIMER:** the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

The information in this Health & Safety Data Sheet is required pursuant to EC Regulation 1907(2006) and the Chemicals (Hazard Information & Packaging for Supply) Regulations 2009.

Key to 'Comments' column in Section 8.

- (+) There is a risk of absorption through unbroken skin.
- (C) Capable of causing cancer and/or heritable genetic damage.
- (R) Suppliers recommended limit.
- (S) Capable of causing occupational asthma.

The full text of the R, H & EUH phrases appearing in section 3 is:

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H341 Suspected of causing genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R20/22 Harmful by inhalation and if swallowed.

R22 Harmful if swallowed.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R34 Causes burns.

R35 Causes severe burns.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R68 Possible risk of irreversible effects.

**The following sections have changed since the previous revision.**

End of document



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : [www.yachtpaint.com](http://www.yachtpaint.com) , [www.international-marine.com](http://www.international-marine.com), [www.international-pc.com](http://www.international-pc.com)