

Safety Data Sheet
Devthane 389H OSHA Yellow Part A

Sales
Order: {SalesOrd}
DC389F8050
06/11/2015
A0-4

Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:



1. Identification of the preparation and company

1.1. Product identifier

Product Identity Devthane 389H OSHA Yellow Part A
Bulk Sales Reference No. DC389F8050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
Org. Perox. C;H242 Heating may cause a fire.
Skin Irrit. 3;H316 Causes mild skin irritation.
Skin Sens. 1;H317 May cause an allergic skin reaction.
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
 P234 Keep only in original container.
 P260 Do not breathe mist / vapors / spray.
 P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P302+352 IF ON SKIN: Wash with soap and water.
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P331 Do NOT induce vomiting.
 P332+313 If skin irritation occurs: Get medical advice/attention.
 P333 If skin irritation or a rash occurs:.
 P363 Wash contaminated clothing before reuse.
 P370 In case of fire: Use water spray, fog, or regular foam..
 P403+233 Store in a well ventilated place. Keep container tightly closed.
 P410 Protect from sunlight.
 P420 Store away from other materials.
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3 Flammability: 3 Reactivity: 0

| |
|---|
| 3. Composition/information on ingredients |
|---|

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|---|------------|--|--------|
| Barium sulfate CAS Number: 0007727-43-7 | 10 - 25 | ---- | [1][2] |
| Methyl n-amyl ketone CAS Number: 0000110-43-0 | 1.0 - 10 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302 | [1][2] |
| BUTYL ACETATE CAS Number: 0000123-86-4 | 1.0 - 10 | Flam. Liq. 3;H226 STOT SE 3;H336 | [1][2] |
| Titanium dioxide CAS Number: 0013463-67-7 | 1.0 - 10 | ---- | [1][2] |
| Diisobutylketone CAS Number: 0000108-83-8 | 1.0 - 10 | Flam. Liq. 3;H226 STOT SE 3;H335 | [1][2] |
| Ethylene glycol monobutyl ether acetate CAS Number: 0000112-07-2 | 1.0 - 10 | Acute Tox. 4;H332 Acute Tox. 4;H312 | [1][2] |
| BUTYL PEROXYBENZOATE CAS Number: 0000614-45-9 | 1.0 - 10 | Org. Perox. C;H242 Acute Tox. 4;H332 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Acute 1;H400 | [1] |
| 2-Heptanone, 4,6-dimethyl- CAS Number: 0019549-80-5 | 1.0 - 10 | ---- | [1] |
| Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate CAS Number: 0041556-26-7 | 1.0 - 10 | Skin Sens. 1;H317 Aquatic Chronic 1;H410 Aquatic Acute 1;H400 | [1] |
| DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P CAS Number: 0082919-37-7 | 0.10 - 1.0 | Skin Sens. 1;H317 Aquatic Chronic 1;H410 | [1] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

| | |
|------------|---|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. |

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

DC389F8050_A0

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

| |
|-------------------------|
| 7. Handling and storage |
|-------------------------|

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

| |
|--|
| 8. Exposure controls and personal protection |
|--|

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|---|-----------|---|
| 0000108-83-8 | Diisobutylketone | OSHA | 50 ppm TWA; 290 mg/m3 TWA |
| | | ACGIH | 25 ppm TWA |
| | | NIOSH | 25 ppm TWA; 150 mg/m3 TWA500 ppm IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 25 ppm TWA |
| | | Mexico | 25 ppm TWA LMPE-PPT; 145 mg/m3 TWA LMPE-PPT |
| | | Brazil | No Established Limit |
| 0000110-43-0 | Methyl n-amyl ketone | OSHA | 100 ppm TWA; 465 mg/m3 TWA |
| | | ACGIH | 50 ppm TWA |
| | | NIOSH | 100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 25 ppm TWA; 115 mg/m3 TWA |
| | | Mexico | 50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT] |
| | | Brazil | No Established Limit |
| 0000112-07-2 | Ethylene glycol monobutyl ether acetate | OSHA | No Established Limit |
| | | ACGIH | 20 ppm TWA |
| | | NIOSH | 5 ppm TWA; 33 mg/m3 TWA |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 20 ppm TWA |
| | | Mexico | No Established Limit |
| | | | |

DC389F8050_A0

| | | | |
|--------------|--|-----------|--|
| 0000123-86-4 | BUTYL ACETATE | Brazil | No Established Limit |
| | | OSHA | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL |
| | | ACGIH | 150 ppm TWA200 ppm STEL |
| | | NIOSH | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 150 ppm TWA200 ppm STEL |
| | | Mexico | 150 ppm TWA LMPE-PPT; 710 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 950 mg/m3 STEL [LMPE-CT] |
| 0000614-45-9 | BUTYL PEROXYBENZOATE | Brazil | No Established Limit |
| | | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| 0007727-43-7 | Barium sulfate | Brazil | No Established Limit |
| | | OSHA | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| | | ACGIH | 10 mg/m3 TWA |
| | | NIOSH | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 10 mg/m3 TWA |
| | | Mexico | No Established Limit |
| 0013463-67-7 | Titanium dioxide | Brazil | No Established Limit |
| | | OSHA | 15 mg/m3 TWA (total dust) |
| | | ACGIH | 10 mg/m3 TWA |
| | | NIOSH | 5000 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 10 mg/m3 TWA |
| | | Mexico | 10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti) |
| 0019549-80-5 | 2-Heptanone, 4,6-dimethyl- | Brazil | No Established Limit |
| | | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| 0041556-26-7 | Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | Brazil | No Established Limit |
| | | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| 0082919-37-7 | DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P | Brazil | No Established Limit |
| | | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |

DC389F8050_A0

| | | |
|--|--------------|----------------------|
| | NIOSH | No Established Limit |
| | Supplier | No Established Limit |
| | OHSA, CAN | No Established Limit |
| | Mexico | No Established Limit |
| | Brazil | No Established Limit |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000108-83-8 | Diisobutylketone | NIOSH | Irritation; liver kidney |
| 0000110-43-0 | Methyl n-amyl ketone | NIOSH | Irritation; liver kidney |
| 0000112-07-2 | Ethylene glycol monobutyl ether acetate | NIOSH | Adverse effects on blood and hematopoietic system tissue irritation |
| 0000123-86-4 | BUTYL ACETATE | NIOSH | Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals |
| 0000614-45-9 | BUTYL PEROXYBENZOATE | NIOSH | No Established Limit |
| 0007727-43-7 | Barium sulfate | NIOSH | Eye nose |
| 0013463-67-7 | Titanium dioxide | NIOSH | Lung tumors in animals |
| 0019549-80-5 | 2-Heptanone, 4,6-dimethyl- | NIOSH | No Established Limit |
| 0041556-26-7 | Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | NIOSH | No Established Limit |
| 0082919-37-7 | DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P | NIOSH | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|---|--------|---|
| 0000108-83-8 | Diisobutylketone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000110-43-0 | Methyl n-amyl ketone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000112-07-2 | Ethylene glycol monobutyl ether acetate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000123-86-4 | BUTYL ACETATE | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000614-45-9 | BUTYL PEROXYBENZOATE | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0007727-43-7 | Barium sulfate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0019549-80-5 | 2-Heptanone, 4,6-dimethyl- | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0041556-26-7 | | OSHA | Select Carcinogen: No |

DC389F8050_A0

| | | | |
|--------------|--|------|--|
| | Bis (1,2,2,6,6-pentamethyl-4-piperidinyloxy) sebacate | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0082919-37-7 | DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

| | |
|----------------------|---|
| Respiratory | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

9. Physical and chemical properties

| | |
|---|--|
| Appearance | Coloured Liquid |
| Odour threshold | Not Measured |
| pH | No Established Limit |
| Melting point / freezing point | Not Measured |
| Initial boiling point and boiling range | 124 (C) 255 (F) |
| Flash Point | 27 (C) 81 (F) |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Not Applicable |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: .81 Upper Explosive Limit: No Established Limit |
| vapor pressure (Pa) | Not Measured |
| Vapor Density | Heavier than air |
| Specific Gravity | 1.19 |
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | Not Measured |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | No Established Limit Not Measured |
| VOC % | Refer to the Technical Data Sheet or label where information is available. |
| VOHAP content (gm/litre of paint) | 5.43 (as supplied) |

VOHAP content (gm/litre of Solid Coating) 3.49 (as supplied)

9.2. Other information

No further information

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|--|-------------------------------|----------------------------------|---------------------------------|-------------------------------------|
| Barium sulfate - (7727-43-7) | 3,000.00, Mouse - Category: 5 | No data available | No data available | No data available |
| Methyl n-amyl ketone - (110-43-0) | 1,670.00, Rat - Category: 4 | 12,600.00, Rabbit - Category: NA | No data available | No data available |
| BUTYL ACETATE - (123-86-4) | 10,700.00, Rat - Category: NA | 17,600.00, Rabbit - Category: NA | No data available | No data available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA |
| Diisobutylketone - (108-83-8) | 5,750.00, Rat - Category: NA | 16,000.00, Rabbit - Category: NA | No data available | No data available |
| Ethylene glycol monobutyl ether acetate - (112-07-2) | 2,400.00, Rat - Category: 5 | 1,500.00, Rabbit - Category: 4 | No data available | No data available |
| BUTYL PEROXYBENZOATE - (614-45-9) | 4,838.00, Rat - Category: 5 | 2,000.00, Rabbit - Category: 4 | No data available | 4.90, Rat - Category: 4 |
| 2-Heptanone, 4,6-dimethyl- - (19549-80-5) | No data available | No data available | No data available | No data available |

DC389F8050_A0

| | | | | |
|---|-----------------------------|-------------------|-------------------|-------------------|
| Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate - (41556-26-7) | 2,615.00, Rat - Category: 5 | No data available | No data available | No data available |
| DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P - (82919-37-7) | No data available | No data available | No data available | No data available |

| Item | Category | Hazard |
|---|----------------|--------------------------------------|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 3 | Causes mild skin irritation. |
| Eye damage/irritation | Not Classified | Not Applicable |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure) | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|---|---------------------------------|----------------------------|---|
| Barium sulfate - (7727-43-7) | 59,000.00, Poecilia sphenops | 32.00, Daphnia magna | Not Available |
| Methyl n-amyl ketone - (110-43-0) | 131.00, Pimephales promelas | Not Available | Not Available |
| BUTYL ACETATE - (123-86-4) | 18.00, Pimephales promelas | 32.00, Artemia salina | 674.70 (72 hr), Scenedesmus subspicatus |
| Titanium dioxide - (13463-67-7) | 1,000.00, Fundulus heteroclitus | 5.50, Daphnia magna | 5.83 (72 hr), Pseudokirchneriella subcapitata |
| Diisobutylketone - (108-83-8) | 140.00, Oncorhynchus mykiss | 250.00, Daphnia magna | 100.00 (96 hr), Selenastrum capricornutum |
| Ethylene glycol monobutyl ether acetate - (112-07-2) | Not Available | Not Available | Not Available |
| BUTYL PEROXYBENZOATE - (614-45-9) | 1.50, Danio rerio | Not Available | Not Available |
| 2-Heptanone, 4,6-dimethyl- - (19549-80-5) | Not Available | Not Available | Not Available |
| Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate - (41556-26-7) | 1.00, Lepomis macrochirus | 20.00, Daphnia magna | Not Available |
| DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P - (82919-37-7) | Not Available | Not Available | Not Available |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|------------------------|-----------------------------------|-------|
| DOT Proper Shipping Name | PAINT | IMDG Proper Shipping Name | PAINT |
| DOT Hazard Class | 3 | IMDG Hazard Class | 3 |
| | | Sub Class | 3 |
| UN / NA Number | UN 1263 | | |
| DOT Packing Group | III | IMDG Packing Group | III |
| CERCLA/DOT RQ | 4334 gal. / 43100 lbs. | System Reference Code | 1 |

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B C

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

1,2,4-Trimethyl benzene
Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

Barium sulfate
Diisobutylketone
Methyl n-amyl ketone
BUTYL ACETATE
BUTYL PEROXYBENZOATE
Titanium dioxide

Penn RTK Substances (>1%) :

Barium sulfate
Diisobutylketone
Methyl n-amyl ketone
BUTYL ACETATE
BUTYL PEROXYBENZOATE
Titanium dioxide

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Barium sulfate
Diisobutylketone
Ethylene glycol monobutyl ether acetate
Methyl n-amyl ketone
BUTYL ACETATE
BUTYL PEROXYBENZOATE
Titanium dioxide

N.J. Special Hazardous Substances (>.01%) :

Benzene, ethyl-
BUTYL ACETATE
Quartz
BUTYL PEROXYBENZOATE
Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-Trimethyl benzene
Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Cumene
Benzene, ethyl-
Quartz
Titanium dioxide

Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

| |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health

and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document