

**Safety Data Sheet**

**EAA969/1LT INTERZONE 954 ??????????**

**Version 1 Revision Date 10/21/13**

**1. Product and company identification**

**1.1. Product identifier** INTERZONE 954 ??????????  
 Product Code EAA969/1LT

**1.2. Relevant identified uses of the substance or mixture and uses advised against**  
 Intended use Refer Technical Data Sheet.  
 Application Method Refer Technical Data Sheet.

**1.3. Details of the supplier of the safety data sheet**

**Manufacturer** International Paint Taiwan  
 No. 20, Yumin St.,  
 Dafa Industrial Park  
 Daliao District, Kaohsiung City 83162,  
 Taiwan (R.O.C.)

**Telephone No.** 07-787 3959  
**Fax No.** 07-787 3953  
**1.4. Emergency telephone number** 07-787 3959  
**For Poisons Advice telephone** For Advice to Doctors & Hospitals only

**2. Hazard identification of the product**

**2.1. Classification of the substance or mixture**

**2.2. Label elements**

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

[Prevention]:

[Response]:

[Storage]:

[Disposal]:

**2.3. Other hazards**

**3. Composition/information on ingredients**

This product contains the following hazardous substances.

| Ingredient/Chemical Designations           | Weight % | GHS Classification                     | Notes |
|--|----------|--|-------|
| Benzyl alcohol<br>CAS Number: 0000100-51-6 | 25-50    | Acute Tox. 4;H332<br>Acute Tox. 4;H302 | [1]   |

|  |        |   |        |
|--|--------|---|--------|
| Isophorone diamine<br>CAS Number: 0002855-13-2                   | 10-25  | Acute Tox. 4;H312<br>Acute Tox. 4;H302<br>Skin Corr. 1B;H314<br>Skin Sens. 1;H317<br>Aquatic Chronic 3;H412 | [1]    |
| M-xylolenediamine<br>CAS Number: 0001477-55-0                    | 10-25  | Acute Tox. 4;H302<br>Acute Tox. 3;H331<br>Skin Corr. 1;H314<br>Skin Sens. 1;H317<br>Aquatic Chronic 3;H412  | [1][2] |
| N-tallow-1,3-diaminopropane dioleate<br>CAS Number: 0061791-53-5 | 2.5-10 | Aquatic Acute 1;H400  | [1]    |
| Methyl isobutyl ketone<br>CAS Number: 0000108-10-1               | 2.5-10 | Flam. Liq. 2;H225<br>Acute Tox. 4;H332<br>Eye Irrit. 2;H319<br>STOT SE 3;H335                               | [1][2] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the Hazard (H) phrases are shown in Section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

#### Inhalation

#### Skin Contact

#### Eye Contact

#### Ingestion

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## 5. Fire-fighting measures

### 5.1. Extinguishing media

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for fire-fighters

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

## 7. Handling and storage

## 7.1. Precautions for safe handling

### Handling

### In Storage

## 7.2. Conditions for safe storage, including any incompatibilities

## 7.3. Specific end use(s)

# 8. Exposure controls and personal protection

## 8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygienists).

| Material               | Short term (15 min. ave) |                   | Long term (8hr time weighted average) |       | Comments |
|------------------------|--------------------------|-------------------|---------------------------------------|-------|----------|
|                        | ppm                      | mg/m <sup>3</sup> | ppm                                   | mg/M3 |          |
| Methyl isobutyl ketone | 75                       | 307               | 50                                    | 205   |          |

Key to notification

(P) Peak exposure limit

(R) Suppliers Recommended Limit

(Sk) There is a risk of absorption through unbroken skin

(Sen) Sensitiser

(Cat1) Category 1 - established human carcinogen

(Cat2) Category 2 - probable human carcinogen

(Cat3) Category 3 - substances suspected of having carcinogenic potential

## DNEL/PNEC values

## 8.2. Exposure controls

### Eye Protection

### Skin Protection

### Other

### Respiratory Protection

### Thermal hazards

# 9. Physical and chemical properties

## Colour

## Odour

## Odour threshold

## pH

## Melting point / freezing point (°C)

Initial boiling point and boiling range (°C)

Flash Point (C)

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Lower Explosive Limit: 1.4 ( Methyl isobutyl ketone )

Upper Explosive Limit: No data available

Vapour pressure (Pa)

Vapour Density

Specific Gravity

0.00

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Autoignition temperature ( )

Decomposition temperature

Viscosity (cSt)

## 9.2. Other information

No further information

## 10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

## 11. Toxicological information

### Acute toxicity

| Ingredient  | Oral LD50, mg/kg | Skin LD50, mg/kg  | Inhalation Vapour LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|---|------------------|-------------------|----------------------------------|-------------------------------------|
| Benzyl alcohol - (100-51-6)                         | 1,230.00, Rat    | 2,000.00, Rabbit  | Not Available                    | 4.178, Rat                          |
| Isophorone diamine - (2855-13-2)                    | 1,030.00, Rat    | 2,000.00, Rabbit  | Not Available                    | 5.02, Rat                           |
| M-xylolenediamine - (1477-55-0)                     | 930.00, Rat      | 2,000.00, Rabbit  | 0.00, Rat                        | 1.34, Rat                           |
| Methyl isobutyl ketone - (108-10-1)                 | 2,080.00, Rat    | 16,000.00, Rabbit | Not Available                    | Not Available                       |
| N-tallow-1,3-diaminopropane dioleate - (61791-53-5) | 5,000.00, Rat    | Not Available     | Not Available                    | Not Available                       |

| Item                        | Category       | Hazard         |
|-----------------------------|----------------|----------------|
| Acute Toxicity (mouth)      | Not Classified | Not Applicable |
| Acute Toxicity (skin)       | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation   | Not Classified | Not Applicable |
| Eye damage/irritation       | Not Classified | Not Applicable |
| Sensitization (respiratory) | Not Classified | Not Applicable |

|   |                |                |
|---|----------------|----------------|
| Sensitization (skin)  | Not Classified | Not Applicable |
| Germ toxicity   | Not Classified | Not Applicable |
| Carcinogenicity   | Not Classified | Not Applicable |
| Reproductive Toxicity                                       | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure)   | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard   | Not Classified | Not Applicable |

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

| Ingredient  | 96 hr LC50 fish, mg/l       | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l                       |
|---|-----------------------------|----------------------------|---|
| Benzyl alcohol - (100-51-6)                         | 10.00, Lepomis macrochirus  | 55.00, Daphnia magna       | 700.00 (72 hr), Algae                   |
| Isophorone diamine - (2855-13-2)                    | 110.00, Leuciscus idus      | 17.40, Daphnia magna       | 37.00 (72 hr), Scenedesmus subspicatus  |
| M-xylylenediamine - (1477-55-0)                     | 100.00, Oncorhynchus mykiss | 16.00, Daphnia magna       | Not Available                           |
| N-tallow-1,3-diaminopropane dioleate - (61791-53-5) | 0.10, Fish (Piscis)         | 0.001, Daphnia magna       | 0.01 (72 hr), Algae                     |
| Methyl isobutyl ketone - (108-10-1)                 | 505.00, Pimephales promelas | 1,550.00, Daphnia magna    | 980.00 (48 hr), Scenedesmus subspicatus |

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## 13. Disposal considerations

### 13.1. Waste treatment methods

## 14. Transport information

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

#### Road and Rail Transport

IMDG

Class/Div

Sub Class

reference :

Ems

| ICAO/IATA | Class | Sub Class |
|-----------|-------|-----------|
|-----------|-------|-----------|

#### 14.4. Packing group

#### 14.5. Environmental hazards

Road and Rail Environmentally Hazardous:  
Transport

IMDG Marine Pollutant:  
reference :

#### 14.6. Special precautions for user

No further information

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15. Regulatory information

The product and all its components complies with these local regulations:

NICNAS - Australia  
EPA - New Zealand

Labor Health & Safety facility  
Lead toxic prevention  
Public Traffic safety  
Toxic substance management  
Hazard substance awarenessLead  
Labor permit exposure limit of airborne concentration at work place  
Waste treatment method and facility standard

### 16. Other information

The information on this SDS is based upon the present state of our knowledge and on current law.  
The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H400 Very toxic to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

**This SDS is valid for 5 years from the revised date on page 1.  
The revision date is in American format (e.g. MM/DD/YY).**

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.