

THA127 INTERLINE 925 WHITE PART B

1

08/31/13

1.

1.1. INTERLINE 925 WHITE PART B  
THA127

1.2.

1.3.

International Paint Singapore Pte Ltd  
3 Neythal Road  
Jurong Town  
Singapore 628570

+65 6261 5033

+65 6264 4612

1.4.

+65 6261 5033

2.

- 2.1. .
  - 4;H302
  - 4;H312
- /
- 1A;H314
- /
- 1;H318
- 1;H317
- 
- 3;H373

2.2.

11 , 12



H302  
H312  
H314  
H317  
H318  
H373  
H412

[ ]:

P260 / /

P264

P270

P272

P273

P280 / / /

[ ]:

P301+330+331 :

P302+352 :

P303+361+353 ( ) :

P304+312 :

P305+351+338 가 : .가

P310 /

P314 /

P321 ( ).

P322 ( ).

P333+313 /

P340 가

P363

[ ]:

P405 가

[ ]:

P501 ( )

2.3. PBT ( , ) vPvB ( , )

3.

/	%	GHS	
Silica(quartz) CAS No: 0014808-60-7	40-50	- 4;H332 - 3;H373	[1][2]
Isophorone diamine CAS No: 0002855-13-2	20-30	- 4;H312 - 4;H302 / 1B;H314 1;H317 - 3;H412	[1]
3,3'-Dimethyl-4,4'- diaminodicyclohexylmethane CAS No: 0006864-37-5	5-10	- 3;H331 - 3;H311 - 4;H302 / 1A;H314	[1]

- 1)
  - 2) 가
  - 3) PBT vPvB  
16
- 가 , 가  
가 .

4.

4.1.

가 .

가 , .

가 .

가 .

가 .

가 .

15 .

4.2. 가 /

4.3.

5. ,

5.1.

;

,

,

,

.

Note; 가 .

가 .

5.2.

가 . :

,

5.3.

가

가

6.

6.1.

가 가 가 , 가

6.2.

가

6.3.

, ( 13 ).

가

가

가

7.

7.1.

가

가 (LEL)

(OEL)

가

7.2.

( )

,8

가 , 1 가

7.3. Specific end use(s)

가

,가

8.

8.1.

(OEL) (ACGIH)

(ACGIH)

ppm mg/m<sup>3</sup> ppm mg/m<sup>3</sup>

Barium Sulphate

- - - 10

Silica(quartz)

- - - 0.1

(P) (Peak exposure limit)

(R)

(Sk)

(Sen)

(Cat 1)

(Cat 2) 가

(Cat 3)

DNEL/PNEC

8.2.

가

PVC

가

(overall)

가

가

.가

가

9.

pH / (°C) (°C) 155  
 101  
 ( = 1)  
 ( , ) / :  
 :  
 (Pa)  
 1.64

n- / (Log Kow)

9.2.

10.

10.1.

10.2.

.(Section 7 ) ,

10.3.

가 ,

가

10.4.

: , , .

10.5.

.(7 .)

10.6.

: , , .

가 . :

11.

(OEL)

가

가

가

2

	LD50, mg/kg	LD50, mg/kg	LD50, mg/L/4hr	/ LD50, mg/L/4hr
3,3'-Dimethyl-4,4'-diaminodicyclohexylmethane - (6864-37-5)	320.00,	200.00,		
Isophorone diamine - (2855-13-2)	1,030.00,	2,000.00,		5.02,
Silica(quartz) - (14808-60-7)				

( )	4	
( )	4	
( )		
/	1A	
/	1	
	1	
(1 )		
( )	2	

12.

12.1.

Dangerous Preparations Directive 1999/45/EC

가  
( 3 )

가

	96 hr LC50	,	49 hr EC50	,	ErC50	,
--	------------	---	------------	---	-------	---

	mg/l	mg/l	mg/l
Silica(quartz) - (14808-60-7)			
Isophorone diamine - (2855-13-2)	110.00, Leuciscus idus	17.40, Daphnia magna	37.00 (72 hr), Scenedesmus subspicatus
3,3'-Dimethyl-4,4'-diaminodicyclohexylmethane - (6864-37-5)	21.50, Leuciscus idus	15.20, Daphnia magna	5.00 (72 hr), Scenedesmus subspicatus

12.2.

가 .

12.3.

12.4.

12.5. , , 가

PBT ( , ) vPvB ( , ) .

12.6.

13.

13.1.

가

14.

14.1.

3066

14.2.

UN3066, Paint, 8, II

14.3.

UN3066,paint,II,HACCHEM 2X

IMDG

Class/Div. 8

EmS

F-A,S-B

ICAO/IATA

8

14.4.

II

14.5.

:

IMDG

:

14.6.

가

가

15.

None noted.

16.

SDS

Section 3            Phrases

- H302
- H311
- H312
- H314
- H317
- H331
- H332
- H373
- H411
- H412

**SDS**



Akzo Nobel

가