

HAM272 INTERTHERM 875 RAL3009 RED OXIDE

4

10/27/14

1.

1.1. INTERTHERM 875 RAL3009 RED OXIDE
HAM272

1.2.

1.3.

626-6

(8-6)

1.4.

055-632-6286(),055 586 2310()
055 587 6276()
055 586 2310()
055 586 2310()

2.

2.1. .
3; H226
/
2;H315
/
2;H319
-1 ;H335

2.2.
11 , 12



H226
H315
H319

H335

[]:

P210 / / /

P261 / /가 / / /

P264

P271 가

P280 / / /

[]:

P302+352 :

P303+361+353 () :

P304+312 :

P305+351+338 가 : .가

P312 /

P321 ().

P337+313 : /

P340 가

P362

P370 :

P378 , , ,

[]:

P403+233 가

P405 가

[]:

P501 ()

2.3. PBT (,) vPvB (,)

3.

/	%	GHS	
xylene CAS No: 0001330-20-7	30-40	3; H226 - 4;H312 - 4;H332 / 2;H315 / 2AIH319 -1 ;H336 - 1;H372	[1][2]
Ethylbenzene CAS No: 0000100-41-4	5-10	2;H225 - 4;H332 - 3;H373 1;H304 / 2;H315 / 2;H319 -1 ;H335	[1][2]
n-Butanol CAS No: 0000071-36-3	2.5-5	3; H226 - 4;H302 -1 ;H335 / 2;H315 / 1;H318 -1 ;H336	[1][2]

Toluene CAS No: 0000108-88-3	<1	2;H225 / 2;H315 2;H361 - 4;H332 1;H317 - 2;H411	[1][2]
	50-60	---	---

- 1)
- 2) 가
- 3) PBT vPvB
16

4.

4.1.

가

가

10

4.2. 가 /

4.3.

5. ,

5.1.

;

Note; 가

가

5.2.

가

5.3.

가

가

6.

6.1.

가

가

가

가

6.2.

가

6.3.

.8

가

(13)

가

가

가

가

7.

7.1.

가

가 (LEL)

(OEL)

가

가

가 (LEL)

(OEL)

7.2.

()

가 , 가 .
 가 , 61
 1 .

7.3. Specific end use(s)

가 .
 , 가 . 3

Hot surfaces, Sparks,

가 , (60% ,)

8.

8.1.

(OEL)

(ACGIH)

(ACGIH)

ppm

mg/m³

ppm

mg/m³

Barium Sulphate

2

10

Ethylbenzene

125

545

100

435

n-Butanol

C50

C150

Toluene

150

560

100

375

xylene

150

655

100

434

(P) (Peak exposure limit)

(R)

(Sk)

(Sen)

(Cat 1)

(Cat 2) 가

(Cat 3)

DNEL/PNEC

8.2.

가

가

(visor)

(overall)

가

For Professional Applications (Indoor and Outdoor) the maximum daily exposure allowed is less than or equal to 8 hours. This is for natural, local exhaust or no ventilation wearing the PPE requirements highlighted above.

9.

pH / (°C) (°C) 108
 24
 (= 1)
 (,) / : 1.1 (xylene)
 : 6.6 (xylene)
 (Pa)
 1.11

n- / (Log Kow)

9.2.

10.

10.1.

10.2.

(Section 7)

가

10.3. 가

10.4.

(7 .)

10.5.

10.6.

가

11.

(OEL)

가

가

가

2

	LD50, mg/kg	LD50, mg/kg	LD50, mg/L/4hr	/ LD50, mg/L/4hr
Ethylbenzene - (100-41-4)	3,500.00,	15,433.00,	17.20,	
n-Butanol - (71-36-3)	2,292.00,	3,430.00,		
Toluene - (108-88-3)	636.00,	8,400.00,		
xylene - (1330-20-7)	4,299.00,	1,548.00,		20.00,

()		
()		
()		
/	2	
/	2	

(1)	3	.
()		

12.

12.1.

1999/45/EC 가 ,

가

	96 hr LC50 mg/l ,	49 hr EC50 mg/l ,	ErC50 mg/l ,
xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Ethylbenzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata
n-Butanol - (71-36-3)	1,376.00, Pimephales promelas	1,328.00, Daphnia magna	500.00 (96 hr), Scenedesmus subspicatus
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	

12.2.

가

12.3.

12.4.

12.5. , 가

PBT (,) vPvB (,)

12.6.

13.

13.1.

가

14.

14.1. 1263
14.2.
14.3.

1263, , 3, III, 3[Y]

IMDG Class/Div. 3

EmS F-E,S-E

ICAO/IATA 3

14.4. III

14.5.
:

IMDG :

14.6. 가 가

14.7. MARPOL73/78 Annex II IBC Code .

15.

4 , 2 , III

MSDS 8 .

n-Butanol (0000071-36-3)
Ethylbenzene (0000100-41-4)

(CMR):

carbon black (0001333-86-4)
Silica(quartz) (0014808-60-7)
Ethylbenzene (0000100-41-4)
Toluene (0000108-88-3)

:

n-Butanol (0000071-36-3)
Ethylbenzene (0000100-41-4)
xylene (0001330-20-7)

:

n-Butanol (0000071-36-3)
Ethylbenzene (0000100-41-4)
xylene (0001330-20-7)

가 :
()

:
()

:
()

:
()

Group I:
()

Group II:

Barium Sulphate (0007727-43-7)
Ethylbenzene (0000100-41-4)
xylene (0001330-20-7)

:
()

()

:
()

16.

: 10/27/2014

: 4

: 02/27/2008

MSDS KOSHA, NITE, ESIS, NLM, SIDS, IPCS, NCIS

SDS

Section 3 Phrases

H225

H226

H302

H304

H312

H315

H318

H319

H332

H335

H336

H372

H373

This SDS is valid for 5 years from the revised date on page 1.



Akzo Nobel

가