#### Material Safety Data Sheet DEVTHANE 359H CASE RED PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number:

Sales Order: {SalesOrd} HT7435 03/12/2012 A1-

# X.International.

| 1. Identification of the preparation and company |                               |  |
|--|-------------------------------|--|
| Product Identity                                 | DEVTHANE 359H CASE RED PART A |  |
| Bulk Sales Reference No.                         | HT7435                        |  |
| Company Name                                     | International Paint LLC       |  |
|  | 6001 Antoine Drive            |  |
|  | Houston Texas 77091           |  |
| Emergency  |                               |  |
| CHEMTREC (USA)                                   | (800) 424–9300                |  |
| International Paint                              | (713) 682–1711                |  |
| Poison Control Center                            | (800) 854–6813                |  |
| Customer Service                                 |                               |  |
| International Paint                              | (800) 589–1267                |  |
| Fax No.  | (800) 631–7481                |  |

2. Hazard identification of the product



#### GHS Classification;

| GHS Classification,   |                |  |
|---|----------------|--|
| Item  | Category       | Hazard   |
| Flammability  | 3              | Flammable liquid and vapor                               |
| Acute Toxicity (mouth)                                      | Not classified | Not applicable   |
| Acute Toxicity (skin)                                       | Not classified | Not applicable   |
| Acute Toxicity (inhalation)                                 | Not classified | Not applicable   |
| Acute Toxicity (ingestion)                                  | Not classified | Not applicable   |
| Skin corrosion/irritation                                   | Not classified | Not applicable   |
| Eye damage/irritation                                       | Not classified | Not applicable   |
| Sensitization (respiratory)                                 | Not classified | Not applicable   |
| Sensitization (skin)  | Not classified | Not applicable   |
| Germ toxicity   | Not classified | Not applicable   |
| Specific target organ systemic toxicity (single exposure)   | 1              | central nerve system                                     |
|   | 2              | Not applicable   |
|   | 3              | narcotic effects, respiratory tract irritation           |
| Specific target organ systemic Toxicity (repeated exposure) | 1              | auditory apparatus, central nerve system                 |
|   | 2              | Not applicable   |
| Aspiration hazard   | Not classified | Not applicable   |
| Harmfulness to aquatic Environment (acute)                  | 3              | Harmful to aquatic life.                                 |
| Harmfulness to aquatic Environment (long term effect)       | 4              | May cause harm to aquatic life with long lasting effects |
| Carcinogenicity   | Not classified | Not applicable   |

| Reproductive Toxicity | Not classified | Not applicable |
|-----------------------|----------------|----------------|
| Organic Peroxide      | Not classified | Not applicable |

#### Safety Phrases:

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

| Overview        | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |  |  |  |
|-----------------|--|--|--|--|
| Inhalation      | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.  |  |  |  |
| Eyes            | Causes severe eye irritation. Avoid contact with eyes.   |  |  |  |
| Skin            | Causes skin irritation. May be harmful if absorbed through the skin.   |  |  |  |
| Ingestion       | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.   |  |  |  |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.   |  |  |  |
| HMIS Rating     | Health: 3 Flammability: 3 Reactivity: 0 PPE: X   |  |  |  |

| 3. Composition/information on ingredients            |              |          |  |  |
|--|--------------|----------|--|--|
| Ingredient   | CAS No.      | Percent  |  |  |
| Butanol  | 0000071-36-3 | 1.0 – 10 |  |  |
| Dicumyl peroxide                                     | 0000080-43-3 | 1.0 – 10 |  |  |
| Diisobutylketone                                     | 0000108-83-8 | 1.0 – 10 |  |  |
| Ethyl orthoformate                                   | 0000122-51-0 | 1.0 – 10 |  |  |
| BUTYL ACETATE  | 0000123-86-4 | 1.0 – 10 |  |  |
| BUTYL ACETATE  | 0000540-88-5 | 1.0 – 10 |  |  |
| BUTYL PEROXYBENZOATE                                 | 0000614-45-9 | 1.0 – 10 |  |  |
| Ethyl 3-ethoxypropionate                             | 0000763-69-9 | 1.0 – 10 |  |  |
| Barium sulfate                                       | 0007727-43-7 | 1.0 – 10 |  |  |
| 2-Heptanone, 4,6-dimethyl-                           | 0019549-80-5 | 1.0 – 10 |  |  |
| Acetic acid, C6–8–branched alkyl esters              | 0090438-79-2 | 1.0 – 10 |  |  |
| PROPRIETARY INGREDIENT (NJTSR<br>678290–00–2–5028–P) | Proprietary  | 1.0 – 10 |  |  |

|             | 4. First aid measures   |
|-------------|---|
| General     | Remove contaminated clothing and shoes. Get medical attention<br>immediately. Wash clothing before reuse. Thoroughly clean or destroy<br>contaminated shoes.  |
| Inhalation  | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.  |
| Eyes        | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.   |
| Skin        | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.  |
| Ingestion   | If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |
|             | 5. Fire-fighting measures   |
| Flash Point | F: 80   |

| ERG Guide No.                       | Not Determined  |
|-------------------------------------|---|
|                                     |   |
|                                     | 6. Accidental release measures  |
| Spill Response<br>Procedures        | ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |
| Public Safety                       | CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).  |
| ERG Guide No.                       | Not Determined  |
|                                     |   |
|                                     | 7. Handling and storage   |
|                                     | ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~   |
| Storage Temperature                 | Store between 40–100F (4–38C).  |
| Handling and Storage<br>Precautions | Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.                          |

#### 8. Exposure controls and personal protection

| CAS No.        | Ingredient         | Source       | Value  |
|----------------|--------------------|--------------|--|
| 0000071–36–3 E | Butanol            | OSHA         | 100 ppm TWA; 300 mg/m3 TWA50 ppm Ceiling;<br>150 mg/m3 Ceiling |
|                |                    | ACGIH        | 20 ppm TWA   |
|                |                    | NIOSH        | 50 ppm Ceiling; 150 mg/m3 Ceiling1400 ppm IDLH<br>(10% LEL)    |
|                |                    | Supplier     | No Established Limit   |
|                |                    | OHSA,<br>CAN | 20 ppm TWA   |
|                |                    | Mexico       | No Established Limit   |
|                |                    | Brazil       | No Established Limit   |
| 0000080-43-3   | Dicumyl peroxide   | OSHA         | No Established Limit   |
|                |                    | ACGIH        | No Established Limit   |
|                |                    | NIOSH        | No Established Limit   |
|                |                    | Supplier     | No Established Limit   |
|                |                    | OHSA,<br>CAN | No Established Limit   |
|                |                    | Mexico       | No Established Limit   |
|                |                    | Brazil       | No Established Limit   |
| 0000108-83-8   | Diisobutylketone   | OSHA         | 50 ppm TWA; 290 mg/m3 TWA                                      |
|                |                    | ACGIH        | 25 ppm TWA   |
|                |                    | NIOSH        | 25 ppm TWA; 150 mg/m3 TWA500 ppm IDLH                          |
|                |                    | Supplier     | No Established Limit   |
|                |                    | OHSA,<br>CAN | 25 ppm TWA   |
|                |                    | Mexico       | 25 ppm TWA; 145 mg/m3 TWA                                      |
|                |                    | Brazil       | No Established Limit   |
| 0000122–51–0 E | Ethyl orthoformate | OSHA         | No Established Limit   |
|                |                    | ACGIH        | No Established Limit   |

|              |                            | NIOSH          | No Established Limit   |
|--------------|----------------------------|----------------|--|
|              |                            | Supplier       | No Established Limit   |
|              |                            | OHSA,<br>CAN   | No Established Limit   |
|              |                            | Mexico         | No Established Limit   |
|              |                            | Brazil         | No Established Limit   |
| 0000123-86-4 | BUTYL ACETATE              | OSHA           | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL;<br>950 mg/m3 STEL                                |
|              |                            | ACGIH          | 150 ppm TWA200 ppm STEL  |
|              |                            | NIOSH          | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL;<br>950 mg/m3 STEL1700 ppm IDLH (10% LEL)         |
|              |                            | Supplier       | No Established Limit   |
|              |                            | OHSA,<br>CAN   | 150 ppm TWA200 ppm STEL  |
|              |                            | Mexico         | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL;<br>950 mg/m3 STEL                                |
|              |                            | Brazil         | No Established Limit   |
| 0000540-88-5 | BUTYL ACETATE              | OSHA           | 200 ppm TWA; 950 mg/m3 TWA   |
|              |                            | ACGIH          | 200 ppm TWA  |
|              |                            | NIOSH          | 200 ppm TWA; 950 mg/m3 TWA1500 ppm IDLH<br>(10% LEL)                                     |
|              |                            | Supplier       | No Established Limit   |
|              |                            | OHSA,<br>CAN   | 200 ppm TWA  |
|              |                            | Mexico         | 200 ppm TWA; 950 mg/m3 TWA250 ppm STEL;<br>1190 mg/m3 STEL                               |
|              |                            | Brazil         | No Established Limit   |
| 0000614-45-9 | BUTYL PEROXYBENZOATE       | OSHA           | No Established Limit   |
|              |                            | ACGIH          | No Established Limit   |
|              |                            | NIOSH          | No Established Limit   |
|              |                            | Supplier       | No Established Limit   |
|              |                            | OHSA,<br>CAN   | No Established Limit   |
|              |                            | Mexico         | No Established Limit   |
|              |                            | Brazil         | No Established Limit   |
| 0000763-69-9 | Ethyl 3–ethoxypropionate   | OSHA           | No Established Limit   |
|              |                            | ACGIH          | No Established Limit   |
|              |                            | NIOSH          | No Established Limit   |
|              |                            | Supplier       |  |
|              |                            | OHSA,<br>CAN   | 50 ppm TWA; 300 mg/m3 TWA  |
|              |                            | Mexico         | No Established Limit   |
| 0007727–43–7 | Barium sulfate             | Brazil<br>OSHA | No Established Limit<br>15 mg/m3 TWA (total dust); 5 mg/m3 TWA<br>(reasticable fraction) |
|              |                            | ACGIH          | (respirable fraction)<br>10 mg/m3 TWA  |
|              |                            | NIOSH          | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)                                 |
|              |                            | Supplier       | No Established Limit   |
|              |                            | OHSA,<br>CAN   | 10 mg/m3 TWA (total dust)  |
|              |                            | Mexico         | No Established Limit   |
|              |                            | Brazil         | No Established Limit   |
| 0019549-80-5 | 2–Heptanone, 4,6–dimethyl– | OSHA           | No Established Limit   |
|              |                            | ACGIH          | No Established Limit   |
|              |                            | NIOSH          | No Established Limit   |
|              |                            | Supplier       | No Established Limit   |
|              |                            | Ouppliel       |  |

| 1            | I                          | Mexico       | No Established Limit |
|--------------|----------------------------|--------------|----------------------|
|              |                            |              |                      |
|              |                            | Brazil       | No Established Limit |
| 0090438-79-2 | Acetic acid, C6–8–branched | OSHA         | No Established Limit |
|              | alkyl esters               | ACGIH        | No Established Limit |
|              |                            | NIOSH        | No Established Limit |
|              |                            | Supplier     | No Established Limit |
|              |                            | OHSA,<br>CAN | No Established Limit |
|              |                            | Mexico       | No Established Limit |
|              |                            | Brazil       | No Established Limit |
| Proprietary  | (NJTSR                     | OSHA         | No Established Limit |
|              |                            | ACGIH        | No Established Limit |
|              | 678290-00-2-5028-P)        | NIOSH        | No Established Limit |
|              |                            | Supplier     | No Established Limit |
|              |                            | OHSA,<br>CAN | No Established Limit |
|              |                            | Mexico       | No Established Limit |
|              |                            | Brazil       | No Established Limit |

| Health Data  |  |        |   |
|--------------|--|--------|---|
| CAS No.      | Ingredient   | Source | Value   |
| 0000071–36–3 | Butanol  |        | Eye and mucous membrane<br>irritation CNS depression  |
| 0000080-43-3 | Dicumyl peroxide                                     | NIOSH  | No Established Limit  |
| 0000108-83-8 | Diisobutylketone                                     | NIOSH  | Irritation; liver kidney  |
| 0000122-51-0 | Ethyl orthoformate                                   | NIOSH  | No Established Limit  |
| 0000123–86–4 | BUTYL ACETATE  | NIOSH  | Mucous membrane and eye irritation;<br>high concentrations cause nervous<br>system effects in animals |
| 0000540-88-5 | BUTYL ACETATE  | NIOSH  | Eye and throat irritation CNS depression  |
| 0000614-45-9 | BUTYL PEROXYBENZOATE                                 | NIOSH  | No Established Limit  |
| 0000763–69–9 | Ethyl 3-ethoxypropionate                             | NIOSH  | No Established Limit  |
| 0007727-43-7 | Barium sulfate                                       | NIOSH  | Eye nose  |
| 0019549–80–5 | 2–Heptanone, 4,6–dimethyl–                           | NIOSH  | No Established Limit  |
| 0090438–79–2 | Acetic acid, C6–8–branched alkyl esters              | NIOSH  | No Established Limit  |
| Proprietary  | PROPRIETARY INGREDIENT (NJTSR<br>678290–00–2–5028–P) | NIOSH  | No Established Limit  |

| CAS No.      | Ingredient          | Source | Value   |
|--------------|---------------------|--------|---|
| 0000071-36-3 | Butanol             | OSHA   | Select Carcinogen: No   |
|              |                     | NTP    | Known: No; Suspected: No  |
|              |                     |        | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0000080-43-3 | Dicumyl peroxide    | OSHA   | Select Carcinogen: No   |
|              |                     | NTP    | Known: No; Suspected: No  |
|              |                     | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0000108-83-8 | Diisobutylketone OS |        | Select Carcinogen: No   |
|              |                     | NTP    | Known: No; Suspected: No  |
|              |                     |        | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0000122-51-0 | Ethyl orthoformate  | OSHA   | Select Carcinogen: No   |
|              | Ι                   | NTP    | Known: No; Suspected: No  |
|              |                     | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0000123-86-4 | BUTYL ACETATE       | OSHA   | Select Carcinogen: No   |
|              |                     | NTP    | Known: No; Suspected: No  |
|              |                     | IARC   |   |

|              |   |      | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
|--------------|---|------|---|
| 0000540-88-5 | BUTYL ACETATE                                 | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              |   | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0000614–45–9 | BUTYL<br>PEROXYBENZOATE                       | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              |   | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0000763–69–9 | Ethyl 3-ethoxypropionate                      | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              |   | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0007727–43–7 |   | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              |   | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0019549–80–5 | 2-Heptanone,<br>4,6-dimethyl-                 | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              |   | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| 0090438–79–2 | Acetic acid,<br>C6–8–branched alkyl<br>esters | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              |   | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |
| . ,          | INGREDIENT (NJTSR                             | OSHA | Select Carcinogen: No   |
|              |   | NTP  | Known: No; Suspected: No  |
|              | 678290-00-2-5028-P)                           | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group<br>3: No; Group 4: No; |

| Respiratory          | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye     |
|----------------------|---|
|                      | watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist  |
|                      | levels are above applicable limits, wear an appropriate, properly fitted respirator   |
|                      | (NIOSH approved) during and after application. Follow respirator manufacturer's   |
|                      | directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION<br>ONLY: For information and assistance on 3M occupational health and safety                                |
|                      | products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in  |
|                      | Canada call 1–800–267–4414. Please do not contact these numbers regarding other   |
|                      | manufacturer's respiratory protection products. 3M does not endorse the accuracy of   |
|                      | the information contained in this Material Safety Data Sheet.   |
| Eyes                 | Avoid contact with eyes. Protective equipment should be selected to provide<br>protection from exposure to the chemicals listed in Section 3 of this document.                    |
|                      | Depending on the site-specific conditions of use, safety glasses, chemical goggles,   |
|                      | and/or head and face protection may be required to prevent contact. The equipment   |
|                      | must be thoroughly cleaned, or discarded after each use.  |
| Skin                 | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific                 |
|                      | conditions of use, protective gloves, apron, boots, head and face protection may be   |
|                      | required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.   |
| Engineering Controle |   |
| Engineering Controls | Prevent build-up of vapors by opening all windows and doors to achieve<br>cross-ventilation.  |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the  |
|                      | immediate vicinity of any potential exposure. Use good personal hygiene practices.  |
|                      | Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled<br>clothing and wash clothing thoroughly before reuse. Shower after work using plenty of |
|                      | soap and water.   |
|                      |   |
|                      | 9. Physical and chemical properties   |

Physical State

Liquid Coloured

| рН               | No Established Limit   |
|------------------|--|
| Specific Gravity | 1.06   |
| Boiling Point F  | 208  |
| Vapor Density    | Heavier than air   |
| VOC %            | Refer to the Technical Data Sheet or label where information is available. |
| Evaporation Rate | Slower than ether  |
|                  |  |

| 10. Stability and reactivity |  |  |  |
|------------------------------|--|--|--|
| General                      | This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled. |  |  |
| Incompatible Materials       | s Strong oxidizing agents.   |  |  |
| Hazardous<br>Decompostion    | May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.  |  |  |

| 11. Toxicological information  |                                  |                                     |                                       |  |
|--|----------------------------------|-------------------------------------|---------------------------------------|--|
| Ingredient   | Oral LD50,<br>mg/kg              | Skin LD50,<br>mg/kg                 | Inhalation<br>Vapor LD50,<br>mg/L/4hr |  |
| Butanol – (0000071–36–3)   | 790.00, Rat –<br>Category: 4     | 3,400.00, Rabbit<br>- Category: 5   | 17.70, Rat –<br>Category: 4           |  |
| Dicumyl peroxide – (0000080–43–3)                                    | 4,000.00, Rat –<br>Category: 5   |                                     |                                       |  |
| Diisobutylketone – (0000108–83–8)                                    | 5,750.00, Rat –<br>Category: NA  | 16,000.00, Rabbit<br>– Category: NA |                                       |  |
| Ethyl orthoformate – (0000122–51–0)                                  | 7,060.00, Rat –<br>Category: NA  |                                     |                                       |  |
| BUTYL ACETATE – (0000123–86–4)                                       | 10,768.00, Rat –<br>Category: NA | 17,600.00, Rabbit<br>– Category: NA |                                       |  |
| BUTYL ACETATE – (0000540–88–5)                                       | 4,100.00, Rat –<br>Category: 5   | 2,000.00, Rabbit<br>- Category: 4   |                                       |  |
| BUTYL PEROXYBENZOATE – (0000614–45–9)                                | 1,012.00, Rat –<br>Category: 4   |                                     |                                       |  |
| Ethyl 3-ethoxypropionate - (0000763-69-9)                            | 3,200.00, Rat –<br>Category: 5   |                                     |                                       |  |
| Barium sulfate – (0007727–43–7)                                      |                                  |                                     |                                       |  |
| 2-Heptanone, 4,6-dimethyl (0019549-80-5)                             |                                  |                                     |                                       |  |
| Acetic acid, C6–8–branched alkyl esters –<br>(0090438–79–2)          |                                  |                                     |                                       |  |
| PROPRIETARY INGREDIENT (NJTSR<br>678290–00–2–5028–P) – (Proprietary) |                                  |                                     |                                       |  |

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

| DOT (Domestic Surface  | Transportation)                 | IMO / IMDG (Ocean Transportation)   |  |  |  |  |  |  |
|--|---------------------------------|---|--|--|--|--|--|--|
| DOT Proper Shipping  |                                 | IMDG Proper Shipping  |  |  |  |  |  |  |
| Name   |                                 | Name  |  |  |  |  |  |  |
| DOT Hazard Class   |                                 | IMDG Hazard Class<br>UN / NA Number   |  |  |  |  |  |  |
| UN / NA Number   |                                 |   |  |  |  |  |  |  |
| DOT Packing Group<br>CERCLA/DOT RQ 438                         | 6 gal. / 38724 lbs.             | IMDG Packing Group<br>System Reference 0  |  |  |  |  |  |  |
|  | o gai. / 0072+100.              | Code  |  |  |  |  |  |  |
|  | 15. Regulatory information      |   |  |  |  |  |  |  |
| Degulatory Quartian  |                                 |   |  |  |  |  |  |  |
| Regulatory Overview  | selected regulations are r      | ction 15 is not intended to be all-inclusive, only<br>represented. All ingredients of this product are listed<br>stance Control Act) Inventory or are not required to be<br>tory. |  |  |  |  |  |  |
| WHMIS Classification   | B2:D2B                          |   |  |  |  |  |  |  |
| DOT Marine Pollutants (10%<br>(No Product Ingredien            |                                 |   |  |  |  |  |  |  |
| DOT Severe Marine Pollutar<br>(No Product Ingredien            | ( )                             |   |  |  |  |  |  |  |
| EPCRA 311/312 Chemicals  | ,                               |   |  |  |  |  |  |  |
| BUTYL ACETA  | ATE (5000 lb final RQ; 227      | 70 kg final RQ)   |  |  |  |  |  |  |
| ·  | 00 lb final RQ; 2270 kg final I | ,   |  |  |  |  |  |  |
| BUTYL ACETA<br>under Butyl ac                                  |                                 | ed under Butyl acetate); 2270 kg final RQ (listed   |  |  |  |  |  |  |
| •  |                                 | al RQ; 45.4 kg final RQ)  |  |  |  |  |  |  |
| EPCRA 302 Extremely Haza<br>(No Product Ingredien              |                                 |   |  |  |  |  |  |  |
| EPCRA 313 Toxic Chemical                                       | s (>.1%) :                      |   |  |  |  |  |  |  |
| Butanol  |                                 |   |  |  |  |  |  |  |
| Xylenes (o–, m   | · · ·                           |   |  |  |  |  |  |  |
| Mass RTK Substances (>1%<br>Barium sulfate                     | 5):                             |   |  |  |  |  |  |  |
| Diisobutylketor  |                                 |   |  |  |  |  |  |  |
| Ethyl orthoform  |                                 |   |  |  |  |  |  |  |
| BUTYL ACETA  |                                 |   |  |  |  |  |  |  |
| Butanol  |                                 |   |  |  |  |  |  |  |
| BUTYL ACETA  | ATE                             |   |  |  |  |  |  |  |
| BUTYL PERO   | XYBENZOATE                      |   |  |  |  |  |  |  |
| Mass Extraordinarily Haz Su                                    | b (>.01%) :                     |   |  |  |  |  |  |  |
| (No Product Ingredien  |                                 |   |  |  |  |  |  |  |
| Penn RTK Substances (>1%<br>Barium sulfate                     | ).                              |   |  |  |  |  |  |  |
| Diisobutylketor  |                                 |   |  |  |  |  |  |  |
| Ethyl orthoform  |                                 |   |  |  |  |  |  |  |
| BUTYL ACETA  |                                 |   |  |  |  |  |  |  |
| Butanol  |                                 |   |  |  |  |  |  |  |
| BUTYL ACETA  | ATE                             |   |  |  |  |  |  |  |
| BUTYL PERO   | XYBENZOATE                      |   |  |  |  |  |  |  |
| Penn Special Hazardous Sul                                     |                                 |   |  |  |  |  |  |  |
| (No Product Ingredien<br>Bhode Island Hazardous Sul            |                                 |   |  |  |  |  |  |  |
| Rhode Island Hazardous Substances (>.1%) :<br>Diisobutylketone |                                 |   |  |  |  |  |  |  |
| BUTYL ACETA  |                                 |   |  |  |  |  |  |  |
| Butanol  |                                 |   |  |  |  |  |  |  |
| BUTYL ACETA  | ATE                             |   |  |  |  |  |  |  |
| BUTYL PERO   | XYBENZOATE                      |   |  |  |  |  |  |  |
| Xylenes (o-, m   | n–, p– isomers)                 |   |  |  |  |  |  |  |
|  |                                 |   |  |  |  |  |  |  |

**RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : Barium sulfate Diisobutylketone Ethyl orthoformate BUTYL ACETATE Butanol BUTYL ACETATE BUTYL PEROXYBENZOATE N.J. Special Hazardous Substances (>.01%) : **BUTYL ALCOHOL** Benzene, ethyl-Ethyl orthoformate **BUTYL ACETATE** Butanol Resin acids and Rosin acids, calcium salts **BUTYL ACETATE** BUTYL PEROXYBENZOATE Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%) : Butanol Xylenes (o-, m-, p- isomers) Proposition 65 – Carcinogens (>0%): Benzene, ethyl-Formaldehyde Proposition 65 – Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed) **Risk Phrases:** 

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.