

Interplus 356

WORLD WIDE PRODUCT RANGE



VOC (MIO) (-5, 23°F), surface tolerant

Hydroblasting
Interplus 356 가

70%
75-125 (4.3-7.1) / 107-179
5.6m²/ (125)
225sq.ft/US (5)

5 (41°F)	8	18	10	*
15 (59°F)	2	10	6	*
25 (77°F)	90	6	4	*
40 (104°F)	45	3	2	*

* International

(Part A) 44 (111°F) 1.5 kg/l (12.7 lb/gal)
(Part B) 27 (81°F) 40(104°F)
305g/l - PG6/23(92), Appendix 3
2.55 lb/gal (305g/l) - EPA Method 24



Ecotech

International

Interplus 356

ISO 8504:1992 가,
 가,
 Interplus 356 Sa1 (ISO 8501-1:1988) C D , SSPC-SP7
 /
 St2 (ISO 8501-1:1988) SSPC-SP2 /
 : needle gun
 Sa2 (ISO 8501-1:1988) SSPC-SP6
 C/D
 가 100 (212°F) St3 (ISO 8501-1:1988) SSPC-SP3
 (Hydroblasting) /
 Sa2½ (ISO 8501-1:1988) SSPC-SP6 , HB2½ M
 (International Hydroblasting Standards)
 International 가
 Interplus 356

가
 (1) (A)
 (2) (B) (A)
 3 :1 ()
 가 5 (41°F) 15 (59°F) 25 (77°F) 40 (104°F)
 8 4 2 45
 - 0.48-0.58mm (19-23 thou)
 - 211kg/cm² (3,000 p.s.i)
 (pot) Gun DeVilbiss MBC JGA
 Air Cap 704 765
 Fluid Tip E
 75-100 (3-4)
 50-75 (2-3)
 International GTA220
 (GTA415)
 International GTA822
 (GTA415)
 International GTA822 가
 가 가
 International GTA822
 ()

Interplus 356

200 (8)
 Interplus 356
 ()
 , Interline 356

Interplus 356

Interplus 356 0 (32°F) 가 가
 가

-5 (23°F)	24	60	60	*
0 (32°F)	16	36	36	*

* International

0 (32°F)

International GTA220 5% Interplus 356 ()
 Interplus 356 100 (212°F)
 Interplus 356

Interplus 356

Intercure 200	Interseal 670 HS	Interzinc 52
Intergard 251	Interzinc 12	Interzinc 280
Intergard 269	Interzinc 22	Interzinc 315
Intergard 270	Interzinc 42	

/ :

Intercure 420	Interplus 356	Interthane 990
Interfine 629 HS	Interplus 770	Interzone 505
Intergard 475 HS	Interplus 880	Interzone 954
Intergard 740	Interseal 670 HS	

: Interplus 356 가 , ,

/ International .

Interplus 356

가 가 , IP Data sheet , International

- &
-
-
-

가
(MSDS)

, International

20	Interplus 356	20	15
5	Interplus 356	5	5
5	Interplus 356	5	3
	Interplus 356	1	1
	International		
U.N. Shipping No.: 1263			
20	27.7kg(61.1lb)	(Part A)	5.3kg(11.7lb) (Part B)
5	25.5kg(56.3lb)	(Part A)	4.0kg(8.8lb) (Part B)
	25 (77°F)	12	

data sheet

가
(data sheet)

가

가

data sheet

data sheet가

: 1997 6 1

Copyright International Paint Ltd ✕ International

International Protective Coatings

Worldwide Availability

World Centre

P.O. Box 20980
Oriol House
16 Connaught Place
London, W2 2ZB
England

Tel: (44) 20 71 479 6000
Fax: (44) 20 71 479 6500

3 Neythal Road
Jurong Town
Singapore 628570

Tel: (65) 663 3051
Fax: (65) 266 5287

115 Hyde Road
Yerongs
Queensland

Tel: (61) 7 3892 8866
Fax: (61) 7 3892 4287
H&S: (61) 800 707 001

P.O. Box 20980
Oriol House
16 Connaught Place
London, W2 2ZB
England

Tel: (44) 20 71 479 6000
Fax: (44) 20 71 479 6500

PO Box 37
Dammam 31411

Tel: (966) 3 842 8436
Fax: (966) 2 842 4361

6001 Antoine Dr.
Houston
Texas 77091

Tel: (1) 713 682 1711
Fax: (1) 713 684 1514

Rua Gomes de Carvalho, 1356,
15º Andar, Vila Olrmpia,
Sao Paulo, S. P.
CEP: 04547-005

Tel: (011) 3044 0344
Fax: (011) 3044 0322

- 615 Tel: 82 (0) 343 448 8556-9 Fax: 82 (0) 2 863 8948
- 244-3 Tel: 82 (0) 51 516 7111-3 Fax: 82 (0) 51 513 3428