Material Safety Data Sheet DEVTHANE 389 SAFETY YELLOW KIT

Sales

0-

Order: {SalesOrd}

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: DC389K9400 08/20/2012



1. Identification of the preparation and company

Product Identity DEVTHANE 389 SAFETY YELLOW KIT

Bulk Sales Reference No. DC389K9400

Company Name International Paint LLC

6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product





Danger

GHS Classification;

GHS Classification,		
Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	1	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
	Not classified	Not applicable

Harmfulness to aquatic Environment (long term effect)		
Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S23: Do not breathe vapor/spray.

S24/25: Avoid contact with skin and eyes.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. May cause allergic

respiratory reaction.

Inhalation Harmful if inhaled. May cause lung injury. Causes nose and throat irritation. Vapors

may affect the brain or nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 3 Flammability: 3 Reactivity: 1 PPE: X

3. Composition/information on ingredients

Ingredient 1,2,4–Trimethyl benzene	CAS No. 0000095-63-6	Percent 1.0 – 10
Benzene, ethyl-	0000100-41-4	0.10 - 1.0
Diisobutylketone	0000108-83-8	1.0 – 10
Methyl n-amyl ketone	0000110-43-0	1.0 – 10
Ethylene glycol monobutyl ether acetate	0000112-07-2	1.0 – 10
BUTYL ACETATE	0000123-86-4	10 – 25
BUTYL PEROXYBENZOATE	0000614-45-9	1.0 – 10
Barium sulfate	0007727-43-7	10 – 25
Titanium dioxide	0013463-67-7	1.0 – 10
2-Heptanone, 4,6-dimethyl-	0019549-80-5	1.0 – 10
Hexamethylene diisocyanate homopolymer	0028182-81-2	1.0 – 10
Petroleum naphtha	0064742-95-6	1.0 – 10

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

Ingestion

If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Flash Point F: 80

C: 27

Lower Explosive Limit (LEL)

.81 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 128

6. Accidental release measures

Spill Response **Procedures**

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

Public Safety

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. 128

7. Handling and storage

Storage Temperature

Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes, skin and clothing. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000100-41-4	Benzene, ethyl-	OSHA	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		ACGIH	100 ppm TWA125 ppm STEL
		NIOSH	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA125 ppm STEL
		Mexico	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
1			

	Brazil	78 ppm TWA; 340 mg/m3 TWA	
0000108-83-8 Diisobutylketone	OSHA	50 ppm TWA; 290 mg/m3 TWA	
	ACGIH	25 ppm TWA	
	NIOSH	25 ppm TWA; 150 mg/m3 TWA500 ppm IDLH	
	Supplier	No Established Limit	
	OHSA, CAN	25 ppm TWA	
	Mexico	25 ppm TWA; 145 mg/m3 TWA	
	Brazil	No Established Limit	
0000110-43-0 Methyl n-amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA	
	ACGIH	50 ppm TWA	
	NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH	
	Supplier	No Established Limit	
	OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA	
	Mexico	50 ppm TWA; 235 mg/m3 TWA100 ppm STEL; 465 mg/m3 STEL	
	Brazil	No Established Limit	
0000112-07-2 Ethylene glycol monobutyl	OSHA	No Established Limit	
ether acetate	ACGIH	20 ppm TWA	
	NIOSH	5 ppm TWA; 33 mg/m3 TWA	
	Supplier	No Established Limit	
	OHSA, CAN	20 ppm TWA	
	Mexico	No Established Limit	
	Brazil	No Established Limit	
0000123-86-4 BUTYL ACETATE	OSHA	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL	
	ACGIH	150 ppm TWA200 ppm STEL	
	NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)	
	Supplier	No Established Limit	
	OHSA, CAN	150 ppm TWA200 ppm STEL	
	Mexico	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL	
	Brazil	No Established Limit	
0000614-45-9 BUTYL PEROXYBENZOATE	OSHA	No Established Limit	
	ACGIH	No Established Limit	
	NIOSH	No Established Limit	
	Supplier	No Established Limit	
	OHSA, CAN	No Established Limit	
	Mexico	No Established Limit	
	Brazil	No Established Limit	
0007727-43-7 Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	
	ACGIH	10 mg/m3 TWA	
	NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	
	Supplier	No Established Limit	
	OHSA, CAN	10 mg/m3 TWA (total dust)	
	Mexico	No Established Limit	
	Brazil	No Established Limit	
0013463–67–7 Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)	
	ACGIH	10 mg/m3 TWA	
	NIOSH	5000 mg/m3 IDLH	
	Supplier	No Established Limit	

		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
0019549-80-5	2-Heptanone, 4,6-dimethyl-	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0028182-81-2	Hexamethylene diisocyanate	OSHA	No Established Limit
	homopolymer	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-95-6	Petroleum naphtha	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4–Trimethyl benzene	NIOSH	No Established Limit
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin
0000108-83-8	Diisobutylketone	NIOSH	Irritation; liver kidney
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000112-07-2	Ethylene glycol monobutyl ether acetate	NIOSH	Adverse effects on blood and hematopoietic system tissue irritation
0000123-86-4	BUTYL ACETATE	NIOSH	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
0000614-45-9	BUTYL PEROXYBENZOATE	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0019549-80-5	2-Heptanone, 4,6-dimethyl-	NIOSH	No Established Limit
	Hexamethylene diisocyanate homopolymer	NIOSH	No Established Limit
0064742-95-6	Petroleum naphtha	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4–Trimethyl benzene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000100-41-4	Benzene, ethyl-	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000108-83-8	Diisobutylketone	OSHA	Select Carcinogen: No

I	1	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;
		IANC	Group 4: No;
0000110-43-0	Methyl n–amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000112-07-2	Ethylene glycol	OSHA	Select Carcinogen: No
	monobutyl ether acetate	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000614-45-9	BUTYL	OSHA	Select Carcinogen: No
	PEROXYBENZOATE	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0019549-80-5	2–Heptanone, 4,6–dimethyl–	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0028182-81-2	Hexamethylene	OSHA	Select Carcinogen: No
	diisocyanate homopolymer	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. A supplied air respirator (either positive pressure or continous flow type) is required. Follow manufacturer's directions for respirator use and observe requirements specified in 29 CFR 1910.134. Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses,

Eyes

chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded

after each use.

Skin Protective equipment should be selected to provide protection from

exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment

must be thoroughly cleaned, or discarded after each use.

Engineering Controls Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

Other Work Practices Emergency eye wash fountains and safety showers should be available in

the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before

reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured

рΗ

Specific Gravity 1.13 Boiling Point F 257

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
1,2,4–Trimethyl benzene – (0000095–63–6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit – Category: 5	
Benzene, ethyl (0000100-41-4)	3,500.00, Rat – Category: 5	15,354.00, Rabbit - Category: NA	17.20, Rat – Category: 4
Diisobutylketone – (0000108–83–8)	5,750.00, Rat – Category: NA	16,000.00, Rabbit - Category: NA	
Methyl n–amyl ketone – (0000110–43–0)	1,670.00, Rat – Category: 4		
Ethylene glycol monobutyl ether acetate – (0000112–07–2)	1,600.00, Rat – Category: 4	1,480.00, Rabbit - Category: 4	
BUTYL ACETATE - (0000123-86-4)	10,768.00, Rat – Category: NA	17,600.00, Rabbit - Category: NA	
BUTYL PEROXYBENZOATE – (0000614–45–9)	1,012.00, Rat – Category: 4		
Barium sulfate - (0007727-43-7)			
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit - Category: NA	6,082.00, Rat – Category: NA
2-Heptanone, 4,6-dimethyl (0019549-80-5)			
Hexamethylene diisocyanate homopolymer – (0028182–81–2)			
Petroleum naphtha – (0064742–95–6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit – Category: 4	5.20, Rat – Category: 3

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

DOT Proper Shipping PAINT IMDG Proper Shipping PAINT

Name Name

DOT Hazard Class 3 – Flammable and

Combustible liquid

UN / NA Number UN 1263 UN / NA Number UN 1263

DOT Packing Group III IMDG Packing Group III

CERCLA/DOT RQ 3156 gal. / 29695 lbs. System Reference 1

Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification B2:D2B

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)

 $BUTYL\ ACETATE~~(5000\ lb\ final\ RQ; 2270\ kg\ final\ RQ)$

Benzene, 1,2-dimethyl- $\,$ (1000 lb final RQ; 454 kg final RQ)

Benzene, 1,4-dimethyl- (100 lb final RQ; 45.4 kg final RQ)

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

1,2,4-Trimethyl benzene

Benzene, ethyl-

Benzene, 1,2-dimethyl-

Benzene, 1,4-dimethyl-

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%):

1,2,4-Trimethyl benzene

Barium sulfate

Diisobutylketone

Methyl n-amyl ketone

BUTYL ACETATE

BUTYL PEROXYBENZOATE

Titanium dioxide

```
Mass Extraordinarily Haz Sub (>.01%):
            Quartz
Penn RTK Substances (>1%):
            1,2,4-Trimethyl benzene
            Barium sulfate
            Diisobutylketone
            Methyl n-amyl ketone
            BUTYL ACETATE
            BUTYL PEROXYBENZOATE
            Titanium dioxide
Penn Special Hazardous Substances (>.01%):
     (No Product Ingredients Listed)
Rhode Island Hazardous Substances (>.1%):
            Diisobutylketone
            Benzene, ethyl-
            Kaolin
            Methyl n-amyl ketone
            BUTYL ACETATE
            BUTYL PEROXYBENZOATE
            Titanium dioxide
            Xylenes (o-, m-, p- isomers)
RCRA Status:
     (No Product Ingredients Listed)
N.J. RTK Substances (>1%):
            1,2,4-Trimethyl benzene
            Barium sulfate
            Diisobutylketone
            Ethylene glycol monobutyl ether acetate
            Methyl n-amyl ketone
            BUTYL ACETATE
            BUTYL PEROXYBENZOATE
            Titanium dioxide
N.J. Special Hazardous Substances (>.01%):
            Cumene
            Benzene, ethyl-
            BUTYL ACETATE
            Benzene, 1,2-dimethyl-
            Quartz
            BUTYL PEROXYBENZOATE
            Benzene, 1,4-dimethyl-
            Xylenes (o-, m-, p- isomers)
N.J. Env. Hazardous Substances (>.1%):
            1,2,4-Trimethyl benzene
            Benzene, ethyl-
            Benzene, 1,2-dimethyl-
            Benzene, 1,4-dimethyl-
            Xylenes (o-, m-, p- isomers)
Proposition 65 - Carcinogens (>0%):
            Cumene
            Benzene, ethyl-
            Quartz
Proposition 65 – Female Repro Toxins (>0%):
     (No Product Ingredients Listed)
Proposition 65 – Male Repro Toxins (>0%):
     (No Product Ingredients Listed)
Proposition 65 – Developmental Toxins (>0%):
```

(No Product Ingredients Listed)

Risk Phrases:

R42/43: May cause sensitisation by inhalation and skin contact.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.