

Safety Data Sheet
DEVTHANE 379 CLEAR GLOSS PART A



Bulk Sales Reference No.:
SDS Revision Date:
SDS Revision Number:

Sales
Order: {SalesOrd}
DC379B0036
08/15/2016
A2-4

1. Identification of the preparation and company

1.1. Product identifier

Product Identity DEVTHANE 379 CLEAR GLOSS PART A
Bulk Sales Reference No. DC379B0036

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
Eye Irrit. 2;H319 Causes serious eye irritation.
Skin Sens. 1;H317 May cause an allergic skin reaction.
STOT SE 3;H336 May cause drowsiness or dizziness.
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist / vapors / spray.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+352 IF ON SKIN: Wash with soap and water.
- P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P331 Do NOT induce vomiting.
- P333+313 If skin irritation or a rash occurs: Get medical advice/attention.
- P337 If eye irritation persists:.
- P363 Wash contaminated clothing before reuse.
- P370 In case of fire: Use water spray, fog, or regular foam..
- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3 Flammability: 4 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
ACRYLIC POLYMER (PROPRIETARY) CAS Number: Proprietary	25 - 50	Eye Dam. 2A;H319	[1]
BUTYL ACETATE CAS Number: 0000123-86-4	10 - 25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Methyl n-amy ketone CAS Number: 0000110-43-0	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6	1.0 - 10	Flam. Liq. 3;H226	[1]
Propylene carbonate CAS Number: 0000108-32-7	1.0 - 10	Eye Irrit. 2;H319	[1]
Silica, amorphous, fumed, cryst.-free CAS Number: 0112945-52-5	1.0 - 10	----	[1]
Petroleum naphtha CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304 Aquatic Chronic 2;H411 (Self Classification)	[1]
Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate CAS Number: 0041556-26-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410 Aquatic Acute 1;H400	[1]
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P CAS Number: 0082919-37-7	0.10 - 1.0	Skin Sens. 1;H317 Aquatic Chronic 1;H410	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO₂, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection
--

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-32-7	Propylene carbonate	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0000108-65-6	Propylene glycol monomethyl ether acetate	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	50 ppm TWA; 270 mg/m3 TWA
		Mexico	
		Brazil	
0000110-43-0	Methyl n-amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA 800 ppm IDLH
		Supplier	
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT 100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT]

DC379B0036_A2

0000123-86-4	BUTYL ACETATE	Brazil	
		OSHA	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH	150 ppm TWA200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier	
		OHSA, CAN	150 ppm TWA200 ppm STEL
		Mexico	150 ppm TWA LMPE-PPT; 710 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 950 mg/m3 STEL [LMPE-CT]
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Brazil	
		OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
0064742-95-6	Petroleum naphtha	Brazil	
		OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	Brazil	
		OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
0112945-52-5	Silica, amorphous, fumed, cryst.-free	Brazil	
		OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
Proprietary	ACRYLIC POLYMER (PROPRIETARY)	Brazil	
		OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	

Health Data

CAS No.	Ingredient	Source	Value
0000108-32-7	Propylene carbonate	NIOSH	
0000108-65-6	Propylene glycol monomethyl ether acetate	NIOSH	

DC379B0036_A2

0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000123-86-4	BUTYL ACETATE	NIOSH	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	NIOSH	
0064742-95-6	Petroleum naphtha	NIOSH	
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	NIOSH	
0112945-52-5	Silica, amorphous, fumed, cryst.-free	NIOSH	
Proprietary	ACRYLIC POLYMER (PROPRIETARY)	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-32-7	Propylene carbonate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-65-6	Propylene glycol monomethyl ether acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0041556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0112945-52-5	Silica, amorphous, fumed, cryst.-free	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
Proprietary	ACRYLIC POLYMER (PROPRIETARY)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other

manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	100 (°C) 212 (°F)
Flash Point	27 (°C) 81 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.01
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.
VOHAP content (gm/litre of paint)	0.74 (as supplied)
VOHAP content (gm/litre of Solid Coating)	0.39 (as supplied)

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

DC379B0036_A2

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
ACRYLIC POLYMER (PROPRIETARY) - (Proprietary)	No data available	No data available	No data available	No data available
BUTYL ACETATE - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available
Methyl n-amyl ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available
Propylene glycol monomethyl ether acetate - (108-65-6)	8,532.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available
Propylene carbonate - (108-32-7)	29,000.00, Rat - Category: NA	23,780.00, Rabbit - Category: NA	No data available	No data available
Silica, amorphous, fumed, cryst.-free - (112945-52-5)	3,160.00, Rat - Category: 5	No data available	No data available	No data available
Petroleum naphtha - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	2,615.00, Rat - Category: 5	No data available	No data available	No data available
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P - (82919-37-7)	No data available	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	3	May cause drowsiness or dizziness.
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

DC379B0036_A2

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
ACRYLIC POLYMER (PROPRIETARY) - (Proprietary)	Not Available	Not Available	0.00 (hr),
BUTYL ACETATE - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Methyl n-amyl ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
Propylene glycol monomethyl ether acetate - (108-65-6)	100.00, Salmo gairdneri	500.00, Daphnia magna	Not Available
Propylene carbonate - (108-32-7)	5,300.00, Leuciscus idus	500.00, Daphnia magna	500.00 (72 hr), Scenedesmus subspicatus
Silica, amorphous, fumed, cryst.-free - (112945-52-5)	Not Available	Not Available	Not Available
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Bis (1,2,2,6,6-pentamethyl-4-piperidiny) sebacate - (41556-26-7)	1.00, Lepomis macrochirus	20.00, Daphnia magna	Not Available
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P - (82919-37-7)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number

Not Regulated

14.2. UN proper shipping name

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)
DOT Proper Shipping Name
Not Regulated

IMO / IMDG (Ocean Transportation)
IMDG Proper Shipping Name

DC379B0036_A2

DOT Hazard Class		IMDG Hazard Class	Not Regulated
		Sub Class	Not applicable
UN / NA Number	Not Regulated		
DOT Packing Group		IMDG Packing Group	Not Regulated
CERCLA/DOT RQ	2800 gal. / 23458 lbs.	System Reference Code	0

14.4. Packing group Not Regulated

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :
1,2,4-Trimethyl benzene

Mass RTK Substances (>1%) :

Methyl n-amyl ketone

BUTYL ACETATE

Penn RTK Substances (>1%) :

Methyl n-amyl ketone

BUTYL ACETATE

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Methyl n-amyl ketone

BUTYL ACETATE

N.J. Special Hazardous Substances (>.01%) :

Cumene

BUTYL ACETATE

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-Trimethyl benzene

Proposition 65 - Carcinogens (>0%):

Cumene

Benzene, ethyl-

Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

- SECTION 2: Hazards identification
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 14: Transport information

End of Document