# Material Safety Data Sheet BAR-RUST 231 HIGH HIDE WHITE PART A

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: NDA003 MSDS Revision Date: 03/20/2012 MSDS Revision Number: A0-



## 1. Identification of the preparation and company

Product Identity BAR-RUST 231 HIGH HIDE WHITE PART A

Bulk Sales Reference No. NDA003

Company Name International Paint LLC 6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

**Customer Service** 

International Paint (800) 589–1267 Fax No. (800) 631–7481

### 2. Hazard identification of the product





Warning

### GHS Classification;

Item	Category	Hazard	
Flammability	3	Flammable liquid and vapor	
Acute Toxicity (mouth)	Not classified	Not applicable	
Acute Toxicity (skin)	Not classified	Not applicable	
Acute Toxicity (inhalation)	Not classified	Not applicable	
Acute Toxicity (ingestion)	Not classified	Not applicable	
Skin corrosion/irritation	Not classified	Not applicable	
Eye damage/irritation	2A	Causes serious eye irritation	
Sensitization (respiratory)	Not classified	Not applicable	
Sensitization (skin)	Not classified	Not applicable	
Germ toxicity	Not classified	Not applicable	
Specific target organ systemic toxicity (single exposure)	1	central nerve system, kidneys, liver, respiratory system	
	2	Not applicable	
	3	narcotic effects, respiratory tract irritation	
Specific target organ systemic Toxicity (repeated exposure)	1	auditory apparatus, central nerve system, lung, respiratory system	
	2	Not applicable	
Aspiration hazard	Not classified	Not applicable	
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.	
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects	

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

#### Safety Phrases:

S28: After contact with skin, wash immediately with plenty of soap and water.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be

selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.

Skin Causes skin irritation. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 3 Flammability: 2 Reactivity: 0 PPE: X

# 3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Butanol	0000071-36-3	1.0 – 10
	0000071-36-3	
1,2,4–Trimethyl benzene	0000095–63–6	1.0 – 10
Benzene, ethyl-	0000100-41-4	0.10 - 1.0
1,3,5–Trimethylbenzene	0000108-67-8	1.0 – 10
Methyl n-amyl ketone	0000110-43-0	1.0 – 10
Magnesium carbonate	0000546-93-0	1.0 – 10
Xylenes (o-, m-, p- isomers)	0001330-20-7	1.0 – 10
Silica, amorphous	0007631-86-9	1.0 – 10
Titanium dioxide	0013463-67-7	10 – 25
Talc	0014807-96-6	1.0 – 10
Aluminum hydroxide	0021645-51-2	1.0 – 10
Polymer of epoxy resin and bisphenol A	0025036-25-3	1.0 – 10
Reaction of epichlorohydrin and bisphenol A	0025085-99-8	10 – 25
Petroleum naphtha	0064742-95-6	1.0 – 10

#### 4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

Ingestion

If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

## 5. Fire-fighting measures

Flash Point

F: 100 C: 38

Lower Explosive Limit (LEL) ERG Guide No.

1 (%vol in air) at Normal Atmospheric Temp and Pressure

Not Determined

### 6. Accidental release measures

Spill Response **Procedures** 

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

**Public Safety** 

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. Not Determined

### 7. Handling and storage

Storage Temperature

Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.

### 8. Exposure controls and personal protection

#### Exposure

CAS No.	Ingredient	Source	Value
0000071–36–3	Butanol	OSHA	100 ppm TWA; 300 mg/m3 TWA50 ppm Ceiling; 150 mg/m3 Ceiling
		ACGIH	20 ppm TWA
		NIOSH	50 ppm Ceiling; 150 mg/m3 Ceiling1400 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit

1	I	Drozil	No Fatablished Limit
0000100 11 1	D	Brazil	No Established Limit
0000100-41-4	Benzene, ethyl-	OSHA	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		ACGIH	100 ppm TWA125 ppm STEL
		NIOSH	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA125 ppm STEL
		Mexico	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
0000108-67-8	1,3,5–Trimethylbenzene	OSHA	No Established Limit
	,,,,,	ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA,	No Established Limit
		CAN	Little Established Ellint
		Mexico	No Established Limit
		Brazil	No Established Limit
0000110-43-0	Methyl n–amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA,	25 ppm TWA; 115 mg/m3 TWA
		CAN	, ,
		Mexico	50 ppm TWA; 235 mg/m3 TWA100 ppm STEL; 465 mg/m3 STEL
		Brazil	No Established Limit
0000546 02 0	Magnesium carbonate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA
0000346-93-0	iwagnesium carbonate		(respirable fraction)
		ACGIH	No Established Limit
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (containing no Asbestos and
		Mexico	10 mg/m3 TWA20 mg/m3 STEL
		Brazil	No Established Limit
0001330–20–7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		Brazil	78 ppm TWA; 340 mg/m3 TWA
0007631-86-9	Silica, amorphous	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	6 mg/m3 TWA3000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA

	NIOSH	5000 mg/m3 IDLH		
	Supplier	No Established Limit		
	OHSA,	10 mg/m3 TWA (total dust)		
	CAN	(10.00)		
	Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)		
	Brazil	No Established Limit		
0014807-96-6 Talc	OSHA	No Established Limit		
	ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and		
	NIOSH	2 mg/m3 TWA (containing no Asbestos and		
	Supplier	No Established Limit		
	OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and		
	Mexico	2 mg/m3 TWA (respirable fraction)		
	Brazil	No Established Limit		
0021645-51-2 Aluminum hydroxide	OSHA	No Established Limit		
	ACGIH	No Established Limit		
	NIOSH	No Established Limit		
	Supplier	No Established Limit		
	OHSA, CAN	No Established Limit		
	Mexico	No Established Limit		
	Brazil	No Established Limit		
0025036-25-3 Polymer of epoxy resin and	OSHA	No Established Limit		
bisphenol A	ACGIH	No Established Limit		
	NIOSH	No Established Limit		
	Supplier	No Established Limit		
	OHSA, CAN	No Established Limit		
	Mexico	No Established Limit		
	Brazil	No Established Limit		
0025085-99-8 Reaction of epichlorohydrin	OSHA	No Established Limit		
and bisphenol A	ACGIH	No Established Limit		
	NIOSH	No Established Limit		
	Supplier	No Established Limit		
	OHSA, CAN	No Established Limit		
	Mexico	No Established Limit		
	Brazil	No Established Limit		
0064742-95-6 Petroleum naphtha	OSHA	No Established Limit		
	ACGIH	No Established Limit		
	NIOSH	No Established Limit		
	Supplier	No Established Limit		
	OHSA, CAN	No Established Limit		
	Mexico	No Established Limit		
	Brazil	No Established Limit		

# Health Data

CAS No.	Ingredient	Source	Value
0000071–36–3	Butanol		Eye and mucous membrane irritation CNS depression
0000095-63-6	1,2,4–Trimethyl benzene	NIOSH	No Established Limit
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin
0000108–67–8	1,3,5–Trimethylbenzene	NIOSH	No Established Limit
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000546-93-0	Magnesium carbonate	NIOSH	Skin mucous membrane
0001330–20–7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant;

			respiratory and eye irritation
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0014807–96–6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit
0025036-25-3	Polymer of epoxy resin and bisphenol A	NIOSH	No Established Limit
0025085–99–8	Reaction of epichlorohydrin and bisphenol A	NIOSH	No Established Limit
0064742-95-6	Petroleum naphtha	NIOSH	No Established Limit

		Carcinogen Data					
CAS No.	Ingredient	Source	Value				
0000071–36–3	Butanol	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0000095–63–6	1,2,4–Trimethyl benzene	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0000100-41-4	Benzene, ethyl-	OSHA	Select Carcinogen: Yes				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;				
0000108–67–8	1,3,5-Trimethylbenzene	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0000546-93-0	Magnesium carbonate	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0001330-20-7	Xylenes (o-, m-, p-	OSHA	Select Carcinogen: No				
isomers)		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;				
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;				
0013463–67–7	Titanium dioxide	OSHA	Select Carcinogen: Yes				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;				
0014807–96–6	Talc	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;				
0021645–51–2	Aluminum hydroxide	OSHA	Select Carcinogen: No				
		NTP	Known: No; Suspected: No				
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;				
0025036-25-3		OSHA	Select Carcinogen: No				

	1	NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0025085-99-8	epichlorohydrin and	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-95-6		OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

**Engineering Controls** 

Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

#### 9. Physical and chemical properties

Physical State Liquid Coloured pH No Established Limit

Specific Gravity 1.44 Boiling Point F 210

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

### 10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

## 11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Butanol - (0000071-36-3)	790.00, Rat – Category: 4	3,400.00, Rabbit - Category: 5	17.70, Rat – Category: 4
1,2,4-Trimethyl benzene – (0000095–63–6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit - Category: 5	
Benzene, ethyl (0000100-41-4)	3,500.00, Rat – Category: 5	15,354.00, Rabbit - Category: NA	17.20, Rat – Category: 4
1,3,5–Trimethylbenzene – (0000108–67–8)	5,000.00, Rat – Category: 5		
Methyl n-amyl ketone - (0000110-43-0)	1,670.00, Rat – Category: 4		
Magnesium carbonate – (0000546–93–0)			
Xylenes (o-, m-, p- isomers) - (0001330-20-7)	4,300.00, Rat – Category: 5	1,700.00, Rabbit - Category: 4	29.08, rat – Category: NA
Silica, amorphous – (0007631–86–9)	5,000.00, Rat – Category: 5	2,000.00, Rabbit - Category: 4	
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit - Category: NA	6,082.00, Rat – Category: NA
Talc - (0014807-96-6)			
Aluminum hydroxide – (0021645–51–2)	5,000.00, Rat – Category: 5		
Polymer of epoxy resin and bisphenol A – (0025036–25–3)			
Reaction of epichlorohydrin and bisphenol A – (0025085–99–8)			
Petroleum naphtha – (0064742–95–6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit - Category: 4	5.20, Rat – Category: 3

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

### 12. Ecological information

### Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

### 13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

# 14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

**DOT Proper Shipping IMDG** Proper Shipping

Name Name

**DOT Hazard Class IMDG Hazard Class** UN / NA Number UN / NA Number **IMDG Packing Group DOT Packing Group** CERCLA/DOT RQ 713 gal. / 8581 lbs. System Reference

0

Code

### 15. Regulatory information

Regulatory Overview

The regulatory data in Section 15 is not intended to be all–inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2:D2B DOT Marine Pollutants (10%): (No Product Ingredient's Listed) DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) EPCRA 311/312 Chemicals and RQs (>.1%): Cumene (5000 lb final RQ; 2270 kg final RQ) Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ) Butanol (5000 lb final RQ; 2270 kg final RQ) Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ) EPCRA 302 Extremely Hazardous (>.1%): (No Product Ingredients Listed) EPCRA 313 Toxic Chemicals (>.1%): 1,2,4-Trimethyl benzene Cumene Benzene, ethyl-Butanol Xylenes (o-, m-, p- isomers) Mass RTK Substances (>1%): 1,2,4-Trimethyl benzene Magnesium carbonate Methyl n-amyl ketone Butanol Silica, amorphous Talc Titanium dioxide 1,3,5-Trimethylbenzene Xylenes (o-, m-, p- isomers) Mass Extraordinarily Haz Sub (>.01%): (No Product Ingredients Listed) Penn RTK Substances (>1%): 1,2,4-Trimethyl benzene Methyl n-amyl ketone Butanol Silica, amorphous Titanium dioxide Xylenes (o-, m-, p- isomers) Penn Special Hazardous Substances (>.01%): (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%): 2-Butoxyethanol Cumene Benzene, ethyl-Magnesium carbonate Methyl n-amyl ketone Butanol Talc Titanium dioxide Xylenes (o-, m-, p- isomers) **RCRA Status:** 

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

1,2,4-Trimethyl benzene

Magnesium carbonate

Methyl n-amyl ketone

Butanol

Talc

Titanium dioxide

Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%):

2-Butoxyethanol

Cumene

Benzene, ethyl-

Isobutyl alcohol

Butanol

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%):

1,2,4-Trimethyl benzene

Cumene

Benzene, ethyl-

Butanol

Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Carbon black

Cumene

Benzene, ethyl-

Proposition 65 – Female Repro Toxins (>0%):

Benzene, methyl-

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

Benzene, methyl-

Risk Phrases:

R36: Irritating to eyes.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.