# Material Safety Data Sheet DEVTHANE 379 SAFETY ORANGE PART A

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: DC379B9200
MSDS Revision Date: 02/17/2015
MSDS Revision Number: A1-



### 1. Identification of the preparation and company

1.1. Product identifier

Product Identity DEVTHANE 379 SAFETY ORANGE PART A

Bulk Sales Reference No. DC379B9200

1.2. Relevant identified uses of the substance or mixture and uses advised against
 Intended Use
 Application Method
 See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC

6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424-9300

 International Paint
 (713) 682-1711

 Poison Control Center
 (800) 854-6813

**Customer Service** 

International Paint (800) 589-1267 Fax No. (800) 631-7481

# 2. Hazard identification of the product

# 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
Org. Perox. C;H242 Heating may cause a fire.
Skin Irrit. 3;H316 Causes mild skin irritation.
Eye Irrit. 2;H319 Causes serious eye irritation.
Skin Sens. 1;H317 May cause an allergic skin reaction.

Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.





Danger.

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P234 Keep only in original container.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P333 If skin irritation or a rash occurs:.

P337 If eye irritation persists:.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P410 Protect from sunlight.

P420 Store away from other materials.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3 Flammability: 3 Reactivity: 0

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

and Federal Hazardous Substances regulations.					
Ingredient/Chemical Designations	Weight %	GHS Classification	Notes		
ACRYLIC POLYMER (PROPRIETARY) CAS Number: Proprietary	10 - 25	Eye Dam. 2A;H319	[1]		
Methyl n-amyl ketone CAS Number: 0000110-43-0	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]		
BUTYL ACETATE CAS Number: 0000123-86-4	10 - 25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]		
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10		[1][2]		
Barium sulfate CAS Number: 0007727-43-7	1.0 - 10		[1][2]		
Dicumyl peroxide CAS Number: 0000080-43-3	1.0 - 10	Org. Perox. F;H242 Eye Irrit. 2;H319 Skin Irrit. 2;H315 Aquatic Chronic 2;H411	[1]		
BUTYL PEROXYBENZOATE CAS Number: 0000614-45-9	1.0 - 10	Org. Perox. C;H242 Acute Tox. 4;H332 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Acute 1;H400	[1]		
Ethyl orthoformate CAS Number: 0000122-51-0	1.0 - 10	Flam. Liq. 2;H225	[1]		
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	1.0 - 10	Skin Sens. 1;H317 Aquatic Chronic 1;H410	[1]		

CAS Number: 0041556-26-7	Aquatic Acute 1;H400	
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P CAS Number: 0082919-37-7	0.10 - 1.0 Skin Sens. 1;H317 Aquatic Chronic 1:H410	[1]

<sup>[1]</sup> Substance classified with a health or environmental hazard.

### 4. First aid measures

### 4.1. Description of first aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash

clothing before reuse. Thoroughly clean or destroy contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get medical

attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT

induce vomiting unless instructed to do so by medical personnel. Never give anything

by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed

through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

### 5. Fire-fighting measures

### 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

### 5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.

<sup>\*</sup>The full texts of the phrases are shown in Section 16.

areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

# 7. Handling and storage

### 7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

#### In Storage

Keep away from heat, sparks and flame.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

### 8. Exposure controls and personal protection

### 8.1. Control parameters

### Exposure

CAS No.	Ingredient	Source	Value
0000080-43-3	Dicumyl peroxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000110-43-0	Methyl n-amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0000122-51-0	Ethyl orthoformate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

1	1	Cupplier	No Established Limit
		Supplier OHSA,	No Established Limit
		CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000123-86-4	BUTYL ACETATE	OSHA	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH	150 ppm TWA200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA,	150 ppm TWA200 ppm STEL
		CAN	
		Mexico	150 ppm TWA LMPE-PPT; 710 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 950 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0000614-45-9	BUTYL PEROXYBENZOATE	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)
		Brazil	No Established Limit
0041556-26-7		OSHA	No Established Limit
	(1,2,2,6,6-pentamethyl-4-piperidinyl)	ACGIH	No Established Limit
	sebacate	NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0082919-37-7	DECANEDIOIC ACID, METHYL	OSHA	No Established Limit
	1,2,2,6,6-PENTAMETHYL-4-P	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit

		Mexico	No Established Limit
		Brazil	No Established Limit
Proprietary ACRYLIC POLYMER	OSHA	No Established Limit	
	(PROPRIETARY)	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
	Mexico	No Established Limit	
	Brazil	No Established Limit	

# Health Data

CAS No.	Ingredient	Source	Value
0000080-43-3	Dicumyl peroxide	NIOSH	No Established Limit
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000122-51-0	Ethyl orthoformate	NIOSH	No Established Limit
0000123-86-4	BUTYL ACETATE	NIOSH	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
0000614-45-9	BUTYL PEROXYBENZOATE	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	NIOSH	No Established Limit
0082919-37-7	DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P	NIOSH	No Established Limit
Proprietary	ACRYLIC POLYMER (PROPRIETARY)	NIOSH	No Established Limit

# Carcinogen Data

CAS No.	Ingredient	Source	Value
0000080-43-3	Dicumyl peroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000122-51-0	Ethyl orthoformate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4 BUTYL ACETATE	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000614-45-9	BUTYL PEROXYBENZOATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
041556-26-7	Bis	OSHA	Select Carcinogen: No

1	1			
(1,2,2,6,6-pentamethyl-4-pip sebacate	(1,2,2,6,6-pentamethyl-4-piperidinyl)	NTP	Known: No; Suspected: No	
	sebacate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0082919-37-7	0082919-37-7 DECANEDIOIC ACID, METHYL	OSHA	Select Carcinogen: No	
1,2,2,6,6-PENTAMETHYL-4-P	1,2,2,6,6-PENTAMETHYL-4-P	NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
Proprietary ACRYLIC POLYMER		OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

### 8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of

the information contained in this Material Safety Data Sheet.

Avoid contact with eyes. Protective equipment should be selected to provide Eyes

> protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment

must be thoroughly cleaned, or discarded after each use.

Skin Protective equipment should be selected to provide protection from exposure to the

> chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded

after each use.

**Engineering Controls** Depending on the site-specific conditions of use, provide adequate ventilation.

Other Work Practices Emergency eye wash fountains and safety showers should be available in the

immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.

### 9. Physical and chemical properties

Appearance Coloured Liquid Odour threshold Not Measured рΗ No Established Limit Melting point / freezing point Not Measured Initial boiling point and boiling range 100 (C) 212 (F) Flash Point 27 (C) 80 (F) Not Measured Evaporation rate (Ether = 1) Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive

limits

Lower Explosive Limit: .6

Not Measured

Upper Explosive Limit: No Established Limit

vapor pressure (Pa) Not Measured Vapor Density Heavier than air

Specific Gravity 1.07

Partition coefficient n-octanol/water (Log

Not Measured Auto-ignition temperature Decomposition temperature Not Measured

Viscosity (cSt) No Established Limit Not Measured VOC %

Refer to the Technical Data Sheet or label where information is available.

### 9.2. Other information

No further information

### 10. Stability and reactivity

### 10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

# 11. Toxicological information

### Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
ACRYLIC POLYMER (PROPRIETARY) - (Proprietary)	No data available	No data available	No data available	No data available
Methyl n-amyl ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available
BUTYL ACETATE - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Dicumyl peroxide - (80-43-3)	4,000.00, Rat - Category: 5	No data available	No data available	No data available
BUTYL PEROXYBENZOATE - (614-45-9)	4,838.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	4.90, Rat - Category: 4
Ethyl orthoformate - (122-51-0)	7,060.00, Rat - Category: NA	17,820.00, Rabbit - Category: NA	No data available	No data available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	2,615.00, Rat - Category: 5	No data available	No data available	No data available

DECANEDIOIC ACID, METHYL	No data	No data	No data	No data available
1,2,2,6,6-PENTAMETHYL-4-P -	available	available	available	
(82919-37-7)				

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

# 12. Ecological information

# 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

# Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
ACRYLIC POLYMER (PROPRIETARY) - (Proprietary)	Not Available	Not Available	Not Available
Methyl n-amyl ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
BUTYL ACETATE - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Dicumyl peroxide - (80-43-3)	Not Available	Not Available	Not Available
BUTYL PEROXYBENZOATE - (614-45-9)	1.50, Danio rerio	Not Available	Not Available
Ethyl orthoformate - (122-51-0)	592.00, Leuciscus idus	Not Available	Not Available
Bis (1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate - (41556-26-7)	1.00, Lepomis macrochirus	20.00, Daphnia magna	Not Available
DECANEDIOIC ACID, METHYL 1,2,2,6,6-PENTAMETHYL-4-P - (82919-37-7)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

#### 14. Transport information

14.1. UN number Not Regulated

14.2. UN proper shipping name

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

DOT Proper Shipping Not Regulated IMDG Proper Name Shipping Name

Sub Class Not applicable

UN / NA Number Not Regulated

CERCLA/DOT RQ 2972 gal. / 26421 lbs. System Reference 0

Code

14.4. Packing group Not Regulated

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA

Inventory.

WHMIS Classification B2 D2B C

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ

(listed under Butyl acetate))

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

Xylenes (o-, m-, p- isomers)

```
Mass RTK Substances (>1%):
     Barium sulfate
     Methyl n-amyl ketone
     BUTYL ACETATE
     BUTYL PEROXYBENZOATE
     Titanium dioxide
Penn RTK Substances (>1%):
     Barium sulfate
     Ethyl orthoformate
     Methyl n-amyl ketone
     BUTYL ACETATE
     BUTYL PEROXYBENZOATE
     Titanium dioxide
Penn Special Hazardous Substances (>.01%):
      (No Product Ingredients Listed)
RCRA Status:
      (No Product Ingredients Listed)
N.J. RTK Substances (>1%):
     Barium sulfate
     Ethyl orthoformate
     Methyl n-amyl ketone
     BUTYL ACETATE
     BUTYL PEROXYBENZOATE
     Titanium dioxide
N.J. Special Hazardous Substances (>.01%):
     2-Butoxyethanol
     Benzene, ethyl-
     Ethyl orthoformate
     BUTYL ACETATE
     BUTYL PEROXYBENZOATE
     Xylenes (o-, m-, p- isomers)
N.J. Env. Hazardous Substances (>.1%):
     Xylenes (o-, m-, p- isomers)
Proposition 65 - Carcinogens (>0%):
     Benzene, ethyl-
     Quartz
     Titanium dioxide
Proposition 65 - Female Repro Toxins (>0%):
     (No Product Ingredients Listed)
Proposition 65 - Male Repro Toxins (>0%):
     (No Product Ingredients Listed)
Proposition 65 - Developmental Toxins (>0%):
     (No Product Ingredients Listed)
```

# 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

**End of Document**