Material Safety Data Sheet DEVMAT 101 CLEAR PART B

WAT TOT GELAR PART B

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} NDA444 04/22/2013 A0-

X.International.

1. Identification of the preparation and company		
Product Identity	DEVMAT 101 CLEAR PART B	
Bulk Sales Reference No.	NDA444	
Company Name	International Paint LLC	
	6001 Antoine Drive	
	Houston Texas 77091	
Emergency		
CHEMTREC (USA)	(800) 424–9300	
International Paint	(713) 682–1711	
Poison Control Center	(800) 854–6813	
Customer Service		
International Paint	(800) 589–1267	
Fax No.	(800) 631–7481	

2. Hazard identification of the product



		1
GHS Classification;		
Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	4	Harmful if swallowed
Acute Toxicity (skin)	4	Harmful in contact with skin
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	1A	Causes severe skin burns and eye damage
Eye damage/irritation	2A	Causes serious eye irritation
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	respiratory system
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	Not classified	Not applicable
Harmfulness to aquatic Environment (long term effect)	Not classified	Not applicable

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S1: Keep locked up.

S9: Keep container in a well-ventilated place.

S23: Do not breathe vapor/spray.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27: Take off immediately all contaminated clothing.

S28: After contact with skin, wash immediately with plenty of soap and water.

S36/37: Wear suitable protective clothing and gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S49: Keep only in the original container.

S51: Use only in well-ventilated areas.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.		
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.		
Eyes	Causes eye burns. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.		
Skin	Causes skin burns. May cause delayed skin irritation. May be fatal if absorbed through the skin.		
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.		
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.		
HMIS Rating	Health: 3 Flammability: 1 Reactivity: 0 PPE: X		

3. Composition/information on ingredients				
Ingredient	CAS No.	Percent		
2,4,6-Tri(dimethylaminomethyl)phenol	0000090-72-2	1.0 – 10		
Furfuryl alcohol	0000098-00-0	25 – 50		
Barium sulfate	0007727-43-7	10 – 25		
Wollastonite (Ca(SiO3))	0013983-17-0	10 – 25		
Talc	0014807–96–6	1.0 – 10		
Quartz	0014808-60-7	0.10 – 1.0		
MIXTURE OF CYCLOALIPHATIC AMINES AND ORGANIC ACID	Proprietary	25 – 50		

This product contains 0.14 percent Quartz.

4. First aid measures

General

Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.

			5/(+++_/(0		
Inhalation			f not breathing, give artificial respiration. If en. Get medical attention immediately.		
Eyes	In case of contact, in 15 minutes. Get med		flush eyes with plenty of water for at least on immediately.		
Skin		In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.			
Ingestion	If swallowed, immed 1–800–854–6813. D	iately conta O NOT inc	act Poison Control Center at luce vomiting unless instructed to do so by anything by mouth to an unconscious		
	5. Fire-fight	ing measu	res		
Flash Point			117 47		
Lower Explosive Lin (LEL)	nit No Established Limit (%vol	in air) at N	ormal Atmospheric Temp and Pressure		
ERG Guide No.	Not Determined				
	6. Accidental re	elease mea	sures		
Spill Response Procedures	immediate area). Use only nor absorbent. Do not touch or wa without risk. Prevent entry into vapor suppressing foam may b	n-sparking lk through waterway be used to bustible m	no smoking, flares, sparks or flames in equipment to handle spilled material and spilled material. Stop leak if you can do so s, sewers, basements or confined areas. A reduce vapors. Absorb or cover with dry aterial and transfer to containers. Use naterial.		
Public Safety	CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).				
ERG Guide No.	Not Determined				
	7. Handling	and storag	ge		
Storage Temperatur Handling and Storag Precautions	ge Keep away from hea flames and pilot light sources of ignition du cause flash fire or igr all windows and door	t, sparks a s, and turn uring use a nite explosi rs to achiev	C). Ind flame. Do not smoke. Extinguish all off stoves, heaters, electric motors and other ind until all vapors are gone. Vapors may vely. Prevent build–up of vapors by opening ve cross–ventilation. Do not get in eyes, on r after each use. Wash thoroughly after		
	8. Exposure controls a	and person	al protection		
	Exp	osure			
CAS No.	Ingredient	Source	Value		
0000090-72-2 2,4,	6-Tri(dimethylaminomethyl)phenol	OSHA	No Established Limit		
		ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
	and shall all a shall a	00114			

OSHA

ACGIH

0000098–00–0 Furfuryl alcohol

50 ppm TWA; 200 mg/m3 TWA15 ppm STEL; 60 mg/m3 STEL

10 ppm TWA15 ppm STEL

		NIOSH	10 ppm TWA; 40 mg/m3 TWA15 ppm STEL; 60 mg/m3 STEL75 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 ppm TWA15 ppm STEL
		Mexico	10 ppm TWA; 40 mg/m3 TWA15 ppm STEL; 60 mg/m3 STEL
		Brazil	4 ppm TWA; 15.5 mg/m3 TWA
0007727–43–7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0013983–17–0	Wollastonite (Ca(SiO3))	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0014807–96–6	Talc	OSHA	No Established Limit
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
		Supplier	No Established Limit
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA (respirable fraction)
		Brazil	No Established Limit
0014808–60–7	Quartz	OSHA	No Established Limit
		ACGIH	0.025 mg/m3 TWA (respirable fraction)
		NIOSH	0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	0.10 mg/m3 TWA (designated substance regulation, respirable)0.10 mg/m3 TWA (respirable fraction)
		Mexico	0.1 mg/m3 TWA (respirable fraction)
		Brazil	No Established Limit
Proprietary	MIXTURE OF CYCLOALIPHATIC AMINES AND ORGANIC ACID	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data			
CAS No.	Ingredient	Source	Value
0000090-72-2	2,4,6–Tri(dimethylaminomethyl)phenol	NIOSH	No Established Limit
0000098-00-0	Furfuryl alcohol	NIOSH	Respiratory effects
0007727-43-7	Barium sulfate	NIOSH	Eye nose

0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit
0014807–96–6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0014808-60-7	Quartz	NIOSH	Chronic lung disease (silicosis)
	MIXTURE OF CYCLOALIPHATIC AMINES AND ORGANIC ACID	NIOSH	No Established Limit

CAS No.	Ingredient	gen Data Source	
	2,4,6-Tri(dimethylaminomethyl)phenol		Select Carcinogen: No
0000000-72-2		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000098-00-0	Furfuryl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013983–17–0	Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0014807–96–6		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0014808–60–7	Quartz	OSHA	Select Carcinogen: Yes
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	MIXTURE OF CYCLOALIPHATIC	OSHA	Select Carcinogen: No
	AMINES AND ORGANIC ACID	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be

required to prevent contact.	The equipment must	be thoroughly	cleaned,	or discarded
after each use.				

Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties				
Physical State	Liquid Coloured			
pH	10			
Specific Gravity	1.37			
Boiling Point F	324			
Vapor Density	Heavier than air			
VOC %	Refer to the Technical Data Sheet or label where information is available.			
Evaporation Rate	Slower than ether			
10. Stability and reactivity				
General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.			
Incompatible Materials	Strong oxidizing agents.			
Hazardous Decompostion	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.			

11. Toxicological information Oral LD50, Skin LD50, Ingredient Inhalation mg/kg Vapor LD50, mg/kg mg/L/4hr 2,4,6-Tri(dimethylaminomethyl)phenol -1,000.00, Rat -1,280.00, Rat -____ (0000090 - 72 - 2)Category: 4 Category: 4 Furfuryl alcohol - (0000098-00-0) 177.00, Rat -400.00, Rabbit -____ Category: 3 Category: 3 Barium sulfate – (0007727–43–7) _____ _____ ____ Wollastonite (Ca(SiO3)) - (0013983-17-0) _____ _____ ____ Talc - (0014807-96-6) Quartz - (0014808-60-7) 500.00, Rat -Category: 4 MIXTURE OF CYCLOALIPHATIC AMINES AND ____ ____ ____ ORGANIC ACID – (Proprietary)

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Demestic	Curfa e e T	······				
,	DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)			
Shipping Name	N.O.S. (C	IVE LIQUIDS, TOXIC, YCLOALIPHATIC JRFURYLALCOHOL)	IMDG Proper Shipping Name	CORROSIVE LIQUIDS, TOXIC, N.O.S. (CYCLOALIPHATIC AMINE/FURFURYLALCOHOL)		
DOT Hazard Class			IMDG Hazard Class	8 (6.1)		
UN / NA Number	UN 2922		UN / NA Number	LINI 2022		
	II		IMDG Packing			
Group	11		Group	11		
CERCLA/DOT RQ	Not Applic	able gal / Not	System	1357		
	Applicable		Reference Code	1007		
		15. Regulatory	information			
		selected regulations are re	epresented. All ingr tance Control Act) I	ded to be all-inclusive, only edients of this product are listed aventory or are not required to be		
WHMIS Classification	WHMIS Classification		ory.			
DOT Marine Polluta (No Product Ir		Listed)				
DOT Severe Marine (No Product Ir						
EPCRA 311/312 Chemicals and RQs (>.1%) : (No Product Ingredients Listed)						
EPCRA 302 Extrem (No Product Ir						
EPCRA 313 Toxic C (No Product Ir		. ,				
Mass RTK Substand	ces (>1%)	:				
Bariun	n sulfate					
Furfur	yl alcohol					
Talc						
Mass Extraordinarily	/ Haz Sub	(>.01%) :				
Quartz						
Penn RTK Substand		:				
	n sulfate					
Talc	Furfuryl alcohol					
	daua Suba	(10/1)				
Penn Special Hazar (No Product Ir	ngredients	Listed)				
Rhode Island Hazardous Substances (>.1%):						
Furfuryl alcohol						
Quartz	Ζ					
Talc						
RCRA Status: (No Product Ir	ngredients	Listed)				
N.J. RTK Substance	es (>1%) :					
Bariun	n sulfate					
Furfur	yl alcohol					
Talc						
N.J. Special Hazard (No Product Ir						
Quartz						
N.J. Env. Hazardous (No Product Ir						
Proposition 65 – Carcinogens (>0%):						
Quartz	Ζ					

Proposition 65 – Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed)

Risk Phrases: R23/24: Toxic by inhalation and in contact with skin. R34: Causes burns. R36/38: Irritating to eyes and skin.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.