In accordance with the Standard for Classification and Labelling of Chemical Substance and Material Safety Data Sheet, Article 10 Paragraph

# SAFETY DATA SHEET

Interzone 101 Chrome Free Yellow Part A

### Section 1. Chemical product and company identification

#### A. Product name : Interzone 101 Chrome Free Yellow Part A

Product code : EAA003

#### B. <u>Relevant identified uses of the substance or mixture and uses advised against</u>

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

C. Manufacturer	: International Paint Ltd. Stoneygate Lane Felling Gateshead Tyne and Wear NE10 0JY UK Tel: +44 (0)191 469 6111	Fax: +44 (0)191 438 3711
Emergency telephone number (with hours of operation)	: +44 (0)191 469 6111 (24H)	
e-mail address of person responsible for this SDS	: sdsfellinguk@akzonobel.com	

## Section 2. Hazards identification

Α.	Hazard classification	<ul> <li>SKIN CORROSION/IRRITATION - Category 2</li> <li>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2</li> <li>SKIN SENSITIZATION - Category 1</li> <li>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1</li> </ul>
		LONG-TERM AQUATIC HAZARD - Category 2

#### B. GHS label elements, including precautionary statements



Signal word	:	Danger	
Hazard statements	:	<ul> <li>Causes serious eye irritation.</li> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes damage to organs through prolonged or repeated exposure.</li> <li>Toxic to aquatic life with long lasting effects.</li> </ul>	
Precautionary statement	<u>s</u>		
Prevention	:	Wear protective gloves. Wear eye or face protection. Avoid release to the environment. Do not breathe dust. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.	

Symbol

٠



# K.International.

## Section 2. Hazards identification

Response	:	Collect spillage. Get medical attention if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Wear appropriate respirator when ventilation is inadequate.
C. Other hazards which do	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture

not result in classification

: Mixture

Ingredient name	Common name	CAS number	%	Classification
crystalline silica, non- respirable powder	silica, crystalline - quartz	14808-60-7	≥30 - <40	Not classified.
Phenol, polymer with formaldehyde, glycidyl ether	phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	≥20 - <30	Skin Irrit. 2, H315
				Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
reaction product: bisphenol-A-	phenoxy resin	25068-38-6	≥20 - <30	Skin Irrit. 2, H315
(epichlorhydrin); epoxy resin				Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
crystalline silica, respirable powder	Respirable content of crystalline silica in whole product	14808-60-7	≥10 - <20	STOT RE 1, H372
Talc , not containing asbestiform fibres	talc (non-asbestos form)	14807-96-6	≥1 - <5	Not classified.
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs	68609-97-2	<10	Skin Irrit. 2, H315
	uciivə			Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.



### Section 4. First-aid measures

Α.	Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
В.	Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
C.	Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
D.	Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
E.	Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
	Specific treatments	:	No specific treatment.
	Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

## **Section 5. Fire-fighting measures**

Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
Specific hazards arising from the chemical	:	This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
	Suitable extinguishing media Unsuitable extinguishing media Specific hazards arising from the chemical Hazardous thermal	Suitable extinguishing media:Unsuitable extinguishing media:Specific hazards arising from the chemical:Hazardous thermal:

### Section 5. Fire-fighting measures

C.	Special protective equipment for fire- fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
	Special precautions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

### Section 6. Accidental release measures

Α.	Personal precautions, protective equipment and emergency	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation.
	procedures		Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

B. Environmental precautions
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### C. Methods and material for containment and cleaning up

Small spill	: Move containers from spill area. Avoid dust generation. Do not dry sweep.
	Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled
	waste container. Place spilled material in a designated, labeled waste container.
	Dispose of via a licensed waste disposal contractor.

Large spill: Move containers from spill area. Approach the release from upwind. Prevent entry<br/>into sewers, water courses, basements or confined areas. Avoid dust generation.<br/>Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place<br/>in a closed, labeled waste container. Dispose of via a licensed waste disposal<br/>contractor. Note: see Section 1 for emergency contact information and Section 13<br/>for waste disposal.

### Section 7. Handling and storage

#### A. Precautions for safe handling

	Protective measures	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
	Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
В.	Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.



# **%**International.

### Section 8. Exposure controls/personal protection

#### A. Control parameters

#### **Occupational exposure limits**

Ingredient name	Exposure limits
crystalline silica, non- respirable powder	Ministry of Labor (Republic of Korea, 8/2013). TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form:
crystalline silica, respirable powder	Respirable fraction Ministry of Labor (Republic of Korea, 8/2013).
Talc , not containing asbestiform fibres	TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction <b>Ministry of Labor (Republic of Korea,</b>
	<b>8/2013).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 6 mg/m <sup>3</sup> 8 hours. Form: total fiber ( fiber size less than 5 μm)

В.	Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
	Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### C. Personal protective equipment

Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Hand protection	: Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>



# **X**.International.

### Section 8. Exposure controls/personal protection

```
Hygiene measures
```

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Section 9. Physical and chemical properties**

Α.	Appearance		
	Physical state	:	Solid.
	Colour	:	Yellow.
В.	Odour	:	Odourless.
C.	Odour threshold	:	Not available.
D.	рН	:	Not applicable.
Ε.	Melting/freezing point	:	Not available.
F.	Boiling point/boiling range	:	Not available.
G.	Flash point	:	Closed cup: 101°C (213.8°F)
Н.	Evaporation rate	:	Not available.
I.	Flammability (solid, gas)	:	Not available.
J.	Lower and upper explosive (flammable) limits	:	Not available.
Κ.	Vapour pressure	:	Not available.
L.	Solubility	:	Not available.
Μ.	Vapour density	:	Not available.
Ν.	Relative density	:	1.63
О.	Partition coefficient: n- octanol/water	:	Not available.
Ρ.	Auto-ignition temperature	:	Not available.
Q.	Decomposition temperature	:	Not available.
R.	Viscosity	:	Kinematic (room temperature): Not applicable.
S.	Molecular weight	:	Not applicable.

### Section 10. Stability and reactivity

Α.	Chemical stability	:	The product is stable.
	Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
В.	Conditions to avoid	:	No specific data.
C.	Incompatible materials	:	No specific data.
D.	Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

٠



# **X**.International.

## Section 11. Toxicological information

Information on the likely routes of exposure	:	Not available.		
Potential acute health effe	ect	<u>'S</u>		
Inhalation	:	No known significant effects or critical hazards.		
Ingestion	:	Irritating to mouth, throat and stomach.		
Skin contact	:	Causes skin irritation. May cause an allergic skin reaction.		
Eye contact	:	Causes serious eye irritation.		
<u>Over-exposure signs/sym</u>	Over-exposure signs/symptoms			
Inhalation	:	No specific data.		
Ingestion	:	No specific data.		
Skin contact	:	Adverse symptoms may include the following: irritation redness		
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness		

#### B. Health hazards

Α.

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	LD50 Oral	Rat	17100 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
Talc , not containing asbestiform fibres	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-

#### Sensitisation

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

### Section 11. Toxicological information

#### Reproductive toxicity

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Name	· · · · · · · ·	Route of exposure	Target organs
crystalline silica, respirable powder	Category 1	Not determined	Not determined

#### Aspiration hazard

Not available.

#### Potential chronic health effects

**Chronic toxicity** 

Not available.

General	<ul> <li>Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.</li> </ul>
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

#### ATE value

Route	Result
Oral	105333.3 mg/kg
Dermal	484362.8 mg/kg

# Section 12. Ecological information

#### A. Ecotoxicity

:

Product/ingredient name	Result	Species	Exposure
oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	IC50 843.75 mg/m <sup>3</sup>	Algae	72 hours
	LC50 5000 mg/l	Fish	96 hours

#### B. Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.		- 87%; 28 to 100 day(s)	Not readily Readily



### Section 12. Ecological information

#### C. Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol- A-(epichlorhydrin); epoxy resin oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	2.64 to 3.78 3.77	- 160 to 263	low

#### D. <u>Mobility in soil</u>

Soil/water partition	: Not available.
coefficient (Koc)	

E. Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Α.	Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

```
    B. Disposal precautions
    This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
```

### Section 14. Transport information

	UN	IMDG	ΙΑΤΑ
A. UN number	UN3077	UN3077	UN3077
B. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Phenol, polymer with formaldehyde, glycidyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Phenol, polymer with formaldehyde, glycidyl ether). Marine pollutant (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (reaction product: bisphenol-A- (epichlorhydrin); epoxy resin, Phenol, polymer with formaldehyde, glycidyl ether)
C. Transport hazard class(es)	9	9	9
D. Packing group	III	III	111
E. Environmental hazards	Yes.	Yes.	Yes.

Date of issue/Date of revision : 14/06/2016 Version 2 :

1



## Section 14. Transport information

F. Additional information	This product is not regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of $\leq 5$ L or $\leq 5$ kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6. 1.1 and 5.0.2.8.
------------------------------	---	---	---

IMDG Code Segregation : Not applicable. group

**Special precautions for user : Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### Section 15. Regulatory information

Α.	Regulation according to ISHA		
	ISHA Article 37	: The following components are listed: Talc	
	ISHA Article 38	: None of the components are listed.	
	Article 2 of Youth	: Not applicable.	
	Protection Act on Substances Hazardous		
	to Youth		
	Exposure Limits of Chemical Substances and Physical Factors		
	The following components have an OEL: crystalline silica, non- respirable powder crystalline silica, respirable powder Talc , not containing asbestiform fibres		
	Exposure Standards established for Harmful Factors	: None of the components are listed.	
	Harmful Factors Subject to Work Environment Measurement	: The following components are listed: Quartz; Quartz; Talc, non-asbestos form	
	Harmful Factors Subject to Special Health Check- up	: None of the components are listed.	
	Hazardous Substances Subject to Control	: None of the components are listed.	
В.	Regulation according to	<u>FCCA</u>	
	TCCA Toxic chemicals	: Not applicable	
	TCCA Observational chemicals	: None of the components are listed.	
	TCCA Article 32 (Banned)	: The following components are listed: Talc	
	TCCA Article 32 (Restricted)	: None of the components are listed.	
	TCCA Article 17 (TRI)	: The following components are listed: 4,4'-(1-Methylethylidene) bisphenol polymer with (chloromethyl)oxirane	
	Korea inventory	: Not determined.	
	Accident Precaution chemicals	: None of the components are listed.	



## Section 15. Regulatory information

C.	Dangerous Materials Safety Management Act	:	Not available.
D.	Wastes regulation	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Ε.	Regulation according to	oth	er foreign laws
	Europe inventory	:	Not determined.
	United States inventory (TSCA 8b)	:	Not determined.
	Japan inventory	:	Not determined.
	Safety, health and environmental regulations specific for the product	:	No known specific national and/or regional regulations applicable to this product (including its ingredients).

### **Section 16. Other information**

Α.	References	:	Not available.
В.	Date of issue/Date of revision	:	14/06/2016
C.	Version	:	2
	Date of printing	:	14/06/2016
D.	Other		
	Indicates information that	ha	s changed from previously issued version.
	Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

#### Notice to reader

•

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).



# X.International.

# Section 16. Other information

© AkzoNobel

:

### AkzoNobel