Material Safety Data Sheet DEVCHEM 253 PASTEL RED KIT

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: DC253K7750 12/04/2012 0-3



1. Identification of the preparation and company

Product Identity DEVCHEM 253 PASTEL RED KIT

Bulk Sales Reference No. DC253K7750

Company Name International Paint LLC

6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product









Danger

GHS Classification;

ario diassilication,			
Item	Category	Hazard	
Flammability	3	Flammable liquid and vapor	
Acute Toxicity (mouth)	4	Harmful if swallowed	
Acute Toxicity (skin)	5	May be harmful in contact with skin	
Acute Toxicity (inhalation)	Not classified	Not applicable	
Acute Toxicity (ingestion)	Not classified	Not applicable	
Skin corrosion/irritation	1A	Causes severe skin burns and eye damage	
Eye damage/irritation	2A	Causes serious eye irritation	
Sensitization (respiratory)	Not classified	Not applicable	
Sensitization (skin)	1	May cause allergic reaction.	
Germ toxicity	Not classified	Not applicable	
Specific target organ systemic toxicity (single exposure)	1	Not applicable	
	2	Not applicable	
	3	narcotic effects, respiratory tract irritation	
Specific target organ systemic Toxicity (repeated exposure)	1	lung, respiratory system	
	2	Not applicable	
Aspiration hazard	Not classified	Not applicable	
Harmfulness to aquatic Environment (acute)	2	Toxic to aquatic life.	
Harmfulness to aquatic Environment (long term effect)	2	Toxic to aquatic life with long lasting effects	

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S1: Keep locked up.

S9: Keep container in a well-ventilated place.

S23: Do not breathe vapor/spray.

S24: Avoid contact with skin.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27: Take off immediately all contaminated clothing.

S28: After contact with skin, wash immediately with plenty of soap and water.

S36/37: Wear suitable protective clothing and gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S49: Keep only in the original container.

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes eye burns. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this

document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The

equipment must be thouroughly cleaned, or discarded after each use.

Skin Causes skin burns. May cause delayed skin irritation. May cause allergic skin

reaction. May be fatal if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 3* Flammability: 2 Reactivity: 0 PPE: X

3. Composition/information on ingredients

Ingredient	CAS No.	Percent
Furfuryl alcohol	0000098-00-0	1.0 – 10
Methyl n-amyl ketone	0000110-43-0	10 – 25
Barium sulfate	0007727-43-7	10 – 25
Titanium dioxide	0013463-67-7	1.0 – 10
Wollastonite (Ca(SiO3))	0013983-17-0	1.0 – 10
Talc	0014807-96-6	1.0 – 10
Reaction of epichlorohydrin and bisphenol A	0025085-99-8	1.0 – 10
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	0028064-14-4	25 – 50
Petroleum naphtha	0064742-95-6	1.0 – 10
MIXTURE OF CYCLOALIPHATIC AMINES AND ORGANIC ACID	Proprietary	10 – 25

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If Inhalation

breathing is difficult, give oxygen. Get medical attention immediately.

In case of contact, immediately flush eyes with plenty of water for at least Eyes

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

If swallowed, immediately contact Poison Control Center at Ingestion

> 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious

person.

5. Fire-fighting measures

Flash Point F: 80

C: 27

Lower Explosive Limit (LEL)

1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No.

6. Accidental release measures

Spill Response Procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. Fully Encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.

Public Safety

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 meters (75 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 100 meters (330 feet).

ERG Guide No. 127

7. Handling and storage

Storage Temperature

Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value
0000098-00-0	Furfuryl alcohol	OSHA	50 ppm TWA; 200 mg/m3 TWA15 ppm STEL; 60 mg/m3 STEL
		ACGIH	10 ppm TWA15 ppm STEL
			10 ppm TWA; 40 mg/m3 TWA15 ppm STEL; 60 mg/m3 STEL75 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 ppm TWA15 ppm STEL

mg/m3 STEL Brazil 4 ppm TWA; 15.5 mg/m3 TWA	
0000110-43-0 Methyl n-amyl ketone OSHA 100 ppm TWA; 465 mg/m3 TWA ACGIH 50 ppm TWA	
ACGIH 50 ppm TWA	
NIOSH 100 ppm TWA; 465 mg/m3 TWA800	
	ppm IDLH
Supplier No Established Limit	
OHSA, 25 ppm TWA; 115 mg/m3 TWA	
Mexico 50 ppm TWA; 235 mg/m3 TWA100 p mg/m3 STEL	pm STEL; 465
Brazil No Established Limit	
0007727-43-7 Barium sulfate OSHA 15 mg/m3 TWA (total dust); 5 mg/m3 (respirable fraction)	TWA
ACGIH 10 mg/m3 TWA	
NIOSH 10 mg/m3 TWA (total dust); 5 mg/m3 (respirable dust)	TWA
Supplier No Established Limit	
OHSA, 10 mg/m3 TWA (total dust) CAN	
Mexico No Established Limit	
Brazil No Established Limit	
0013463-67-7 Titanium dioxide OSHA 15 mg/m3 TWA (total dust)	
ACGIH 10 mg/m3 TWA	
NIOSH 5000 mg/m3 IDLH	
Supplier No Established Limit	
OHSA, 10 mg/m3 TWA (total dust) CAN	
Mexico 10 mg/m3 TWA (as Ti)20 mg/m3 STE	EL (as Ti)
Brazil No Established Limit	
0013983–17–0 Wollastonite (Ca(SiO3)) OSHA No Established Limit	
ACGIH No Established Limit	
NIOSH No Established Limit	
Supplier No Established Limit	
OHSA, No Established Limit CAN	
Mexico No Established Limit	
Brazil No Established Limit	
0014807–96–6 Talc OSHA No Established Limit ACGIH 2 mg/m3 TWA (particulate matter cor asbestos and	ntaining no
NIOSH 2 mg/m3 TWA (containing no Asbest	oc and
Supplier No Established Limit	os anu
OHSA, 2 mg/m3 TWA (containing no Asbest	os and
Mexico 2 mg/m3 TWA (respirable fraction)	
Brazil No Established Limit	
0025085–99–8 Reaction of epichlorohydrin OSHA No Established Limit	
and bisphenol A ACGIH No Established Limit	
NIOSH No Established Limit	
Supplier No Established Limit	
OHSA, No Established Limit CAN	
Mexico No Established Limit	
Brazil No Established Limit	
0028064-14-4 PHENOL, POLYMER WITH OSHA No Established Limit	
FORMALDEHYDE, ACGIH No Established Limit	
GLYCIDYL ETHER NIOSH No Established Limit	
Supplier No Established Limit	·

		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-95-6	Petroleum naphtha	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
Proprietary	MIXTURE OF	OSHA	No Established Limit
	CYCLOALIPHATIC AMINES AND ORGANIC ACID	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000098-00-0	Furfuryl alcohol	NIOSH	Respiratory effects
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	No Established Limit
0014807–96–6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0025085–99–8	Reaction of epichlorohydrin and bisphenol A	NIOSH	No Established Limit
	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	NIOSH	No Established Limit
0064742-95-6	Petroleum naphtha	NIOSH	No Established Limit
- /	MIXTURE OF CYCLOALIPHATIC AMINES AND ORGANIC ACID	NIOSH	No Established Limit

Carcinogen Data

Ingredient	Source	Value	
Furfuryl alcohol	OSHA	Select Carcinogen: No	
	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
Methyl n-amyl ketone	OSHA	Select Carcinogen: No	
	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0007727-43-7 Barium sulfate		Select Carcinogen: No	
		Known: No; Suspected: No	
		Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0013463-67-7 Titanium dioxide		Select Carcinogen: Yes	
	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;	
Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No	
P	Methyl n–amyl ketone Barium sulfate Titanium dioxide	Methyl n-amyl ketone OSHA NTP IARC Barium sulfate OSHA NTP IARC Titanium dioxide OSHA NTP IARC	

I	l	NITO	Marriago Nacio Oceano etc. Il No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0014807-96-6	Talc	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;	
0025085-99-8	Reaction of	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
	bisphenol A	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0028064-14-4	WITH	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
Proprietary	CYCLOALIPHATIC	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site—specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured pH No Established Limit

Specific Gravity 1.19 Boiling Point F 210

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
Furfuryl alcohol – (0000098–00–0)	177.00, Rat – Category: 3	400.00, Rabbit – Category: 3	
Methyl n-amyl ketone - (0000110-43-0)	1,670.00, Rat – Category: 4		
Barium sulfate - (0007727-43-7)			
Titanium dioxide – (0013463–67–7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	6,082.00, Rat – Category: NA
Wollastonite (Ca(SiO3)) - (0013983-17-0)			
Talc - (0014807-96-6)			
Reaction of epichlorohydrin and bisphenol A – (0025085–99–8)			
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER – (0028064–14–4)			
Petroleum naphtha – (0064742–95–6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit - Category: 4	5.20, Rat – Category: 3
MIXTURE OF CYCLOALIPHATIC AMINES AND ORGANIC ACID – (Proprietary)			

General NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage.

Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8

and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation)

DOT Proper Shipping
Name

PAINT, FLAMMABLE
LIQUID, CORROSIVE
DOT Hazard Class

IMDG Proper Shipping
Name

PAINT, FLAMMABLE
Name
LIQUID, CORROSIVE
Name

IMDG Hazard Class

3 Flammable and

Combustible Liquids, 8 Corrosive Liquids

UN / NA Number UN 3469 UN / NA Number UN 3469
DOT Packing Group III IMDG Packing Group III

CERCLA/DOT RQ 2214 gal. / 21950 lbs. System Reference 206

Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all–inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification B2:D2B

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Butanol (5000 lb final RQ; 2270 kg final RQ)

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

1,2,4-Trimethyl benzene

Butanol

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%):

Barium sulfate

Furfuryl alcohol

Methyl n-amyl ketone

Talc

Titanium dioxide

Mass Extraordinarily Haz Sub (>.01%) :

Quartz

Penn RTK Substances (>1%):

Barium sulfate

Furfuryl alcohol

Methyl n-amyl ketone

Talc

Titanium dioxide

Penn Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%):

Furfuryl alcohol

Methyl n-amyl ketone

Butanol

Talc

Titanium dioxide

Xylenes (o-, m-, p- isomers)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Barium sulfate

Furfuryl alcohol

Methyl n-amyl ketone

Talc

Titanium dioxide

N.J. Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

Cumene

Benzene, ethyl-

Butanol

Quartz

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%):

1,2,4-Trimethyl benzene

Butanol

Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Cumene

Benzene, ethyl-

Quartz

Proposition 65 – Female Repro Toxins (>0%):

Benzene, methyl-

Proposition 65 – Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

Benzene, methyl-

Risk Phrases:

R23/24: Toxic by inhalation and in contact with skin.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.