

Material Safety Data Sheet
DEVTHANE 389 BASE WHITE TINT PART A

Sales
Order: {SalesOrd}
HV9500
04/07/2015
A1-2

Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:



1. Identification of the preparation and company

1.1. Product identifier

Product Identity DEVTHANE 389 BASE WHITE TINT PART A
Bulk Sales Reference No. HV9500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
Org. Perox. C;H242 Heating may cause a fire.
Skin Irrit. 3;H316 Causes mild skin irritation.
Skin Sens. 1;H317 May cause an allergic skin reaction.
Aquatic Acute 2;H401 Toxic to aquatic life.
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.
H242 Heating may cause a fire.
H316 Causes mild skin irritation.
H317 May cause an allergic skin reaction.
H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P234 Keep only in original container.

P260 Do not breathe mist / vapors / spray.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P333 If skin irritation or a rash occurs:.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P410 Protect from sunlight.

P420 Store away from other materials.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3 Flammability: 3 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Titanium dioxide CAS Number: 0013463-67-7	10 - 25	----	[1][2]
Barium sulfate CAS Number: 0007727-43-7	10 - 25	----	[1][2]
Methyl n-amyI ketone CAS Number: 0000110-43-0	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
BUTYL ACETATE CAS Number: 0000123-86-4	10 - 25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Diisobutylketone CAS Number: 0000108-83-8	1.0 - 10	Flam. Liq. 3;H226 STOT SE 3;H335	[1][2]
Ethylene glycol monobutyl ether acetate CAS Number: 0000112-07-2	1.0 - 10	Acute Tox. 4;H332 Acute Tox. 4;H312	[1][2]
BUTYL PEROXYBENZOATE CAS Number: 0000614-45-9	1.0 - 10	Org. Perox. C;H242 Acute Tox. 4;H332 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Acute 1;H400	[1]
2-Heptanone, 4,6-dimethyl- CAS Number: 0019549-80-5	1.0 - 10	----	[1]
Silica, amorphous CAS Number: 0007631-86-9	1.0 - 10	----	[1][2]
Aluminum hydroxide CAS Number: 0021645-51-2	1.0 - 10	Eye Irrit. 2;H319 STOT SE 3;H335	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.
 CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.
 SMALL FIRES: Use dry chemical, CO2, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

HV9500_A1

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-83-8	Diisobutylketone	OSHA	50 ppm TWA; 290 mg/m3 TWA
		ACGIH	25 ppm TWA
		NIOSH	25 ppm TWA; 150 mg/m3 TWA500 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA
		Mexico	25 ppm TWA LMPE-PPT; 145 mg/m3 TWA LMPE-PPT
		Brazil	No Established Limit
0000110-43-0	Methyl n-amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0000112-07-2	Ethylene glycol monobutyl ether acetate	OSHA	No Established Limit
		ACGIH	20 ppm TWA
		NIOSH	5 ppm TWA; 33 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0000123-86-4	BUTYL ACETATE	OSHA	

HV9500_A1

			150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH	150 ppm TWA200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	150 ppm TWA200 ppm STEL
		Mexico	150 ppm TWA LMPE-PPT; 710 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 950 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0000614-45-9	BUTYL PEROXYBENZOATE	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007631-86-9	Silica, amorphous	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	6 mg/m3 TWA3000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)
		Brazil	No Established Limit
0019549-80-5	2-Heptanone, 4,6-dimethyl-	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0021645-51-2	Aluminum hydroxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

HV9500_A1

		OSHA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000108-83-8	Diisobutylketone	NIOSH	Irritation; liver kidney
0000110-43-0	Methyl n-amyl ketone	NIOSH	Irritation; liver kidney
0000112-07-2	Ethylene glycol monobutyl ether acetate	NIOSH	Adverse effects on blood and hematopoietic system tissue irritation
0000123-86-4	BUTYL ACETATE	NIOSH	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
0000614-45-9	BUTYL PEROXYBENZOATE	NIOSH	No Established Limit
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0019549-80-5	2-Heptanone, 4,6-dimethyl-	NIOSH	No Established Limit
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-83-8	Diisobutylketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000112-07-2	Ethylene glycol monobutyl ether acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000614-45-9	BUTYL PEROXYBENZOATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0019549-80-5	2-Heptanone, 4,6-dimethyl-	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

HV9500_A1

0021645-51-2	Aluminum hydroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	125 (C) 257 (F)
Flash Point	27 (C) 80 (F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .81 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.28
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

9.2. Other information

No further information

10. Stability and reactivity

HV9500_A1

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Methyl n-amyl ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available
BUTYL ACETATE - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available
Diisobutylketone - (108-83-8)	5,750.00, Rat - Category: NA	16,000.00, Rabbit - Category: NA	No data available	No data available
Ethylene glycol monobutyl ether acetate - (112-07-2)	2,400.00, Rat - Category: 5	1,500.00, Rabbit - Category: 4	No data available	No data available
BUTYL PEROXYBENZOATE - (614-45-9)	4,838.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	4.90, Rat - Category: 4
2-Heptanone, 4,6-dimethyl- - (19549-80-5)	No data available	No data available	No data available	No data available
Silica, amorphous - (7631-86-9)	5,110.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available
Aluminum hydroxide - (21645-51-2)	5,000.00, Rat - Category: 5	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable

HV9500_A1

Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Methyl n-amyl ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
BUTYL ACETATE - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Diisobutylketone - (108-83-8)	140.00, Oncorhynchus mykiss	250.00, Daphnia magna	100.00 (96 hr), Selenastrum capricornutum
Ethylene glycol monobutyl ether acetate - (112-07-2)	Not Available	Not Available	Not Available
BUTYL PEROXYBENZOATE - (614-45-9)	1.50, Danio rerio	Not Available	Not Available
2-Heptanone, 4,6-dimethyl- - (19549-80-5)	Not Available	Not Available	Not Available
Silica, amorphous - (7631-86-9)	10,000.00, Danio rerio	10,000.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus
Aluminum hydroxide - (21645-51-2)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class	3
		Sub Class	3
UN / NA Number	UN 1263		
DOT Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	4539 gal. / 48435 lbs.	System Reference Code	2

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B C

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :
1,2,4-Trimethyl benzene

Mass RTK Substances (>1%) :

Barium sulfate
Diisobutylketone
Methyl n-amyl ketone
BUTYL ACETATE
Silica, amorphous
BUTYL PEROXYBENZOATE

- Titanium dioxide
- Penn RTK Substances (>1%) :
 - Barium sulfate
 - Diisobutylketone
 - Methyl n-amyl ketone
 - BUTYL ACETATE
 - Silica, amorphous
 - BUTYL PEROXYBENZOATE
 - Titanium dioxide
- Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)
- RCRA Status:
(No Product Ingredients Listed)
- N.J. RTK Substances (>1%) :
 - Barium sulfate
 - Diisobutylketone
 - Ethylene glycol monobutyl ether acetate
 - Methyl n-amyl ketone
 - BUTYL ACETATE
 - Silica, amorphous
 - BUTYL PEROXYBENZOATE
 - Titanium dioxide
- N.J. Special Hazardous Substances (>.01%) :
 - BUTYL ACETATE
 - Quartz
 - BUTYL PEROXYBENZOATE
- N.J. Env. Hazardous Substances (>.1%) :
 - 1,2,4-Trimethyl benzene
- Proposition 65 - Carcinogens (>0%):
 - Cumene
 - Benzene, ethyl-
 - Quartz
 - Titanium dioxide
- Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)
- Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)
- Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

The following sections have changed since the previous revision.

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 9: Physical and chemical properties

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 14: Transport information

End of Document