Material Safety Data Sheet CEILCOTE 660 HV COROCRETE BUFF PART A

OTE 660 HV COROCRETE BUFF PART

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} NCA662 12/08/2011 A0-5

X.International.

1. Identification of	the preparation and company
Product Identity	CEILCOTE 660 HV COROCRETE BUFF PART A
Bulk Sales Reference No.	NCA662
Company Name	International Paint LLC
	6001 Antoine Drive
	Houston Texas 77091
Emergency	
CHEMTREC (USA)	(800) 424–9300
International Paint	(713) 682–1711
Poison Control Center	(800) 854–6813
Customer Service	
International Paint	(800) 589–1267
Fax No.	(800) 631–7481

2. Hazard identification of the product



arning	

		5
GHS Classification;		
Item	Category	Hazard
Flammability	4	Combustible liquid
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	2	Causes skin irritation
Eye damage/irritation	2A	Causes serious eye irritation
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S1: Keep locked up.

S23: Do not breathe vapor/spray.

S24: Avoid contact with skin.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27: Take off immediately all contaminated clothing.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.					
Inhalation		Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.				
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.					
Skin	Causes skin irritation. May cause delayed skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.					
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.					
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.					
HMIS Rating	Health: 1*	Flammability: 1	Reactivity: 0	PPE: X		

3. Composition/information on ingredients					
Ingredient	CAS No.	Percent			
Propylene glycol monomethyl ether acetate	0000108-65-6	1.0 – 10			
Silica, amorphous	0007631-86-9	1.0 – 10			
Titanium dioxide 0013463–67–7 1.0 – 10					
Reaction product of epichlorohydrin & bisphenol A 0025085–99–8 25 – 50					
PHENOL, POLYMER WITH FORMALDEHYDE, 0028064–14–4 10 – 25 GLYCIDYL ETHER 10 – 25					
Oxirane, mono[(C12–14–alkyloxy)methyl] derivs. 0068609–97–2 1.0 – 10					
Talc (*non-asbestiform) 14807-96-6* 10 - 25					
4. First aid measures					

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	

			ately flush eyes with plenty of water for at least ttention immediately.		
Skin	In case of co	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.			
Ingestion	lf swallowed 1–800–854–	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious			
	5. Fi	re-fighting m	easures		
Flash Point			F: 200 C: 93		
Lower Explosive ERG Guide No.	Limit (LEL) 1 (%vol ir 159	n air) at Norm	al Atmospheric Temp and Pressure		
	6. Accid	dental release	measures		
Spill Response Procedures	immediate area). Do n do so without risk. Pre areas. Absorb or cove	ot touch or wa vent entry into r with dry eart LARGE SPIL	EES (no smoking, flares, sparks or flames in alk through spilled material. Stop leak if you can b waterways, sewers, basements or confined h, sand, or other non-combustible material and LS: Dike far ahead of liquid spill to contain e control.		
Public Safety	area immediately for a	CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed			
ERG Guide No.	159				
	7. ⊦	landling and s	storage		
Storage Temper:	atura Store betwee	n 40_100E (4	-38C)		
Storage TemperatureStore between 40–100F (4–38C).Handling and StorageKeep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and othe sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.					
	8. Exposure c	ontrols and pe	ersonal protection		
		Exposure			
CAS No.	Ingredient	Source	Value		
	Propylene glycol monomethyl	OSHA	No Established Limit		
e	ther acetate	ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	50 ppm TWA; 270 mg/m3 TWA		

Mexico

Brazil

OSHA

ACGIH

NIOSH

Supplier

OHSA,

CAN Mexico

0007631-86-9 Silica, amorphous

No Established Limit

6 mg/m3 TWA3000 mg/m3 IDLH

		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)
		Brazil	No Established Limit
025085-99-8	Reaction product of	OSHA	No Established Limit
	epichlorohydrin & bisphenol A	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
028064-14-4	PHENOL, POLYMER WITH	OSHA	No Established Limit
	FORMALDEHYDE, GLYCIDYL	ACGIH	No Established Limit
	ETHER	NIOSH	No Established Limit
		Supplier	No Established Limit
	OHSA, CAN	No Established Limit	
	Mexico	No Established Limit	
	Brazil	No Established Limit	
168609–97–2 Oxirane,		OSHA	No Established Limit
	mono[(C12–14–alkyloxy)methyl]	ACGIH	No Established Limit
	derivs.	NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
4807–96–6*	Talc (*non-asbestiform)	OSHA	No Established Limit
	. , ,	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

	Health Data			
CAS No.	Ingredient	Source	Value	
	Propylene glycol monomethyl ether acetate	NIOSH	No Established Limit	
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit	
0013463–67–7	Titanium dioxide	NIOSH	Lung tumors in animals	
	Reaction product of epichlorohydrin & bisphenol A	NIOSH	No Established Limit	
	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	NIOSH	No Established Limit	
	Oxirane, mono[(C12–14–alkyloxy)methyl] derivs.	NIOSH	No Established Limit	
14807–96–6*	Talc (*non-asbestiform)	NIOSH	No Established Limit	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-65-6		OSHA	Select Carcinogen: No

	Propylene glycol monomethyl	NTP	Known: No; Suspected: No
	ether acetate	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007631–86–9	Silica, amorphous	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0013463–67–7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0025085–99–8 Reaction product of epichlorohydrin & bisphenol A	Reaction product of	OSHA	Select Carcinogen: No
	epichlorohydrin & bisphenol A	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0028064–14–4 PHENOL, POLYMER WITH	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No
ETHER	ETHER	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068609–97–2	Oxirane,	OSHA	Select Carcinogen: No
	mono[(C12–14–alkyloxy)methyl] derivs.	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
14807–96–6*	Talc (*non-asbestiform)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.
	9. Physical and chemical properties

рН	No Established Limit
Specific Gravity	1.45
Boiling Point F	220
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether

10. Stability and reactivity		
General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.	
Incompatible Materials	Strong oxidizing agents.	
Hazardous Decompostion	May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.	

11. Toxicological information					
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr		
Propylene glycol monomethyl ether acetate – (0000108–65–6)	8,532.00, Rat – Category: NA	5,000.00, Rabbit - Category: 5			
Silica, amorphous – (0007631–86–9)	5,000.00, Rat – Category: 5	2,000.00, Rabbit - Category: 4			
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA		
Reaction product of epichlorohydrin & bisphenol A – (0025085–99–8)					
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER – (0028064–14–4)					
Oxirane, mono[(C12–14–alkyloxy)methyl] derivs. – (0068609–97–2)	17,100.00, Rat – Category: NA				
Talc (*non-asbestiform) - (14807-96-6*)					

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation) IMDG Proper Shipping PAINT OR PAINT PAINT OR PAINT **DOT Proper Shipping** RELATED MATERIAL, Name RELATED MATERIAL, Name NMFC 149980 NMFC 149980 DOT Hazard Class NR IMDG Hazard Class Not Regulated UN / NA Number UN / NA Number Not Regulated Not Regulated **DOT Packing Group** Not Regulated IMDG Packing Group Not Regulated System Reference CERCLA/DOT RQ Not Applicable gal. / 9 Not Applicable lbs. Code

	15. Regulatory information
Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.
WHMIS Classification	No Established Limit
DOT Marine Pollutants (10%) (No Product Ingredient	
DOT Severe Marine Pollutant (No Product Ingredient	
EPCRA 311/312 Chemicals a (No Product Ingredient	
EPCRA 302 Extremely Hazar (No Product Ingredient)	
EPCRA 313 Toxic Chemicals No Product Ingredient	
Mass RTK Substances (>1%)):
Silica, amorpho	
Titanium dioxid	-
Mass Extraordinarily Haz Sub (No Product Ingredient	s Listed)
Penn RTK Substances (>1%)	
Silica, amorpho Titanium dioxid	
Penn Special Hazardous Sub	-
(No Product Ingredient	
Rhode Island Hazardous Sub	ostances (>.1%) :
Magnesium car	bonate
Titanium dioxid	e
RCRA Status: (No Product Ingredient	s Listed)
N.J. RTK Substances (>1%)	
Titanium dioxid	
N.J. Special Hazardous Subs (No Product Ingredient)	
Carbon black	
Benzene, ethyl-	
Isobutyl alcohol Xylenes (o–, m	
N.J. Env. Hazardous Substar (No Product Ingredient)	nces (>.1%) :
Proposition 65 – Carcinogens	
Carbon black	
Benzene, ethyl-	-
Quartz	
Proposition 65 – Female Rep (No Product Ingredient	
Proposition 65 – Male Repro (No Product Ingredient	s Listed)
Proposition 65 – Developmer (No Product Ingredient	
Risk Phrases:	
R36/38: Irritating to eyes and	skin.
R43: May cause sensitisation	
R52/53: Harmful to aquatic or	rganisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.