

Safety Data Sheet
INTERZONE 954 AMARELO RAL 1004

Bulk Sales Reference No.: EAG135
SDS Revision Date: 04/13/2016
SDS Revision Number: A1



1. Identification of the preparation and company

1.1. Product identifier

Product Identity INTERZONE 954 AMARELO RAL 1004
Bulk Sales Reference Number EAG135

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name

International Paint Ltda

ARGENTINA:

Ruta Panamericana Km 37,5
Garin, Buenos Aires
PO Box: B1606DQE

AKZONOBEL CHILE:

Calle Limache 3363 Local 3, El Salto
Viña del Mar, Chile
C.P. 2520642 - Rut 76.048140-8

BRAZIL:

Avenida Paiva, 999 - Neves
Sao Goncalo, RJ
24426-148 Brazil

Emergency

Suatrans Cotec 0800 7071 767 or 0800 7077 022 or 0800 172020 or
55*2*7500 (24 hr)

International Paint

ARGENTINA:

+54 3327 44 7777

CHILE:

+56 32 267 1174

BRAZIL:

+55 21 2199-7100

Poison Control Center (Brazil)

0800-0148110 or +55 11 3069-8800

Medical Service (Argentina)

+54 3327 44 7144 or +54 3327 44 7282

Firefighter/HSE (Argentina)

+54 3327 44 7123

Customer Service

ARGENTINA:

+54 3327 44 7777 Fax: +54 3327 44 7738

CHILE:

+56 32 267 1174 Fax: +56 32 263 1496

BRAZIL:

+55 21 2199-7100 Fax: +55 21 2199-7124

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226
Skin Irrit. 3;H316
Eye Irrit. 2;H319
Aquatic Chronic 3;H412

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapour.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P332+313 If skin irritation occurs: Get medical advice/attention.

P337 If eye irritation persists:.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %
Barium sulfate CAS Number: 0007727-43-7	25 - 50
Reaction of epichlorohydrin and bisphenol A CAS Number: Proprietary	25 - 50
Talc CAS Number: 0014807-96-6	1.0 - 10
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	1.0 - 10
Distillates, petroleum CAS Number: 0068410-16-2	1.0 - 10
Benzene, ethyl- CAS Number: 0000100-41-4	1.0 - 10
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10
Glycidoxypropyltrimethoxysilane CAS Number: 0002530-83-8	1.0 - 10
Methylisobutyl ketone CAS Number: 0000108-10-1	1.0 - 10
Epoxy Resin CAS Number: 0025068-38-6	0.01 -