

SAFETY DATA SHEET

Interplus 356 Aerosol Part B

Safety Data Sheet according to GB/T 16483-2008 and GB/T 17519-2013

Section 1. Chemical product and company identification

GHS product identifier : Interplus 356 Aerosol Part B
 Product code : EPA909

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Professional application of coatings and inks	
Uses advised against	Reason
All Other Uses	

Manufacturer : International Farg AB
 Holmedalen 3
 Asperedes Industriomrade
 SE-424 22 Angered
 Sweden
 Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

Emergency telephone number (with hours of operation) : +46 8 33 12 31

e-mail address of person responsible for this SDS : sdsfellinguk@akzonobel.com

Section 2. Hazards identification

Classification of the substance or mixture according to GB 13690-2009 and GB 30000-2013

Classification of the substance or mixture : AEROSOLS - Category 1
 SKIN CORROSION/IRRITATION - Category 2
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
 RESPIRATORY SENSITIZATION - Category 1
 SKIN SENSITIZATION - Category 1
 CARCINOGENICITY - Category 2
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
 ACUTE AQUATIC HAZARD - Category 3
 LONG-TERM AQUATIC HAZARD - Category 3
 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 49%

GHS label elements

Hazard pictograms : 

Signal word : Danger

Date of issue/Date of revision : 17/08/2017

Version 3 :

Section 2. Hazards identification

- Hazard statements** : Extremely flammable aerosol.
Causes serious eye damage.
Causes skin irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure.
Harmful to aquatic life with long lasting effects.
Pressurised container: May burst if heated.
- Precautionary statements**
- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear respiratory protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Avoid release to the environment. Do not breathe dust or mist. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not pierce or burn, even after use.
- Response** : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
- Storage** : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Wear appropriate respirator when ventilation is inadequate.
- Other hazards which do not result in classification** : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
xylene isomers mixture	≥10 - ≤18	1330-20-7
n-butanol	≤9.7	71-36-3
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha - unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	≤3	64742-95-6
ethylbenzene	≤3	100-41-4
2,4,6-tris(dimethylaminomethyl)phenol	<1	90-72-2
1,2-ethylenediamine	≤0.3	107-15-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Date of issue/Date of revision : 17/08/2017

Version 3 :

2/14

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
wheezing and breathing difficulties
asthma

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

3/14

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

4/14

Section 6. Accidental release measures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid breathing gas. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

5/14

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
xylene	GBZ 2.1 (China, 4/2007). PC-STEL: 100 mg/m ³ 15 minutes. PC-TWA: 50 mg/m ³ 8 hours.
butan-1-ol	GBZ 2.1 (China, 4/2007). PC-TWA: 100 mg/m ³ 8 hours.
ethylbenzene	GBZ 2.1 (China, 4/2007). PC-STEL: 150 mg/m ³ 15 minutes. PC-TWA: 100 mg/m ³ 8 hours.
ethylenediamine	GBZ 2.1 (China, 4/2007). Absorbed through skin. PC-STEL: 10 mg/m ³ 15 minutes. PC-TWA: 4 mg/m ³ 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE:

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

6/14

Section 8. Exposure controls/personal protection

The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended : multi-gas/vapour and particulate filter

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Colourless.
- Odour** : Solvent.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : Lowest known value: 136.16°C (277.1°F) (xylene).
- Flash point** : Not available.
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Greatest known range: Lower: 1.4% Upper: 11.3% (butan-1-ol)
- Vapour pressure** : Not available.
- Vapour density** : Not available.
- Relative density** : 0.79
- Solubility** : Insoluble in the following materials: cold water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.

Aerosol product

- Type of aerosol** : Spray
- Heat of combustion** : 22.78 kJ/g
- Ignition distance** : 75 cm

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

7/14

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LD50 Oral	Rat	4300 mg/kg	-
butan-1-ol	LC50 Inhalation Vapour	Rat	24 mg/l	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	790 mg/kg	-
Solvent naphtha (petroleum), light arom.	LD50 Oral	Rat	8400 mg/kg	-
ethylbenzene	LC50 Inhalation Gas.	Rabbit	4000 ppm	4 hours
	LD50 Dermal	Rabbit	17800 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
2,4,6-tris (dimethylaminomethyl) phenol	LD50 Dermal	Rat	1280 mg/kg	-
	LD50 Oral	Rat	2169 mg/kg	-
ethylenediamine	LD50 Oral	Rat	1200 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
butan-1-ol	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Eyes - Severe irritant	Rabbit	-	0.005 Milliliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Solvent naphtha (petroleum), light arom. ethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

Section 11. Toxicological information

2,4,6-tris (dimethylaminomethyl) phenol	Eyes - Severe irritant	Rabbit	-	24 hours 50 Micrograms	-
	Skin - Mild irritant	Rat	-	0.025 Milliliters	-
ethylenediamine	Skin - Severe irritant	Rat	-	0.25 Milliliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	750 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	450 milligrams	-
	Skin - Severe irritant	Rabbit	-	24 hours 10 milligrams	-

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
butan-1-ol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Solvent naphtha (petroleum), light arom.	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

9/14

Section 11. Toxicological information

- Inhalation** : May give off gas, vapour or dust that is very irritating or corrosive to the respiratory system. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
wheezing and breathing difficulties
asthma
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

10/14

Section 11. Toxicological information

Route	ATE value
Oral	9506.8 mg/kg
Dermal	8563.6 mg/kg
Inhalation (gases)	33175.9 ppm
Inhalation (vapours)	66.65 mg/l
Inhalation (dusts and mists)	11.06 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
xylene	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
butan-1-ol	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 1983 to 2072 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1910 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
Solvent naphtha (petroleum), light arom.	Acute EC50 6.14 mg/m ³	Daphnia	48 hours
ethylbenzene	Acute LC50 9.22 mg/m ³	Fish - Mykiss	96 hours
	Acute EC50 3.6 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
2,4,6-tris (dimethylaminomethyl)phenol ethylenediamine	Acute LC50 18.4 to 25.4 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 5.1 to 5.7 mg/l Marine water	Fish - Menidia menidia	96 hours
	Acute LC50 175 mg/l	Fish - Cyprinus carpio	96 hours
	Acute EC50 100000 µg/l Fresh water	Algae - Chlorella pyrenoidosa	96 hours
	Acute LC50 46000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1544700 µg/l Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 160 µg/l Fresh water	Daphnia - Daphnia magna	21 days

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethylbenzene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 to 25.9	low
butan-1-ol	1	-	low
ethylbenzene	3.6	15	low
2,4,6-tris (dimethylaminomethyl)phenol ethylenediamine	0.219	-	low
	-7.02	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

11/14

Section 12. Ecological information





Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	China	UN	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

IMDG Code Segregation group : Not applicable.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product : No known specific national and/or regional regulations applicable to this product (including its ingredients).

China inventory (IECSC) : Not determined.

List of Goods banned for Importing

None of the components are listed.

List of Goods banned for Exporting

None of the components are listed.

List of Toxic Chemicals Severely Restricted for Importing & Exporting by China

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

12/14

Section 15. Regulatory information

None of the components are listed.

Section 16. Other information

History

Date of printing : 17/08/2017

Date of issue/Date of revision : 17/08/2017

Date of previous issue : 30/05/2017

Version : 3

Key to abbreviations : ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC = Intermediate Bulk Container
 IMDG = International Maritime Dangerous Goods
 LogPow = logarithm of the octanol/water partition coefficient
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
 UN = United Nations

References : Not available.

Procedure used to derive the classification

Classification	Justification
Aerosol 1, H222, H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 2, H351	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Acute 3, H402	Calculation method
Aquatic Chronic 3, H412	Calculation method

✓ Indicates information that has changed from previously issued version.

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

:

Date of issue/Date of revision : 17/08/2017

Version 3 :

13/14

Section 16. Other information