# X.International.

#### Safety Data Sheet

ECB000/B INTERGARD 740 WHITE

Version No 1 Revision Date 08/19/13

1. Product and company identi	fication	
1.1. Product identifier	INTERGARD 740 WHITE	
Product Code	ECB000/B	
1.2. Relevant identified uses of the	e substance or mixture and uses advised against	
Intended use	Refer Technical Data Sheet.	
Application Method	Refer Technical Data Sheet.	
1.3. Details of the supplier of the s	safety data sheet	
Manufacturer	International Paint (Korea) Limited (8-6B/L Chilseo Industrial Complex), 626-6 Gyenae-Ri, Chilseo-Myeon, Haman-Gun, Gyeongsangnam-Do Korea	
Telephone No. Fax No. 1.4. Emergency telephone number For Poisons Advice telephone	055-632-6286(R&D), 055 586 2310(Fact 055 632-6287(R&D), 055 587 6276(Fact 055-586-2310(Factory) 055-586-2310(Factory) For Advice to Doctors & Hospitals only	

#### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

[Prevention]:
[Response]:
[Storage]:
[Disposal]:
2.3. Other hazards

#### 3. Composition/information on ingredients

This product contains the following hazardous substances.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Xylene CAS Number: 0001330-20-7		Flam. Liq. 3;H226 Acute Tox. 4;H312 Acute Tox. 4;H332 Skin Irrit. 2;H315 Eye Dam. 2A;H319	[1][2]

		STOT SE 3;H336 STOT RE 1;H372	
Epoxy Resin liquid CAS Number: 0025036-25-3	20-30	Eye Irrit. 2;H319 Skin Irrit. 2;H315, Skin Sens. 1;H317	[1]
Titanium dioxide CAS Number: 0013463-67-7	20-30		[1][2]
Talc CAS Number: 0014807-96-6	10-20		[1][2]
1-METHOXYPROPAN-2-OL CAS Number: Not Available	5-10	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Ethyl Benzene CAS Number: 0000100-41-4	2.5-5	Flam. Liq. 2;H225 Acute Tox. 4;H332	[1][2]
Barium Sulphate CAS Number: 0007727-43-7	1-2.5		[1][2]
Solvent Naphtha (Petroleum), light aromatic CAS Number: 0064742-95-6	1-2.5	Asp. Tox. 1;H304	[1]
Silica (quartz) CAS Number: 0014808-60-7	1-2.5	Acute Tox. 4;H332 STOT RE 2;H373	[1][2]
polyamide dispersion CAS Number: 0055349-01-4	<1	Skin Sens. 1;H317 Aquatic Chronic 4;H413	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the Hazard (H) phrases are shown in Section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

#### 4. First aid measures

#### 4.1. Description of first aid measures

General

Inhalation

Skin Contact

Eye Contact

Ingestion

#### 4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

#### 5. Fire-fighting measures

#### 5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for fire-fighters

#### 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

#### 7. Handling and storage

7.1. Precautions for safe handling Handling

In Storage

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

#### 8. Exposure controls and personal protection

#### 8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygenists).

Material	Short te	rm (15 min. ave)	Long ter average)	m (8hr time weighted	Comments
	ppm	mg/m³	ppm	mg/M3	
1-METHOXYPROPAN-2-OL	150	540	100	360	
Barium Sulphate			2	10	
Ethyl Benzene	125	545	100	435	
Silica (quartz)				0.1	
Talc				2	
Titanium dioxide				10	
Xylene	150	655	100	434	
Key to notification					

(P) Peak exposure limit

(R) Suppliers Recommended Limit

(Sk) There is a risk of absorption through unbroken skin

(Sen) Sensitiser

(Cat1) Category 1 - established human carcinogen

(Cat2) Category 2 - probable human carcinogen

(Cat3) Category 3 - substances suspected of having carcinogenic potential

#### DNEL/PNEC values

8.2. Exposure controls

Eye Protection

**Skin Protection** 

Other

**Respiratory Protection** 

Thermal hazards

#### 9. Physical and chemical properties

Colour Odour Odour threshold pH Melting point / freezing point (°C) Initial boiling point and boiling range (°C) Flash Point (C) Evaporation rate (Ether = 1) Flammability (solid, gas) Upper/lower flammability or explosive limits Upper Explosive Limit: 1.1 ( Xylene ) Upper Explosive Limit: 6.6 ( Xylene )

Vapour pressure (Pa) Vapour Density Specific Gravity Solubility in Water Partition coefficient n-octanol/water (Log Kow) Autoignition temperature ( ) Decomposition temperature Viscosity (cSt)

0.00

# 9.2. Other information

No further information

#### 10. Stability and reactivity

- 10.1. Reactivity
- 10.2. Chemical stability
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid
- 10.5. Incompatible materials
- 10.6. Hazardous decomposition products

#### 11. Toxicological information

#### Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
1-METHOXYPROPAN-2-OL - (Not Available)	5,000.00, Rat	13,000.00, Rabbit	Not Available	Not Available
Barium Sulphate - (7727-43-7)	3,000.00, Mouse	Not Available	Not Available	Not Available
Epoxy Resin liquid - (25036-25-3)	Not Available	Not Available	Not Available	Not Available
Ethyl Benzene - (100-41-4)	3,500.00, Rat	15,433.00, Rabbit	17.20, Rat	Not Available
polyamide dispersion - (55349-01-4)	Not Available	Not Available	Not Available	Not Available
Silica (quartz) - (14808-60-7)	Not Available	Not Available	Not Available	Not Available
Solvent Naphtha (Petroleum), light aromatic - (64742-95-6)	6,800.00, Rat	3,400.00, Rabbit	Not Available	Not Available

Talc - (14807-96-6)	Not Available	Not Available	Not Available	Not Available
Titanium dioxide - (13463-67-7)	10,000.00, Rat	10,000.00, Rabbit	Not Available	6.82, Rat
Xylene - (1330-20-7)	4,299.00, Rat	1,548.00, Rabbit	Not Available	20.00, Rat

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

# 12. Ecological information

# 12.1. Toxicity

# Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Epoxy Resin liquid - (25036-25- 3)	Not Available	Not Available	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
Talc - (14807-96-6)	Not Available	Not Available	Not Available
1-METHOXYPROPAN-2-OL - (Not Available)	1,000.00, Oncorhynchus mykiss	500.00, Daphnia magna	1,000.00 (96 hr), Selenastrum capricornutum
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata
Barium Sulphate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Solvent Naphtha (Petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Silica (quartz) - (14808-60-7)	Not Available	Not Available	Not Available
polyamide dispersion - (55349- 01-4)	Not Available	Not Available	Not Available

# 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

#### 13. Disposal considerations

#### 13.1. Waste treatment methods

#### **14. Transport information**

### 14.1. UN number 14.2. UN proper shipping name

# 14.3. Transport hazard class(es)

Road and Rail Transport

IMDG	Class/Div	Sub Class
reference :		

Ems

- ICAO/IATA Class Sub Class
- 14.4. Packing group
- 14.5. Environmental hazards

# Road and Rail Environmentally Hazardous: Transport

IMDG Marine Pollutant: reference :

#### 14.6. Special precautions for user

No further information

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

# 15. Regulatory information

The product and all its components complies with these local regulations: NICNAS - Australia EPA - New Zealand

Korean OHS Act	See Section 2
Toxic Substances Act	Not Toxic
Dangerous Goods Act	Class 4 Flammable Liquid, 1st Petroleum Division, Hazard Class II
Waste Control Act	Hazardous Waste

#### 16. Other information

The information on this SDS is based upon the present state of our knowledge and on current law. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

#### This SDS is valid for 5 years from the revised date on page 1. The revision date is in American format (e.g. MM/DD/YY).

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.