# Material Safety Data Sheet ENVIROLINE B-FLEX 9400TR TAN TROWEL CAULK PART A

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: NVA904
MSDS Revision Date: 03/11/2015
MSDS Revision Number: A1-2



### 1. Identification of the preparation and company

1.1. Product identifier

Product Identity ENVIROLINE B-FLEX 9400TR TAN TROWEL

CAULK PART A

Bulk Sales Reference No. NVA904

1.2. Relevant identified uses of the substance or mixture and uses advised against
 Intended Use
 Application Method
 See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC

6001 Antoine Drive Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424-9300

 International Paint
 (713) 682-1711

 Poison Control Center
 (800) 854-6813

Customer Service

International Paint (800) 589-1267 Fax No. (800) 631-7481

# 2. Hazard identification of the product

# 2.1. Classification of the substance or mixture

Combustible Liquid; H227 Combustible Liquid.

Acute Tox. 5;H303 May be harmful if swallowed. Skin Irrit. 2;H315 Causes skin irritation.

Eye Irrit. 2;H319 Causes serious eye irritation.

Skin Sens. 1;H317 May cause an allergic skin reaction.

STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H227 Combustible liquid.

H303 May be harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P314 Get Medical advice / attention if you feel unwell.

P331 Do NOT induce vomiting.

P333+313 If skin irritation or a rash occurs: Get medical advice/attention.

P337 If eye irritation persists:.

P362 Take off contaminated clothing and wash before reuse.

P363 Wash contaminated clothing before reuse.

P370+376 In case of fire: Stop leak if safe to do so.

P391 Collect spillage.

P403+235 Store in a well ventilated place. Keep cool.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 2\* Flammability: 2 Reactivity: 0

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations  | Weight % | GHS Classification  | Notes  |
|---|----------|---|--------|
| PHENOL, POLYMER WITH<br>FORMALDEHYDE, GLYCIDYL<br>ETHER<br>CAS Number: 0028064-14-4 | 25 - 50  | Skin Irrit. 2;H315<br>Eye Irrit. 2;H319<br>Skin Sens. 1;H317<br>Aquatic Chronic<br>2;H411 | [1]    |
| Quartz<br>CAS Number: 0014808-60-7  | 25 - 50  | Acute Tox. 4;H332<br>STOT RE 2;H373   | [1][2] |
| Wollastonite (Ca(SiO3)) CAS Number: 0013983-17-0                                    | 10 - 25  |   | [1]    |
| Mica<br>CAS Number: 0012001-26-2  | 1.0 - 10 |   | [1][2] |
| Titanium dioxide<br>CAS Number: 0013463-67-7  | 1.0 - 10 |   | [1][2] |

<sup>[1]</sup> Substance classified with a health or environmental hazard.

# 4. First aid measures

### 4.1. Description of first aid measures

General Remove contaminated clothing and shoes. Get medical attention immediately. Wash

clothing before reuse. Thoroughly clean or destroy contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention immediately.

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.

<sup>\*</sup>The full texts of the phrases are shown in Section 16.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get medical

attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT

induce vomiting unless instructed to do so by medical personnel. Never give anything

by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed

through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO2, water spray or foam. LARGE FIRES: Use water spray, fog, or foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 159

### 6. Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

#### 7. Handling and storage

#### 7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

# 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

# 8. Exposure controls and personal protection

### 8.1. Control parameters

### Exposure

| CAS No                  | Ingredient              | Expos<br>Source      |   |
|-------------------------|-------------------------|----------------------|---|
| CAS No.                 | Ingredient              |                      | Value   |
| 0012001-26-2 Mica       | Mica                    | OSHA                 | No Established Limit  |
|                         |                         | ACGIH                | 3 mg/m3 TWA (respirable fraction)   |
|                         |                         | NIOSH                | 3 mg/m3 TWA (containing   |
|                         |                         | Supplier             | No Established Limit  |
|                         |                         | OHSA,<br>CAN         | 3 mg/m3 TWA (respirable)  |
|                         |                         | Mexico               | 3 mg/m3 TWA LMPE-PPT (respirable fraction)  |
|                         |                         | Brazil               | No Established Limit  |
| 0013463-67-7            | Titanium dioxide        | OSHA                 | 15 mg/m3 TWA (total dust)   |
|                         |                         | ACGIH                | 10 mg/m3 TWA  |
|                         |                         | NIOSH                | 5000 mg/m3 IDLH   |
|                         |                         | Supplier             | No Established Limit  |
|                         |                         | OHSA,<br>CAN         | 10 mg/m3 TWA  |
|                         |                         | Mexico               | 10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)  |
|                         |                         | Brazil               | No Established Limit  |
| 0013983-17-0            | Wollastonite (Ca(SiO3)) | OSHA                 | No Established Limit  |
|                         |                         | ACGIH                | No Established Limit  |
|                         |                         | NIOSH                | No Established Limit  |
|                         |                         | Supplier             | No Established Limit  |
|                         | OHSA,<br>CAN            | No Established Limit |   |
|                         |                         | Mexico               | No Established Limit  |
|                         | Brazil                  | No Established Limit |   |
| 0014808-60-7            | Quartz                  | OSHA                 | No Established Limit  |
|                         |                         | ACGIH                | 0.025 mg/m3 TWA (respirable fraction)   |
|                         |                         | NIOSH                | 0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust)   |
|                         |                         | Supplier             | No Established Limit  |
|                         |                         | OHSA,                | 0.10 mg/m3 TWA (designated substances   |
|                         |                         | CAN                  | regulation, respirable, listed under Silica,<br>crystalline)0.10 mg/m3 TWA (respirable fraction,<br>listed under Silica, crystalline) |
|                         |                         | Mexico               | 0.1 mg/m3 TWA LMPE-PPT (respirable fraction)  |
|                         |                         | Brazil               | No Established Limit  |
| 0028064-14-4 PHENOL. PC | PHENOL, POLYMER WITH    | OSHA                 | No Established Limit  |
|                         | FORMALDEHYDE,           | ACGIH                | No Established Limit  |
| GLYCIDYL ETHER          | NIOSH                   | No Established Limit |   |
|                         |                         | Supplier             | No Established Limit  |
|                         | OHSA,<br>CAN            | No Established Limit |   |
|                         |                         | OAN                  | 1   |

|  | Mexico | No Established Limit |
|--|--------|----------------------|
|  | Brazil | No Established Limit |

#### Health Data

| CAS No.      | Ingredient                   | Source | Value                                    |
|--------------|------------------------------|--------|--|
| 0012001-26-2 | Mica                         | NIOSH  | respirable dust; Fibrotic pneumoconiosis |
| 0013463-67-7 | Titanium dioxide             | NIOSH  | Lung tumors in animals                   |
| 0013983-17-0 | Wollastonite (Ca(SiO3))      | NIOSH  | No Established Limit                     |
| 0014808-60-7 | Quartz                       | NIOSH  | Chronic lung disease (silicosis)         |
| 0028064-14-4 | PHENOL, POLYMER WITH         | NIOSH  | No Established Limit                     |
|              | FORMALDEHYDE, GLYCIDYL ETHER |        |  |

Carcinogen Data

| CAS No.                              | Ingredient       | Source | Value   |  |
|--------------------------------------|------------------|--------|---|--|
| 0012001-26-2                         | Mica             | OSHA   | Select Carcinogen: No   |  |
|                                      |                  | NTP    | Known: No; Suspected: No  |  |
|                                      |                  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |  |
| 0013463-67-7                         | Titanium dioxide | OSHA   | Select Carcinogen: Yes  |  |
|                                      |                  | NTP    | Known: No; Suspected: No  |  |
|                                      |                  | IARC   | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |  |
| 0013983-17-0 Wollastonite (Ca(SiO3)) |                  | OSHA   | Select Carcinogen: No   |  |
|                                      |                  | NTP    | Known: No; Suspected: No  |  |
|                                      |                  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |  |
| 0014808-60-7                         | Quartz           | OSHA   | Select Carcinogen: Yes  |  |
|                                      |                  | NTP    | Known: Yes; Suspected: No   |  |
|                                      |                  | IARC   | Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |  |
| 0028064-14-4 PHENOL, POLYMER O       |                  | OSHA   | Select Carcinogen: No   |  |
|                                      | WITH             |        | Known: No; Suspected: No  |  |
| FORMALDEHYDE,<br>GLYCIDYL ETHER      |                  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |  |

#### 8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls
Other Work Practices

Depending on the site-specific conditions of use, provide adequate ventilation.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

#### soap and water.

### 9. Physical and chemical properties

Coloured Liquid **Appearance** Odour threshold Not Measured No Established Limit рΗ Melting point / freezing point Not Measured Initial boiling point and boiling range 146 (C) 295 (F) Flash Point 66 (C) 151 (F) Evaporation rate (Ether = 1) Not Measured Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive

limits

Lower Explosive Limit: 1

Upper Explosive Limit: No Established Limit

vapor pressure (Pa) Not Measured
Vapor Density Heavier than air

Specific Gravity 1.60

Partition coefficient n-octanol/water (Log

) Na

Kow)

Not Measured

Auto-ignition temperature Not Measured Decomposition temperature Not Measured

Viscosity (cSt)

No Established Limit Not Measured

VOC % Refer to the Technical Data Sheet or label where information is

available.

9.2. Other information

No further information

#### 10. Stability and reactivity

# 10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

# 11. Toxicological information

### Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient   | Oral LD50,<br>mg/kg            | Skin LD50,<br>mg/kg  | Inhalation<br>Vapor LD50,<br>mg/L/4hr | Inhalation<br>Dust/Mist LD50,<br>mg/L/4hr |
|--|--------------------------------|----------------------|---------------------------------------|---|
| PHENOL, POLYMER WITH<br>FORMALDEHYDE, GLYCIDYL ETHER -<br>(28064-14-4) | 2,000.00, Rat -<br>Category: 4 | No data<br>available | No data<br>available                  | No data available                         |

# NVA904\_A1

| Quartz - (14808-60-7)                  | No data<br>available             | No data<br>available                   | No data<br>available | No data available           |
|--|----------------------------------|--|----------------------|-----------------------------|
| Wollastonite (Ca(SiO3)) - (13983-17-0) | No data<br>available             | No data<br>available                   | No data<br>available | No data available           |
| Mica - (12001-26-2)                    | No data<br>available             | No data<br>available                   | No data<br>available | No data available           |
| Titanium dioxide - (13463-67-7)        | 10,000.00, Rat<br>- Category: NA | 10,000.00,<br>Rabbit -<br>Category: NA | No data<br>available | 6.82, Rat -<br>Category: NA |

| Item   | Category       | Hazard   |
|--|----------------|--|
| Acute Toxicity (mouth)   | 5              | May be harmful if swallowed.                                       |
| Acute Toxicity (skin)  | Not Classified | Not Applicable   |
| Acute Toxicity (inhalation)                                    | Not Classified | Not Applicable   |
| Skin corrosion/irritation                                      | 2              | Causes skin irritation.  |
| Eye damage/irritation  | 2              | Causes serious eye irritation.                                     |
| Sensitization (respiratory)                                    | Not Classified | Not Applicable   |
| Sensitization (skin)   | 1              | May cause an allergic skin reaction.                               |
| Germ toxicity  | Not Classified | Not Applicable   |
| Carcinogenicity  | Not Classified | Not Applicable   |
| Reproductive Toxicity  | Not Classified | Not Applicable   |
| Specific target organ systemic toxicity (single exposure)      | Not Classified | Not Applicable   |
| Specific target organ systemic<br>Toxicity (repeated exposure) | 2              | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard  | Not Classified | Not Applicable   |

# 12. Ecological information

# 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

# Aquatic Ecotoxicity

| Ingredient  | 96 hr LC50 fish,<br>mg/l           | 48 hr EC50 crustacea,<br>mg/l | ErC50 algae,<br>mg/l                          |
|---|------------------------------------|-------------------------------|---|
| PHENOL, POLYMER WITH<br>FORMALDEHYDE,<br>GLYCIDYL ETHER -<br>(28064-14-4) | 9.00, Oncorhynchus<br>mykiss       | 9.00, Daphnia magna           | Not Available                                 |
| Quartz - (14808-60-7)   | Not Available                      | Not Available                 | Not Available                                 |
| Wollastonite (Ca(SiO3)) - (13983-17-0)                                    | Not Available                      | Not Available                 | Not Available                                 |
| Mica - (12001-26-2)   | Not Available                      | Not Available                 | Not Available                                 |
| Titanium dioxide -<br>(13463-67-7)  | 1,000.00, Fundulus<br>heteroclitus | 5.50, Daphnia magna           | 5.83 (72 hr), Pseudokirchneriella subcapitata |

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

### 13. Disposal considerations

### 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

#### 14. Transport information

14.1. UN number14.2. UN proper shipping nameNot RegulatedNot Regulated

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

DOT Proper Shipping Not Regulated IMDG Proper Not Regulated

Name Shipping Name

DOT Hazard Class Not Regulated IMDG Hazard Class Not Regulated Sub Class Not applicable

UN / NA Number Not Regulated

DOT Packing Group Not Regulated IMDG Packing Group Not Regulated

CERCLA/DOT RQ Not Applicable gal. / System Reference 9

Not Applicable lbs. Code

14.4. Packing group Not Regulated

14.5. Environmental hazards

IMDG Marine Pollutant: Yes ( PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER )

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA

Inventory.

WHMIS Classification B3 D2B

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

Aluminum oxide

Mass RTK Substances (>1%):

Mica

Quartz

Titanium dioxide

Penn RTK Substances (>1%):

Mica

Quartz

Titanium dioxide

Penn Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

**RCRA Status:** 

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Mica

Quartz

Titanium dioxide

N.J. Special Hazardous Substances (>.01%):

Quartz

N.J. Env. Hazardous Substances (>.1%):

Aluminum oxide

Proposition 65 - Carcinogens (>0%):

Quartz

Titanium dioxide

Proposition 65 - Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):

(No Product Ingredients Listed)

#### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

End of Document