

Material Safety Data Sheet  
DEVTHANE 349 ENH SAFETY ORANGE KIT

Sales  
Order: {SalesOrd}  
DC349K9200E  
08/22/2012  
0-

Bulk Sales Reference No.:  
MSDS Revision Date:  
MSDS Revision Number:



1. Identification of the preparation and company

|                          |  |
|--------------------------|--|
| Product Identity         | DEVTHANE 349 ENH SAFETY ORANGE KIT                                   |
| Bulk Sales Reference No. | DC349K9200E  |
| Company Name             | International Paint LLC<br>6001 Antoine Drive<br>Houston Texas 77091 |
| Emergency                |  |
| CHEMTREC (USA)           | (800) 424-9300   |
| International Paint      | (713) 682-1711   |
| Poison Control Center    | (800) 854-6813   |
| Customer Service         |  |
| International Paint      | (800) 589-1267   |
| Fax No.                  | (800) 631-7481   |

2. Hazard identification of the product



Danger

GHS Classification:

| Item  | Category       | Hazard   |
|---|----------------|--|
| Flammability  | Not classified | Not applicable   |
| Acute Toxicity (mouth)                                      | Not classified | Not applicable   |
| Acute Toxicity (skin)                                       | Not classified | Not applicable   |
| Acute Toxicity (inhalation)                                 | Not classified | Not applicable   |
| Acute Toxicity (ingestion)                                  | Not classified | Not applicable   |
| Skin corrosion/irritation                                   | Not classified | Not applicable   |
| Eye damage/irritation                                       | Not classified | Not applicable   |
| Sensitization (respiratory)                                 | 1              | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Sensitization (skin)  | 1              | May cause allergic reaction.   |
| Germ toxicity   | Not classified | Not applicable   |
| Specific target organ systemic toxicity (single exposure)   | 1              | central nerve system   |
|   | 2              | Not applicable   |
|   | 3              | respiratory tract irritation   |
| Specific target organ systemic Toxicity (repeated exposure) | 1              | lung   |
|   | 2              | Not applicable   |
| Aspiration hazard   | Not classified | Not applicable   |
| Harmfulness to aquatic Environment (acute)                  | 3              | Harmful to aquatic life.   |
|   | 4              |  |

## DC349K9200E\_0

|   |                |  |
|---|----------------|--|
| Harmfulness to aquatic Environment (long term effect) |                | May cause harm to aquatic life with long lasting effects |
| Carcinogenicity                                       | Not classified | Not applicable   |
| Reproductive Toxicity                                 | Not classified | Not applicable   |
| Organic Peroxide                                      | Not classified | Not applicable   |

### Safety Phrases:

S23: Do not breathe vapor/spray.

S24/25: Avoid contact with skin and eyes.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

|                 |  |                 |               |        |
|-----------------|--|-----------------|---------------|--------|
| Overview        | Avoid contact with eyes, skin and clothing. May cause allergic respiratory reaction.   |                 |               |        |
| Inhalation      | Harmful if inhaled. May cause lung injury. Causes nose and throat irritation.  |                 |               |        |
| Eyes            | Causes severe eye irritation. Avoid contact with eyes.   |                 |               |        |
| Skin            | Causes skin irritation. May be harmful if absorbed through the skin.   |                 |               |        |
| Ingestion       | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.   |                 |               |        |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. |                 |               |        |
| HMIS Rating     | Health: 4  | Flammability: 3 | Reactivity: 1 | PPE: X |

### 3. Composition/information on ingredients

| Ingredient                             | CAS No.      | Percent    |
|--|--------------|------------|
| BUTYL ACETATE                          | 0000123-86-4 | 1.0 – 10   |
| BUTYL PEROXYBENZOATE                   | 0000614-45-9 | 0.10 – 1.0 |
| Ethyl 3-ethoxypropionate               | 0000763-69-9 | 1.0 – 10   |
| Silica, amorphous                      | 0007631-86-9 | 1.0 – 10   |
| Barium sulfate                         | 0007727-43-7 | 10 – 25    |
| Titanium dioxide                       | 0013463-67-7 | 1.0 – 10   |
| Hexamethylene diisocyanate homopolymer | 0028182-81-2 | 10 – 25    |
| Petroleum naphtha                      | 0064742-95-6 | 1.0 – 10   |
| AMINOFUNCTIONAL REACTIVE THINNER RESIN | TS-KH3190    | 1.0 – 10   |
| ASPARTIC ESTER (PROPRIETARY)           | Proprietary  | 1.0 – 10   |

### 4. First aid measures

|            |   |
|------------|---|
| General    | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.  |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.  |
| Eyes       | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.   |
| Skin       | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.  |
| Ingestion  | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

### 5. Fire-fighting measures

## DC349K9200E\_0

Flash Point

F: 65

C: 18

Lower Explosive Limit (LEL)

1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No.

128

### 6. Accidental release measures

Spill Response Procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

Public Safety

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. **LARGE SPILLS:** Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No.

128

### 7. Handling and storage

Storage Temperature

Store between 40–100F (4–38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Avoid contact with eyes, skin and clothing. Close container after each use. Wash thoroughly after handling.

### 8. Exposure controls and personal protection

#### Exposure

| CAS No.      | Ingredient               | Source    | Value   |
|--------------|--------------------------|-----------|---|
| 0000123–86–4 | BUTYL ACETATE            | OSHA      | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL                        |
|              |                          | ACGIH     | 150 ppm TWA200 ppm STEL   |
|              |                          | NIOSH     | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL) |
|              |                          | Supplier  | No Established Limit  |
|              |                          | OHSA, CAN | 150 ppm TWA200 ppm STEL   |
|              |                          | Mexico    | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL                        |
|              |                          | Brazil    | No Established Limit  |
| 0000614–45–9 | BUTYL PEROXYBENZOATE     | OSHA      | No Established Limit  |
|              |                          | ACGIH     | No Established Limit  |
|              |                          | NIOSH     | No Established Limit  |
|              |                          | Supplier  | No Established Limit  |
|              |                          | OHSA, CAN | No Established Limit  |
|              |                          | Mexico    | No Established Limit  |
|              |                          | Brazil    | No Established Limit  |
| 0000763–69–9 | Ethyl 3–ethoxypropionate | OSHA      | No Established Limit  |
|              |                          | ACGIH     | No Established Limit  |
|              |                          | NIOSH     | No Established Limit  |
|              |                          | Supplier  | No Established Limit  |
|              |                          | OHSA,     | 50 ppm TWA; 300 mg/m3 TWA   |

## DC349K9200E\_0

|              |  |              |  |
|--------------|--|--------------|--|
|              |  | CAN          |  |
|              |  | Mexico       | No Established Limit   |
|              |  | Brazil       | No Established Limit   |
| 0007631-86-9 | Silica, amorphous                      | OSHA         | No Established Limit   |
|              |  | ACGIH        | No Established Limit   |
|              |  | NIOSH        | 6 mg/m3 TWA 3000 mg/m3 IDLH                                  |
|              |  | Supplier     | No Established Limit   |
|              |  | OHSA,<br>CAN | No Established Limit   |
|              |  | Mexico       | No Established Limit   |
|              |  | Brazil       | No Established Limit   |
| 0007727-43-7 | Barium sulfate                         | OSHA         | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
|              |  | ACGIH        | 10 mg/m3 TWA   |
|              |  | NIOSH        | 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)     |
|              |  | Supplier     | No Established Limit   |
|              |  | OHSA,<br>CAN | 10 mg/m3 TWA (total dust)                                    |
|              |  | Mexico       | No Established Limit   |
|              |  | Brazil       | No Established Limit   |
| 0013463-67-7 | Titanium dioxide                       | OSHA         | 15 mg/m3 TWA (total dust)                                    |
|              |  | ACGIH        | 10 mg/m3 TWA   |
|              |  | NIOSH        | 5000 mg/m3 IDLH  |
|              |  | Supplier     | No Established Limit   |
|              |  | OHSA,<br>CAN | 10 mg/m3 TWA (total dust)                                    |
|              |  | Mexico       | 10 mg/m3 TWA (as Ti) 20 mg/m3 STEL (as Ti)                   |
|              |  | Brazil       | No Established Limit   |
| 0028182-81-2 | Hexamethylene diisocyanate homopolymer | OSHA         | No Established Limit   |
|              |  | ACGIH        | No Established Limit   |
|              |  | NIOSH        | No Established Limit   |
|              |  | Supplier     | No Established Limit   |
|              |  | OHSA,<br>CAN | No Established Limit   |
|              |  | Mexico       | No Established Limit   |
|              |  | Brazil       | No Established Limit   |
| 0064742-95-6 | Petroleum naphtha                      | OSHA         | No Established Limit   |
|              |  | ACGIH        | No Established Limit   |
|              |  | NIOSH        | No Established Limit   |
|              |  | Supplier     | No Established Limit   |
|              |  | OHSA,<br>CAN | No Established Limit   |
|              |  | Mexico       | No Established Limit   |
|              |  | Brazil       | No Established Limit   |
| TS-KH3190    | AMINOFUNCTIONAL REACTIVE THINNER RESIN | OSHA         | No Established Limit   |
|              |  | ACGIH        | No Established Limit   |
|              |  | NIOSH        | No Established Limit   |
|              |  | Supplier     | No Established Limit   |
|              |  | OHSA,<br>CAN | No Established Limit   |
|              |  | Mexico       | No Established Limit   |
|              |  | Brazil       | No Established Limit   |
| Proprietary  | ASPARTIC ESTER (PROPRIETARY)           | OSHA         | No Established Limit   |
|              |  | ACGIH        | No Established Limit   |
|              |  | NIOSH        | No Established Limit   |
|              |  | Supplier     | No Established Limit   |
|              |  |              | No Established Limit   |

## DC349K9200E\_0

|  |  |              |                      |
|--|--|--------------|----------------------|
|  |  | OSHA,<br>CAN |                      |
|  |  | Mexico       | No Established Limit |
|  |  | Brazil       | No Established Limit |

## Health Data

| CAS No.      | Ingredient                             | Source | Value   |
|--------------|--|--------|---|
| 0000123-86-4 | BUTYL ACETATE                          | NIOSH  | Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals |
| 0000614-45-9 | BUTYL PEROXYBENZOATE                   | NIOSH  | No Established Limit  |
| 0000763-69-9 | Ethyl 3-ethoxypropionate               | NIOSH  | No Established Limit  |
| 0007631-86-9 | Silica, amorphous                      | NIOSH  | No Established Limit  |
| 0007727-43-7 | Barium sulfate                         | NIOSH  | Eye nose  |
| 0013463-67-7 | Titanium dioxide                       | NIOSH  | Lung tumors in animals  |
| 0028182-81-2 | Hexamethylene diisocyanate homopolymer | NIOSH  | No Established Limit  |
| 0064742-95-6 | Petroleum naphtha                      | NIOSH  | No Established Limit  |
| TS-KH3190    | AMINOFUNCTIONAL REACTIVE THINNER RESIN | NIOSH  | No Established Limit  |
| Proprietary  | ASPARTIC ESTER (PROPRIETARY)           | NIOSH  | No Established Limit  |

## Carcinogen Data

| CAS No.      | Ingredient                             | Source | Value   |
|--------------|--|--------|---|
| 0000123-86-4 | BUTYL ACETATE                          | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0000614-45-9 | BUTYL PEROXYBENZOATE                   | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0000763-69-9 | Ethyl 3-ethoxypropionate               | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0007631-86-9 | Silica, amorphous                      | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0007727-43-7 | Barium sulfate                         | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0013463-67-7 | Titanium dioxide                       | OSHA   | Select Carcinogen: Yes  |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0028182-81-2 | Hexamethylene diisocyanate homopolymer | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| 0064742-95-6 | Petroleum naphtha                      | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |
| TS-KH3190    | AMINOFUNCTIONAL REACTIVE THINNER RESIN | OSHA   | Select Carcinogen: No   |
|              |  | NTP    | Known: No; Suspected: No  |
|              |  | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |

## DC349K9200E\_0

|             |                                 |      |   |
|-------------|---------------------------------|------|---|
| Proprietary | ASPARTIC ESTER<br>(PROPRIETARY) | OSHA | Select Carcinogen: No   |
|             |                                 | NTP  | Known: No; Suspected: No  |
|             |                                 | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No;<br>Group 4: No; |

|                      |   |
|----------------------|---|
| Respiratory          | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. A supplied air respirator (either positive pressure or continuous flow type) is required. Follow manufacturer's directions for respirator use and observe requirements specified in 29 CFR 1910.134. |
| Eyes                 | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.  |
| Skin                 | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.   |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation.   |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.  |

### 9. Physical and chemical properties

|                  |  |
|------------------|--|
| Physical State   | No Information Provided Coloured   |
| pH               | No Established Limit   |
| Specific Gravity | 1.34   |
| Boiling Point F  | 244  |
| Vapor Density    | Heavier than air   |
| VOC %            | Refer to the Technical Data Sheet or label where information is available. |
| Evaporation Rate | Slower than ether  |

### 10. Stability and reactivity

|                         |  |
|-------------------------|--|
| General                 | This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled. |
| Incompatible Materials  | Strong oxidizing agents.   |
| Hazardous Decomposition | May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.  |

### 11. Toxicological information

DC349K9200E\_0

| Ingredient  | Oral LD50, mg/kg              | Skin LD50, mg/kg                 | Inhalation Vapor LD50, mg/L/4hr |
|---|-------------------------------|----------------------------------|---------------------------------|
| BUTYL ACETATE – (0000123–86–4)                          | 10,768.00, Rat – Category: NA | 17,600.00, Rabbit – Category: NA | -----                           |
| BUTYL PEROXYBENZOATE – (0000614–45–9)                   | 1,012.00, Rat – Category: 4   | -----                            | -----                           |
| Ethyl 3–ethoxypropionate – (0000763–69–9)               | 3,200.00, Rat – Category: 5   | -----                            | -----                           |
| Silica, amorphous – (0007631–86–9)                      | 5,000.00, Rat – Category: 5   | 2,000.00, Rabbit – Category: 4   | -----                           |
| Barium sulfate – (0007727–43–7)                         | -----                         | -----                            | -----                           |
| Titanium dioxide – (0013463–67–7)                       | 10,000.00, Rat – Category: NA | 10,000.00, Rabbit – Category: NA | 6,082.00, Rat – Category: NA    |
| Hexamethylene diisocyanate homopolymer – (0028182–81–2) | -----                         | -----                            | -----                           |
| Petroleum naphtha – (0064742–95–6)                      | 8,400.00, Rat – Category: NA  | 2,000.00, Rabbit – Category: 4   | 5.20, Rat – Category: 3         |
| AMINOFUNCTIONAL REACTIVE THINNER RESIN – (TS–KH3190)    | -----                         | -----                            | -----                           |
| ASPARTIC ESTER (PROPRIETARY) – (Proprietary)            | -----                         | -----                            | -----                           |

General No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined  
No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

| DOT (Domestic Surface Transportation) |                        | IMO / IMDG (Ocean Transportation) |                                      |
|---------------------------------------|------------------------|-----------------------------------|--------------------------------------|
| DOT Proper Shipping Name              | PAINT                  | IMDG Proper Shipping Name         | PAINT                                |
| DOT Hazard Class                      | 3                      | IMDG Hazard Class                 | 3 – Flammable and Combustible liquid |
| UN / NA Number                        | UN 1263                | UN / NA Number                    | UN 1263                              |
| DOT Packing Group                     | III                    | IMDG Packing Group                | III                                  |
| CERCLA/DOT RQ                         | 3131 gal. / 34894 lbs. | System Reference Code             | 2                                    |

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all–inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2;D2B

DOT Marine Pollutants (10%):  
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :  
 BUTYL ACETATE (5000 lb final RQ; 2270 kg final RQ)  
 Butanol (5000 lb final RQ; 2270 kg final RQ)

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :  
Aluminum oxide  
Butanol  
Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :  
Barium sulfate  
BUTYL ACETATE  
Silica, amorphous  
Titanium dioxide

Mass Extraordinarily Haz Sub (>.01%) :  
Quartz

Penn RTK Substances (>1%) :  
Barium sulfate  
BUTYL ACETATE  
Silica, amorphous  
Titanium dioxide

Penn Special Hazardous Substances (>.01%) :  
(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%) :  
Aluminum oxide  
Diisobutylketone  
Kaolin  
BUTYL ACETATE  
Butanol  
BUTYL PEROXYBENZOATE  
Titanium dioxide  
Xylenes (o-, m-, p- isomers)

RCRA Status:  
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :  
Barium sulfate  
BUTYL ACETATE  
Titanium dioxide

N.J. Special Hazardous Substances (>.01%) :  
Benzene, ethyl-  
BUTYL ACETATE  
Butanol  
Potassium oxide  
Quartz  
BUTYL PEROXYBENZOATE  
Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :  
Aluminum oxide  
Butanol  
Xylenes (o-, m-, p- isomers)

Proposition 65 – Carcinogens (>0%):  
Benzene, ethyl-  
Formaldehyde  
Quartz  
Refractory ceramic fibers

Proposition 65 – Female Repro Toxins (>0%):  
(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):  
(No Product Ingredients Listed)



Proposition 65 – Developmental Toxins (>0%):  
(No Product Ingredients Listed)

Risk Phrases:

R42/43: May cause sensitisation by inhalation and skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

|                       |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.