MATERIAL SAFETY DATA SHEET

			. ,
Ceilcote EJ-3	MSDS Revision No: MSDS Revision Date:	06/20/2007	
		EMERGENCY NUMBERS	S:
	International Paint LLC	(800) 424-9300	CHEMTREC (USA)
		(703) 527-3887	CHEMTREC (Intl)
X.International.	6001 Antoine Drive	(800) 854-6813	Poison Control Center
		CUSTOMER SERVICE:	(Non-Emergency)
	Houston, Texas 77091	(800) 589-1267	International Paint
		(800) 631-7481	Interlux

1. GENERAL INFORMATION

Product Identity:

Ceilcote EJ-3 Liquid Resin Part A

Bulk Sales Reference No: NCA055

IMPORTANT: Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the correct MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard.

NOTICE: OSHA hazardous chemicals are listed in Section 2 if present at 1% or more. Carcinogens and extraordinarily/special hazardous chemicals are listed in Section 2 if present at .1% or more. Additional regulatory information for specific chemical categories is included in Section 15.

CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	125 ppm STEL; 545 mg/m3 STEL
		ACGIH:	100 ppm TWA125 ppm STEL
		NIOSH:	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH
		Supplier:	No Established Limit
	Ethyl benzene	OHSA, CAN:	100 ppm TWAEV; 435 mg/m3 TWAEV125 ppm STEV; 540 mg/m3 STEV
000100-41-4	1.0 – 10% by Weight	Mexico:	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL
		Brazil:	78 ppm TWA; 340 mg/m3 TWA
		Source	Health Data
		NIOSH:	Eye skin
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: Yes; Group 3: No; Group 4: No
CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	10 mg/m3 STEL (fume)
		ACGIH:	2 mg/m3 TWA (respirable fraction)10 mg/m3 STEL (respirable fraction)
		NIOSH:	5 mg/m3 TWA (dust and fume)10 mg/m3 STEL (fume)15 mg/m3 Ceiling (dust)500 mg/m3 IDLH
		Supplier:	No Established Limit
001217 12 2	Zinc oxide 1.0 – 10% by Weight	OHSA, CAN:	5 mg/m3 TWAEV (fume); 10 mg/m3 TWAEV (dust)10 mg/m3 STEV (fume)
		Mexico:	5 mg/m3 TWA (fume); 10 mg/m3 TWA (dust)10 mg/m3 STEL (fume)
		Brazil:	No Established Limit
		Source	Health Data
		NIOSH:	Metal fume fever
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No

2. HAZARDOUS INGREDIENT INFORMATION

Sales Order: {SalesOrd}

		NTP:	Known Carcinogen: No; Suspected Carcinogen: No Group 1: No; Group 2A: No;
		IARC:	Group 2b: No; Group 3: No; Group 4: No
CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	150 ppm STEL; 655 mg/m3 STEL
		ACGIH:	100 ppm TWA150 ppm STEL
		NIOSH:	No Established Limit
		Supplier:	No Established Limit
		OHSA, CAN:	100 ppm TWAEV; 435 mg/m3 TWAEV150 ppm STEV; 650 mg/m3 STEV
	Xylenes (o–, m–, p– isomers) 1.0 – 10% by Weight	Mexico:	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
	1.0 – 10 % by Weight	Brazil:	78 ppm TWA; 340 mg/m3 TWA
		Source	Health Data
		NIOSH:	Central nervous system depressant; respiratory and eye irritation
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No; Group 2b: No; Group 3: Yes; Group 4: No

3. HAZARD IDENTIFICATION

Overview:	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.		
Inhalation:	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.		
Eyes:	Causes severe eye irritation. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.		
Skin:	Causes skin irritation. May be harmful if absorbed through the skin.		
Ingestion:	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.		
Chronic Effects:	Contains an ingredient which can cause organ damage (See Section 2 and Section 15 for each ingredient).		
HMIS Rating:	Health: 2	Flammability: 3	Reactivity: 1

4. FIRST AID MEASURES

General:	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes:	In case of contact, immediately flush eyes with plenty of water, lifting upper and lower lids occasionally for at least 15 minutes. Get medical attention immediately.
Skin:	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion:	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. Give large quantities of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs.

5. PROTECTIVE EQUIPMENT AND CONTROL MEASURES

Respiratory: Select equipment to provide protection from the ingredients listed in Section 2 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not

	contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes:	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin/Hand:	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls:	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices:	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. Personal Protective Equipment: Do not wear contact lenses when working with this material, Use chemical goggles/safety glasses with side shields and Rubber/Latex gloves. Selection of specific items such as boots and apron will depend on operation. Confined spaces, rooms, or tanks are areas where concern for TLV's is especially important. Personal Protective Equipment: Do not wear contact lenses when working with this material, Use chemical goggles/safety glasses with side shields and Rubber/Latex gloves. Selection of specific items such as boots and apron will depend on operation.

Flash Point:	F: 106 C: 41
Lower Explosive Limit (LEL):	1.0 (%vol in air) at Normal Atmospheric Temp and Pressure
Fire and Explosion Hazards:	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discared after each use. FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.
Fire Fighting Procedures:	CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol–resistant foam. LARGE FIRES: Use water spray, fog, or alcohol–resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material. Extinguishing Media: Carbon dioxide, foam, dry chemical & water fog. Special Fire & Unusual Hazards: At higher temperature vapors can cause pressure build up in sealed containers. use water to cool containers exposed to fire. Self–contained respirator equipment and full protective clothing required when smoke or fumes are generated. Electrical grounding is not recommended. Also Reference Emergency Response Guide Number: 127

6. FIRE AND EXPLOSION INFORMATION

7. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
pH:	No Established Limit
Specific Gravity:	1.29
Boiling Point (F):	138
Vapor Density:	Heavier than air
VOC Content (lbs):	Refer to the Technical Data Sheet for this product.
Evaporation Rate:	Slower than ether

8. STABILITY AND REACTIVITY DATA

General:

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

		NCA055	
Incompatible Materials:		ercaptans and peroxides may initia	te polymerization possibly hazardously. Avoid
Hazardous Decompositon:	sources of ignition. Oxides of carbon and nitrogen; aldehydes, acids and various unknown hydrocarbons from incomplete		
•	combustion. Avoid sources of ignition. Will not occur when handled per instruction.		
	9. I	HANDLING AND STORAGE	
Storage Temperature:	Store in dry place below 70F (21	1C).	
Handling and Storage Precautions:	Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after handling.		
	10.	TOXICOLOGICAL DATA	
General:	permanent brain and nervous sy	stem damage. Intentional misuse	ational overexposure to solvents with by deliberately concentrating and inhaling the d for this product. See Section 2 for chemical
	11.	ECOLOGICAL DATA	
General:	No additional information provid	ed for this product. See Section 2 f	or chemical specific data.
	12. ACC	IDENTAL RELEASE MEASURES	
ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Spill Response Procedures: Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.			
Public Safety:	CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet). Also, Reference Emergency Response Guide Number: 127		
	13. [DISPOSAL CONSIDERATION	
Waste Disposal:	Dispose of in accordance with lo 15 if listed).	ocal, state and federal regulations.	(Also reference RCRA information in Section
	14. TRA	ANSPORTATION INFORMATION	
			IMDG (Occop Transportation)
DOT (Dome DOT Proper Shipping Name RESIN SOLUTION	estic Surface Transportation) e:	IMO / IMDG Proper Shipping RESIN SOLUTION	IMDG (Ocean Transportation) Name:
DOT Hazard Class:	3	IMDG Hazard Class:	3.3 – High flashpoint flammable liquids
UN / NA Number:	UN1866	UN Number:	UN1866
DOT Packing Group:	III	IMDG Packing Group:	Ш
CERCLA/DOT RQ:	116 gal. / 1250 lbs.	System Reference Cod	e:210

15. REGULATORY INFORMATION

Regulatory Overview:	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory. Note: Any chemical ingredients listed in Section 15, that do not also appear in Section 2, are contained in the product at a concentration below the applicable OSHA threshold level of 1% or 0.1%.
WHMIS Classification:	B3;D2A;D2B
Regulatory List DOT Marine Pollutants (10%): (No Product Ingredients Listed) DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) EPCRA 311/312 Chemicals and RQS (>.1%): (No Product Ingredients	Product Ingredients on List
(No Product Ingredients Listed) EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed)	
EPCRA 313 Toxic Chemicals (>.1%) : 000100-41-4 001330-20-7 Mass RTK Substances (>1%) : 000100-41-4 001330-20-7 001314-13-2 Mass Extraordinarily Haz Sub (>.01%) : (No Product Ingredients	Ethyl benzene Xylenes (o-, m-, p- isomers) Ethyl benzene Xylenes (o-, m-, p- isomers) Zinc oxide
Listed) Penn RTK Substances (>1%) : 000100-41-4 001330-20-7 001314-13-2 Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed)	Ethyl benzene Xylenes (o–, m–, p– isomers) Zinc oxide
Rhode Island Hazardous Substances (>.1%) : (No Product Ingredients Listed) RCRA Status (>.01%) : (No Product Ingredients Listed) N.J. RTK Substances (>1%) : (No Product Ingredients Listed) N.J. Special Hazardous Substances (>.01%) :	
000100-41-4 001330-20-7 N.J. Env. Hazardous Substances (>.1%) : 000100-41-4 001330-20-7	Ethyl benzene Xylenes (o-, m-, p- isomers) Ethyl benzene Xylenes (o-, m-, p- isomers)
Proposition 65 – Carcinogens (>0%): 000100–41–4 Proposition 65 – Female Repro Toxins (>0%):	Ethyl benzene

(No Product Ingredients Listed) Proposition 65 - Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed)

OTHER INFORMATION 16.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise. we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

International Paint, LLC, 6001 Antoine Drive, Houston, Texas 77091. http://www.international-pc.com or http://www.international-marine.com

End Of Document