NCA396_A0

Material Safety Data Sheet CEILCOTE 389 HYBRICRETE CLEAR PTA

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: NCA396
MSDS Revision Date: 12/07/2011
MSDS Revision Number: A0-2



1. Identification of the preparation and company

Product Identity CEILCOTE 389 HYBRICRETE CLEAR PTA

Bulk Sales Reference No. NCA396

Company Name International Paint LLC 6001 Antoine Drive

Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product



Danger

GHS Classification;

C	Category	Hazard		
mability	Not classified	Not applicable		
e Toxicity (mouth)	Not classified	Not applicable		
e Toxicity (skin)	Not classified	Not applicable		
e Toxicity (inhalation)	Not classified	Not applicable		
e Toxicity (ingestion)	Not classified	Not applicable		
corrosion/irritation 2	2	Causes skin irritation		
damage/irritation 2	2A	Causes serious eye irritation		
sitization (respiratory)	Not classified	Not applicable		
sitization (skin)	1	May cause allergic reaction.		
n toxicity N	Not classified	Not applicable		
rific target organ systemic toxicity le exposure)	1	Not applicable		
2	2	Not applicable		
3	3	Not applicable		
eific target organ systemic Toxicity pated exposure)	1	Not applicable		
2	2	Not applicable		
ration hazard	Not classified	Not applicable		
nfulness to aquatic Environment (re)	Not classified	Not applicable		
nfulness to aquatic Environment Nature (1971)	Not classified	Not applicable		
sitization (respiratory) sitization (skin) n toxicity sific target organ systemic toxicity le exposure) sific target organ systemic Toxicity eated exposure) sation hazard fulness to aquatic Environment lee) nfulness to aquatic Environment sitization (respiratory) sitization (skin) 1 2 3 3 3 4 5 6 6 7 7 8 7 8 8 8 9 9 9 1 1 1 1 1 1 1 1 1 1	Not classified 1 Not classified 1 2 3 1 Not classified Not classified Not classified	Not applicable May cause allergic reaction. Not applicable		

NCA396 A0

Carcinogenicity	1A	May cause cancer
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S1: Keep locked up.

S9: Keep container in a well-ventilated place.

S23: Do not breathe vapor/spray.

S24: Avoid contact with skin.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27: Take off immediately all contaminated clothing.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. May cause allergic respiratory reaction. Causes nose and throat

irritation. Vapors may affect the brain or nervous system causing dizziness, headache

or nausea.

Eyes Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of

this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.

Causes skin irritation. May cause delayed skin irritation. May cause allergic skin

reaction. May be harmful if absorbed through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

lrowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 1 Flammability: 1 Reactivity: 1 PPE: X

3. Composition/information on ingredients

Ingredient CAS No. Percent
PETROLEUM DISTILLATES, HYDROTREATED 0064742–55–8 1.0 – 10

LIGHT PARAFFIN

Skin

Oligomer Polyol Acrylate TS-RC6311 50 – 75

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

1–800–854–6813. DO NOT induce vomiting unless instructed to do so by

NCA396 A0

medical personnel. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Flash Point F: 208

C: 98

Lower Explosive Limit (LEL)

1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No.

6. Accidental release measures

Spill Response **Procedures**

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control.

Public Safety

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

ERG Guide No. 159

7. Handling and storage

Storage Temperature Handling and Storage

Precautions

Store between 40-100F (4-38C).

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not get in eyes, on skin or clothing. Close container after each use. Wash thoroughly after

handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value
0064742-55-8	PETROLEUM DISTILLATES,	OSHA	No Established Limit
	HYDROTREATED LIGHT PARAFFIN	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
TS-RC6311	Oligomer Polyol Acrylate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0064742-55-8	PETROLEUM DISTILLATES,	NIOSH	No Established Limit

NCA396 A0

	HYDROTREATED LIGHT PARAFFIN		
TS-RC6311	Oligomer Polyol Acrylate	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value	
0064742–55–8 PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFIN		OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
TS-RC6311	Oligomer Polyol Acrylate	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

Respiratory Select equipment to provide protection from the ingredients listed in Section 3 of this

document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of

the information contained in this Material Safety Data Sheet.

Eyes Do not get in eyes. Protective equipment should be selected to provide protection

from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent

chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded

after each use.

Engineering Controls Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured pH No Established Limit

Specific Gravity 1.08 Boiling Point F 212

Skin

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous Decompostion May produce hazardous fumes when heated to decomposition as in welding. Fumes

may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFIN – (0064742–55–8)	5,000.00, Rat – Category: 5	2,000.00, Rabbit - Category: 4	2.18, Rat – Category: 3
Oligomer Polyol Acrylate – (TS-RC6311)			

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation) PAINT OR PAINT IMDG Proper Shipping PAINT OR PAINT **DOT Proper Shipping** Name RELATED MATERIAL, Name RELATED MATERIAL, NMFC 149980 NMFC 149980 NR **IMDG Hazard Class** Not Regulated

DOT Hazard Class UN / NA Number Not Regulated UN / NA Number Not Regulated **DOT Packing Group** Not Regulated IMDG Packing Group Not Regulated

CERCLA/DOT RQ Not Applicable gal. / System Reference 9

Not Applicable lbs. Code

15. Regulatory information

The regulatory data in Section 15 is not intended to be all-inclusive, only Regulatory Overview

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification No Established Limit

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

(No Product Ingredients Listed)

Mass RTK Substances (>1%):

PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFIN

Mass Extraordinarily Haz Sub (>.01%):

Benzenediol

PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFIN

```
Penn RTK Substances (>1%):
      (No Product Ingredients Listed)
Penn Special Hazardous Substances (>.01%):
      (No Product Ingredients Listed)
Rhode Island Hazardous Substances (>.1%):
             Dipropylene glycol monomethyl ether
             Stoddard solvent
RCRA Status:
      (No Product Ingredients Listed)
N.J. RTK Substances (>1%):
      (No Product Ingredients Listed)
N.J. Special Hazardous Substances (>.01%):
      (No Product Ingredients Listed)
             Benzene, ethyl-
             Isobutyl alcohol
             Butanol
             Solvent naphtha (petroleum), medium aliphatic
             Xylenes (o-, m-, p- isomers)
N.J. Env. Hazardous Substances (>.1%):
      (No Product Ingredients Listed)
Proposition 65 - Carcinogens (>0%):
             Benzene, ethyl-
Proposition 65 – Female Repro Toxins (>0%):
      (No Product Ingredients Listed)
Proposition 65 - Male Repro Toxins (>0%):
      (No Product Ingredients Listed)
Proposition 65 – Developmental Toxins (>0%):
      (No Product Ingredients Listed)
Risk Phrases:
R36/37/38: Irritating to eyes, respiratory system and skin.
R43: May cause sensitisation by skin contact.
R45: May cause cancer.
```

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.