

# SY50V\_A2

Safety Data Sheet  
INTERFINE 979 FED STD 26329 GREY PT A

Sales  
Order: {SalesOrd}  
SY50V  
06/29/2016  
A2-

Bulk Sales Reference No.:  
SDS Revision Date:  
SDS Revision Number:



## 1. Identification of the preparation and company

### 1.1. Product identifier

Product Identity INTERFINE 979 FED STD 26329 GREY PT A  
Bulk Sales Reference No. SY50V

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
Application Method See Technical Data Sheet.

### 1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC  
6001 Antoine Drive  
Houston Texas 77091

### Emergency

CHEMTREC (USA) (800) 424-9300  
International Paint (713) 682-1711  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

## 2. Hazard identification of the product

### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
Skin Irrit. 2;H315 Causes skin irritation.  
Eye Irrit. 2;H319 Causes serious eye irritation.  
Skin Sens. 1;H317 May cause an allergic skin reaction.  
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

## SYY50V\_A2

- P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.
- P302+352 IF ON SKIN: Wash with soap and water.
- P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P333+313 If skin irritation or a rash occurs: Get medical advice/attention.
- P337 If eye irritation persists:.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370 In case of fire: Use water spray, fog, or regular foam..
- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating            Health: 3            Flammability: 3            Reactivity: 0

3. Composition/information on ingredients
---

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME CAS Number: 0068957-04-0	25 - 50	Acute Tox. 4;H302	[1]
Titanium dioxide CAS Number: 0013463-67-7	10 - 25	----	[1][2]
1,6-Hexanediol diacrylate CAS Number: 0013048-33-4	10 - 25	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
Acrylated Urethane Oligomer CAS Number: TS-KH6529	10 - 25	----	[1]
Barium sulfate CAS Number: 0007727-43-7	1.0 - 10	----	[1][2]
Isopropyl alcohol CAS Number: 0000067-63-0	1.0 - 10	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

4. First aid measures
-----------------------

#### 4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

## SY50V\_A2

Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects, both acute and delayed	
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.  
CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.  
SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

#### 5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

#### 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

#### 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

### 7. Handling and storage

#### 7.1. Precautions for safe handling

##### Handling

Vapors may cause flash fire or ignite explosively.

##### In Storage

## SYY50V\_A2

Keep away from heat, sparks and flame.

### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection
--

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl alcohol	OSHA	400 ppm TWA; 980 mg/m3 TWA500 ppm STEL; 1225 mg/m3 STEL
		ACGIH	200 ppm TWA400 ppm STEL
		NIOSH	400 ppm TWA; 980 mg/m3 TWA500 ppm STEL; 1225 mg/m3 STEL2000 ppm IDLH (10% LEL)
		Supplier	
		OHSA, CAN	200 ppm TWA400 ppm STEL
		Mexico	400 ppm TWA LMPE-PPT; 980 mg/m3 TWA LMPE-PPT500 ppm STEL [LMPE-CT]; 1225 mg/m3 STEL [LMPE-CT]
		Brazil	310 ppm TWA LT; 765 mg/m3 TWA LT
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	
		OHSA, CAN	10 mg/m3 TWA
		Mexico	
		Brazil	
0013048-33-4	1,6-Hexanediol diacrylate	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	
		OHSA, CAN	10 mg/m3 TWA
		Mexico	10 mg/m3 TWA LMPE-PPT (as Ti)20 mg/m3 STEL [LMPE-CT] (as Ti)
		Brazil	
0068957-04-0		OSHA	

SYY50V\_A2

	SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	ACGIH	
		NIOSH	
		Supplier	
		OSHA, CAN	
		Mexico	
		Brazil	
TS-KH6529	Acrylated Urethane Oligomer	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OSHA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl alcohol	NIOSH	Mucous membrane irritation; possible carcinogenic effects
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013048-33-4	1,6-Hexanediol diacrylate	NIOSH	
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0068957-04-0	SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	NIOSH	
TS-KH6529	Acrylated Urethane Oligomer	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-63-0	Isopropyl alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013048-33-4	1,6-Hexanediol diacrylate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0068957-04-0	SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
TS-KH6529	Acrylated Urethane Oligomer	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's

## SYY50V\_A2

directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

### 9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	82 (°C) 180 (°F)
Flash Point	32 (°C) 90 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1.5 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.37
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

### 10. Stability and reactivity

#### 10.1. Reactivity

No data available

#### 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

#### 10.3. Possibility of hazardous reactions

No data available

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Strong oxidizing agents.

## SYY50V\_A2

### 10.6. Hazardous decomposition products

**HIGHLY FLAMMABLE MATERIALS:** Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological information
-------------------------------

#### Acute toxicity

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME - (68957-04-0)	No data available	No data available	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
1,6-Hexanediol diacrylate - (13048-33-4)	5,000.00, Rat - Category: 5	No data available	No data available	No data available
Acrylated Urethane Oligomer - (TS-KH6529)	No data available	No data available	No data available	No data available
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
Isopropyl alcohol - (67-63-0)	4,710.00, Rat - Category: 5	12,800.00, Rat - Category: NA	72.60, Rat - Category: NA	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information
----------------------------

#### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

#### Aquatic Ecotoxicity

Ingredient			

SY50V\_A2

	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
SILOXANES AND SILICONES, DI-ME, METHOXY PH, POLYME - (68957-04-0)	Not Available	Not Available	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
1,6-Hexanediol diacrylate - (13048-33-4)	Not Available	Not Available	Not Available
Acrylated Urethane Oligomer - (TS-KH6529)	Not Available	Not Available	0.00 ( hr),
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
Isopropyl alcohol - (67-63-0)	1,400.00, Lepomis macrochirus	100.00, Daphnia magna	100.00 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Name PAINT

DOT Hazard Class 3 - Flammable and Combustible liquid

UN / NA Number UN 1263

DOT Packing Group III

CERCLA/DOT RQ Not Applicable gal. / Not Applicable lbs.

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name PAINT

IMDG Hazard Class Sub Class 3 - Flammable and Combustible liquid 3 - Flammable and Combustible liquid

IMDG Packing Group III

System Reference Code 2

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No



## SYY50V\_A2

### 14.6. Special precautions for user

Not Applicable

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

## 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

**WHMIS Classification** B2 D2B

**DOT Marine Pollutants (10%):**  
(No Product Ingredients Listed)

**DOT Severe Marine Pollutants (1%):**  
(No Product Ingredients Listed)

**EPCRA 311/312 Chemicals and RQs (>.1%):**  
(No Product Ingredients Listed)

**EPCRA 302 Extremely Hazardous (>.1%):**  
(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals (>.1%):**

Aluminum oxide

Isopropyl alcohol

**Mass RTK Substances (>1%):**

Barium sulfate

Isopropyl alcohol

Titanium dioxide

**Penn RTK Substances (>1%):**

Barium sulfate

Isopropyl alcohol

Titanium dioxide

**Penn Special Hazardous Substances (>.01%):**  
(No Product Ingredients Listed)

**RCRA Status:**  
(No Product Ingredients Listed)

**N.J. RTK Substances (>1%):**

Barium sulfate

Isopropyl alcohol

Titanium dioxide

**N.J. Special Hazardous Substances (>.01%):**

Carbon black

Isopropyl alcohol

Phosphoric acid

**N.J. Env. Hazardous Substances (>.1%):**

Aluminum oxide

Isopropyl alcohol

**Proposition 65 - Carcinogens (>0%):**

Carbon black

Nickel

Titanium dioxide

**Proposition 65 - Female Repro Toxins (>0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Developmental Toxins (>0%):**  
(No Product Ingredients Listed)

## 16. Other information

## SYY50V\_A2

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

This is the first revision of this SDS format, changes from previous revision not applicable.

End of Document