#### Material Safety Data Sheet DEVRAN 133 RED OXIDE PART A

Bulk Sales Reference No.: MSDS Revision Date: MSDS Revision Number:

Sales Order: {SalesOrd} NDA487 03/12/2012 A0-

# X.International.

1. Identi	fication of the preparation and company
Product Identity	DEVRAN 133 RED OXIDE PART A
Bulk Sales Reference No.	NDA487
Company Name	International Paint LLC
	6001 Antoine Drive
	Houston Texas 77091
Emergency	
CHEMTREC (USA)	(800) 424–9300
International Paint	(713) 682–1711
Poison Control Center	(800) 854–6813
Customer Service	
International Paint	(800) 589–1267
Fax No.	(800) 631–7481

2. Hazard identification of the product



Warning

		5
GHS Classification;		
Item	Category	Hazard
Flammability	4	Combustible liquid
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	2	Causes skin irritation
Eye damage/irritation	2A	Causes serious eye irritation
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	Not applicable
Specific target organ systemic Toxicity (repeated exposure)	1	Not applicable
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	2	Toxic to aquatic life.
Harmfulness to aquatic Environment (long term effect)	2	Toxic to aquatic life with long lasting effects

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S1: Keep locked up.

S23: Do not breathe vapor/spray.

S24: Avoid contact with skin.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S27: Take off immediately all contaminated clothing.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S39: Wear eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.					
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.					
Eyes	Risk of serious damage to eyes. Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use.					
Skin	Causes skin irritation. May cause delayed skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.					
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.					
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.					
HMIS Rating	Health: 3 Flammability: 1 Reactivity: 1 PPE: X					

CAS No.	Percent
0000100-41-4	0.10 - 1.0
0001332-37-2	1.0 – 10
0007727-43-7	50 – 75
0025068-38-6	25 – 50
0068609-97-2	1.0 – 10
	0000100-41-4 0001332-37-2 0007727-43-7 0025068-38-6

4. First aid measures

# GeneralRemove contaminated clothing and shoes. Get medical attention<br/>immediately. Wash clothing before reuse. Thoroughly clean or destroy<br/>contaminated shoes.InhalationIf inhaled, remove to fresh air. If not breathing, give artificial respiration. If<br/>breathing is difficult, give oxygen. Get medical attention immediately.EyesIn case of contact, immediately flush eyes with plenty of water for at least<br/>15 minutes. Get medical attention immediately.SkinIn case of contact, immediately flush skin with soap and plenty of water. Get<br/>medical attention immediately.

Ingestion	1 r	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.				
		5. Fire-fighting r	neasures			
Flash Point	lash Point F: 200 C: 93					
Lower Explosive ERG Guide No.	, ,	1 (%vol in air) at Norr 128	nal Atmospheric Temp and Pressure			
		6. Accidental releas	e measures			
Spill Response ProceduresELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do s without risk. Prevent entry into waterways, sewers, basements or confined areas. vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.Public SafetyCALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or lead (150 for the reduce to reduce to reduce to reduce to reduce use to reduce use the reduce used to reduce use to reduce use the used to reduce use to reduce use used to reduce use the used to reduce use use used to reduce us						
ERG Guide No.	area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet). RG Guide No. 128					
		7. Handling and	storage			
Storage Tempe Handling and S Precautions	torage K fl s c a s s	ames and pilot lights, ar ources of ignition during ause flash fire or ignite e Il windows and doors to	(4–38C). arks and flame. Do not smoke. Extinguish all id turn off stoves, heaters, electric motors and other use and until all vapors are gone. Vapors may explosively. Prevent build-up of vapors by opening achieve cross-ventilation. Do not get in eyes, on ntainer after each use. Wash thoroughly after			
	8.	Exposure controls and	personal protection			
			-			
CAS No.	Ingredi	Exposur ent Source				
	Benzene, ethyl-	OSHA	100 ppm TWA; 435 mg/m3 TWA125 ppm STEL;			
	-		545 mg/m3 STEL			
			100 ppm TWA125 ppm STEL 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL;			
		NIOSH	100 ppm 1WA; 435 mg/m3 1WA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL)			
		Supplier	No Established Limit			

OHSA,

Mexico

Brazil

OSHA

ACGIH

NIOSH

Supplier OHSA, CAN

0001332-37-2 Iron oxide

CAN

100 ppm TWA125 ppm STEL

78 ppm TWA; 340 mg/m3 TWA

No Established Limit

No Established Limit

No Established Limit No Established Limit

No Established Limit

100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL

		Mexico	No Established Limit
		Brazil	No Established Limit
0007727–43–7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0025068-38-6	Bisphenol A – Epichlorohydrin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0068609-97-2	Oxirane, mono[(C12–14–alkyloxy)methyl] derivs.	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data					
CAS No.	Ingredient	Source	Value		
0000100-41-4	Benzene, ethyl-	NIOSH	Eye skin		
0001332–37–2	Iron oxide	NIOSH	No Established Limit		
0007727-43-7	Barium sulfate	NIOSH	Eye nose		
0025068-38-6	Bisphenol A – Epichlorohydrin	NIOSH	No Established Limit		
	Oxirane, mono[(C12–14–alkyloxy)methyl] derivs.	NIOSH	No Established Limit		

CAS No.	Ingredient	Source	Value
0000100-41-4	Benzene, ethyl–	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0001332–37–2	Iron oxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727–43–7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025068–38–6	Bisphenol A – Epichlorohydrin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068609–97–2		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	

Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
---

	0.110, Gloup 4.110,
Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Do not get in eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific condition of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thouroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.
	9. Physical and chemical properties
Physical State pH Specific Gravity	Liquid Coloured No Established Limit 2.01
Boiling Point F Vapor Density	210 Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether
	10. Stability and reactivity
General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.

HazardousMay produce hazardous fumes when heated to decomposition as in welding. Fumes<br/>may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information					
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr		
Benzene, ethyl (0000100-41-4)	3,500.00, Rat – Category: 5	15,354.00, Rabbit – Category: NA	17.20, Rat – Category: 4		
Iron oxide – (0001332–37–2)					
Barium sulfate – (0007727–43–7)					

Bisphenol A – Epichlorohydrin – (0025068–38–6)	11,400.00, Rat – Category: NA	 
Oxirane, mono[(C12–14–alkyloxy)methyl] derivs. – (0068609–97–2)	17,100.00, Rat – Category: NA	 

General NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

#### Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information					
DOT (Domestic Surface Transportation)		IMO / IMDG (Oce	IMO / IMDG (Ocean Transportation)		
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	• •		
DOT Hazard Class	3	IMDG Hazard Class	3 – Flammable and Combustible liquid		
UN / NA Number	UN 1263	UN / NA Number	UN 1263		
DOT Packing Group	III	IMDG Packing Group	III		
CERCLA/DOT RQ	741 gal. / 12414 lbs.	System Reference Code	2		
15. Regulatory information					
Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.					
WHMIS Classification	B2:D2B				
DOT Marine Pollutants (10%): (No Product Ingredients Listed) DOT Severe Marine Pollutants (1%):					
(No Product Ingredients Listed)					
EPCRA 311/312 Chemicals and RQs (>.1%):					
Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)					
Benzene, 1,2–dimethyl– (1000 lb final RQ; 454 kg final RQ)					
Benzene, 1,4–dimethyl– (100 lb final RQ; 45.4 kg final RQ)					
Xylenes (o–, m–, p– isomers) (100 lb final RQ; 45.4 kg final RQ) EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed)					
EPCRA 313 Toxic Chemicals (>.1%):					
Benzene, ethyl-					
Benzene, 1,2-dimethyl-					
Benzene, 1,4–dimethyl–					
Xylenes (o-, m-, p- isomers)					
Mass RTK Substances (>1%) :					
Barium sulfate Mass Extraordinarily Haz Sub (>.01%) :					
(No Product Ingredients Listed)					

Penn RTK Substances (>1%) : Barium sulfate Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%) : Benzene, ethyl-Xylenes (o-, m-, p- isomers) **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : Barium sulfate N.J. Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Benzene, ethyl-Isobutyl alcohol Benzene, 1,2-dimethyl-Benzene, 1,4-dimethyl-Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%) : Benzene, ethyl-Benzene, 1,2-dimethyl-Benzene, 1,4-dimethyl-Xylenes (o-, m-, p- isomers) Proposition 65 - Carcinogens (>0%): Benzene, ethyl-Proposition 65 – Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed) **Risk Phrases:** R36/38: Irritating to eyes and skin. R43: May cause sensitisation by skin contact. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.