

EGF321 INTERSEAL 670HS LIGHT GREEN PART A

1

09/07/13

1.

1.1. INTERSEAL 670HS LIGHT GREEN PART A
EGF321

1.2.

1.3.

International Paint Singapore Pte Ltd
3 Neythal Road
Jurong Town
Singapore 628570

+65 6261 5033

+65 6264 4612

1.4.

+65 6261 5033

2.

2.1. .
3; H226
/
2;H315
/
2;H319
1;H317

2.2.

11 , 12



H226
H315
H317

H319

[]:

P210 / / /

P261 / /가 / / /

P264

P272

P273

P280 / / /

[]:

P302+352 :

P303+361+353 () :

/

P305+351+338 가 : .가

P312 /

P321 ().

P333+313 /

P337 :

P362

P363

P370 :

P378 , , ,

[]:

P403+233 가

[]:

P501 ()

2.3. PBT (,) vPvB (,)

3.

/	%	GHS	
Epoxy resin (av.mol.wt.<700) CAS No: 0025068-38-6	20-30	/ 2;H319 / 2;H315 1;H317 - 2;H411	[1]
xylene CAS No: 0001330-20-7	10-20	3; H226 - 4;H332 - 4;H312 / 2;H315	[1][2]
Propylene glycol mono methyl ether CAS No: 0000107-98-2	1-2.5	3; H226 -1 ;H336	[1][2]

- 1)
- 2) 가
- 3) PBT vPvB
16 가 , 가
가

4.

4.1.

가

가

10

4.2.

가

/

4.3.

5. ,

5.1.

; , , , .

Note;

가

가

5.2.

가

:

5.3.

가

가

6.

6.1.

가 가

가

,

가

6.2.

가

6.3.

.8

, ,

가

(13 .)

가

가

, 가 ,

가

7.

7.1.

가

, 가 (LEL) (OEL)

가

가

, 가 (LEL) (OEL)

7.2.

()

: , ,

,8

가 , 가

1

가

7.3. Specific end use(s)

가

,가

.3

Hot surfaces, Sparks,

가 (60%)

8.

8.1.

(OEL)

(ACGIH)

(ACGIH)

ppm

mg/m³

ppm

mg/m³

Propylene glycol mono methyl ether

150

553

100

369

Titanium dioxide

-

-

-

10

xylene

150

651

100

434

(P) (Peak exposure limit)

(R)

(Sk)

(Sen)

(Cat 1)

(Cat 2)

(Cat 3)

가

DNEL/PNEC

8.2.

가

가

(visor)

(overall)

가

가

.가

가

9.

pH

/ (°C)

(°C)

116

35

(= 1)

(,)

/

: 1.1 (xylene)

: 6.6 (xylene)

(Pa)

1.69

n-

/

(Log Kow)

9.2.

10.

10.1.

10.2.

.(Section 7)

가

10.3.

가

10.4.

.(7 .)

10.5.

10.6.

가

:

11.

(OEL)

가

가

Data

2

가

	LD50, mg/kg	LD50, mg/kg	LD50, mg/L/4hr	/ LD50, mg/L/4hr
Epoxy resin (av.mol.wt.<700) - (25068-38-6)	2,000.00,	2,000.00,		
Propylene glycol mono methyl ether - (107-98-2)	5,000.00,	13,000.00,		
xylene - (1330-20-7)	4,299.00,	1,548.00,		20.00,

()		
()		
()		
/	2	
/	2	
	1	
(1)		
()		

12.

12.1.

Dangerous Preparations Directive 1999/45/EC

가
(3)

가

	96 hr LC50 mg/l	49 hr EC50 mg/l	ErC50 mg/l
Epoxy resin (av.mol.wt.<700) - (25068-38-6)	3.10, Pimephales promelas	1.40, Daphnia magna	
xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
Propylene glycol mono methyl ether - (107-98-2)	1,000.00, Oncorhynchus mykiss	500.00, Daphnia magna	1,000.00 (96 hr), Selenastrum capricornutum

12.2.

가 .

12.3.

12.4.

12.5. , 가

PBT (,) vPvB (,) .

12.6.

13.

13.1.

가

..

14.

14.1. 1263

14.2.

14.3.

1263, , 3, III, 3[Y]

IMDG Class/Div. 3

EmS F-E,S-E

ICAO/IATA 3

14.4. III

14.5.

:

IMDG

:

14.6. 가

가

14.7. MARPOL73/78 Annex II IBC Code .

15.

None noted.

16.

SDS

Section 3 Phrases

- H226
- H312
- H315
- H317
- H319
- H332
- H336
- H372
- H411

SDS



Akzo Nobel

가