Material Safety Data Sheet INTERLINE 850 CRUISER BLUE PART A

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: TLA855
MSDS Revision Date: 05/16/2011
MSDS Revision Number: A7–6



1. Identification of the preparation and company

Product Identity INTERLINE 850 CRUISER BLUE PART A

Bulk Sales Reference No. TLA855

Company Name International Paint LLC 6001 Antoine Drive

Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product







Warning

GHS Classification;

Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S24: Avoid contact with skin.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed

through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 2 Flammability: 2 Reactivity: 0 PPE: X

3. Composition/information on ingredients

Ingredient 1,2,4-Trimethyl benzene Methyl n-amyl ketone Titanium dioxide	CAS No. 0000095-63-6 0000110-43-0 0013463-67-7	Percent 1.0 – 10 1.0 – 10 10 – 25
Talc Aluminum hydroxide	0014807–96–6 0021645–51–2	10 – 25 10 – 25 1.0 – 10
Reaction product of epichlorohydrin & bisphenol A PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	0025085–99–8 0028064–14–4	10 – 25 1.0 – 10
Nepheline syenite Petroleum naphtha, light aromatic Silica gel, pptd., cryst.–free	0037244-96-5 0064742-95-6 0112926-00-8	25 – 50 1.0 – 10 1.0 – 10

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get

medical attention immediately.

Ingestion If swallowed, immediately contact Poison Control Center at

1–800–854–6813. DO NOT induce vomiting unless instructed to do so by

medical personnel. Never give anything by mouth to an unconscious

person.

5. Fire-fighting measures

Flash Point F: 108

C: 42

Lower Explosive Limit (LEL)

1 (%vol in air) at Normal Atmospheric Temp and Pressure

ERG Guide No. 128

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non–sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non–combustible material and transfer to containers. Use non–sparking tools to collect absorbed material.

Public Safety

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

ERG Guide No. 128

7. Handling and storage

Storage Temperature Handling and Storage Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build—up of vapors by opening all windows and doors to achieve cross—ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4-Trimethyl benzene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	25 ppm TWA; 125 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000110-43-0	Methyl n–amyl ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA; 235 mg/m3 TWA100 ppm STEL; 465 mg/m3 STEL
		Brazil	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m3 TWA (total dust)
		ACGIH	10 mg/m3 TWA
		NIOSH	5000 mg/m3 IDLH
		Supplier	No Established Limit
			10 mg/m3 TWA (total dust)

		OHSA, CAN			
		Mexico	10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti)		
		Brazil	No Established Limit		
014807-96-6	Talc	OSHA	No Established Limit		
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and		
		NIOSH	2 mg/m3 TWA (containing no Asbestos and		
		Supplier	No Established Limit		
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and		
		Mexico	2 mg/m3 TWA (respirable fraction)		
		Brazil	No Established Limit		
021645-51-2	Aluminum hydroxide	OSHA	No Established Limit		
	-	ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
	Reaction product of	OSHA	No Established Limit		
	epichlorohydrin & bisphenol A	ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
028064-14-4	PHENOL, POLYMER WITH	OSHA	No Established Limit		
	FORMALDEHYDE,	ACGIH	No Established Limit		
	GLYCIDYL ETHER	NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
037244-96-5	Nepheline syenite	OSHA	No Established Limit		
		ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	10 mg/m3 TWA (total dust)		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
064742-95-6	Petroleum naphtha, light	OSHA	No Established Limit		
	aromatic	ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		
		OHSA, CAN	No Established Limit		
		Mexico	No Established Limit		
		Brazil	No Established Limit		
112926-00-8	Silica gel, pptd., crystfree	OSHA	No Established Limit		
	- ·· · · ·	ACGIH	No Established Limit		
		NIOSH	No Established Limit		
		Supplier	No Established Limit		

	OHSA, CAN	
M	1exico	10 mg/m3 TWA
В	Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000095-63-6	1,2,4–Trimethyl benzene	NIOSH	No Established Limit
0000110-43-0	Methyl n–amyl ketone	NIOSH	Irritation; liver kidney
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0014807–96–6	Talc		(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit
	Reaction product of epichlorohydrin & bisphenol A	NIOSH	No Established Limit
	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	NIOSH	No Established Limit
0037244-96-5	Nepheline syenite	NIOSH	No Established Limit
0064742-95-6	Petroleum naphtha, light aromatic	NIOSH	No Established Limit
0112926-00-8	Silica gel, pptd., crystfree	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value		
0000095–63–6	1,2,4-Trimethyl benzene	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0000110-43-0	Methyl n-amyl ketone	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0013463–67–7	Titanium dioxide	OSHA	Select Carcinogen: Yes		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;		
0014807-96-6	Talc	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;		
0021645-51-2	Aluminum hydroxide	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0025085-99-8	Reaction product of	OSHA	Select Carcinogen: No		
	epichlorohydrin &	NTP	Known: No; Suspected: No		
	bisphenol A	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0037244-96-5	Nepheline syenite	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-95-6	Petroleum naphtha, light	OSHA	Select Carcinogen: No		
	aromatic	NTP	Known: No; Suspected: No		
		IARC			

			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0112926-00-8 Silica gel, pptd.,	OSHA	Select Carcinogen: No	
	crystfree	NTP	Known: No; Suspected: No
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

Respiratory Select equipment to provide protection from the ingredients listed in Section 3 of this

document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of

the information contained in this Material Safety Data Sheet.

Eyes Avoid contact with eyes. Protective equipment should be selected to provide

protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment

must be thoroughly cleaned, or discarded after each use.

Skin Protective equipment should be selected to provide protection from exposure to the

chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded

after each use.

Engineering Controls Prevent build-up of vapors by opening all windows and doors to achieve

cross-ventilation.

Other Work Practices
Emergency eye wash fountains and safety showers should be available in the

immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of

soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured pH No Established Limit

Specific Gravity 1.74 Boiling Point F 210

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

General This product is stable and hazardous polymerization will not occur. Not sensitive to

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

Hazardous May produce hazardous fumes when heated to decomposition as in welding. Fumes

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr
1,2,4–Trimethyl benzene – (0000095–63–6)	3,400.00, Rat – Category: 5	3,160.00, Rabbit - Category: 5	
Methyl n-amyl ketone - (0000110-43-0)	1,670.00, Rat – Category: 4		

Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit - Category: NA	6,082.00, Rat – Category: NA
Talc - (0014807-96-6)			
Aluminum hydroxide – (0021645–51–2)	5,000.00, Rat – Category: 5		
Reaction product of epichlorohydrin & bisphenol A – (0025085–99–8)			
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER – (0028064–14–4)			
Nepheline syenite – (0037244–96–5)			
Petroleum naphtha, light aromatic – (0064742–95–6)	8,400.00, Rat – Category: NA	2,000.00, Rabbit – Category: 4	5.20, Rat – Category: 3
Silica gel, pptd., crystfree - (0112926-00-8)			

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation)

DOT Proper Shipping PAINT IMDG Proper Shipping PAINT

Name Name

DOT Hazard Class 3 – Flammable and

Combustible liquid

UN / NA Number UN 1263 UN / NA Number UN 1263

DOT Packing Group III IMDG Packing Group III

CERCLA/DOT RQ 2071 gal. / 30012 lbs. System Reference 2

Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification b3;d2b

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

1,2,4-Trimethyl benzene

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%):

```
1,2,4-Trimethyl benzene
             Methyl n-amyl ketone
             Silica gel, pptd., cryst.-free
             Talc
             Titanium dioxide
Mass Extraordinarily Haz Sub (>.01%):
      (No Product Ingredients Listed)
Penn RTK Substances (>1%):
             1,2,4-Trimethyl benzene
             Methyl n-amyl ketone
             Silica gel, pptd., cryst.-free
             Talc
             Titanium dioxide
Penn Special Hazardous Substances (>.01%):
      No Product Ingredients Listed)
Rhode Island Hazardous Substances (>.1%):
             Magnesium carbonate
             Methyl n-amyl ketone
             Talc
             Titanium dioxide
             Xylenes (o-, m-, p- isomers)
RCRA Status:
      (No Product Ingredients Listed)
N.J. RTK Substances (>1%):
             1,2,4-Trimethyl benzene
             Methyl n-amyl ketone
             Silica gel, pptd., cryst.-free
             Talc
             Titanium dioxide
N.J. Special Hazardous Substances (>.01%):
      (No Product Ingredients Listed)
             Cumene
             Isobutyl alcohol
             Xylenes (o-, m-, p- isomers)
N.J. Env. Hazardous Substances (>.1%):
             1,2,4-Trimethyl benzene
             Xylenes (o-, m-, p- isomers)
Proposition 65 - Carcinogens (>0%):
             Cumene
             Quartz
Proposition 65 - Female Repro Toxins (>0%):
      (No Product Ingredients Listed)
Proposition 65 – Male Repro Toxins (>0%):
      (No Product Ingredients Listed)
Proposition 65 – Developmental Toxins (>0%):
      (No Product Ingredients Listed)
Risk Phrases:
```

R43: May cause sensitisation by skin contact.

16. Other information

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health

and safety laws, regulations, and orders.