

EGA088 INTERGARD 269 RED PART A

1

09/07/13

1.

1.1. INTERGARD 269 RED PART A
EGA088

1.2.

1.3.

International Paint Singapore Pte Ltd
3 Neythal Road
Jurong Town
Singapore 628570

+65 6261 5033

+65 6264 4612

1.4.

+65 6261 5033

2.

- 2.1.** .
 - 3; H226
 - 4;H312
 - 4;H332
- /
- 2;H315
- /
- 1;H318
- 1;H317

2.2.

11 , 12



H312
H315
H317
H318
H332

[]:

P210 / / /
P261 / /가 / / /
P264
P271 가
P272
P273
P280 / / /

[]:

P302+352 :
P303+361+353 () :
/
P304+312 : /
P305+351+338 가 : .가
P310 /
P321 ().
P322 ().
P333+313 /
P340 가
P362
P363
P370 :
P378 , , ,

[]:

P403+233 가

[]:

P501 ()

2.3. PBT (,) vPvB (,)

3.

/	%	GHS	
Epoxy resin (av.mol.wt.<700) CAS No: 0025068-38-6	10-20	/ 2;H319 / 2;H315 1;H317 - 2;H411	[1]
xylene CAS No: 0001330-20-7	10-20	3; H226 - 4;H332 - 4;H312 / 2;H315	[1][2]
n-Butanol CAS No: 0000071-36-3	10-20	3; H226 - 4;H302 -1 ;H335	[1][2]

		/ 2;H315 / 1;H318 -1 ;H336	
Ethylbenzene CAS No: 0000100-41-4	1-2.5	2;H225 - 4;H332	[1][2]

- 1)
- 2) 가
- 3) PBT vPvB
16 가 , 가
가 .

4.

4.1.

가

가 ,

10 ,

4.2. 가 /

4.3.

5. ,

5.1.

; , , , .

Note; 가 .

가 .

5.2.

가 . :

5.3.

가

가

6.

6.1.

가

가

가

가

6.2.

가

6.3.

.8

, ,

가

. (13 .)

가

가

, 가

가

7.

7.1.

가

가 (LEL)

(OEL)

가

가

가 (LEL)

(OEL)

7.2.

()

가 , 가 .
가 , 61
1

7.3. Specific end use(s)

가 .
, 가 . 3

Hot surfaces, Sparks,

가 , (60% ,)

8.

8.1.

,
(OEL) (ACGIH)

(ACGIH)

	ppm	mg/m ³	ppm	mg/m ³
Barium Sulphate	-	-	-	10
Ethylbenzene	125	543	100	434
n-Butanol	50	152	-	-
xylene	150	651	100	434

(P) (Peak exposure limit)
(R)
(Sk)
(Sen)
(Cat 1)
(Cat 2) 가
(Cat 3)

DNEL/PNEC

8.2.

가

가

(visor)

(overall)

가

가

.가

가

9.

pH

/ (°C)

(°C)

116

26

(= 1)

(,)

/

: 1.1 (xylene)

: 6.6 (xylene)

(Pa)

1.69

n-

/

(Log Kow)

9.2.

10.

10.1.

10.2.

(Section 7)

가

10.3.

가

10.4.

10.5.

10.6.

가

11.

(OEL)

가

Data

가

2

	LD50, mg/kg	LD50, mg/kg	LD50, mg/L/4hr	/ LD50, mg/L/4hr
Epoxy resin (av.mol.wt.<700) - (25068-38-6)	2,000.00,	2,000.00,		
Ethylbenzene - (100-41-4)	3,500.00,	15,433.00,	17.20,	
n-Butanol - (71-36-3)	2,292.00,	3,430.00,		
xylene - (1330-20-7)	4,299.00,	1,548.00,		20.00,

()		
()	4	
()	4	
/	2	
/	1	

	1	
(1)		
()		

12.

12.1.

Dangerous Preparations Directive 1999/45/EC

가
(3)

가

	96 hr LC50 mg/l	49 hr EC50 mg/l	ErC50 mg/l
Epoxy resin (av.mol.wt.<700) - (25068-38-6)	3.10, Pimephales promelas	1.40, Daphnia magna	
xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
n-Butanol - (71-36-3)	1,376.00, Pimephales promelas	1,328.00, Daphnia magna	500.00 (96 hr), Scenedesmus subspicatus
Ethylbenzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata

12.2.

가

12.3.

12.4.

12.5. , 가

PBT (,) vPvB (,)

12.6.

13.

13.1.

가

14.

14.1. 1263

14.2.

14.3.

1263, , 3, III, 3[Y]

IMDG Class/Div. 3

EmS F-E,S-E

ICAO/IATA 3

14.4. III

14.5.

:

IMDG :

14.6. 가 가

14.7. MARPOL73/78 Annex II IBC Code .

15.

None noted.

16.

SDS

Section 3 Phrases

H226

H302

H312

H315

H317

H318

H319

H332

H335

H336

H372

H411

SDS



AkzoNobel

Akzo Nobel

가