Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830. - United Kingdom (UK)

SAFETY DATA SHEET

Interline 955 Part B

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: Interline 955 Part B

Product code

: TEA150

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

1.3 Details of the supplier of the safety data sheet

	-
International Paint Ltd.	
Stoneygate Lane	
Felling	
Gateshead	
Tyne and Wear	
NE10 0JY UK	
Tel: +44 (0)191 469 6111	Fax: +44 (0)191 438 3711
e-mail address of person responsible for this SDS	: sdsfellinguk@akzonobel.com
National contact	

National contact

1.4 Emergency telephone number

National advisory body/	Poison Centre (For use only by licensed medical professionals.)
Telephone number	: +44 (0)844 892 0111
<u>Supplier</u>	
Telephone number	: +44 (0)191 469 6111 (24H)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Org. Perox. D, H242 Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.



SECTION 2: Hazards identification

2.2 Label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 Heating may cause a fire. Harmful if swallowed or if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statements	
General	: Not applicable.
Prevention	: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from clothing, incompatible materials and combustible materials. Keep only in original container. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product.
Response	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF ON SKIN: Take off contaminated clothing and wash it before reuse. IF IN EYES: Immediately call a POISON CENTER or physician.
Storage	: Protect from sunlight. Store at temperatures not exceeding 25°C/77°F. Keep cool. Store away from other materials.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Cumyl hydroperoxide 2-Butanone, peroxide tert-butyl perbenzoate
Supplemental label elements	:
	Wear appropriate respirator when ventilation is inadequate.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
2.3 Other hazards Other hazards which do not result in classification	: Temperature control may be required. Hazardous decomposition may occur.





SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	% by weight	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Nota (s)	Туре
di-"isononyl" phthalate	EC: 249-079-5 CAS: 28553-12-0	≥25 - ≤50	Not classified.	-	[2]
Cumyl hydroperoxide	EC: 201-254-7 CAS: 80-15-9 Index: 617-002-00-8	≥10 - ≤25	Org. Perox. E, H242 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 2, H411	-	[1]
2-Butanone, peroxide	EC: 215-661-2 CAS: 1338-23-4	≥10 - ≤25	Org. Perox. D, H242 Acute Tox. 4, H302 Skin Corr. 1B, H314	-	[1] [2]
tert-butyl perbenzoate	EC: 210-382-2 CAS: 614-45-9	≥10 - <25	Org. Perox. C, H242 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1)	-	[1]
cumene	EC: 202-704-5 CAS: 98-82-8 Index: 601-024-00-X	≤10	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above.	C	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

06/03/2018

:



SECTION 4: First aid measures

Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health e	ffects
Eye contact	: Causes serious eye damage.
Inhalation	: Harmful if inhaled. May cause respiratory irritation.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.
Over-exposure signs/sy	<u>emptoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing headache drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any imm	nediate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if la

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large
quantities have been ingested or inhaled.Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing	: Use dry chemical, CO ₂ , water spray (fog) or foam.
media Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

:

Hazards from the substance or mixture	: This material increases the risk of fire and may aid combustion. Heating may cause a fire. May re-ignite itself after fire is extinguished. Hazardous decomposition may occur. In a fire or if heated, a pressure increase will occur and the container may burst. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
	be contained and prevented norm being discridiged to any waterway, sewer of dialit.

4/16



SECTION 5: Firefighting measures

Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Avoid contamination with reactive substances. Dilute with water and mop up if water-soluble. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid contamination with reactive substances. Do not absorb in sawdust or other combustible material. It may lead to a fire risk when it dries out. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.



SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Keep away from clothing, incompatible materials and combustible materials. Temperature control may be required. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional

7.2 Conditions for safe storage, including any incompatibilities

To avoid the risk of formation of shock-sensitive crystals or loss of stability, it is important to store the product within the recommended temperature range. Temperature control may be required. Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store at temperatures not exceeding 25°C/77°F. Store locked up. Eliminate all ignition sources. Vapours are heavier than air and may spread along floors. Separate from reducing agents and combustible materials. Keep container tightly closed and sealed until ready for use. Prevent product contamination. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

information on hygiene measures.

7.3 Specific end use(s)

Recommendations

: Not available. : Not available.

Industrial sector specific solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
di-"isononyl" phthalate	EH40/2005 WELs (United Kingdom (UK), 12/2011). TWA: 5 mg/m ³ 8 hours.
2-Butanone, peroxide	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 1.5 mg/m ³ 15 minutes. STEL: 0.2 ppm 15 minutes.
cumene	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 250 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes. TWA: 125 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.

06/03/2018



SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs/DMELs		•
No DNELs/DMELs available) .	
PNECs		
No PNECs available		
8.2 Exposure controls		
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measu		-
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection		
Hand protection		Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

:



X.International.

SECTION 8: Exposure controls/personal protection

Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

X.International.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	l a	nd chemical properties
<u>Appearance</u>		
Physical state	:	Liquid.
Colour	:	Yellow.
Odour	:	Pungent.
Odour threshold	:	Not available.
рН	:	Not applicable.
Melting point/freezing point	:	Not available.
Initial boiling point and boiling range	:	Lowest known value: 180.6°C (357.1°F) (ethyl acetoacetate).
Flash point	:	Closed cup: 64°C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or explosive limits	:	Greatest known range: Lower: 1% Upper: 54% (ethyl acetoacetate)
Vapour pressure	:	Not available.
Vapour density	:	Not available.
Relative density	:	1.1
Solubility(ies)	:	Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): 101 mm ² /s
Explosive properties	:	Not available.
Oxidising properties	:	Not available.
9.2 Other information		
SADT	:	60°C See Section 10 of the safety data sheet.
No additional information.		
SECTION 10: Stability a	n	d reactivity

SECTION 10: Stability and reactivity

10.1 Reactivity

: This product, in laboratory testing, either detonates partially, deflagrates slowly or shows a medium effect when heated under confinement.



SECTION 10: Stability and reactivity

10.2 Chemical stability	: SADT (Self-Accelerating Decomposition Temperature) is the lowest temperature at which self-accelerating decomposition may occur with a substance in the packaging as used for transport. A dangerous self-accelerating decomposition reaction and, under certain circumstances, explosion or fire can be caused by thermal decomposition at or above the SADT. Contact with incompatible materials, such as acids, alkalis, heavy metal compounds and reducing agents, will result in hazardous decomposition.
10.3 Possibility of hazardous reactions	: Hazardous reactions or instability may occur under certain conditions of storage or use. Conditions may include the following: temperature increase high temperature Reactions may include the following: hazardous decomposition risk of causing fire
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid increased storage temperature. Drying on clothing or other combustible materials may cause fire.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: combustible materials reducing materials copper iron rust
10.6 Hazardous	: Under normal conditions of storage and use, hazardous decomposition products

10.6 Hazardous : Under normal conditions of storage and use, hazardous decomposition product should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Cumyl hydroperoxide	LD50 Oral	Rat	800 mg/kg	-
	LDLo Dermal	Rabbit	1200 mg/kg	-
2-Butanone, peroxide	LC50 Inhalation Gas.	Rat	200 ppm	4 hours
	LC50 Inhalation Vapour	Rat	3600 mg/m ³	4 hours
	LD50 Oral	Rat	470 mg/kg	-
cumene	LC50 Inhalation Vapour	Rat	39000 mg/m ³	4 hours
	LD50 Oral	Rat	1400 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Route	ATE value		
Oral	1653.3 mg/kg		
	5500 mg/kg		
Inhalation (dusts and mists)	2.5 mg/l		

Irritation/Corrosion

K.International.

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Cumyl hydroperoxide	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	
tert-butyl perbenzoate	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
		D 11 1		milligrams	
	Eyes - Mild irritant	Rabbit	-	1 minutes	-
				100 milligrama	
	Skin - Mild irritant	Rabbit	_	milligrams 24 hours 500	-
		Rabbit	-	milligrams	-
	Skin - Mild irritant	Rabbit	-	4 hours 0.1	-
				Mililiters	
	Skin - Moderate irritant	Rabbit	-	120 hours 0.	-
				1 Mililiters	
				Intermittent	
cumene	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	Even Mild instant	Dabbit		milligrams	
	Eyes - Mild irritant Skin - Mild irritant	Rabbit Rabbit	-	86 milligrams 24 hours 10	-
		Rabbit	-	milligrams	-
	Skin - Moderate irritant	Rabbit	_	24 hours 100	-
				milligrams	
Conclusion/Summary	: Not available.	I			
<u>Sensitisation</u>					
Conclusion/Summary	: Not available.				
Mutagenicity					
Conclusion/Summary	: Not available.				
<u>Carcinogenicity</u>					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
<u>Teratogenicity</u>					

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Cumyl hydroperoxide	Category 3	Not applicable.	Respiratory tract irritation
cumene	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Cumyl hydroperoxide	Category 2	Not determined	Not determined

Aspiration hazard

Product/ingredient name	Result	
cumene	ASPIRATION HAZARD - Category 1	

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: Causes serious eye damage.		
Inhalation	: Harmful if inhaled. May cause respiratory irritation.		

:

06/03/2018

AkzoNobel

SECTION 11: Toxicological information

Skin contact	: Causes severe burns. May cause an allergic skin reaction.			
Ingestion	: Harmful if swallowed. May cause burns to mouth, throat and stomach.			
Symptoms related to t	the physical, chemical and toxicological characteristics			
Eye contact	: Adverse symptoms may include the following: pain watering redness			
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing headache drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness			
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur			
Ingestion	: Adverse symptoms may include the following: stomach pains			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: May cause damage to organs through prolonged or repeated exposure. Once
	sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	
Carcinogenicity Mutagenicity	low levels.
• •	low levels. No known significant effects or critical hazards.
Mutagenicity	low levels.No known significant effects or critical hazards.No known significant effects or critical hazards.
Mutagenicity Teratogenicity	 low levels. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

AkzoNobel

X.International.

X.International

SECTION 12: Ecological information

Result	Species	Exposure
Acute EC50 2600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
Acute EC50 7400 to 11290 µg/l Fresh water	Crustaceans - Artemia sp Nauplii	48 hours
10	Daphnia - Daphnia magna - Neonate	48 hours
Acute LC50 2700 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 2600 µg/l Fresh water Acute EC50 7400 to 11290 µg/l Fresh water Acute EC50 10600 to 14100 µg/l Fresh water	Acute EC50 2600 μg/l Fresh waterAlgae - Pseudokirchneriella subcapitataAcute EC50 7400 to 11290 μg/l Fresh waterCrustaceans - Artemia sp NaupliiAcute EC50 10600 to 14100 μg/l Fresh waterDaphnia - Daphnia magna - Neonate

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Cumyl hydroperoxide	1.6	9	low
2-Butanone, peroxide	<0.3	-	low
tert-butyl perbenzoate	3	-	low
cumene	3.55	35.481338923	low

12.4 Mobility in soil			
Soil/water partition coefficient (Koc)	: Not available.		
Mobility	: Not available.		

12.5 Results of PBT and vPvB assessment

PBT	: Not applicable.
vPvB	: Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

	Code number	Waste designation	
	EWC 16 09 03*	peroxides, for example hydrogen peroxide	
<u>P</u>	Packaging		
	Methods of disposal	: Dispose of containers contaminated by the product in accordance with local or national legal provisions. This material and its container must be disposed of as hazardous waste. Dispose of via a licensed waste disposal contractor.	



SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	UN3105	UN3105	UN3105
shipping name D, LIQUID (2-Butanone, peroxide, tert-butyl perbenzoate)		ORGANIC PEROXIDE TYPE D, LIQUID (2-Butanone, peroxide, tert-butyl perbenzoate). Marine pollutant (Cumyl hydroperoxide)	ORGANIC PEROXIDE TYPE D, LIQUID (2-Butanone, peroxide, tert-butyl perbenzoate)
14.3 Transport hazard class(es)	5.2	5.2	5.2
14.4 Packing group	-	-	-
14.5 Environmental hazards	Yes.	Yes.	No.
Additional information The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg. Tunnel code (D)		The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.	The environmentally hazardous substance mark may appear if required by other transportation regulations.

IMDG Code Segregation : 16 - Peroxides group

14.6 Special precautions for user: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk: Not available.according to Annex II ofMarpol and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

<u>Annex XIV</u>

Substances of very high concern

None of the components are listed.



X.International.

SECTION 15: Regulatory information

of the regulatory monnation				
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	placing on the market and use of certain dangerous substances,			
Other EU regulations				
Europe inventory	: All components are listed or exempted.			
Special packaging requirem	<u>ients</u>			
Containers to be fitted with child-resistant fastenings	: Not applicable.			
Tactile warning of danger	: Not applicable.			
<u>Ozone depleting substances (1005/2009/EU)</u> Not listed.				
Prior Informed Consent (P Not listed.	<u>IC) (649/2012/EU)</u>			
<u>National regulations</u> References	: Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II and Regulation (EC) No. 1272/2008 (CLP)			
15.2 Chemical safety assessment	: No Chemical Safety Assessment has been carried out.			
SECTION 16: Other information				
Indicates information that h	has changed from previously issued version.			
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level 			

EUH statement = CLP-specific Hazard statement

- PBT = Persistent, Bioaccumulative and Toxic
 - PNEC = Predicted No Effect Concentration
 - RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Org. Perox. D, H242	Expert judgment
Acute Tox. 4, H302	Calculation method
Acute Tox. 4, H332	Calculation method
Skin Corr. 1B, H314	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 2, H411	Calculation method

14/16

:

SECTION 16: Other information

X.International.

Full text of abbreviated H	:	H226	Flammable liquid and vapour.
statements		H242	Heating may cause a fire.
		H302	Harmful if swallowed.
		H304	May be fatal if swallowed and enters airways.
		H312	Harmful in contact with skin.
		H314	Causes severe skin burns and eye damage.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H331	Toxic if inhaled.
		H332	Harmful if inhaled.
		H335	May cause respiratory irritation.
		H373	May cause damage to organs through prolonged or
			repeated exposure.
		H400	Very toxic to aquatic life.
		H411	Toxic to aquatic life with long lasting effects.
Full text of classifications	•	Acute Tox. 3, H331	ACUTE TOXICITY (inhalation) - Category 3
[CLP/GHS]	•	Acute Tox. 3, H302	
			ACUTE TOXICITY (oral) - Category 4
		Acute Tox. 4, H312 Acute Tox. 4, H332	ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4
		Aquatic Acute 1, H400	
		Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 2
		Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
		Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category
		Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3
		Org. Perox. C, H242	ORGANIC PEROXIDES - Type C
		Org. Perox. D, H242	ORGANIC PEROXIDES - Type D
		Org. Perox. E, H242	ORGANIC PEROXIDES - Type D
		Skin Corr. 1B, H314	SKIN CORROSION/IRRITATION - Category 1B
		Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 1
		Skin Sens. 1, H317	SKIN CORROSION/IRRITATION - Calegoly 2 SKIN SENSITIZATION - Category 1
			SPECIFIC TARGET ORGAN TOXICITY (REPEATED
		STOT RE 2, H373	
			EXPOSURE) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE
		STOT SE 3, H335	
			EXPOSURE) (Respiratory tract irritation) - Category 3
Date of printing	:	06/03/2018	
Date of issue/ Date of	•	06/03/2018	
revision	•	00,00,2010	
Date of previous issue	:	05/06/2017	
Version	:	5	
	•	-	

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.



SECTION 16: Other information

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be). © AkzoNobel

XInternational.

