

Safety Data Sheet
HAK766 INTERTHERM 875 RAL7001 SILVER GREY
Version Number 1 Revision Date 11/27/13
1. Product and company identification

| | |
|---|--|
| 1.1. Product identifier | INTERTHERM 875 RAL7001 SILVER GREY |
| Product Code | HAK766 |
| 1.2. Relevant identified uses of the substance or mixture and uses advised against | |
| Intended use | Refer Technical Data Sheet. For professional use only. |
| Application Method | Refer Technical Data Sheet. |
| 1.3. Details of the supplier of the safety data sheet | |
| Manufacturer | PT. International Paint Indonesia Cikarang Industrial Estate Jl. Jababeka Raya Blok E 9-11 17530, Cikarang, Indonesia |
| Telephone No. | 021 8934270 |
| Fax No. | 021 8934275 |
| 1.4. Emergency telephone number | 021 8934270 |
| For Poisons Advice telephone | For Advice to Doctors & Hospitals only |

2. Hazard identification of the product
2.1. Classification of the substance or mixture
2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

[Prevention]:

[Response]:

[Storage]:

[Disposal]:

2.3. Other hazards
3. Composition/information on ingredients

This product contains the following hazardous substances.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|------------------------------------|----------|---|--------|
| Xylene CAS Number: 0001330-20-7 | 25-50 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 | [1][2] |

| | | | |
|--|--------|---|--------|
| Titanium dioxide CAS Number: 0013463-67-7 | 10-25 | | [1][2] |
| Ethyl Benzene CAS Number: 0000100-41-4 | 2.5-10 | Flam. Liq. 2;H225 Acute Tox. 4;H332 | [1][2] |
| n-Butanol CAS Number: 0000071-36-3 | 2.5-10 | Flam. Liq. 3;H226 Acute Tox. 4;H302 STOT SE 3;H335 Skin Irrit. 2;H315 Eye Dam. 1;H318 STOT SE 3;H336 | [1][2] |
| Methanol CAS Number: 0000067-56-1 | <1 | Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370 | [1][2] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the Hazard (H) phrases are shown in Section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

4. First aid measures

4.1. Description of first aid measures

General

Inhalation

Skin Contact

Eye Contact

Ingestion

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for fire-fighters

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

7. Handling and storage

7.1. Precautions for safe handling

Handling

In Storage

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

8. Exposure controls and personal protection

8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygienists).

| Material | Short term (15 min. ave) | | Long term (8hr time weighted average) | | Comments |
|------------------|--------------------------|-------------------|---------------------------------------|-------|----------|
| | ppm | mg/m ³ | ppm | mg/M3 | |
| Ethyl Benzene | 125 | 543 | 100 | 434 | |
| Methanol | 250 | 328 | 200 | 262 | |
| n-Butanol | 50 | 152 | - | - | |
| Titanium dioxide | - | - | - | 10 | |
| Xylene | 150 | 651 | 100 | 434 | |

Key to notification

(P) Peak exposure limit

(R) Suppliers Recommended Limit

(Sk) There is a risk of absorption through unbroken skin

(Sen) Sensitiser

(Cat1) Category 1 - established human carcinogen

(Cat2) Category 2 - probable human carcinogen

(Cat3) Category 3 - substances suspected of having carcinogenic potential

DNEL/PNEC values

8.2. Exposure controls

Eye Protection

Skin Protection

Other

Respiratory Protection

Thermal hazards

9. Physical and chemical properties

Colour

Odour

Odour threshold

pH

Melting point / freezing point (°C)

Initial boiling point and boiling range (°C)

Flash Point (C)

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Lower Explosive Limit: 1.1 (Xylene)

Upper Explosive Limit: 6.6 (Xylene)

Vapour pressure (Pa)

Vapour Density

Specific Gravity

0.00

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Autoignition temperature ()

Decomposition temperature

Viscosity (cSt)

9.2. Other information

No further information

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

11. Toxicological information

Acute toxicity

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapour LD50, mg/L/4hr | Inhalation Dust/Mist LD50, mg/L/4hr |
|---------------------------------|------------------|-------------------|----------------------------------|-------------------------------------|
| Ethyl Benzene - (100-41-4) | 3,500.00, Rat | 15,433.00, Rabbit | 17.20, Rat | Not Available |
| Methanol - (67-56-1) | 5,628.00, Rat | 15,800.00, Rabbit | 85.00, Rat | Not Available |
| n-Butanol - (71-36-3) | 2,292.00, Rat | 3,430.00, Rabbit | Not Available | Not Available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat | 10,000.00, Rabbit | Not Available | 6.82, Rat |
| Xylene - (1330-20-7) | 4,299.00, Rat | 1,548.00, Rabbit | Not Available | 20.00, Rat |

| Item | Category | Hazard |
|-----------------------------|----------------|----------------|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | Not Classified | Not Applicable |
| Eye damage/irritation | Not Classified | Not Applicable |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | Not Classified | Not Applicable |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |

| | | |
|---|----------------|----------------|
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic toxicity (single exposure) | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l |
|---------------------------------|---------------------------------|----------------------------|---|
| Xylene - (1330-20-7) | 3.30, Oncorhynchus mykiss | 8.50, Palaemonetes pugio | 100.00 (72 hr), Chlorococcales |
| Titanium dioxide - (13463-67-7) | 1,000.00, Fundulus heteroclitus | 5.50, Daphnia magna | 5.83 (72 hr), Pseudokirchneriella subcapitata |
| Ethyl Benzene - (100-41-4) | 4.20, Oncorhynchus mykiss | 2.93, Daphnia magna | 3.60 (96 hr), Pseudokirchneriella subcapitata |
| n-Butanol - (71-36-3) | 1,376.00, Pimephales promelas | 1,328.00, Daphnia magna | 500.00 (96 hr), Scenedesmus subspicatus |
| Methanol - (67-56-1) | 100.00, Pimephales promelas | 10,000.00, Daphnia magna | 16.912 (96 hr), Ulva pertusa |

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

14. Transport information

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Road and Rail Transport

IMDG Class/Div Sub Class
reference :

Ems

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.