

NVA349_A1

Material Safety Data Sheet ENVIROLINE 375 GREY PART A



Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:

Sales
Order: {SalesOrd}
NVA349
10/01/2011
A1-5

1. Identification of the preparation and company

Product Identity ENVIROLINE 375 GREY PART A
Bulk Sales Reference No. NVA349
Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency
CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product



Warning

GHS Classification:

| Item | Category | Hazard |
|---|----------------|--|
| Flammability | 3 | Flammable liquid and vapor |
| Acute Toxicity (mouth) | 5 | May be harmful if swallowed |
| Acute Toxicity (skin) | Not classified | Not applicable |
| Acute Toxicity (inhalation) | Not classified | Not applicable |
| Acute Toxicity (ingestion) | Not classified | Not applicable |
| Skin corrosion/irritation | 2 | Causes skin irritation |
| Eye damage/irritation | Not classified | Not applicable |
| Sensitization (respiratory) | Not classified | Not applicable |
| Sensitization (skin) | 1 | May cause allergic reaction. |
| Germ toxicity | Not classified | Not applicable |
| Specific target organ systemic toxicity (single exposure) | 1 | central nerve system, kidneys, liver, respiratory system |
| | 2 | central nerve system |
| | 3 | respiratory tract irritation |
| Specific target organ systemic Toxicity (repeated exposure) | 1 | central nerve system, kidneys, lung, respiratory system |
| | 2 | Not applicable |
| Aspiration hazard | Not classified | Not applicable |
| Harmfulness to aquatic Environment (acute) | 3 | Harmful to aquatic life. |
| Harmfulness to aquatic Environment (long term effect) | 4 | May cause harm to aquatic life with long lasting effects |

NVA349_A1

| | | |
|-----------------------|----------------|----------------|
| Carcinogenicity | Not classified | Not applicable |
| Reproductive Toxicity | Not classified | Not applicable |
| Organic Peroxide | Not classified | Not applicable |

Safety Phrases:

- S1: Keep locked up.
- S20: When using do not eat or drink.
- S23: Do not breathe vapor/spray.
- S24: Avoid contact with skin.
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S27: Take off immediately all contaminated clothing.
- S28: After contact with skin, wash immediately with plenty of soap and water.
- S36/37: Wear suitable protective clothing and gloves.
- S39: Wear eye/face protection.
- S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- S51: Use only in well-ventilated areas.
- S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.
- S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

| | |
|-----------------|--|
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May cause delayed skin irritation. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| Chronic effects | Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. |
| HMIS Rating | Health: 2 Flammability: 3 Reactivity: 1 PPE: X |

3. Composition/information on ingredients

| Ingredient | CAS No. | Percent |
|---|--------------|----------|
| Benzene, ethyl- | 0000100-41-4 | 1.0 - 10 |
| Xylenes (o-, m-, p- isomers) | 0001330-20-7 | 10 - 25 |
| OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS | 0002425-79-8 | 1.0 - 10 |
| Titanium dioxide | 0013463-67-7 | 1.0 - 10 |
| Wollastonite (Ca(SiO3)) | 0013983-17-0 | 1.0 - 10 |
| Quartz | 0014808-60-7 | 10 - 25 |
| Reaction product of epichlorohydrin & bisphenol A | 0025085-99-8 | 25 - 50 |
| PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER | 0028064-14-4 | 10 - 25 |
| Talc (*non-asbestiform) | 14807-96-6* | 1.0 - 10 |

This product contains 16.56 percent Quartz.

4. First aid measures

| | |
|---------|--|
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
|---------|--|

NVA349_A1

| | |
|------------|---|
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

| |
|----------------------------------|
| 5. Fire-fighting measures |
|----------------------------------|

| | |
|-----------------------------|---|
| Flash Point | F: 80 C: 27 |
| Lower Explosive Limit (LEL) | 1 (%vol in air) at Normal Atmospheric Temp and Pressure |
| ERG Guide No. | 127 |

| |
|---------------------------------------|
| 6. Accidental release measures |
|---------------------------------------|

| | |
|---------------------------|---|
| Spill Response Procedures | ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material. |
| Public Safety | CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet). |
| ERG Guide No. | 127 |

| |
|--------------------------------|
| 7. Handling and storage |
|--------------------------------|

| | |
|----------------------------------|---|
| Storage Temperature | Store between 40-100F (4-38C). |
| Handling and Storage Precautions | Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes, skin and clothing. Close container after each use. Wash thoroughly after handling. |

| |
|---|
| 8. Exposure controls and personal protection |
|---|

| Exposure | | | |
|--------------|-----------------|-----------|--|
| CAS No. | Ingredient | Source | Value |
| 0000100-41-4 | Benzene, ethyl- | OSHA | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA125 ppm STEL |
| | | NIOSH | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL800 ppm IDLH (10% LEL) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 100 ppm TWAEV; 435 mg/m3 TWAEV125 ppm STEV; 540 mg/m3 STEV |
| | | Mexico | |

NVA349_A1

| | | | |
|--------------|---|--------------|---|
| | | | 100 ppm TWA; 435 mg/m3 TWA125 ppm STEL; 545 mg/m3 STEL |
| | | Brazil | 78 ppm TWA; 340 mg/m3 TWA |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | OSHA | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA150 ppm STEL |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 100 ppm TWAEV; 435 mg/m3 TWAEV150 ppm STEV; 650 mg/m3 STEV |
| | | Mexico | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | Brazil | 78 ppm TWA; 340 mg/m3 TWA |
| 0002425-79-8 | OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0013463-67-7 | Titanium dioxide | OSHA | 15 mg/m3 TWA (total dust) |
| | | ACGIH | 10 mg/m3 TWA |
| | | NIOSH | 5000 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 10 mg/m3 TWAEV (total dust) |
| | | Mexico | 10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti) |
| | | Brazil | No Established Limit |
| 0013983-17-0 | Wollastonite (Ca(SiO3)) | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0014808-60-7 | Quartz | OSHA | No Established Limit |
| | | ACGIH | 0.025 mg/m3 TWA (respirable fraction) |
| | | NIOSH | 0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust) |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 0.10 mg/m3 TWAEV (designated substance regulation)0.10 mg/m3 TWAEV |
| | | Mexico | 0.1 mg/m3 TWA |
| | | Brazil | No Established Limit |
| 0025085-99-8 | Reaction product of epichlorohydrin & bisphenol A | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |

NVA349_A1

| | | | |
|--------------|---|-----------|----------------------|
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0028064-14-4 | PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 14807-96-6* | Talc (*non-asbestiform) | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000100-41-4 | Benzene, ethyl- | NIOSH | Eye skin |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | NIOSH | Central nervous system depressant; respiratory and eye irritation |
| 0002425-79-8 | OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS | NIOSH | No Established Limit |
| 0013463-67-7 | Titanium dioxide | NIOSH | Lung tumors in animals |
| 0013983-17-0 | Wollastonite (Ca(SiO3)) | NIOSH | No Established Limit |
| 0014808-60-7 | Quartz | NIOSH | Chronic lung disease (silicosis) |
| 0025085-99-8 | Reaction product of epichlorohydrin & bisphenol A | NIOSH | No Established Limit |
| 0028064-14-4 | PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER | NIOSH | No Established Limit |
| 14807-96-6* | Talc (*non-asbestiform) | NIOSH | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| 0000100-41-4 | Benzene, ethyl- | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0002425-79-8 | OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; |

NVA349_A1

| | | | |
|--------------|---|------|---|
| 0013983-17-0 | Wollastonite (Ca(SiO3)) | | Group 4: No; |
| | | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0014808-60-7 | Quartz | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: Yes; Suspected: No |
| | | IARC | Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0025085-99-8 | Reaction product of epichlorohydrin & bisphenol A | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0028064-14-4 | PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 14807-96-6* | Talc (*non-asbestiform) | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

| | |
|----------------------|---|
| Respiratory | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Skin | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. |
| Engineering Controls | Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

| |
|-------------------------------------|
| 9. Physical and chemical properties |
|-------------------------------------|

| | |
|------------------|----------------------|
| Physical State | Liquid Coloured |
| pH | No Established Limit |
| Specific Gravity | 1.37 |
| Boiling Point F | 243 |
| Vapor Density | Heavier than air |

NVA349_A1

VOC % Refer to the Technical Data Sheet or label where information is available.
 Evaporation Rate Slower than ether

| |
|------------------------------|
| 10. Stability and reactivity |
|------------------------------|

General This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

Incompatible Materials Strong oxidizing agents.

Hazardous Decomposition May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

| |
|-------------------------------|
| 11. Toxicological information |
|-------------------------------|

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr |
|---|----------------------------------|-------------------------------------|---------------------------------------|
| Benzene, ethyl- (0000100-41-4) | 3,500.00, Rat – Category: 5 | 15,354.00, Rabbit – Category: NA | 17.20, Rat – Category: 4 |
| Xylenes (o-, m-, p- isomers) (0001330-20-7) | 4,300.00, Rat – Category: 5 | 1,700.00, Rabbit – Category: 4 | 29.08, rat – Category: NA |
| OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS – (0002425-79-8) | 1,134.00, Rat – Category: 4 | 1,130.00, Rabbit – Category: 4 | ----- |
| Titanium dioxide (0013463-67-7) | 10,000.00, Rat – Category: NA | 10,000.00, Rabbit – Category: NA | 6,082.00, Rat – Category: NA |
| Wollastonite (Ca(SiO3)) (0013983-17-0) | ----- | ----- | ----- |
| Quartz (0014808-60-7) | 500.00, Rat – Category: 4 | ----- | ----- |
| Reaction product of epichlorohydrin & bisphenol A – (0025085-99-8) | ----- | ----- | ----- |
| PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER (0028064-14-4) | ----- | ----- | ----- |
| Talc (*non-asbestiform) (14807-96-6*) | ----- | ----- | ----- |

General NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

| |
|----------------------------|
| 12. Ecological information |
|----------------------------|

Not Defined
 No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

| |
|-----------------------------|
| 13. Disposal considerations |
|-----------------------------|

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

| |
|---------------------------|
| 14. Transport information |
|---------------------------|

| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | |
|---------------------------------------|--------------------|-----------------------------------|--------------------------------------|
| DOT Proper Shipping Name | PAINT | IMDG Proper Shipping Name | PAINT |
| DOT Hazard Class | 3 | IMDG Hazard Class | 3 – Flammable and Combustible liquid |
| UN / NA Number | UN 1263 | UN / NA Number | UN 1263 |
| DOT Packing Group | III | IMDG Packing Group | III |
| CERCLA/DOT RQ | 74 gal. / 836 lbs. | System Reference Code | 2 |

15. Regulatory information

| | |
|---|--|
| Regulatory Overview | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory. |
| WHMIS Classification | B2;D2B |
| DOT Marine Pollutants (10%): (No Product Ingredients Listed) | |
| DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) | |
| EPCRA 311/312 Chemicals and RQs (>.1%) : | |
| | Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ) |
| | Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ) |
| EPCRA 302 Extremely Hazardous (>.1%) : | |
| | (No Product Ingredients Listed) |
| EPCRA 313 Toxic Chemicals (>.1%) : | |
| | Aluminum oxide |
| | Benzene, ethyl- |
| | Xylenes (o-, m-, p- isomers) |
| Mass RTK Substances (>1%) : | |
| | Benzene, ethyl- |
| | Quartz |
| | Titanium dioxide |
| | Xylenes (o-, m-, p- isomers) |
| Mass Extraordinarily Haz Sub (>.01%) : | |
| | Quartz |
| Penn RTK Substances (>1%) : | |
| | Benzene, ethyl- |
| | Quartz |
| | Titanium dioxide |
| | Xylenes (o-, m-, p- isomers) |
| Penn Special Hazardous Substances (>.01%) : | |
| | (No Product Ingredients Listed) |
| Rhode Island Hazardous Substances (>.1%) : | |
| | Aluminum oxide |
| | Benzene, ethyl- |
| | Propylene glycol monomethyl ether |
| | Quartz |
| | Titanium dioxide |
| | Xylenes (o-, m-, p- isomers) |
| RCRA Status: | |
| | (No Product Ingredients Listed) |
| N.J. RTK Substances (>1%) : | |
| | Benzene, ethyl- |
| | Quartz |
| | Titanium dioxide |
| | Xylenes (o-, m-, p- isomers) |
| N.J. Special Hazardous Substances (>.01%) : | |
| | Benzene, ethyl- |
| | Xylenes (o-, m-, p- isomers) |
| N.J. Env. Hazardous Substances (>.1%) : | |
| | Aluminum oxide |
| | Benzene, ethyl- |
| | Xylenes (o-, m-, p- isomers) |
| Proposition 65 – Carcinogens (>0%): | |
| | Carbon black |

Benzene, ethyl-
Quartz

Proposition 65 – Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):
(No Product Ingredients Listed)

Risk Phrases:

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.