NCA669_A1

Material Safety Data Sheet CEILCOTE 660 HV COROCRETE LT GREY PTA

Sales

Order: {SalesOrd}

Bulk Sales Reference No.: NCA669
MSDS Revision Date: 12/08/2011
MSDS Revision Number: A1-2



1. Identification of the preparation and company

Product Identity CEILCOTE 660 HV COROCRETE LT GREY PTA

Bulk Sales Reference No. NCA669

Company Name International Paint LLC 6001 Antoine Drive

Houston Texas 77091

Emergency

 CHEMTREC (USA)
 (800) 424–9300

 International Paint
 (713) 682–1711

 Poison Control Center
 (800) 854–6813

Customer Service

International Paint (800) 589–1267 Fax No. (800) 631–7481

2. Hazard identification of the product







Warning

GHS Classification;

| Item | Category | Hazard | |
|---|----------------|--|--|
| Flammability | 4 | Combustible liquid | |
| Acute Toxicity (mouth) | Not classified | Not applicable | |
| Acute Toxicity (skin) | Not classified | Not applicable | |
| Acute Toxicity (inhalation) | Not classified | Not applicable | |
| Acute Toxicity (ingestion) | Not classified | Not applicable | |
| Skin corrosion/irritation | Not classified | Not applicable | |
| Eye damage/irritation | Not classified | Not applicable | |
| Sensitization (respiratory) | Not classified | Not applicable | |
| Sensitization (skin) | 1 | May cause allergic reaction. | |
| Germ toxicity | Not classified | Not applicable | |
| Specific target organ systemic toxicity (single exposure) | 1 | Not applicable | |
| | 2 | Not applicable | |
| | 3 | respiratory tract irritation | |
| Specific target organ systemic Toxicity (repeated exposure) | 1 | lung | |
| | 2 | Not applicable | |
| Aspiration hazard | Not classified | Not applicable | |
| Harmfulness to aquatic Environment (acute) | 3 | Harmful to aquatic life. | |
| Harmfulness to aquatic Environment (long term effect) | 4 | May cause harm to aquatic life with long lasting effects | |

| Carcinogenicity | Not classified | Not applicable |
|-----------------------|----------------|----------------|
| Reproductive Toxicity | Not classified | Not applicable |
| Organic Peroxide | Not classified | Not applicable |

Safety Phrases:

Ingestion

S24: Avoid contact with skin.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be

harmful or fatal. Avoid contact with eyes, skin and clothing.

Inhalation Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or

nervous system causing dizziness, headache or nausea.

Eyes Causes severe eye irritation. Avoid contact with eyes.

Skin Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed

through the skin.

Ingestion Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or

drowsiness.

Chronic effects Possible cancer hazard. Contains an ingredient which may cause cancer based on

animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer

depends on duration and level of exposure.

HMIS Rating Health: 1* Flammability: 1 Reactivity: 0 PPE: X

3. Composition/information on ingredients

| Ingredient | CAS No. | Percent |
|---|--------------|------------|
| Carbon black | 0001333-86-4 | 0.10 - 1.0 |
| Silica, amorphous | 0007631-86-9 | 1.0 – 10 |
| Titanium dioxide | 0013463-67-7 | 10 – 25 |
| Aluminum hydroxide | 0021645-51-2 | 1.0 – 10 |
| Reaction product of epichlorohydrin & bisphenol A | 0025085-99-8 | 25 – 50 |
| PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER | 0028064-14-4 | 10 – 25 |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. | 0068609-97-2 | 1.0 – 10 |
| Talc (*non-asbestiform) | 14807-96-6* | 10 – 25 |

4. First aid measures

General Remove contaminated clothing and shoes. Get medical attention

immediately. Wash clothing before reuse. Thoroughly clean or destroy

contaminated shoes.

Inhalation If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical attention immediately.

Eyes In case of contact, immediately flush eyes with plenty of water for at least

15 minutes. Get medical attention immediately.

Skin In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.

If swallowed, immediately contact Poison Control Center at

1-800-854-6813. DO NOT induce vomiting unless instructed to do so by

medical personnel. Never give anything by mouth to an unconscious

person.

5. Fire–fighting measures

Flash Point F: 200 C: 93

Lower Explosive Limit (LEL) ERG Guide No.

1 (%vol in air) at Normal Atmospheric Temp and Pressure

G Guide No. 159

6. Accidental release measures

Spill Response Procedures ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non–combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control.

Public Safety

CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

ERG Guide No. 159

7. Handling and storage

Storage Temperature

Store between 40-100F (4-38C).

Handling and Storage Precautions

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build—up of vapors by opening all windows and doors to achieve cross—ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|-------------------|--------------|---|
| 0001333-86-4 | Carbon black | OSHA | 3.5 mg/m3 TWA |
| | | ACGIH | 3.5 mg/m3 TWA |
| | | | 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as1750 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 3.5 mg/m3 TWA |
| | | Mexico | 3.5 mg/m3 TWA7 mg/m3 STEL |
| | | Brazil | No Established Limit |
| 0007631-86-9 | Silica, amorphous | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | 6 mg/m3 TWA3000 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0013463-67-7 | Titanium dioxide | OSHA | 15 mg/m3 TWA (total dust) |
| | | ACGIH | 10 mg/m3 TWA |
| | | NIOSH | 5000 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 10 mg/m3 TWA (total dust) |
| | | Mexico | 10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti) |
| | | Brazil | No Established Limit |

NCA669_A1

| 0021645-51-2 | Aluminum hydroxide | OSHA | No Established Limit |
|--------------|-------------------------------|-------------------|-----------------------|
| 0021010 01 2 | Alammam nyaroxide | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0025095 00 9 | Reaction product of | OSHA | No Established Limit |
| | epichlorohydrin & bisphenol A | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | | No Established Limit |
| | | Supplier OHSA, | No Established Limit |
| | | CAN | INO Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| | PHENOL, POLYMER WITH | OSHA | No Established Limit |
| | FORMALDEHYDE, GLYCIDYL | ACGIH | No Established Limit |
| | ETHER | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0068609-97-2 | Oxirane, | OSHA | No Established Limit |
| | mono[(C12-14-alkyloxy)methyl] | ACGIH | No Established Limit |
| | derivs. | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 14807–96–6* | Talc (*non-asbestiform) | OSHA | No Established Limit |
| | , | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |

Health Data

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|------------------------|
| 0001333-86-4 | Carbon black | NIOSH | Lung cardiovascular |
| 0007631-86-9 | Silica, amorphous | NIOSH | No Established Limit |
| 0013463-67-7 | Titanium dioxide | NIOSH | Lung tumors in animals |
| 0021645-51-2 | Aluminum hydroxide | NIOSH | No Established Limit |
| | Reaction product of epichlorohydrin & bisphenol A | NIOSH | No Established Limit |
| 0028064-14-4 | PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER | NIOSH | No Established Limit |
| | Oxirane, mono[(C12–14–alkyloxy)methyl] derivs. | NIOSH | No Established Limit |
| 14807–96–6* | Talc (*non-asbestiform) | NIOSH | No Established Limit |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|--------------|--------|------------------------|
| 0001333-86-4 | Carbon black | OSHA | Select Carcinogen: Yes |
| | | | • |

| 1 | 1 | NTP | Known: No; Suspected: No |
|--------------|---|------|--|
| | | IARC | · ' |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0007631-86-9 | Silica, amorphous | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0021645-51-2 | Aluminum hydroxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| | Reaction product of epichlorohydrin & bisphenol A | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0028064-14-4 | PHENOL, POLYMER WITH | OSHA | Select Carcinogen: No |
| | FORMALDEHYDE, GLYCIDYL ETHER | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0068609-97-2 | l | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 14807-96-6* | (, | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Skin

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Other Work Practices

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Physical State Liquid Coloured рΗ No Established Limit

Specific Gravity 1.47 Boiling Point F 220

Vapor Density Heavier than air

VOC % Refer to the Technical Data Sheet or label where information is available.

Evaporation Rate Slower than ether

10. Stability and reactivity

This product is stable and hazardous polymerization will not occur. Not sensitive to General

mechanical impact. Excessive heat and fumes generation can occur if improperly

handled.

Incompatible Materials Strong oxidizing agents.

May produce hazardous fumes when heated to decomposition as in welding. Fumes Hazardous

Decompostion may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LD50, mg/L/4hr |
|---|----------------------------------|-------------------------------------|---------------------------------------|
| Carbon black – (0001333–86–4) | 15,400.00, Rat – Category: NA | 3,000.00, Rabbit – Category: 5 | |
| Silica, amorphous – (0007631–86–9) | 5,000.00, Rat – Category: 5 | 2,000.00, Rabbit – Category: 4 | |
| Titanium dioxide – (0013463–67–7) | 10,000.00, Rat – Category: NA | 10,000.00, Rabbit - Category: NA | 6,082.00, Rat – Category: NA |
| Aluminum hydroxide – (0021645–51–2) | 5,000.00, Rat – Category: 5 | | |
| Reaction product of epichlorohydrin & bisphenol A – (0025085–99–8) | | | |
| PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER – (0028064–14–4) | | | |
| Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. – (0068609-97-2) | 17,100.00, Rat – Category: NA | | |
| Talc (*non-asbestiform) - (14807-96-6*) | | | |

General NOTICE: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8

and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation) **DOT Proper Shipping** PAINT OR PAINT IMDG Proper Shipping PAINT OR PAINT Name

RELATED MATERIAL, RELATED MATERIAL, Name NMFC 149980

NMFC 149980

IMDG Hazard Class Not Regulated

DOT Hazard Class UN / NA Number UN / NA Number Not Regulated Not Regulated

DOT Packing Group Not Regulated IMDG Packing Group Not Regulated

CERCLA/DOT RQ Not Applicable gal. / System Reference 9

Not Applicable lbs. Code

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only

selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be

listed on the TSCA Inventory.

WHMIS Classification No Established Limit

DOT Marine Pollutants (10%):

(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%):

(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous (>.1%):

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%):

(No Product Ingredients Listed)

Mass RTK Substances (>1%):

Silica, amorphous

Titanium dioxide

Mass Extraordinarily Haz Sub (>.01%):

(No Product Ingredients Listed)

Penn RTK Substances (>1%):

Silica, amorphous

Titanium dioxide

Penn Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

Rhode Island Hazardous Substances (>.1%):

Carbon black

Magnesium carbonate

Titanium dioxide

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Titanium dioxide

N.J. Special Hazardous Substances (>.01%):

(No Product Ingredients Listed)

Carbon black

Benzene, ethyl-

Isobutyl alcohol

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%):

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0%):

Carbon black

Benzene, ethyl-

Quartz

Proposition 65 – Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 – Developmental Toxins (>0%):

(No Product Ingredients Listed)

Risk Phrases:

R43: May cause sensitisation by skin contact.

NCA669_A1

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.