

SAFETY DATA SHEET

INTERPLUS 770 PART B

Section 1. Chemical product and company identification

GHS product identifier : INTERPLUS 770 PART B

Product code : EPA779

Relevant identified uses of the substance or mixture and uses advised against

Identified us	es	
Professional application of coatings and inks		
Uses advised against	Reason	
All Other Uses		

Supplier's details : International Farg AB

Holmedalen 3

Aspereds Industriomrade SE-424 22 Angered

Sweden

Tel: +46 (0) 31 928500 Fax: +46 (0) 31 928530

Emergency telephone number (with hours of

operation)

: +46 8 33 12 31

National advisory body/ : +7 343 229 98 57

Poison Centre (For use only

by licensed medical professionals.)

e-mail address of person responsible for this SDS

: sdsfellinguk@akzonobel.com

Akzo Nobel N.V., International Paint Ltd., 1990020, St. Petersburg, Russia

Tel: +7 812 747 30 52 Fax: +7 812 747 30 51

Section 2. Hazards identification

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 5 SKIN CORROSION/IRRITATION - Category 1B

SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION (Fertility) - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2

ACUTE AQUATIC HAZARD - Category 3 LONG-TERM AQUATIC HAZARD - Category 3

GHS label elements

Date of issue/Date of revision : 01/06/2017

Version : 3 1/14



Section 2. Hazards identification

Hazard pictograms









Signal word : Danger

Hazard statements : Harmful if swallowed.

May be harmful in contact with skin.

Causes severe skin burns and eve damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions

> have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid release to the environment. Avoid breathing vapour. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed

out of the workplace.

: IF exposed or concerned: Get medical attention. IF INHALED: Remove person to Response

> fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician.

Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water or shower.

Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately

call a POISON CENTER or physician.

: Store locked up. **Storage**

: Dispose of contents and container in accordance with all local, regional, national Disposal

and international regulations.

Supplemental label

elements

: Wear appropriate respirator when ventilation is inadequate.

Other hazards which do not : None known.

result in classification

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS number	Classification
benzyl alcohol	≥25 - ≤50	100-51-6	Acute Tox. 4, H302 Acute Tox. 4, H332
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	≥10 - ≤25	2855-13-2	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 3, H402
4-tert-butylphenol	≥10 - ≤25	98-54-4	Aquatic Chronic 3, H412 Skin Irrit. 2, H315 Eye Dam. 1, H318

Date of issue/Date of revision

Version: 3

: 01/06/2017

AkzoNobel

2/14



Section 3. Composition/information on ingredients

			Repr. 2, H361 (Fertility)
m-phenylenebis(methylamine)	≤10	1477-55-0	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
trimethylhexane-1,6-diamine	≤3	25620-58-0	Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
nonylphenol	<2.5	25154-52-3	Acute Tox. 4, H302 Acute Tox. 5, H313 Skin Corr. 1B, H314 Eye Irrit. 2A, H319 Repr. 2, H361fd (Fertility and Unborn child) Aquatic Acute 1, H400 Aquatic Chronic 1, H410

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision Version : 3 : 01/06/2017

AkzoNobel



Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May give off gas, vapour or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

Skin contact: Causes severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing

thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Date of issue/Date of revision Version : 3 : 01/06/2017

AkzoNobel

4/14



Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision Version: 3



Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Vapours are heavier than air and may spread along floors. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
benzyl alcohol	PO Мин3драСоц ПДК (Russian Federation, 9/2011). CEIL: 5 mg/m³ Form: vapor and/or gases
4-tert-butylphenol	PO МинЗдраСоц ПДК (Russian Federation, 9/2011).
m-phenylenebis(methylamine)	TWA: 0.4 mg/m³ 8 hours. Form: Aerosol CEIL: 1 mg/m³ Form: Aerosol ACGIH TLV (United States, 3/2015). Absorbed through skin. C: 0.1 mg/m³

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date of revision Version: 3



Section 8. Exposure controls/personal protection

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/ puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Colourless.

Odour : Amine-like.

Odour threshold : Not available.

pH : Not applicable.

Melting point : Not available.

Boiling point : Lowest known value: 205.3°C (401.5°F) (benzyl alcohol).

Flash point : Closed cup: 101°C (213.8°F)

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive

(flammable) limits

: Greatest known range: Lower: 1.3% Upper: 13% (benzyl alcohol)

Vapour pressure : Not available.
Vapour density : Not available.

Relative density : 1.02

Solubility : Insoluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

Version: 3

: Not available.

Auto-ignition temperature : Not available.

Date of issue/Date of revision

: 01/06/2017

7/14 AkzoNobel



Section 9. Physical and chemical properties

Decomposition temperature: Not available.

Viscosity : Kinematic (room temperature): 372 mm²/s (372 cSt)

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
benzyl alcohol	LC50 Inhalation Vapour	Rat	>4178 mg/l	4 hours
,	LD50 Dermal	Rabbit	2000 mg/kg	_
	LD50 Oral	Rat	1620 mg/kg	_
4-tert-butylphenol	LD50 Oral	Mouse	1030 mg/kg	_
m-phenylenebis (methylamine)	LD50 Dermal	Rabbit	2 g/kg	-
,	LD50 Oral	Rat	930 mg/kg	_
nonylphenol	LD50 Dermal	Rabbit	2033 mg/kg	_
• •	LD50 Oral	Rat	580 mg/kg	_

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
benzyl alcohol	Skin - Mild irritant	Man	-	48 hours 16 milligrams	-
	Skin - Moderate irritant	Pig	-	100 Percent	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
4-tert-butylphenol	Eyes - Severe irritant	Rabbit	-	24 hours 50 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	10 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	4 hours 500 milligrams	-
m-phenylenebis (methylamine)	Eyes - Severe irritant	Rabbit	-	24 hours 50 Micrograms	-
	Skin - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
nonylphenol	Skin - Moderate irritant	Rabbit	-	500 milligrams	-

Sensitisation

Not available.

Date of issue/Date of revision Version : 3 : 01/06/2017

AkzoNobel

8/14



Section 11. Toxicological information

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes: Not available.

of exposure

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May give off gas, vapour or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

Skin contact Causes severe burns. May be harmful in contact with skin. May cause an allergic

skin reaction.

: Harmful if swallowed. May cause burns to mouth, throat and stomach. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : Adverse symptoms may include the following:

headache

drowsiness/fatigue dizziness/vertigo muscle weakness unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Date of issue/Date of revision Version: 3



Section 11. Toxicological information

Ingestion: Adverse symptoms may include the following:

stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity: Suspected of damaging the unborn child.

Developmental effects: No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	847.9 mg/kg
Dermal	4761.6 mg/kg
Inhalation (vapours)	36.58 mg/l
Inhalation (dusts and mists)	27.91 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
3-aminomethyl-3,5, 5-trimethylcyclohexylamine	Acute EC50 17.4 to 21.5 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
4-tert-butylphenol	Acute LC50 6.9 mg/l Fresh water Chronic NOEC 2.3 mg/l Fresh water	Fish - Cyprinus carpio - Adult Fish - Cyprinus carpio - Adult	96 hours 28 days
nonylphenol	Acute EC50 109 μg/l Fresh water	Fish - Oncorhynchus mykiss - Fingerling	96 hours
	Acute LC50 0.18 mg/l Fresh water Acute LC50 135 μg/l Fresh water	Daphnia - Daphnia magna Fish - Pimephales promelas	48 hours 96 hours
	Chronic NOEC 694 μg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Chronic NOEC 901 µg/l Fresh water	Aquatic plants - Lemna minor	96 hours

Persistence and degradability

Date of issue/Date of revision : 01/06/2017

Version: 3



Section 12. Ecological information

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
benzyl alcohol	0.87	-	low
3-aminomethyl-3,5,	0.99	-	low
5-trimethylcyclohexylamine			
4-tert-butylphenol	3	67.608297539	low
m-phenylenebis	0.18	2.691534803	low
(methylamine)			
nonylphenol	3.28	154.881661891	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	ADR/RID	IMDG	IATA
UN number	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	Paint
Transport hazard class(es)	8	8	8
Packing group	II	II	II
Environmental hazards	No.	No.	No.

Date of issue/Date of revision Version : 3 : 01/06/2017

AkzoNobel



Section 14. Transport information

Additional	Hazard identification	Emergency schedules	Passenger and Cargo Aircraft
information	<u>number</u>	(EmS)	Quantity limitation: 1 L
	80	F-A, S-B	Packaging instructions: 851
			Cargo Aircraft Only Quantity
	Limited quantity	Special provisions	limitation: 30 L
	1 L	163	Packaging instructions: 855
			<u>Limited Quantities -</u>
	Special provisions		Passenger Aircraft Quantity
	163		limitation: 0.5 L
			Packaging instructions: Y840
	Tunnel code		
	(E)		Special provisions
			A3, A72, A803

IMDG Code Segregation

group

: Not applicable.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

: No known specific national and/or regional regulations applicable to this product (including its ingredients).

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

References : STATE STANDARD OF RUSSIAN FEDERATION No. 19433-88 'Hazardous Cargo.

Classification and Labelling'

Labour Code of the Russian Federation No. 197-FZ of 30 December 2001

Section 16. Other information

Justification

Date of issue/Date of revision : 01/06/2017 Version: 3 12/14



Section 16. Other information

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
ACUTE TOXICITY (dermal) - Category 5	Calculation method
SKIN CORROSION/IRRITATION - Category 1B	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 2	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
ACUTE AQUATIC HAZARD - Category 3	Calculation method
LONG-TERM AQUATIC HAZARD - Category 3	Calculation method

History

Date of printing : 13/07/2017

Date of issue/Date of : 01/06/2017

revision

Date of previous issue : 08/06/2016

Version : 3

Key to abbreviations : ADN = European Provisions concerning the International Carriage of Dangerous

Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

UN = United Nations

References : Not available.

▼ Indicates information that has changed from previously issued version.

Notice to reader

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

Date of issue/Date of revision Version : 3 : 01/06/2017

AkzoNobel



Section 16. Other information

Date of issue/Date of revision Version : 3