

**Safety Data Sheet**
**EA9E05 INTERZONE 954 INTL. ORANGE LC PART A**
**Version Number 1 Revision Date 11/27/13**
**1. Product and company identification**

<b>1.1. Product identifier</b>	INTERZONE 954 INTL. ORANGE LC PART A
Product Code	EA9E05
<b>1.2. Relevant identified uses of the substance or mixture and uses advised against</b>	
Intended use	Refer Technical Data Sheet. For professional use only.
Application Method	Refer Technical Data Sheet.
<b>1.3. Details of the supplier of the safety data sheet</b>	
<b>Manufacturer</b>	PT. International Paint Indonesia Cikarang Industrial Estate Jl. Jababeka Raya Blok E 9-11 17530, Cikarang, Indonesia
<b>Telephone No.</b>	021 8934270
<b>Fax No.</b>	021 8934275
<b>1.4. Emergency telephone number</b>	021 8934270
<b>For Poisons Advice telephone</b>	For Advice to Doctors & Hospitals only

**2. Hazard identification of the product**
**2.1. Classification of the substance or mixture**
**2.2. Label elements**

Using the Toxicity Data listed in section 11 &amp; 12 the product is labelled as follows.

**[Prevention]:**
**[Response]:**
**[Storage]:**
**[Disposal]:**
**2.3. Other hazards**
**3. Composition/information on ingredients**

This product contains the following hazardous substances.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Epoxy Resin CAS Number: Not Available	10-25	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]

Silicon dioxide (vitreous) CAS Number: 0060676-86-0	10-25		[1]
Xylene CAS Number: 0001330-20-7	2.5-10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]
C.I. pigment red 104 CAS Number: 0012656-85-8	2.5-10	Carc. 1B;H350 Repr. 1A;H360Df STOT RE 2;H373 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Petroleum Resin CAS Number: 0064742-16-1	2.5-10		[1]
Ethyl Benzene CAS Number: 0000100-41-4	1-2.5	Flam. Liq. 2;H225 Acute Tox. 4;H332	[1][2]
Lead chromate C.I. Yellow 34 CAS Number: 0001344-37-2	1-2.5	Carc. 1B;H350 Repr. 1A;H360Df STOT RE 2;H373 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
3-Glycidyloxypropyl-trimethoxysilane CAS Number: 0002530-83-8	1-2.5	Eye Dam. 1;H318	[1]
Methyl isobutyl ketone CAS Number: 0000108-10-1	1-2.5	Flam. Liq. 2;H225 Acute Tox. 4;H332 Eye Irrit. 2;H319 STOT SE 3;H335	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the Hazard (H) phrases are shown in Section 16.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

#### Inhalation

#### Skin Contact

#### Eye Contact

#### Ingestion

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## 5. Fire-fighting measures

### 5.1. Extinguishing media

### 5.2. Special hazards arising from the substance or mixture

### 5.3. Advice for fire-fighters

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Handling

#### In Storage

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.3. Specific end use(s)

## 8. Exposure controls and personal protection

### 8.1. Control parameters

Exposure standards are those provided by the ACGIH (American Conference of Government Industrial Hygienists).

Material	Short term (15 min. ave)		Long term (8hr time weighted average)		Comments
	ppm	mg/m <sup>3</sup>	ppm	mg/M3	
Ethyl Benzene	125	543	100	434	
Methyl isobutyl ketone	75	307	50	205	
Xylene	150	651	100	434	

Key to notification

(P) Peak exposure limit

(R) Suppliers Recommended Limit

(Sk) There is a risk of absorption through unbroken skin

(Sen) Sensitiser

(Cat1) Category 1 - established human carcinogen

(Cat2) Category 2 - probable human carcinogen

(Cat3) Category 3 - substances suspected of having carcinogenic potential

### DNEL/PNEC values

### 8.2. Exposure controls

#### Eye Protection

#### Skin Protection

#### Other

#### Respiratory Protection

#### Thermal hazards

## 9. Physical and chemical properties

Colour

Odour

Odour threshold

pH

Melting point / freezing point (°C)

Initial boiling point and boiling range (°C)

Flash Point (C)

Evaporation rate (Ether = 1)

Flammability (solid, gas)

Upper/lower flammability or explosive limits Lower Explosive Limit: 1.1 ( Xylene )  
Upper Explosive Limit: 6.6 ( Xylene )

Vapour pressure (Pa)

Vapour Density

Specific Gravity 0.00

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Autoignition temperature ( )

Decomposition temperature

Viscosity (cSt)

### 9.2. Other information

No further information

## 10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

## 11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
3-Glycidyoxypropyl-trimethoxysilane - (2530-83-8)	8,030.00, Rat	4,248.00, Rabbit	Not Available	5.30, Rat
C.I. pigment red 104 - (12656-85-8)	5,000.00, Rat	Not Available	Not Available	Not Available
Epoxy Resin - (Not Available)	2,000.00, Rat	2,000.00, Rabbit	Not Available	Not Available
Ethyl Benzene - (100-41-4)	3,500.00, Rat	15,433.00, Rabbit	17.20, Rat	Not Available
Lead chromate C.I. Yellow 34 - (1344-37-2)	5,000.00, Rat	Not Available	Not Available	Not Available
Methyl isobutyl ketone - (108-10-1)	2,080.00, Rat	16,000.00, Rabbit	Not Available	Not Available
Petroleum Resin - (64742-16-1)	2,000.00, Mammal	Not Available	Not Available	Not Available

Silicon dioxide (vitreous) - (60676-86-0)	Not Available	Not Available	Not Available	Not Available
Xylene - (1330-20-7)	4,299.00, Rat	1,548.00, Rabbit	Not Available	20.00, Rat

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Epoxy Resin - (Not Available)	3.10, Pimephales promelas	1.40, Daphnia magna	Not Available
Silicon dioxide (vitreous) - (60676-86-0)	Not Available	Not Available	Not Available
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
C.I. pigment red 104 - (12656-85-8)	2,500.00, Leuciscus idus	Not Available	Not Available
Petroleum Resin - (64742-16-1)	Not Available	Not Available	Not Available
Ethyl Benzene - (100-41-4)	4.20, Oncorhynchus mykiss	2.93, Daphnia magna	3.60 (96 hr), Pseudokirchneriella subcapitata
Lead chromate C.I. Yellow 34 - (1344-37-2)	10,000.00, Leuciscus idus	Not Available	Not Available
3-Glycidioxypropyl-trimethoxysilane - (2530-83-8)	55.00, Cyprinus carpio	473.00, Daphnia magna	255.00 (72 hr), Scenedesmus subspicatus
Methyl isobutyl ketone - (108-10-1)	505.00, Pimephales promelas	1,550.00, Daphnia magna	980.00 (48 hr), Scenedesmus subspicatus

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

## 13. Disposal considerations

### 13.1. Waste treatment methods

## 14. Transport information

### 14.1. UN number

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

#### Road and Rail Transport

**IMDG**                      **Class/Div**                      **Sub Class**  
reference :

**Ems**

**ICAO/IATA**              **Class**                      **Sub Class**

### 14.4. Packing group

### 14.5. Environmental hazards

**Road and Rail** Environmentally Hazardous:  
**Transport**

**IMDG**                      **Marine Pollutant:**  
reference :

### 14.6. Special precautions for user

No further information

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

## 15. Regulatory information

The product and all its components complies with these local regulations:

NICNAS - Australia  
EPA - New Zealand

## 16. Other information

The information on this SDS is based upon the present state of our knowledge and on current law. The product should not be used for purposes other than shown in the product data sheet without first obtaining written advice.

It is always the responsibility of the user to take all necessary steps to meet the demands of applicable legislation.

The information in this Safety Data Sheet is required according to legislation.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H350 May cause cancer.

H360Df May damage the unborn child. Suspected of damaging fertility.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

**This SDS is valid for 5 years from the revised date on page 1.  
The revision date is in American format (e.g. MM/DD/YY).**

End of document



All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Akzo Nobel however makes no warranty as to the accuracy of and/or sufficiency of such information.