### Material Safety Data Sheet CEILCOTE 660 HV COROCRETE LT GREY PTA

Bulk Sales Reference No.:

MSDS Revision Date: MSDS Revision Number: Sales Order: {SalesOrd} NCA669 05/16/2011 A1-2

# X.International.

1. Identification of the preparation and company			
Product Identity	CEILCOTE 660 HV COROCRETE LT GREY PTA		
Bulk Sales Reference No.	NCA669		
Company Name	International Paint LLC		
	6001 Antoine Drive		
	Houston Texas 77091		
Emergency			
CHEMTREC (USA)	(800) 424–9300		
International Paint	(713) 682–1711		
Poison Control Center	(800) 854–6813		
Customer Service			
International Paint	(800) 589–1267		
Fax No.	(800) 631–7481		

2. Hazard identification of the product



arning	

	vvain	
GHS Classification;		
Item	Category	Hazard
Flammability	4	Combustible liquid
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	1	May cause allergic reaction.
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	Not applicable
	2	Not applicable
	3	respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	lung
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects

Carcinogenicity	Not classified	Not applicable
Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S24: Avoid contact with skin.

S28: After contact with skin, wash immediately with plenty of soap and water.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.					
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.					
Eyes	Causes severe eye irritation. Avoid contact with eyes.					
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.					
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.					
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.					
HMIS Rating	Health: 1* Flammability: 1 Reactivity: 0 PPE: X					

3. Composition/information on ingredients				
Ingredient	CAS No.	Percent		
Carbon black	0001333-86-4	0.10 – 1.0		
Silica, amorphous	0007631-86-9	1.0 – 10		
Titanium dioxide	0013463-67-7	10 – 25		
Aluminum hydroxide	0021645-51-2	1.0 – 10		
Reaction product of epichlorohydrin & bisphenol A	0025085-99-8	25 – 50		
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	0028064-14-4	10 – 25		
Oxirane, mono[(C12–14–alkyloxy)methyl] derivs.	0068609–97–2	1.0 – 10		
Talc (*non–asbestiform)	14807–96–6*	10 – 25		

4. First aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.
	5. Fire-fighting measures

		NCA669_A1
Flash Point		F: 200 C: 93
Lower Explosive Limit (LEL)1 (%vol in air) atERG Guide No.159		1 (%vol in air) at Normal Atmospheric Temp and Pressure 159
		6. Accidental release measures
Spill Response Procedures	immediate do so with areas. Ab	E ALL IGNITION SOURCES (no smoking, flares, sparks or flames in e area). Do not touch or walk through spilled material. Stop leak if you can out risk. Prevent entry into waterways, sewers, basements or confined sorb or cover with dry earth, sand, or other non-combustible material and o containers. LARGE SPILLS: Dike far ahead of liquid spill to contain

	released material and runoff from fire control.
Public Safety	CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.
ERG Guide No.	159

7. Handling and storage

Storage TemperatureStore between 40–100F (4–38C).Handling and Storage<br/>PrecautionsKeep away from heat, sparks and flame. Do not smoke. Extinguish all flames and<br/>pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition<br/>during use and until all vapors are gone. Vapors may cause flash fire or ignite<br/>explosively. Prevent build-up of vapors by opening all windows and doors to achieve<br/>cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated<br/>contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection Exposure CAS No. Ingredient Source Value 0001333–86–4 Carbon black OSHA 3.5 mg/m3 TWA ACG<u>IH</u> 3.5 mg/m3 TWA NIOSH 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as1750 mg/m3 IDLH Supplier No Established Limit OHSA, 3.5 mg/m3 TWA CAN Me<u>xico</u> 3.5 mg/m3 TWA7 mg/m3 STEL Brazil No Established Limit 0007631-86-9 Silica, amorphous OSHA No Established Limit ACGIH No Established Limit NIOSH 6 mg/m3 TWA3000 mg/m3 IDLH Supplier No Established Limit OHSA, No Established Limit CAN Mexico No Established Limit Brazil No Established Limit 0013463–67–7 Titanium dioxide OSHA 15 mg/m3 TWA (total dust) ACGIH 10 mg/m3 TWA NIOSH 5000 mg/m3 IDLH Supplier No Established Limit OHSA, 10 mg/m3 TWA (total dust) CAN Mexico 10 mg/m3 TWA (as Ti)20 mg/m3 STEL (as Ti) Brazil No Established Limit

3/8

0021645-51-2	Aluminum hydroxide	OSHA	No Established Limit
0021040 01 2		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA,	No Established Limit
		CAN	
		Mexico	No Established Limit
		Brazil	No Established Limit
0025085–99–8	Reaction product of	OSHA	No Established Limit
	epichlorohydrin & bisphenol A	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0028064-14-4	PHENOL, POLYMER WITH	OSHA	No Established Limit
	FORMALDEHYDE, GLYCIDYL	ACGIH	No Established Limit
	ETHER	NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0068609–97–2	Oxirane,	OSHA	No Established Limit
	mono[(C12-14-alkyloxy)methyl]	ACGIH	No Established Limit
	derivs.	NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
14807–96–6*	Talc (*non-asbestiform)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data				
CAS No.	Ingredient	Source	Value	
0001333-86-4	Carbon black	NIOSH	Lung cardiovascular	
0007631-86-9	Silica, amorphous	NIOSH	No Established Limit	
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals	
0021645-51-2	Aluminum hydroxide	NIOSH	No Established Limit	
	Reaction product of epichlorohydrin & bisphenol A	NIOSH	No Established Limit	
0028064–14–4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	NIOSH	No Established Limit	
	Oxirane, mono[(C12–14–alkyloxy)methyl] derivs.	NIOSH	No Established Limit	
14807–96–6*	Talc (*non-asbestiform)	NIOSH	No Established Limit	

Carcinogen Data				
CAS No.	Ingredient	Source	Value	
0001333-86-4	Carbon black	OSHA	Select Carcinogen: Yes	

		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0007631-86-9	Silica, amorphous	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0013463–67–7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0021645–51–2	Aluminum hydroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025085–99–8		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0028064–14–4		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068609–97–2		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
14807–96–6*	Talc (*non-asbestiform)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site–specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.
	9. Physical and chemical properties

Physical State	Liquid Coloured
рН	No Established Limit
Specific Gravity	1.47
Boiling Point F	220
Vapor Density	Heavier than air
VOC %	Refer to the Technical Data Sheet or label where information is available.
Evaporation Rate	Slower than ether
	10. Stability and reactivity

General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
Incompatible Materials	Strong oxidizing agents.
Hazardous	May produce hazardous fumes when heated to decomposition as in welding. Fumes
Decompostion	may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information				
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	
Carbon black – (0001333–86–4)	15,400.00, Rat – Category: NA	3,000.00, Rabbit - Category: 5		
Silica, amorphous – (0007631–86–9)	5,000.00, Rat – Category: 5	2,000.00, Rabbit - Category: 4		
Titanium dioxide – (0013463–67–7)	10,000.00, Rat – Category: NA	10,000.00, Rabbit – Category: NA	6,082.00, Rat – Category: NA	
Aluminum hydroxide – (0021645–51–2)	5,000.00, Rat – Category: 5			
Reaction product of epichlorohydrin & bisphenol A – (0025085–99–8)				
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER – (0028064–14–4)				
Oxirane, mono[(C12–14–alkyloxy)methyl] derivs. – (0068609–97–2)	17,100.00, Rat – Category: NA			
Talc (*non–asbestiform) – (14807–96–6*)				

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

Not Defined

UN / NA Number

Not Regulated

General

12. Ecological information

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation) PAINT OR PAINT DOT Proper Shipping IMDG Proper Shipping PAINT OR PAINT RELATED MATERIAL, RELATED MATERIAL, Name Name NMFC 149980 NMFC 149980 DOT Hazard Class NR IMDG Hazard Class Not Regulated

UN / NA Number

Not Regulated

DOT Packing Group	Not Regulated	IMDG Packing Group	Not Regulated		
CERCLA/DOT RQ	Not Applicable gal. /	System Reference	9		
	Not Applicable lbs.	Code			
	15. Regulate	ory information			
Regulatory Overview	The regulatory data in	Section 15 is not intended to b	e all-inclusive. only		
selected regulations are represented. All ingredients of this product are on the TSCA (Toxic Substance Control Act) Inventory or are not require listed on the TSCA Inventory.					
WHMIS Classification					
DOT Marine Pollutants (No Product Ing					
DOT Severe Marine Po (No Product Ing	ollutants (1%):				
	nicals and RQs (>.1%) :				
EPCRA 302 Extremely (No Product Ing					
EPCRA 313 Toxic Che (No Product Ing					
Mass RTK Substances	s (>1%) :				
Silica, ar	morphous				
Titanium	dioxide				
Mass Extraordinarily H (No Product Ing					
Penn RTK Substances	s (>1%) :				
Silica, ar	norphous				
Titanium					
(No Product Ing					
Rhode Island Hazardo	ous Substances (>.1%) :				
Carbon b	olack				
Magnesi	um carbonate				
Titanium	dioxide				
RCRA Status: (No Product Ingr	redients Listed)				
N.J. RTK Substances					
Titanium					
	s Substances (>.01%) :				
Carbon b					
Benzene	e, ethyl–				
Isobutyl					
Xylenes	(o-, m-, p- isomers)				
N.J. Env. Hazardous S (No Product Ing	Substances (>.1%) :				
Proposition 65 - Carci	nogens (>0%):				
Carbon k	olack				
Benzene	₂, ethyl–				
Quartz					
Proposition 65 – Fema (No Product Ing	ale Repro Toxins (>0%): redients Listed)				
Proposition 65 – Male (No Product Ing					
Proposition 65 – Deve (No Product Ing	lopmental Toxins (>0%): redients Listed)				
Risk Phrases:					
1 113N 1 111 4353.					

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.