Material Safety Data Sheet DEVTHANE 359H BASE RED PART A

MSDS Revision Date:

Sales Order: {SalesOrd} DC359F9504 03/30/2012 A0–3 Bulk Sales Reference No.: MSDS Revision Number:

X.International.

1. Identif	ication of the preparation and company
Product Identity	DEVTHANE 359H BASE RED PART A
Bulk Sales Reference No.	DC359F9504
Company Name	International Paint LLC
	6001 Antoine Drive
	Houston Texas 77091
mergency	
HEMTREC (USA)	(800) 424–9300
ternational Paint	(713) 682–1711
Poison Control Center	(800) 854–6813
ustomer Service	
nternational Paint	(800) 589–1267
ax No.	(800) 631–7481

2. Hazard identification of the product



GHS Classification;

GHS Classification,		
Item	Category	Hazard
Flammability	3	Flammable liquid and vapor
Acute Toxicity (mouth)	Not classified	Not applicable
Acute Toxicity (skin)	Not classified	Not applicable
Acute Toxicity (inhalation)	Not classified	Not applicable
Acute Toxicity (ingestion)	Not classified	Not applicable
Skin corrosion/irritation	Not classified	Not applicable
Eye damage/irritation	Not classified	Not applicable
Sensitization (respiratory)	Not classified	Not applicable
Sensitization (skin)	Not classified	Not applicable
Germ toxicity	Not classified	Not applicable
Specific target organ systemic toxicity (single exposure)	1	central nerve system
	2	Not applicable
	3	narcotic effects, respiratory tract irritation
Specific target organ systemic Toxicity (repeated exposure)	1	auditory apparatus, central nerve system
	2	Not applicable
Aspiration hazard	Not classified	Not applicable
Harmfulness to aquatic Environment (acute)	3	Harmful to aquatic life.
Harmfulness to aquatic Environment (long term effect)	4	May cause harm to aquatic life with long lasting effects
Carcinogenicity	Not classified	Not applicable

Reproductive Toxicity	Not classified	Not applicable
Organic Peroxide	Not classified	Not applicable

Safety Phrases:

S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.				
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.				
Eyes	Causes severe eye irritation. Avoid contact with eyes.				
Skin	Causes skin irritation. May be harmful if absorbed through the skin.				
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.				
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.				
HMIS Rating	Health: 3 Flammability: 3 Reactivity: 0 PPE: X				

3. Composition/information on ingredients				
Ingredient	CAS No.	Percent		
Butanol	0000071-36-3	1.0 – 10		
Dicumyl peroxide	0000080-43-3	1.0 – 10		
Diisobutylketone	0000108-83-8	1.0 – 10		
Ethyl orthoformate	0000122-51-0	1.0 – 10		
BUTYL ACETATE	0000123-86-4	10 – 25		
BUTYL ACETATE	0000540-88-5	1.0 – 10		
BUTYL PEROXYBENZOATE	0000614-45-9	1.0 – 10		
Ethyl 3–ethoxypropionate	0000763-69-9	1.0 – 10		
Barium sulfate	0007727-43-7	10 – 25		
2-Heptanone, 4,6-dimethyl-	0019549-80-5	1.0 – 10		
Acetic acid, C6–8–branched alkyl esters	0090438-79-2	1.0 – 10		

	4. First aid measures			
General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.			
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.			
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.			
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.			
Ingestion	If swallowed, immediately contact Poison Control Center at 1–800–854–6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.			
	5. Fire-fighting measures			
Flash Point	F: 80 C: 27			
Lower Explosive Limit (LEL) ERG Guide No.	.7 (%vol in air) at Normal Atmospheric Temp and Pressure 128			

	6. Accidental release measures
Spill Response Procedures	ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.
Public Safety	CALL CHEMTREC at (800)–424–9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).
ERG Guide No.	128
	7. Handling and storage
Storage Temperature	Store between 40–100F (4–38C).
Handling and Storage Precautions	Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and clothing. Avoid prolonged or repeated contact with skin. Close container after each use. Wash thoroughly after handling.

8. Exposure controls and personal protection

CAS No.	Ingredient	Source	Value
0000071–36–3 But	anol	OSHA	100 ppm TWA; 300 mg/m3 TWA50 ppm Ceiling; 150 mg/m3 Ceiling
		ACGIH	20 ppm TWA
		NIOSH	50 ppm Ceiling; 150 mg/m3 Ceiling1400 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0000080-43-3 Dic	umyl peroxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000108–83–8 Diis	sobutylketone	OSHA	50 ppm TWA; 290 mg/m3 TWA
		ACGIH	25 ppm TWA
		NIOSH	25 ppm TWA; 150 mg/m3 TWA500 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA
		Mexico	25 ppm TWA; 145 mg/m3 TWA
		Brazil	No Established Limit
0000122–51–0 Eth	yl orthoformate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000123-86-4	BUTYL ACETATE	OSHA	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH	150 ppm TWA200 ppm STEL
		NIOSH	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	150 ppm TWA200 ppm STEL
		Mexico	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		Brazil	No Established Limit
0000540-88-5	BUTYL ACETATE	OSHA	200 ppm TWA; 950 mg/m3 TWA
		ACGIH	200 ppm TWA
		NIOSH	200 ppm TWA; 950 mg/m3 TWA1500 ppm IDLH (10% LEL)
		Supplier	No Established Limit
		OHSA, CAN	200 ppm TWA
		Mexico	200 ppm TWA; 950 mg/m3 TWA250 ppm STEL; 1190 mg/m3 STEL
		Brazil	No Established Limit
0000614–45–9	BUTYL PEROXYBENZOATE	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000763-69-9	Ethyl 3-ethoxypropionate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	50 ppm TWA; 300 mg/m3 TWA
		Mexico	No Established Limit
		Brazil	No Established Limit
0007727–43–7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m3 TWA (total dust)
		Mexico	No Established Limit
		Brazil	No Established Limit
0019549-80-5	2–Heptanone, 4,6–dimethyl–	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
			4
		Mexico	No Established Limit

		Brazil	No Established Limit
0090438-79-2 Acetic acid, C6-8-branched	OSHA	No Established Limit	
	alkyl esters	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
	OHSA, CAN	No Established Limit	
		Mexico	No Established Limit
		Brazil	No Established Limit

	Health Data				
CAS No.	Ingredient	Source	Value		
0000071–36–3	Butanol		Eye and mucous membrane irritation CNS depression		
0000080-43-3	Dicumyl peroxide	NIOSH	No Established Limit		
0000108-83-8	Diisobutylketone	NIOSH	Irritation; liver kidney		
0000122-51-0	Ethyl orthoformate	NIOSH	No Established Limit		
0000123–86–4	BUTYL ACETATE		Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals		
0000540-88-5	BUTYL ACETATE	NIOSH	Eye and throat irritation CNS depression		
0000614-45-9	BUTYL PEROXYBENZOATE	NIOSH	No Established Limit		
0000763-69-9	Ethyl 3–ethoxypropionate	NIOSH	No Established Limit		
0007727-43-7	Barium sulfate	NIOSH	Eye nose		
0019549-80-5	2-Heptanone, 4,6-dimethyl-	NIOSH	No Established Limit		
0090438-79-2	Acetic acid, C6–8–branched alkyl esters	NIOSH	No Established Limit		

CAS No.	Ingredient	Source	Value
0000071-36-3	Butanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000080-43-3	Dicumyl peroxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000108-83-8	Diisobutylketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000122-51-0	Ethyl orthoformate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000123-86-4	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000540-88-5	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000614-45-9	PEROXYBENZOATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No Group 4: No;
0000763-69-9	Ethyl 3–ethoxypropionate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0007727-43-7		OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0019549–80–5	4,6-dimethyl-	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
	C6–8–branched alkyl	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1–800–243–4630, in Canada call 1–800–267–4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties				
Physical State	Liquid Coloured			
рН	No Established Limit			
Specific Gravity	1.09			
Boiling Point F	t F 208			
Vapor Density	apor Density Heavier than air			
VOC %	Refer to the Technical Data Sheet or label where information is available.			
Evaporation Rate	Slower than ether			
10. Stability and reactivity				
General	This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.			
Incompatible Materials Hazardous Decompostion	Strong oxidizing agents. May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.			

11. Toxicological information					
Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr		
Butanol – (0000071–36–3)	790.00, Rat – Category: 4	3,400.00, Rabbit - Category: 5	17.70, Rat – Category: 4		
Dicumyl peroxide – (0000080–43–3)	4,000.00, Rat – Category: 5				
Diisobutylketone – (0000108–83–8)	5,750.00, Rat – Category: NA	16,000.00, Rabbit – Category: NA			
Ethyl orthoformate – (0000122–51–0)	7,060.00, Rat – Category: NA				
BUTYL ACETATE – (0000123–86–4)	10,768.00, Rat – Category: NA	17,600.00, Rabbit – Category: NA			
BUTYL ACETATE – (0000540–88–5)	4,100.00, Rat – Category: 5	2,000.00, Rabbit - Category: 4			
BUTYL PEROXYBENZOATE – (0000614–45–9)	1,012.00, Rat – Category: 4				
Ethyl 3-ethoxypropionate - (0000763-69-9)	3,200.00, Rat – Category: 5				
Barium sulfate – (0007727–43–7)					
2-Heptanone, 4,6-dimethyl (0019549-80-5)					
Acetic acid, C6–8–branched alkyl esters – (0090438–79–2)					

General

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

12. Ecological information

Not Defined

No additional information provided for this product. See Sections 8 and 11 for chemical specific data.

13. Disposal considerations

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information							
DOT (Domestic Su	rface Transportation)	IMO / IMDG (Oce	IMO / IMDG (Ocean Transportation)				
DOT Proper Shipping PAINT IMDG Proper Shipping Name Name		PAINT					
DOT Hazard Class	DOT Hazard Class 3 IMDG Hazard Class		3 – Flammable and Combustible liquid				
UN / NA Number UN 1263		UN / NA Number	UN 1263				
DOT Packing Group III		IMDG Packing Group	111				
CERCLA/DOT RQ	4291 gal. / 38941 lbs.	System Reference Code	1				
15. Regulatory information							
Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.							
WHMIS Classification	B2:D2B						

DOT Marine Pollutants (10%): (No Product Ingredients Listed) DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) EPCRA 311/312 Chemicals and RQs (>.1%) : BUTYL ACETATE (5000 lb final RQ; 2270 kg final RQ) Butanol (5000 lb final RQ; 2270 kg final RQ) BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)) Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ) EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed) EPCRA 313 Toxic Chemicals (>.1%) : Butanol Xylenes (o-, m-, p- isomers) Mass RTK Substances (>1%) : Barium sulfate Diisobutylketone Ethyl orthoformate **BUTYL ACETATE Butanol BUTYL ACETATE** BUTYL PEROXYBENZOATE Mass Extraordinarily Haz Sub (>.01%) : (No Product Ingredients Listed) Penn RTK Substances (>1%) : Barium sulfate Diisobutylketone Ethyl orthoformate **BUTYL ACETATE** Butanol **BUTYL ACETATE** BUTYL PEROXYBENZOATE Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Rhode Island Hazardous Substances (>.1%) : Diisobutylketone Kaolin **BUTYL ACETATE Butanol BUTYL ACETATE** BUTYL PEROXYBENZOATE Xylenes (o-, m-, p- isomers) **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : Barium sulfate Diisobutylketone Ethyl orthoformate **BUTYL ACETATE** Butanol **BUTYL ACETATE** BUTYL PEROXYBENZOATE N.J. Special Hazardous Substances (>.01%) : Benzene, ethyl-Ethyl orthoformate **BUTYL ACETATE Butanol**

BUTYL ACETATE BUTYL PEROXYBENZOATE Xylenes (o-, m-, p- isomers) N.J. Env. Hazardous Substances (>.1%) : Butanol Xylenes (o-, m-, p- isomers) Proposition 65 – Carcinogens (>0%): Benzene, ethyl-Formaldehyde Quartz Proposition 65 – Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 – Developmental Toxins (>0%): (No Product Ingredients Listed) **Risk Phrases:**

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.