

SAFETY DATA SHEET

CEILCOTE 2000 FLAKELINE GREY PART A

Section 1. Identification

GHS product identifier : CEILCOTE 2000 FLAKELINE GREY PART A
 Product code : NCA019

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Professional application of coatings and inks	
Uses advised against	Reason
All Other Uses	

Supplier's details : International Paint (PTY) Ltd
 1 Paints Place
 Dickens Road
 Umbogintwini
 KZN 4120,
 South Africa
 Tel: +27 31 904 8000

 +27 31 904 8000 (24hr)

Emergency telephone number (with hours of operation) : 10177 (For use only by licensed medical professionals.)
 e-mail address of person responsible for this SDS : sdsfellinguk@akzonobel.com

Section 2. Hazards identification

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
 SKIN SENSITIZATION - Category 1
 GERM CELL MUTAGENICITY - Category 2
 LONG-TERM AQUATIC HAZARD - Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Causes serious eye irritation.
 Causes skin irritation.
 May cause an allergic skin reaction.
 Suspected of causing genetic defects.
 Toxic to aquatic life with long lasting effects.

Precautionary statements

Section 2. Hazards identification

- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid release to the environment. Avoid breathing vapour. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
- Response** : Collect spillage. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
- Storage** : Store locked up.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Wear appropriate respirator when ventilation is inadequate.
- Other hazards which do not result in classification** : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS number	Classification
Phenol, polymer with formaldehyde, glycidyl ether	≥50 - ≤75	28064-14-4	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
2,3-epoxypropyl o-tolyl ether	≤10	2210-79-9	Acute Tox. 5, H303 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	≤5	25068-38-6	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Section 4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
glass, oxide, chemicals	<p>ACGIH TLV (United States, 3/2015). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.</p>
Mica-group minerals	<p>DOL OEL (South Africa, 8/1995). TWA: 1 mg/m³ 8 hours. Form: Respirable dust TWA: 10 mg/m³ 8 hours. Form: total inhalable dust</p>
titanium dioxide	<p>DOL OEL (South Africa, 8/1995). TWA: 10 mg/m³ 8 hours. Form: Respirable dust TWA: 5 mg/m³ 8 hours. Form: total inhalable dust</p>

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Section 8. Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection : Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Grey.
Odour : Solvent.
Odour threshold : Not available.
pH : Not applicable.
Melting point : Not available.
Boiling point : Not available.
Flash point : Closed cup: 101°C (213.8°F)

Section 9. Physical and chemical properties

Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 1.29
Solubility	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 13966 mm ² /s (13966 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,3-epoxypropyl o-tolyl ether	LC50 Inhalation Dusts and mists	Rat	6090 mg/m ³	4 hours
	LD50 Oral	Rat	4 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,3-epoxypropyl o-tolyl ether reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	Skin - Severe irritant	Rabbit	-	24 hours 500 microliters	-
	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-

Section 11. Toxicological information

Sensitisation

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Section 11. Toxicological information

Not available.

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: Suspected of causing genetic defects.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	47961.6 mg/kg

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	-	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	2.64 to 3.78	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations







Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned

Section 13. Disposal considerations

or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	UN	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, polymer with formaldehyde, glycidyl ether, 2,3-epoxypropyl o-tolyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, polymer with formaldehyde, glycidyl ether, 2,3-epoxypropyl o-tolyl ether). Marine pollutant	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, polymer with formaldehyde, glycidyl ether, 2,3-epoxypropyl o-tolyl ether)
Transport hazard class(es)	9  	9  	9  
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

IMDG Code Segregation group : Not applicable.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Section 15. Regulatory information

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: <input checked="" type="checkbox"/> Not determined.
Canada	: <input checked="" type="checkbox"/> Not determined.
China	: Not determined.
Europe	: Not determined.
Japan	: <input checked="" type="checkbox"/> Japan inventory (ENCS): Not determined. Japan inventory (ISHL): Not determined.
Malaysia	: <input checked="" type="checkbox"/> Not determined.
New Zealand	: <input checked="" type="checkbox"/> Not determined.
Philippines	: <input checked="" type="checkbox"/> Not determined.
Republic of Korea	: Not determined.
Taiwan	: <input checked="" type="checkbox"/> Not determined.
Turkey	: <input checked="" type="checkbox"/> Not determined.
United States	: Not determined.

Section 16. Other information

Justification

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2A, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Muta. 2, H341	Calculation method
Aquatic Chronic 2, H411	Calculation method

History

Date of printing	: 31/05/2017
Date of issue/Date of revision	: 31/05/2017
Date of previous issue	: 10/06/2016
Version	: 3

Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations
-----------------------------	--

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

Section 16. Other information

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel