

Surface Cleaner & Degreaser

PRODUCT DESCRIPTION A concentrated water based cleaner low in odor, non-flammable and biodegradable.

INTENDED USES Devprep 88 is ideal for cleaning intact painted surfaces in preparation for repainting. It is also useful in cleaning rusted steel, galvanized metal, and masonry surfaces. It is particularly useful for cleaning dirty, greasy concrete floors, walls, machinery, and equipment in industrial and commercial environments.

Devprep 88 can also be used to clean aluminum, galvanized and other surfaces prior to painting. Also effective, prior to abrasive blasting or application of wetting primers, to remove grease, oil, chlorides or other contaminants.

PRACTICAL INFORMATION FOR DEVPREP 88

Color	Colorless
Gloss Level	Not applicable
Volume Solids	Not applicable
Typical Thickness	Not applicable
Theoretical Coverage	Not applicable
Practical Coverage	Not applicable
Method of Application	Brush, Roller, Mop, Low Pressure Spray

Drying Time

Temperature	Touch Dry	Hard Dry	Overcoating Interval with recommended topcoats	
			Minimum	Maximum
77°F (25°C)	*	*	*	*
* not applicable				

REGULATORY DATA Flash Point (Typical) 214°F (101°C)

Product Weight 8.6 lb/gal (1.03 kg/l)
VOC 0 g/lit (0.00 lb/US gal) calculated
 See Product Characteristics section for further details

Devprep® 88



Surface Cleaner & Degreaser

SURFACE PREPARATION Not applicable.

APPLICATION

Mixing Not applicable

Air Spray (Conventional) Suitable

Brush Suitable

Roller Suitable

Thinner Clean Water

Cleaner Clean Water

Work Stoppages Not applicable

Clean Up Not applicable

Devprep 88 may be reduced 2-3 times.

Surface Cleaner & Degreaser

PRODUCT CHARACTERISTICS

Advantages:

- Promotes adhesion as it cleans
- Powerful degreaser
- Solvent free
- Biodegradable
- Easy to apply, low odor
- May eliminate costly abrasive sweeping
- Contains no phosphates, halogens or alkali hydroxides
- Formulated without lead or mercury containing materials
- Dramatically improves recoatability of aged, painted surfaces

Devprep 88 dissolves and removes heavy accumulations of hard-to-remove dirt, oil and grease without the use of solvents. The exceptional cleaning and degreasing power of Devprep 88 exceeds that of conventional water-based degreasers.

When old, painted surfaces are made “super-clean” with Devprep 88, it promotes adhesion as it cleans. Sanding, solvent wiping, grit sweeping and roughing old painted surfaces may be eliminated.

For most applications, Devprep 88 can be reduced 2 or 3 times with fresh, clean water. Test cleaning a small area may be used to determine proper dilution levels and to ensure compatibility with the substrate. Adequate protective equipment and clothing such as rubber gloves and protective eyewear are recommended. Apply the solution with brush, roller, mop or low pressure spray. If surface is hot, wet before applying cleaner solution. Moderate scrubbing will aid in performance and speed of cleaning. Allow cleaner to remain for five to ten minutes, but do not allow the surface to dry. Rinse with large amounts of clean water. For large surfaces, rinsing with a power washer 1500psi (10 Mpa) minimum is recommended. A thorough rinsing is very important. All of the product must be removed. When completely removed, the surface will no longer foam when rinsed. Allow the surface to dry thoroughly before applying any coatings.

Devprep 88 must not be allowed to dry on the surface. Do not apply under freezing conditions. Do not apply to glass surfaces, metallic automobile finishes, aluminum surfaces which will remain unpainted or strong alkali sensitive painted surfaces. May dull glossy surfaces.

Do not discharge into natural waters. Rinse surrounding vegetation and/or cover at all times while cleaner is in use.

Note: VOC values are typical and are provided for guidance purpose only. These may be subject to variation depending on factors such as differences in color and normal manufacturing tolerances.

SYSTEMS COMPATIBILITY

Devprep 88 is designed to be topcoated with itself.

Surface Cleaner & Degreaser

ADDITIONAL INFORMATION

Further information regarding industry standards, terms and abbreviations used in this data sheet can be found in the following documents available at www.international-pc.com:

- Definitions & Abbreviations
- Surface Preparation
- Paint Application
- Theoretical & Practical Coverage

Individual copies of these information sections are available upon request.

SAFETY PRECAUTIONS

This product is intended for use only by professional applicators in industrial situations in accordance with the advice given on this sheet, the Material Safety Data Sheet and the container(s), and should not be used without reference to the Material Safety Data Sheet (MSDS) which International Protective Coatings has provided to its customers.

All work involving the application and use of this product should be performed in compliance with all relevant national, Health, Safety & Environmental standards and regulations.

In the event welding or flame cutting is performed on metal coated with this product, dust and fumes will be emitted which will require the use of appropriate personal protective equipment and adequate local exhaust ventilation.

If in doubt regarding the suitability of use of this product, consult International Protective Coatings for further advice.

PACK SIZE	Unit Size	Vol	Pack
	1 US gal	1 US gal	1 US gal
	5 US gal	5 US gal	5 US gal
For availability of other pack sizes contact International Protective Coatings			
SHIPPING WEIGHT (TYPICAL)	Unit Size		
	1 US gal		10 lb
	5 US gal		50.1 lb
STORAGE	Shelf Life	24 months minimum at 77°F (25°C). Subject to re-inspection thereafter. Store in dry, shaded conditions away from sources of heat and ignition.	

Disclaimer

The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose. All products supplied and technical advice given are subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.

This Technical Data Sheet is available on our website at www.international-marine.com or www.international-pc.com, and should be the same as this document. Should there be any discrepancies between this document and the version of the Technical Data Sheet that appears on the website, then the version on the website will take precedence.

Copyright © AkzoNobel, 2/5/2015.