

NVA965_A0

Safety Data Sheet ENVIROLINE 2900 PALE BLUE PART A



Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:

Sales
Order: {SalesOrd}
NVA965
09/28/2013
A0-2

1. Identification of the preparation and company

1.1. Product identifier

Product Identity ENVIROLINE 2900 PALE BLUE PART A
Bulk Sales Reference No. NVA965

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Combustible Liquid;H227 Combustible Liquid.
Acute Tox. 5;H303 May be harmful if swallowed.
Skin Irrit. 2;H315 Causes skin irritation.
Eye Irrit. 2;H319 Causes serious eye irritation.
Skin Sens. 1;H317 May cause an allergic skin reaction.
STOT RE 2;H373 May cause damage to organs through prolonged or repeated exposure.
Aquatic Acute 2;H401 Toxic to aquatic life.
Aquatic Chronic 3;H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H227 Combustible liquid.

H303 May be harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H401 Toxic to aquatic life.
 H412 Harmful to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
 P260 Do not breathe mist / vapors / spray.
 P262 Do not get in eyes, on skin, or on clothing.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P302+352 IF ON SKIN: Wash with soap and water.
 P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
 P312 Call a POISON CENTER or doctor / physician if you feel unwell.
 P314 Get Medical advice / attention if you feel unwell.
 P331 Do NOT induce vomiting.
 P333+313 If skin irritation or a rash occurs: Get medical advice/attention.
 P337 If eye irritation persists:.
 P362 Take off contaminated clothing and wash before reuse.
 P363 Wash contaminated clothing before reuse.
 P370+376 In case of fire: Stop leak if safe to do so.
 P403+235 Store in a well ventilated place. Keep cool.
 P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3* Flammability: 2 Reactivity: 1

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Reaction of epichlorohydrin and bisphenol A CAS Number: 0025085-99-8	25 - 50	Skin Irrit. 3;H316 Eye Irrit. 2;H319	[1]
Quartz CAS Number: 0014808-60-7	10 - 25	Acute Tox. 4;H332 STOT RE 2;H373	[1][2]
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER CAS Number: 0028064-14-4	10 - 25	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10	----	[1][2]
OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS CAS Number: 0002425-79-8	1.0 - 10	Acute Tox. 4;H332 Acute Tox. 4;H312 Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304	[1][2]

[1] Substance classified with a health or environmental hazard.
 [2] Substance with a workplace exposure limit.
 [3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

SMALL FIRES: Use dry chemical, CO₂, water spray or foam. LARGE FIRES: Use water spray, fog, or foam. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 159

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. LARGE SPILLS: Dike far ahead of liquid spill to contain released material and runoff from fire control.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

7. Handling and storage

7.1. Precautions for safe handling

NVA965_A0

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection
--

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m ³ TWA150 ppm STEL; 655 mg/m ³ STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA LMPE-PPT; 435 mg/m ³ TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 655 mg/m ³ STEL [LMPE-CT]
0002425-79-8	OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	15 mg/m ³ TWA (total dust)
		ACGIH	10 mg/m ³ TWA
		NIOSH	5000 mg/m ³ IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 mg/m ³ TWA
		Mexico	10 mg/m ³ TWA LMPE-PPT (as Ti)20 mg/m ³ STEL [LMPE-CT] (as Ti)
0014808-60-7	Quartz	OSHA	No Established Limit
		ACGIH	0.025 mg/m ³ TWA (respirable fraction)
		NIOSH	

NVA965_A0

			0.05 mg/m3 TWA (respirable dust) 50 mg/m3 IDLH (respirable dust)
		Supplier	No Established Limit
		OHSA, CAN	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline) 0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline)
		Mexico	0.1 mg/m3 TWA LMPE-PPT (respirable fraction)
		Brazil	No Established Limit
0025085-99-8	Reaction of epichlorohydrin and bisphenol A	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0002425-79-8	OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS	NIOSH	No Established Limit
0013463-67-7	Titanium dioxide	NIOSH	Lung tumors in animals
0014808-60-7	Quartz	NIOSH	Chronic lung disease (silicosis)
0025085-99-8	Reaction of epichlorohydrin and bisphenol A	NIOSH	No Established Limit
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0002425-79-8	OXIRANE, 2,2'-[1,4-BUTANEDIYLBIS(OXYMETHYLENE)]BIS	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0014808-60-7	Quartz	OSHA	Select Carcinogen: Yes

NVA965_A0

		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0025085-99-8	Reaction of epichlorohydrin and bisphenol A	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	137 (°C) 279 (°F)
Flash Point	66 (°C) 150 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	1.40
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured

NVA965_A0

Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit
VOC %	Refer to the Technical Data Sheet or label where information is available.

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Material may burn but does not ignite readily. Fire may produce irritating, corrosive and/or toxic gases. Containers may explode when heated.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Reaction of epichlorohydrin and bisphenol A - (25085-99-8)	No data available	No data available	No data available	No data available
Quartz - (14808-60-7)	No data available	No data available	No data available	No data available
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER - (28064-14-4)	2,000.00, Rat - Category: 4	No data available	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA
OXIRANE, 2,2'-[1,4-BUTANEDIYL]BIS(OXYMETHYLENE)]BIS - (2425-79-8)	1,134.00, Rat - Category: 4	1,130.00, Rabbit - Category: 4	No data available	No data available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	5	May be harmful if swallowed.
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2	Causes serious eye irritation.
Sensitization (respiratory)	Not Classified	Not Applicable

NVA965_A0

Sensitization (skin)	1	May cause an allergic skin reaction.
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Reaction of epichlorohydrin and bisphenol A - (25085-99-8)	Not Available	Not Available	Not Available
Quartz - (14808-60-7)	Not Available	Not Available	Not Available
PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER - (28064-14-4)	9.00, Oncorhynchus mykiss	9.00, Daphnia magna	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
OXIRANE, 2,2'-[1,4-BUTANEDIYL]BIS(OXYMETHYLENE)BIS - (2425-79-8)	24.00, Danio rerio	75.00, Daphnia magna	Not Available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number

Not Regulated

NVA965_A0

14.2. UN proper shipping name Not Regulated

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	Not Regulated	IMDG Proper Shipping Name	Not Regulated
DOT Hazard Class	Not Regulated	IMDG Hazard Class Sub Class	Not Regulated Not applicable
UN / NA Number	Not Regulated		
DOT Packing Group	Not Regulated	IMDG Packing Group	Not Regulated
CERCLA/DOT RQ	787 gal. / 9149 lbs.	System Reference Code	9

14.4. Packing group Not Regulated

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D2B

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :
Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)
Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :
Aluminum oxide
Benzene, ethyl-
Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :
Quartz
Titanium dioxide
Xylenes (o-, m-, p- isomers)

Penn RTK Substances (>1%) :
Quartz
Titanium dioxide
Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :
Quartz
Titanium dioxide
Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

- Benzene, ethyl-
- Quartz
- Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

- Aluminum oxide
- Benzene, ethyl-
- Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

- Benzene, ethyl-
- Quartz
- Titanium dioxide

Proposition 65 - Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):

(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H316 Causes mild skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

End of Document